

* RF Exposure

1. Regulation

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this Chapter.

Limits for Maximum Permissive Exposure: RF exposure is calculated.

Emilio for Maximum I offinistive Exposure. It exposure is carealated.								
Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time				
	Strength [V/m]	Strength [A/m]	[mW/cm²]	[minute]				
Limits for General Population / Uncontrolled Exposure								
0.3 ~ 1.34	614	1.63	*(100)	30				
$1.34 \sim 30$	824/f	2.19/f	$*(180/f^2)$	30				
30 ~ 300	27.5	0.073	0.2	30				
300 ~ 1 500	/	/	f/1 500	30				
1 500 ~ 15 000	/	/	1.0	30				

f=frequency in Mz, *= plane-wave equivalent power density

MPE (Maximum Permissive Exposure) Prediction

Predication of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$
 $(\Rightarrow R = \sqrt{PG/4\pi S})$

 $S = power density [mW / cm^2]$

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

EUT: Maximum peak output power = 15.43 [dBm] (34.91 mW) Antenna gain = 12.62 [mW] (11.0 dBi)					
100 mW, at 20 cm from an antenna 6 [dBi]	$S = PG/4\pi R^2 = 100 \times 3.98 / (4 \times \pi \times 400)$ $= 0.079 18 [mW/cm^2] < 1.0 [mW/cm^2]$				
15.43 mW, at 20 cm from an antenna 11.0 [dBi]	$S = PG/4\pi R^2 = 0.087 65 [mW/cm^2] < 1.0 [mW/cm^2]$				

2. RF Exposure Compliance Issue

The information should be included in the user's manual:

This appliance and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter. A minimum separation distance of 20 cm must be maintained between the antenna and the person for this appliance to satisfy the RF exposure requirements.



3. Calculation Result of RF Exposure

* 802.11b 40

Frequency	Ant Gain [dBi]	Power [dBm]	Power	Power Density at 20 cm [mW/cm²]	Power Density at 2.5 cm [mW/cm²]
5 230	9.0	16.65	46.24	0.073 25	4.687 77
5 755	11.0	15.17	32.92	0.082 65	5.289 33
5 795	11.0	15.43	34.88	0.087 56	5.603 67