

MPE CALCULATION

BLE module
FCC ID: APV-BLD01
GSM module
FCC ID: QIPEHS5-US

RF Exposure Requirements:
RF Radiation Exposure Limits:
RF Radiation Exposure Guidelines:

47 CFR §1.1307(b)
47 CFR §1.1310
FCC OST/OET Bulletin Number 65

Limits for General Population/Uncontrolled Exposure in the band of:

300 - 1500 MHz

Power Density Limit:

f/1500 mW / cm²

Limits for General Population/Uncontrolled Exposure in the band of:

1500 - 100,000 MHz

Power Density Limit:

1 mW / cm²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Model No.: LMU-3035

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Directional Gain (dBi)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/Fail
BLE	2402	0.00	2.5	2.5	20	0.00035	1	Pass
GSM	837	32.99	-2	-2	20	0.250	0.558	Pass
WCDMA	1852.6	24.20	-2	-2	20	0.033	1	Pass

Bluetooth and GSM transmit simultaneously. (GSM and WCDMA does not transmit simultaneously)

Total MPE=0.00035/1 + 0.25/0.558 = **0.448 < 1**

The Above Result had shown that the Device complied with MPE requirement.



Completed By: Shuo Zhang

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 03/23/2018