


TEST REPORT

Applicant: E&S International Enterprises, Inc.
Address: 7801 Hayvenhurst Avenue, Van Nuys, CA 91406, USA
Equipment Type: LAPTOP
Model Name: VWNC51529 (refer section 2.4)
Brand Name: VAIO
FCC ID: 2AYPE-VWNC15INCH
Test Standard: FCC 47 CFR Part 2.1093 (refer section 3.1)
Maximum SAR: Body 2.4GHz(1 g@0mm): 0.85 W/kg
Body 5GHz(1 g@0mm): 1.19 W/kg
Test Date: Sep. 03, 2022 - Sep. 06, 2022
Date of Issue: Sep. 15, 2022

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Zhang Jiwei**Checked by:** Liyao Zong**Approved by:** Wei Yanquan
(Chief Engineer)

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Sep. 15, 2022</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	Factory Information	5
2.4	General Description for Equipment under Test (EUT)	5
2.5	Ancillary Equipment	5
2.6	Technical Information	6
3	SUMMARY OF TEST RESULT	7
3.1	Test Standards	7
3.2	Device Category and SAR Limit	8
3.3	Test Result Summary	9
3.4	Test Uncertainty	10
4	MEASUREMENT SYSTEM	11
4.1	Specific Absorption Rate (SAR) Definition	11
4.2	DASY SAR System	12
5	SYSTEM VERIFICATION	20
5.1	Purpose of System Check	20
5.2	System Check Setup	20
6	TEST POSITION CONFIGURATIONS	21
6.1	Laptop Exposure Condition	21

7	MEASUREMENT PROCEDURE	22
7.1	Measurement Process Diagram	22
7.2	SAR Scan General Requirement	23
7.3	Measurement Procedure	24
7.4	Area & Zoom Scan Procedure	24
8	CONDUCTED RF OUPUT POWER	25
8.1	WIFI	25
8.2	Bluetooth (Aux. Antenna)	39
9	TEST EXCLUSION CONSIDERATION	40
9.1	Laptop Mode antenna location sketch	40
9.2	SAR Test Consideration Table	41
10	TEST RESULT	44
10.1	WIFI 2.4GHz	44
10.2	WIFI 5GHz	45
10.3	Bluetooth	46
11	SAR Measurement Variability	47
12	SIMULTANEOUS TRANSMISSION	48
12.1	Simultaneous Transmission Mode Considerations	48
12.2	Sum SAR of Simultaneous Transmission	49
13	TEST EQUIPMENTS LIST	50
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	51
ANNEX B	SYSTEM CHECK RESULT	52
ANNEX C	TEST DATA	57
ANNEX D	EUT EXTERNAL PHOTOS	70
ANNEX E	SAR TEST SETUP PHOTOS	70
ANNEX F	CALIBRATION REPORT	70

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	E&S International Enterprises, Inc.
Address	7801 Hayvenhurst Avenue Van Nuys, California 91406, USA

2.2 Manufacturer Information

Manufacturer	E&S International Enterprises, Inc.
Address	7801 Hayvenhurst Avenue, Van Nuys, CA 91406, USA

2.3 Factory Information

Factory	Shenzhen Bmorn Technology Co., Ltd
Address	6001, 6th Floor, West Building, Hengfang Veterans Industrial City, No.3012, Xingye Road, Yongfeng Community, Xixiang Street, Baoan District, Shenzhen, 51800 Guangdong, P.R. China

2.4 General Description for Equipment under Test (EUT)

EUT Name	LAPTOP
Model Name Under Test	VWNC51529
Series Model Name	VWNC51527
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in shell color and model name. (this information provided by the customer)
Hardware Version	EM_IDL_528_3.0
Software Version	21H2
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery 1	
	Brand Name	Ganfeng
	Model No.	575983
	Serial No.	N/A
	Capacity	4780 mAh
	Rated Voltage	11.55 V
	Limit Charge Voltage	13.20 V
	Manufacturer	Dongguan Ganfeng Electronics Co., Ltd

2.6 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac and 802.11ax U-NII-1/2A/2C/3
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	2.4G WLAN, 5G WLAN, Bluetooth	
Frequency Range	802.11b/g/n (HT20/HT40)	2412 ~ 2462 MHz
	802.11ax (HE20/40)	2412 ~ 2462 MHz
	802.11a/n (HT20/HT40)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11ac (VHT20/VHT40/VHT80)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11ac (VHT160)	5150 ~ 5250 MHz
		5470 ~ 5725 MHz
	802.11ax (HE20/HE40/HE80)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11ax (HE160)	5150 ~ 5250 MHz
		5470 ~ 5725 MHz
	Bluetooth	2402 MHz ~ 2480 MHz
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna	
Hotspot Function	N/A	
Exposure Category	General Population/Uncontrolled exposure	
EUT Stage	Portable Device	
Product	Type	
	☒ Production unit	☐ Identical prototype

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters
8	KDB 616217 D04v01r02	SAR for laptop and tablets

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR (1 g Value)

Frequency Band		Maximum Scaled SAR (W/kg)	Maximum Report SAR (W/kg)
		Body (0mm)	Body (0mm)
WIFI	2.4 G Aux. Antenna	0.85	1.19
	2.4 G Main Antenna	0.38	
	2.4 G MIMO	0.27	
	5.3G WLAN Aux. Antenna	1.19	
	5.3G WLAN Main Antenna	0.94	
	5.3G WLAN MIMO	0.68	
	5.6G WLAN Aux. Antenna	1.05	
	5.6G WLAN Main Antenna	0.98	
	5.6G WLAN MIMO	0.72	
	5.8G WLAN Aux. Antenna	0.87	
	5.8G WLAN Main Antenna	0.99	
	5.8G WLAN MIMO	0.77	
Bluetooth	DH5 Aux. Antenna	0.07	
Limits (W/kg)		1.6	
Test Verdict		Pass	

3.3.2 Highest Simultaneous SAR

Note: The highest simultaneous SAR please refer section 12.

3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.190 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram



The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
6. The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4-SN:7510 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)



E-Field Probe Calibration Process

Probe calibration is realized, in compliance with CENELEC EN 62209-1/-2 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1/2 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200MΩ
- The Inputs: Symmetrical and Floating
- Common Mode Rejection: Above 80dB

4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left hand
- Right hand
- Flat phantom

Photo of Phantom SN1859



Serial Number	Material	Length	Height
SN 1859 SAM	Vinylester, glass fiber reinforced	1000	500

4.2.6 Device Holder

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.




The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE			Salt		Conductivity	Permittivity

		(%)	(%)	σ (S/m)	ε
5200	78.60	21.40	/	5.54	47.86
5800	78.50	21.40	0.1	6.0	48.20


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup


In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS


6.1 Laptop Exposure Condition

This DUT should consider one position which is bottom of laptop touching with phantom 0 mm air gap and the screen portion of the device shall be an open position at a 90° angle.



7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	½·δ·ln(2)±0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUTPUT POWER

8.1 WIFI

8.1.1 2.4G WIFI (Aux. Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
2.4 (2.4~2.483)	802.11b	1	2412	18.63	19.00	Yes
		6	2437	18.85	19.00	Yes
		11	2462	18.58	19.00	Yes
	802.11g	1	2412	15.77	16.00	No
		6	2437	15.80	16.00	No
		11	2462	15.52	16.00	No
	802.11n(HT20)	1	2412	15.59	16.00	No
		6	2437	15.62	16.00	No
		11	2462	15.82	16.00	No
	802.11n(HT40)	3	2422	12.89	14.00	No
		4	2427	15.42	16.00	No
		6	2437	15.86	16.00	No
		9	2452	15.45	16.00	No
	802.11ax(HE20) (SU)	1	2412	15.43	16.00	No
		6	2437	15.43	16.00	No
		11	2462	15.67	16.00	No
	802.11ax(HE40) (SU)	3	2422	13.11	14.00	No
		4	2427	15.35	16.00	No
		6	2437	15.62	16.00	No
		9	2452	15.65	16.00	No
	802.11ax(HE20) (RU26)	1	2412	11.59	12.00	No
		6	2437	11.61	12.00	No
		11	2462	11.77	12.00	No
	802.11ax(HE40) (RU26)	3	2422	11.79	12.00	No
		6	2437	11.75	12.00	No
		9	2452	11.62	12.00	No

Note: When multiple channel bandwidth configurations in a frequency band have the same maximum tune-up output power, the test configuration is determined by applying the following steps sequentially.

- 1) The largest channel bandwidth configuration is selected between the multiple configurations in a frequency band with the same maximum tune-up output power.
- 2) When multiple transmission modes (802.11b/g/n/ax) have the same maximum tune-up output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11b is chosen over 802.11g, and 802.11g & 802.11n chosen over 802.11ax.
- 3) According KDB 247228, when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, OFDM SAR test is not required.

Adjusted SAR = $0.854 * (39.81\text{mW}/79.43\text{mW}) = 0.428$ W/Kg, so 2.4G OFDM SAR test is not required.

8.1.2 2.4G WIFI (Main Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
2.4 (2.4~2.483)	802.11b	1	2412	18.45	19.00	No
		6	2437	18.75	19.00	Yes
		11	2462	18.41	19.00	No
	802.11g	1	2412	15.50	16.00	No
		6	2437	15.32	16.00	No
		11	2462	15.43	16.00	No
	802.11n(HT20)	1	2412	15.47	16.00	No
		6	2437	15.24	16.00	No
		11	2462	15.39	16.00	No
	802.11n(HT40)	3	2422	15.56	16.00	No
		6	2437	15.50	16.00	No
		9	2452	15.03	16.00	No
	802.11ax(HE20) (SU)	1	2412	15.75	16.00	No
		6	2437	15.59	16.00	No
		11	2462	15.72	16.00	No
	802.11ax(HE40) (SU)	3	2422	15.72	16.00	No
		6	2437	15.72	16.00	No
		9	2452	15.66	16.00	No
	802.11ax(HE20) (RU26)	1	2412	11.53	12.00	No
		6	2437	11.81	12.00	No
		11	2462	11.60	12.00	No
	802.11ax(HE40) (RU26)	3	2422	11.71	12.00	No
		6	2437	11.79	12.00	No
		9	2452	11.71	12.00	No

Note: When multiple channel bandwidth configurations in a frequency band have the same maximum tune-up output power, the test configuration is determined by applying the following steps sequentially.

- 1) The largest channel bandwidth configuration is selected between the multiple configurations in a frequency band with the same maximum tune-up output power.
- 2) When multiple transmission modes (802.11b/g/n/ax) have the same maximum tune-up output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11b is chosen over 802.11g, and 802.11g & 802.11n chosen over 802.11ax.
- 3) According KDB 247228, when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, OFDM SAR test is not required.
Adjusted SAR = $0.381 * (39.81\text{mW}/79.43\text{mW}) = 0.191$ W/Kg, so 2.4G OFDM SAR test is not required.

8.1.3 2.4G WIFI (MIMO)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
	802.11n(HT20)	1	2412	15.67	16.00	No
		6	2437	15.62	16.00	No
		11	2462	15.72	16.00	No
	802.11n(HT40)	3	2422	15.84	16.00	Yes
		6	2437	15.81	16.00	No
		9	2452	15.65	16.00	No
	802.11ax(HE20) (SU)	1	2412	15.51	16.00	No
		6	2437	15.73	16.00	No
		11	2462	15.81	16.00	No
	802.11ax(HE40) (SU)	3	2422	15.65	16.00	No
		6	2437	15.66	16.00	No
		9	2452	15.71	16.00	No
	802.11ax(HE20) (RU26)	1	2412	11.36	12.00	No
		6	2437	11.67	12.00	No
		11	2462	11.74	12.00	No
	802.11ax(HE40) (RU26)	3	2422	11.54	12.00	No
		6	2437	11.79	12.00	No
		9	2452	11.74	12.00	No

Note: When multiple channel bandwidth configurations in a frequency band have the same maximum tune-up output power, the test configuration is determined by applying the following steps sequentially.

- 1) The largest channel bandwidth configuration is selected between the multiple configurations in a frequency band with the same maximum tune-up output power.
- 2) When multiple transmission modes (802.11n/ax) have the same maximum tune-up output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11n is chosen over 802.11ax.

8.1.4 5G WIFI (Aux. Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	15.75	16.00	No
		44	5220	15.77	16.00	No
		48	5240	15.66	16.00	No
	802.11n(HT20)	36	5180	15.58	16.00	No
		44	5220	15.61	16.00	No
		48	5240	15.75	16.00	No
	802.11n(HT40)	38	5190	15.53	16.00	No
		46	5230	15.75	16.00	No
	802.11ac(VHT20)	36	5180	15.75	16.00	No
		44	5220	15.69	16.00	No
		48	5240	15.76	16.00	No
	802.11ac(VHT40)	38	5190	15.78	16.00	No
		46	5230	15.81	16.00	No
	802.11ac(VHT80)	42	5210	15.71	16.00	No
	802.11ac(VHT160)	50	5250	15.54	16.00	No
	802.11ax(HE20) (SU)	36	5180	15.82	16.00	No
		44	5220	15.47	16.00	No
		48	5240	15.50	16.00	No
	802.11ax(HE40) (SU)	38	5190	15.76	16.00	No
		46	5230	15.59	16.00	No
	802.11ax(HE80) (SU)	42	5210	15.69	16.00	No
	802.11ax(HE160) (SU)	50	5250	15.74	16.00	No
	802.11ax(HE20) (RU26)	36	5180	11.81	12.00	No
		44	5220	11.84	12.00	No
		48	5240	11.68	12.00	No
	802.11ax(HE40) (RU26)	38	5190	11.66	12.00	No
		46	5230	11.60	12.00	No
	802.11ax(HE80) (RU26)	42	5210	11.74	12.00	No
	802.11ax(HE160) (RU26)	50	5250	11.57	12.00	No
5.3 (5.25~5.35)	802.11a	52	5260	15.78	16.00	No
		60	5300	15.81	16.00	No
		64	5320	15.75	16.00	No
	802.11n(HT20)	52	5260	15.57	16.00	No
		60	5300	15.56	16.00	No
		64	5320	15.51	16.00	No
	802.11n(HT40)	54	5270	15.73	16.00	No

		62	5310	15.78	16.00	No
	802.11ac(VHT20)	52	5260	15.60	16.00	No
		60	5300	15.54	16.00	No
		64	5320	15.51	16.00	No
	802.11ac(VHT40)	54	5270	15.76	16.00	No
		62	5310	15.80	16.00	No
	802.11ac(VHT80)	58	5290	15.58	16.00	Yes
	802.11ax(HE20) (SU)	52	5260	15.81	16.00	No
		60	5300	15.80	16.00	No
		64	5320	15.86	16.00	No
	802.11ax(HE40) (SU)	54	5270	15.79	16.00	No
		62	5310	15.73	16.00	No
	802.11ax(HE80) (SU)	58	5290	15.76	16.00	No
	802.11ax(HE20) (RU26)	52	5260	11.84	12.00	No
		60	5300	11.65	12.00	No
		64	5320	11.85	12.00	No
	802.11ax(HE40) (RU26)	54	5270	11.62	12.00	No
		62	5310	11.61	12.00	No
	802.11ax(HE80) (RU26)	58	5290	11.64	12.00	No
5.6 (5.47~5.725)	802.11a	100	5500	14.72	15.00	No
		116	5580	14.71	15.00	No
		140	5700	14.80	15.00	No
	802.11n(HT20)	100	5500	14.79	15.00	No
		116	5580	14.77	15.00	No
		140	5700	14.74	15.00	No
	802.11n(HT40)	102	5510	14.66	15.00	No
		118	5590	14.58	15.00	No
		134	5670	14.75	15.00	No
	802.11ac(VHT20)	100	5500	14.85	15.00	No
		116	5580	14.71	15.00	No
		140	5700	14.81	15.00	No
	802.11ac(VHT40)	102	5510	14.68	15.00	No
		118	5590	14.52	15.00	No
		134	5670	14.76	15.00	No
	802.11ac(VHT80)	106	5530	14.70	15.00	No
		122	5610	14.46	15.00	No
		138	5690	14.52	15.00	No
	802.11ac(VHT160)	114	5570	14.60	15.00	Yes
	802.11ax(HE20) (SU)	100	5500	14.46	15.00	No
		116	5580	14.49	15.00	No
		140	5700	14.76	15.00	No

	802.11ax(HE40) (SU)	102	5510	14.68	15.00	No
		118	5590	14.84	15.00	No
		134	5670	14.59	15.00	No
	802.11ax(HE80) (SU)	106	5530	14.54	15.00	No
		122	5610	14.79	15.00	No
		138	5690	14.58	15.00	No
	802.11ax(HE160) (SU)	114	5570	14.53	15.00	No
	802.11ax(HE20) (RU26)	100	5500	11.79	12.00	No
		116	5580	11.75	12.00	No
		140	5700	11.70	12.00	No
	802.11ax(HE40) (RU26)	102	5510	11.69	12.00	No
		118	5590	11.62	12.00	No
		134	5670	11.78	12.00	No
	802.11ax(HE80) (RU26)	106	5530	11.66	12.00	No
		122	5610	11.62	12.00	No
		138	5690	11.57	12.00	No
	802.11ax(HE160) (RU26)	114	5570	11.49	12.00	No
5.8 (5.725~5.85)	802.11a	149	5745	15.74	16.00	No
		157	5785	15.71	16.00	No
		165	5825	15.72	16.00	No
	802.11n(HT20)	149	5745	15.66	16.00	No
		157	5785	15.46	16.00	No
		165	5825	15.82	16.00	No
	802.11n(HT40)	151	5755	15.71	16.00	No
		159	5795	15.78	16.00	No
	802.11ac(VHT20)	149	5745	15.68	16.00	No
		157	5785	15.45	16.00	No
		165	5825	15.75	16.00	No
	802.11ac(VHT40)	151	5755	15.77	16.00	No
		159	5795	15.78	16.00	No
	802.11ac(VHT80)	155	5775	15.49	16.00	Yes
	802.11ax(HE20) (SU)	149	5745	15.65	16.00	No
		157	5785	15.81	16.00	No
		165	5825	15.61	16.00	No
	802.11ax(HE40) (SU)	151	5755	15.50	16.00	No
		159	5795	15.42	16.00	No
	802.11ax(HE80) (SU)	155	5775	15.63	16.00	No
	802.11ax(HE20) (RU26)	149	5745	11.59	12.00	No
		157	5785	11.78	12.00	No
		165	5825	11.75	12.00	No

	802.11ax(HE40) (RU26)	151	5755	11.72	12.00	No
		159	5795	11.68	12.00	No
	802.11ax(HE80) (RU26)	155	5775	11.59	12.00	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.1.5 5G WIFI (Main Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	16.27	17.00	No
		44	5220	16.20	17.00	No
		48	5240	16.08	17.00	No
	802.11n(HT20)	36	5180	16.79	17.00	No
		44	5220	16.42	17.00	No
		48	5240	16.24	17.00	No
	802.11n(HT40)	38	5190	16.45	17.00	No
		46	5230	16.60	17.00	No
	802.11ac(VHT20)	36	5180	16.75	17.00	No
		44	5220	16.41	17.00	No
		48	5240	16.30	17.00	No
	802.11ac(VHT40)	38	5190	16.79	17.00	No
		46	5230	16.56	17.00	No
	802.11ac(VHT80)	42	5210	16.51	17.00	No
	802.11ac(VHT160)	50	5250	15.52	17.00	No
	802.11ax(HE20) (SU)	36	5180	16.58	17.00	No
		44	5220	16.65	17.00	No
		48	5240	16.55	17.00	No
	802.11ax(HE40) (SU)	38	5190	16.59	17.00	No
		46	5230	16.81	17.00	No
	802.11ax(HE80) (SU)	42	5210	16.62	17.00	No
	802.11ax(HE160) (SU)	50	5250	15.23	17.00	No
	802.11ax(HE20) (RU26)	36	5180	11.62	12.00	No
		44	5220	11.79	12.00	No
		48	5240	11.65	12.00	No
	802.11ax(HE40) (RU26)	38	5190	11.80	12.00	No
		46	5230	11.61	12.00	No
	802.11ax(HE80) (RU26)	42	5210	11.64	12.00	No
	802.11ax(HE160) (RU26)	50	5250	11.57	12.00	No
5.3 (5.25~5.35)	802.11a	52	5260	16.71	17.00	No
		60	5300	16.69	17.00	No
		64	5320	16.61	17.00	No
	802.11n(HT20)	52	5260	16.80	17.00	No
		60	5300	16.80	17.00	No
		64	5320	16.83	17.00	No
	802.11n(HT40)	54	5270	16.57	17.00	No

		62	5310	16.56	17.00	No
	802.11ac(VHT20)	52	5260	16.85	17.00	No
		60	5300	16.83	17.00	No
		64	5320	16.73	17.00	No
	802.11ac(VHT40)	54	5270	16.56	17.00	No
		62	5310	16.54	17.00	No
	802.11ac(VHT80)	58	5290	16.72	17.00	Yes
	802.11ax(HE20) (SU)	52	5260	16.63	17.00	No
		60	5300	16.61	17.00	No
		64	5320	16.60	17.00	No
	802.11ax(HE40) (SU)	54	5270	16.73	17.00	No
		62	5310	16.82	17.00	No
	802.11ax(HE80) (SU)	58	5290	16.44	17.00	No
	802.11ax(HE20) (RU26)	52	5260	11.77	12.00	No
		60	5300	11.69	12.00	No
		64	5320	11.67	12.00	No
	802.11ax(HE40) (RU26)	54	5270	11.72	12.00	No
		62	5310	11.63	12.00	No
	802.11ax(HE80) (RU26)	58	5290	11.49	12.00	No
5.6 (5.47~5.725)	802.11a	100	5500	16.68	17.00	No
		116	5580	16.47	17.00	No
		140	5700	16.38	17.00	No
	802.11n(HT20)	100	5500	16.49	17.00	No
		116	5580	16.69	17.00	No
		140	5700	16.76	17.00	No
	802.11n(HT40)	102	5510	16.74	17.00	No
		118	5590	16.78	17.00	No
		134	5670	16.76	17.00	No
	802.11ac(VHT20)	100	5500	16.85	17.00	No
		116	5580	16.69	17.00	No
		140	5700	16.72	17.00	No
	802.11ac(VHT40)	102	5510	16.25	17.00	No
		118	5590	16.77	17.00	No
		134	5670	16.82	17.00	No
	802.11ac(VHT80)	106	5530	16.58	17.00	Yes
		122	5610	16.42	17.00	Yes
		138	5690	16.55	17.00	Yes
	802.11ac(VHT160)	114	5570	14.36	16.00	No
	802.11ax(HE20) (SU)	100	5500	16.85	17.00	No
		116	5580	16.95	17.00	No
		140	5700	16.50	17.00	No

	802.11ax(HE40) (SU)	102	5510	16.44	17.00	No
		118	5590	16.48	17.00	No
		134	5670	16.72	17.00	No
	802.11ax(HE80) (SU)	106	5530	16.80	17.00	No
		122	5610	16.65	17.00	No
		138	5690	16.73	17.00	No
	802.11ax(HE160) (SU)	114	5570	15.17	16.00	No
	802.11ax(HE20) (RU26)	100	5500	11.76	12.00	No
		116	5580	11.61	12.00	No
		140	5700	11.61	12.00	No
	802.11ax(HE40) (RU26)	102	5510	11.63	12.00	No
		118	5590	11.72	12.00	No
		134	5670	11.75	12.00	No
	802.11ax(HE80) (RU26)	106	5530	11.57	12.00	No
		122	5610	11.78	12.00	No
		138	5690	11.65	12.00	No
	802.11ax(HE160) (RU26)	114	5570	11.51	12.00	No
5.8 (5.725~5.85)	802.11a	149	5745	16.48	17.00	No
		157	5785	16.56	17.00	No
		165	5825	16.75	17.00	No
	802.11n(HT20)	149	5745	16.67	17.00	No
		157	5785	16.52	17.00	No
		165	5825	16.65	17.00	No
	802.11n(HT40)	151	5755	16.78	17.00	No
		159	5795	16.70	17.00	No
	802.11ac(VHT20)	149	5745	16.62	17.00	No
		157	5785	16.59	17.00	No
		165	5825	16.80	17.00	No
	802.11ac(VHT40)	151	5755	16.59	17.00	No
		159	5795	16.68	17.00	No
	802.11ac(VHT80)	155	5775	16.48	17.00	Yes
	802.11ax(HE20) (SU)	149	5745	16.42	17.00	No
		157	5785	16.79	17.00	No
		165	5825	16.67	17.00	No
	802.11ax(HE40) (SU)	151	5755	16.63	17.00	No
		159	5795	16.45	17.00	No
	802.11ax(HE80) (SU)	155	5775	16.79	17.00	No
	802.11ax(HE20) (RU26)	149	5745	11.61	12.00	No
		157	5785	11.73	12.00	No
		165	5825	11.78	12.00	No

	802.11ax(HE40) (RU26)	151	5755	11.75	12.00	No
		159	5795	11.61	12.00	No
	802.11ax(HE80) (RU26)	155	5775	11.78	12.00	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.1.6 5G WIFI (MIMO)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11n(HT20)	36	5180	16.73	17.00	No
		44	5220	16.71	17.00	No
		48	5240	16.74	17.00	No
	802.11n(HT40)	38	5190	16.64	17.00	No
		46	5230	16.68	17.00	No
	802.11ac(VHT20)	36	5180	16.54	17.00	No
		44	5220	16.63	17.00	No
		48	5240	16.58	17.00	No
	802.11ac(VHT40)	38	5190	16.67	17.00	No
		46	5230	16.70	17.00	No
	802.11ac(VHT80)	42	5210	16.49	17.00	No
	802.11ac(VHT160)	50	5250	16.66	17.00	No
	802.11ax(HE20) (SU)	36	5180	16.70	17.00	No
		44	5220	16.73	17.00	No
		48	5240	16.75	17.00	No
	802.11ax(HE40) (SU)	38	5190	16.67	17.00	No
		46	5230	16.63	17.00	No
	802.11ax(HE80) (SU)	42	5210	16.73	17.00	No
	802.11ax(HE160) (SU)	50	5250	16.65	17.00	No
	802.11ax(HE20) (RU26)	36	5180	11.71	12.00	No
		44	5220	11.60	12.00	No
		48	5240	11.71	12.00	No
	802.11ax(HE40) (RU26)	38	5190	11.69	12.00	No
		46	5230	11.70	12.00	No
	802.11ax(HE80) (RU26)	42	5210	11.61	12.00	No
	802.11ax(HE160) (RU26)	50	5250	11.73	12.00	No
5.3 (5.25~5.35)	802.11n(HT20)	52	5260	16.54	17.00	No
		60	5300	16.62	17.00	No
		64	5320	16.72	17.00	No
	802.11n(HT40)	54	5270	16.58	17.00	No
		62	5310	16.52	17.00	No
	802.11ac(VHT20)	52	5260	16.70	17.00	No
		60	5300	16.69	17.00	No
		64	5320	16.73	17.00	No
	802.11ac(VHT40)	54	5270	16.67	17.00	No
		62	5310	16.66	17.00	No

	802.11ac(VHT80)	58	5290	16.66	17.00	Yes
	802.11ax(HE20) (SU)	52	5260	16.87	17.00	No
		60	5300	16.78	17.00	No
		64	5320	16.78	17.00	No
	802.11ax(HE40) (SU)	54	5270	16.64	17.00	No
		62	5310	16.76	17.00	No
	802.11ax(HE80) (SU)	58	5290	16.61	17.00	No
	802.11ax(HE20) (RU26)	52	5260	11.60	12.00	No
		60	5300	11.68	12.00	No
		64	5320	11.66	12.00	No
	802.11ax(HE40) (RU26)	54	5270	11.70	12.00	No
		62	5310	11.68	12.00	No
	802.11ax(HE80) (RU26)	58	5290	11.60	12.00	No
5.6 (5.47~5.725)	802.11n(HT20)	100	5500	16.78	17.00	No
		116	5580	16.63	17.00	No
		140	5700	16.84	17.00	No
	802.11n(HT40)	102	5510	16.68	17.00	No
		118	5590	16.64	17.00	No
		134	5670	16.71	17.00	No
	802.11ac(VHT20)	100	5500	16.58	17.00	No
		116	5580	16.64	17.00	No
		140	5700	16.77	17.00	No
	802.11ac(VHT40)	102	5510	16.59	17.00	No
		118	5590	16.64	17.00	No
		134	5670	16.67	17.00	No
	802.11ac(VHT80)	106	5530	16.57	17.00	No
		122	5610	16.61	17.00	No
		138	5690	16.57	17.00	No
	802.11ac(VHT160)	114	5570	16.62	17.00	Yes
	802.11ax(HE20) (SU)	100	5500	16.73	17.00	No
		116	5580	16.63	17.00	No
		140	5700	16.66	17.00	No
	802.11ax(HE40) (SU)	102	5510	16.77	17.00	No
		118	5590	16.67	17.00	No
		134	5670	16.67	17.00	No
	802.11ax(HE80) (SU)	106	5530	16.77	17.00	No
		122	5610	16.68	17.00	No
		138	5690	16.61	17.00	No
	802.11ax(HE160) (SU)	114	5570	16.69	17.00	No
	802.11ax(HE20)	100	5500	11.66	12.00	No

	(RU26)	116	5580	11.67	12.00	No
		140	5700	11.78	12.00	No
	802.11ax(HE40) (RU26)	102	5510	11.75	12.00	No
		118	5590	11.77	12.00	No
		134	5670	11.68	12.00	No
	802.11ax(HE80) (RU26)	106	5530	11.69	12.00	No
		122	5610	11.67	12.00	No
		138	5690	11.59	12.00	No
	802.11ax(HE160) (RU26)	114	5570	11.51	12.00	No
5.8 (5.725~5.85)	802.11n(HT20)	149	5745	16.73	17.00	No
		157	5785	16.71	17.00	No
		165	5825	16.75	17.00	No
	802.11n(HT40)	151	5755	16.75	17.00	No
		159	5795	16.65	17.00	No
	802.11ac(VHT20)	149	5745	16.70	17.00	No
		157	5785	16.65	17.00	No
		165	5825	16.57	17.00	No
	802.11ac(VHT40)	151	5755	16.74	17.00	No
		159	5795	16.66	17.00	No
	802.11ac(VHT80)	155	5775	16.56	17.00	Yes
	802.11ax(HE20) (SU)	149	5745	16.72	17.00	No
		157	5785	16.62	17.00	No
		165	5825	16.71	17.00	No
	802.11ax(HE40) (SU)	151	5755	16.65	17.00	No
		159	5795	16.76	17.00	No
	802.11ax(HE80) (SU)	155	5775	16.69	17.00	No
	802.11ax(HE20) (RU26)	149	5745	11.67	12.00	No
		157	5785	11.75	12.00	No
		165	5825	11.62	12.00	No
	802.11ax(HE40) (RU26)	151	5755	11.71	12.00	No
		159	5795	11.72	12.00	No
	802.11ax(HE80) (RU26)	155	5775	11.74	12.00	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.2 Bluetooth (Aux. Antenna)


Mode	GFSK			$\pi/4$ -DQPSK		
Channel	0	39	78	0	39	78
Frequency (MHz)	2402	2441	2480	2402	2441	2480
Conducted Power (dBm)	9.37	9.67	9.73	7.40	7.57	8.01
Tune-Up Limit (dBm)	10.50	10.50	10.50	9.00	9.00	9.00
SAR Test Require	No	No	Yes	No	No	No
Mode	8-DPSK			/		
Channel	0	39	78	/	/	/
Frequency (MHz)	2402	2441	2480	/	/	/
Conducted Power (dBm)	7.38	7.78	7.95	/	/	/
Tune-Up Limit (dBm)	9.00	9.00	9.00	/	/	/
SAR Test Require	No	No	No	/	/	/
Mode	BLE-1Mbps			BLE-2Mbps		
Channel	0	19	39	0	19	39
Frequency (MHz)	2402	2440	2480	2402	2440	2480
Conducted Power (dBm)	8.05	8.56	8.74	8.14	8.57	8.74
Tune-Up Limit (dBm)	10.00	10.00	10.00	10.00	10.00	10.00
SAR Test Require	No	No	No	No	No	No

Note: Since Bluetooth BR mode is the maximum output power mode, SAR measurements were performed with test software using DH5 modulation, and SAR measurement is not required for the EDR and LE. When the secondary mode is $\leq 1/4$ dB higher than the primary mode.

Note: The Bluetooth duty cycle is 76.88 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation.


Duty Cycle

GFSK



9 TEST EXCLUSION CONSIDERATION

9.1 Laptop Mode antenna location sketch



9.2 SAR Test Consideration Table

According with FCC KDB 447498 D04, Appendix B, The SAR-based exemption formula applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). The following table shows the power threshold from 5mm to 50mm.

Power Thresholds (mW)					
Frequency (MHz)	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
300	39 mW	65 mW	88 mW	110 mW	129 mW
450	22 mW	44 mW	67 mW	89 mW	112 mW
835	9 mW	25 mW	44 mW	66 mW	90 mW
1900	3 mW	12 mW	26 mW	44 mW	66 mW
2450	3 mW	10 mW	22 mW	38 mW	59 mW
3600	2 mW	8 mW	18 mW	32 mW	49 mW
5800	1 mW	6 mW	14 mW	25 mW	40 mW
Frequency (MHz)	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of 50 mm
300	148 mW	166 mW	184 mW	201 mW	217 mW
450	135 mW	158 mW	180 mW	203 mW	226 mW
835	116 mW	145 mW	175 mW	207 mW	240 mW
1900	92 mW	122 mW	157 mW	195 mW	236 mW
2450	83 mW	111 mW	143 mW	179 mW	219 mW
3600	71 mW	96 mW	125 mW	158 mW	195 mW
5800	58 mW	80 mW	106 mW	136 mW	169 mW

9.2.1 Laptop mode SAR Test Consideration

Aux. Antenna						
Test Position Configurations	Mode	Bluetooth	WLAN	WLAN	WLAN	WLAN
			2.4GHz	5.3GHz	5.6GHz	5.8GHz
Calculated Frequency(MHz)		2480	2462	5320	5700	5825
Bottom Side of Laptop	Distance to User (mm)	6.00				
	Max Power (dBm)	10.50	19.00	16.00	15.00	16.00
	Max. Power (mW)	11.22	79.43	39.81	31.62	39.81
	Exclusion Threshold (mW)	3.85	3.87	2.15	2.04	2.01
	SAR Test Required	Yes	Yes	Yes	Yes	Yes

Main Antenna					
Test Position Configurations	Mode	WLAN	WLAN	WLAN	WLAN
		2.4GHz	5.3GHz	5.6GHz	5.8GHz
Calculated Frequency(MHz)		2462	5320	5700	5825
Bottom Side of Laptop	Distance to User (mm)	6.00			
	Max Power (dBm)	19.00	17.00	17.00	17.00
	Max. Power (mW)	79.43	50.12	50.12	50.12
	Exclusion Threshold (mW)	3.87	2.15	2.04	2.01
	SAR Test Required	Yes	Yes	Yes	Yes

MIMO					
Test Position Configurations	Mode	WLAN	WLAN	WLAN	WLAN
		2.4GHz	5.3GHz	5.6GHz	5.8GHz
Calculated Frequency(MHz)		2462	5320	5700	5825
Bottom Side of Laptop	Distance to User (mm)	6.00			
	Max Power (dBm)	16.00	17.00	17.00	17.00
	Max. Power (mW)	39.81	50.12	50.12	50.12
	Exclusion Threshold (mW)	3.87	2.15	2.04	2.01
	SAR Test Required	Yes	Yes	Yes	Yes

Note:

1. Maximum power is the source-based time-average power and represents the maximum RF output power including tune-up tolerance among production units
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
4. Per KDB 447498 D04, for separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive), the threshold P_{th} (mW) is given by Following:

$$P_{th}(mW) = \begin{cases} ERP_{20cm}(d/20cm)^x & d \leq 20cm \\ ERP_{20cm} & 20cm < d \leq 40cm \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right)$$

- a. f (GHz) is the RF channel transmit frequency in GHz
- b. d is the separation distance (cm), The result is rounded to one decimal place for comparison
- c. ERP_{20cm} are determined by:

$$ERP_{20cm}(mW) = f(x) = \begin{cases} 2040f & 0.3GHz \leq f < 1.5GHz \\ 3060 & 1.5GHz \leq f \leq 6GHz \end{cases}$$

5. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion.8. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate
6. Per KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions.
 - a. When KDB Publication 447498 D04 SAR test exclusion applies to the OFDM configuration.
 - b. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
7. Per KDB 248227 D01 SAR is not required for the following U-NII-1 and U-NII-2A bands conditions.
 - a. When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
 - b. When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

10 TEST RESULT

10.1 WIFI 2.4GHz

Mode	Antenna	Test Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
Body															
802.11b	Aux.	Laptop	Bottom Side	0	6	2437	-0.12	0.819	18.85	19.00	1.035	99.32	1.007	0.854	1#
802.11b	Aux.	Laptop	Bottom Side	0	1	2412	0.04	0.769	18.63	19.00	1.089	99.32	1.007	0.843	/
802.11b	Aux.	Laptop	Bottom Side	0	11	2462	-0.08	0.588	18.58	19.00	1.102	99.32	1.007	0.652	/
802.11b	Main	Laptop	Bottom Side	0	6	2437	0.19	0.357	18.75	19.00	1.059	99.32	1.007	0.381	2#
802.11n40	MIMO	Laptop	Bottom Side	0	3	2422	0.16	0.258	15.84	16.00	1.038	98.76	1.013	0.271	3#
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

10.2WIFI 5GHz

Mode	Antenna	Test Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
5.3 G-Body															
802.11 ac (VHT80)	Aux.	Laptop	Bottom Side	0	58	5290	0.17	1.070	15.58	16.00	1.102	99.00	1.010	1.190	4#
802.11 ac (VHT80)	Main	Laptop	Bottom Side	0	58	5290	0.14	0.876	16.72	17.00	1.067	99.00	1.010	0.944	5#
802.11 ac (VHT80)	MIMO	Laptop	Bottom Side	0	58	5290	-0.06	0.618	16.66	17.00	1.081	99.00	1.010	0.675	6#
5.6 G-Body															
802.11 ac (VHT160)	Aux.	Laptop	Bottom Side	0	114	5570	0.16	0.948	14.60	15.00	1.096	99.00	1.010	1.050	7#
802.11 ac (VHT80)	Main	Laptop	Bottom Side	0	106	5530	0.05	0.749	16.58	17.00	1.102	99.00	1.010	0.833	/
802.11 ac (VHT80)	Main	Laptop	Bottom Side	0	122	5610	-0.06	0.845	16.42	17.00	1.143	99.00	1.010	0.975	8#
802.11 ac (VHT80)	Main	Laptop	Bottom Side	0	138	5690	0.09	0.850	16.55	17.00	1.109	99.00	1.010	0.952	/
802.11 ac (VHT160)	MIMO	Laptop	Bottom Side	0	114	5570	0.07	0.654	16.62	17.00	1.091	99.00	1.010	0.721	9#
5.8 G-Body															
802.11 ac (VHT80)	Aux.	Laptop	Bottom Side	0	155	5775	0.15	0.768	15.49	16.00	1.125	99.00	1.010	0.872	10#
802.11 ac (VHT80)	Main	Laptop	Bottom Side	0	155	5775	-0.04	0.866	16.48	17.00	1.127	99.00	1.010	0.986	11#
802.11 ac (VHT80)	MIMO	Laptop	Bottom Side	0	155	5775	0.18	0.690	16.56	17.00	1.107	99.00	1.010	0.771	12#
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

10.3 Bluetooth

Mode	Antenna	Test Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle (%)	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
Body															
DH5	Aux.	Laptop	Bottom Side	0	78	2480	0.05	0.044	9.73	10.50	1.194	76.88	1.301	0.068	13#
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Frequency Band (MHz)	Wireless Band	Antenna	Test Position	Highest Measured SAR (W/kg)	Repeated SAR (Yes/No)	Repeated ^{1st} Measured SAR (W/kg)	Largest to Smallest SAR Radio
2450	WLAN 2.4G	Auxiliary	Bottom Side	0.819	Yes	0.803	1.02
5300	WLAN 5.3G	Auxiliary	Bottom Side	1.070	Yes	1.050	1.02
5300	WLAN 5.3G	Main	Bottom Side	0.876	Yes	0.852	1.03
5600	WLAN 5.6G	Auxiliary	Bottom Side	0.948	Yes	0.931	1.02
5600	WLAN 5.6G	Main	Bottom Side	0.845	Yes	0.845	1.00
5800	WLAN 5.8G	Main	Bottom Side	0.866	Yes	0.858	1.01

Note: The ratio of largest to smallest SAR for the original and first repeated measurements is < 1.20 , the second repeated measurement. is not required.

12 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

According KDB 447498 D04, simultaneous transmission:

- a) $SPLSR = (SAR1 + SAR2)^{1.5} / R_i$ (min. separation distance, mm), and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
SAR1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.
SAR2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition as the first.
- b) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
- c) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

12.1 Simultaneous Transmission Mode Considerations

NO.	Mode	Body
1	2.4 G WLAN (Main Antenna)	+ 2.4 G WLAN (Auxiliary Antenna)
2	2.4 G WLAN (Main Antenna)	+ Bluetooth (Auxiliary Antenna)
3	5 G WLAN (Main Antenna)	+ 5 G WLAN (Auxiliary Antenna)
4	5 G WLAN (Main Antenna)	+ Bluetooth (Auxiliary Antenna)
5	5 G WLAN (Main Antenna)	+ 5 G WLAN (Auxiliary Antenna) + Bluetooth (Auxiliary Antenna)

Note:

- The EUT supports the Auxiliary antenna with TX/RX diversity function for WLAN and Bluetooth, the Main antenna with TX/RX diversity function for WLAN.
- WLAN 2.4GHz and Bluetooth will not be transmitting from the Auxiliary antenna at same time.
- 2.4G WLAN can't transmit simultaneously with 5G WLAN.

12.2 Sum SAR of Simultaneous Transmission

12.2.1 Highest Bluetooth and WLAN Sum Body SAR of Simultaneous Transmission

Test Mode	Position	Mode	Max. 1g SAR (W/kg)	1g Sum SAR (W/kg)	SPLSR (Yes/No)	SPLSR Num.
Body (Separation 0 mm)						
Laptop	Bottom Side	2.4 G WLAN Antenna MIMO	0.271	/	No	/
		2.4 G WLAN Antenna Main	0.381	0.449	No	/
		Bluetooth	0.068			
		5.3 G WLAN Antenna MIMO	0.675	/	No	/
		5.3 G WLAN Antenna Main	0.944	1.012	No	/
		Bluetooth	0.068			
		5.3 G WLAN Antenna Auxiliary	1.190	1.258	No	/
		Bluetooth	0.068			
		5.3 G WLAN Antenna MIMO	0.675	0.743	No	/
		Bluetooth	0.068			
		5.6 G WLAN Antenna MIMO	0.721	/	No	/
		5.6 G WLAN Antenna Main	0.975	1.043	No	/
		Bluetooth	0.068			
		5.6 G WLAN Antenna Auxiliary	1.050	1.118	No	/
		Bluetooth	0.068			
		5.6 G WLAN Antenna MIMO	0.721	0.789	No	/
		Bluetooth	0.068			
		5.8 G WLAN Antenna MIMO	0.771	/	No	/
		5.8 G WLAN Antenna Main	0.986	1.054	No	/
		Bluetooth	0.068			
		5.8 G WLAN Antenna Auxiliary	0.872	0.940	No	/
		Bluetooth	0.068			
		5.8 G WLAN Antenna MIMO	0.771	0.839	No	/
		Bluetooth	0.068			

13 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY5	52.8.8.1222	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2021/05/19	2024/05/18
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2021/05/18	2024/05/17
E-Field Probe	Speag	EX3DV4	SN: 7510	2021/12/29	2022/12/28
Data Acquisition Electronicsr	Speag	DAE4	SN: 1454	2021/11/05	2022/11/04
Signal Generator	R&S	SMB100A	182396	2021/12/20	2022/12/19
Power Meter	R&S	NRVD-B2	7250BJ-0112/2011	2021/09/08	2022/09/07
Power Sensor	R&S	NRV-Z4	100381	2021/09/08	2022/09/07
Power Sensor	R&S	NRV-Z2	100211	2021/09/08	2022/09/07
Network Analyzer	Agilent	E5071C	MY46103472	2021/12/29	2022/12/28
Thermometer	Elitech	RC-4HC	EF720B004801	2021/12/22	2022/12/21
Thermometer	Elitech	RC-4HC	EF720B004820	2021/12/22	2022/12/21
Power Amplifier	SATIMO	6552B	22374	N/A	N/A
Dielectric Probe Kit	Speag	DAK3.5	SN: 1312	N/A	N/A
Phantom	Speag	SAM	SN: 1859	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK3.5 Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2022.09.03	Head	2450	21.2	1.83	38.06	1.80	39.20	1.67	-2.91
2022.09.04	Head	5250	21.7	4.72	36.51	4.71	35.93	0.21	1.61
2022.09.05	Head	5600	21.6	5.01	35.64	5.07	35.53	-1.18	0.31
2022.09.06	Head	5750	21.9	5.07	35.93	5.22	35.36	-2.87	1.61
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2022.09.03	Head	2450	100	5.180	51.80	53.00	-2.26
2022.09.04	Head	5250	100	7.920	79.20	77.80	1.80
2022.09.05	Head	5600	100	8.320	83.20	81.20	2.46
2022.09.06	Head	5750	100	7.620	76.20	77.20	-1.30

Note: The tolerance limit of System validation $\pm 10\%$.

System Performance Check Data (2450MHz)

Date: 2022.09.03

Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.83$ S/m; $\epsilon_r = 38.063$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.1°C Liquid Temperature: 21.2°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(7.63, 7.63, 7.63); Calibrated: 2021.12.29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 2450 100mW/Area Scan (101x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 5.78 W/kg


CW 2450 100mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.59 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 11.4 W/kg

SAR(1 g) = 5.18 W/kg; SAR(10 g) = 2.34 W/kg

Maximum value of SAR (measured) = 5.68 W/kg



System Performance Check Data (5250MHz)

Date: 2022.09.04

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.715$ S/m; $\epsilon_r = 36.505$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.5°C Liquid Temperature: 21.7°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(5.42, 5.42, 5.42); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 5250 100mW/Area Scan (101x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 8.52 W/kg


CW 5250 100mW/Zoom Scan (7x7x21)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 35.63 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 31.9 W/kg

SAR(1 g) = 7.92 W/kg; SAR(10 g) = 2.26 W/kg

Maximum value of SAR (measured) = 18.2 W/kg



System Performance Check Data (5600MHz)

Date: 2022.09.05

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.009$ S/m; $\epsilon_r = 35.637$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.2°C Liquid Temperature: 21.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.81, 4.81, 4.81); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 5600 100mW/Area Scan (101x101x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 9.53 W/kg


CW 5600 100mW/Zoom Scan (7x7x21)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 33.48 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 38.1 W/kg

SAR(1 g) = 8.32 W/kg; SAR(10 g) = 2.38 W/kg

Maximum value of SAR (measured) = 16.3 W/kg



0 dB = 16.3 W/kg

System Performance Check Data (5750MHz)

Date: 2022.09.06

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 5750$ MHz; $\sigma = 5.073$ S/m; $\epsilon_r = 35.926$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.8°C Liquid Temperature: 21.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.9, 4.9, 4.9); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

CW 5750 100mW/Area Scan (81x101x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 8.35 W/kg


CW 5750 100mW/Zoom Scan (7x7x21)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 28.48 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 38.2 W/kg

SAR(1 g) = 7.62 W/kg; SAR(10 g) = 2.12 W/kg

Maximum value of SAR (measured) = 16.1 W/kg



0 dB = 16.1 W/kg

ANNEX C TEST DATA

Meas.1 Body Plane with Bottom Side 0mm on 6 Channel in IEEE802.11b mode with Antenna Auxiliary

Date: 2022.09.03

Communication System Band: WLAN(b); Frequency: 2437 MHz; Duty Cycle: 1:1.007

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.815$ S/m; $\epsilon_r = 38.254$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.1°C Liquid Temperature: 21.2°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(7.63, 7.63, 7.63); Calibrated: 2021.12.29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch6/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.780 W/kg


Ch6/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.96 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 2.33 W/kg

SAR(1 g) = 0.819 W/kg; SAR(10 g) = 0.303 W/kg

Maximum value of SAR (measured) = 0.985 W/kg



0 dB = 0.985 W/kg

Meas.2 Body Plane with Bottom Side 0mm on 6 Channel in IEEE802.11b mode with Antenna Main

Date: 2022.09.03

Communication System Band: WLAN(b); Frequency: 2437 MHz; Duty Cycle: 1:1.007

Medium parameters used (interpolated): $f = 2437$ MHz; $\sigma = 1.815$ S/m; $\epsilon_r = 38.254$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.1°C Liquid Temperature: 21.2°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(7.63, 7.63, 7.63); Calibrated: 2021.12.29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch6/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.410 W/kg


Ch6/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.851 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.920 W/kg

SAR(1 g) = 0.357 W/kg; SAR(10 g) = 0.158 W/kg

Maximum value of SAR (measured) = 0.433 W/kg



0 dB = 0.433 W/kg

Meas.3 Body Plane with Bottom Side 0mm on 3 Channel in IEEE802.11n40 mode with Antenna MIMO

Date: 2022.09.03

Communication System Band: WLAN(n) 40Mhz; Frequency: 2422 MHz;Duty Cycle: 1:1.013

Medium parameters used (interpolated): $f = 2422$ MHz; $\sigma = 1.8$ S/m; $\epsilon_r = 38.369$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.1°C Liquid Temperature:21.2°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(7.63, 7.63, 7.63); Calibrated: 2021.12.29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch3/Area Scan (91x151x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.332 W/kg


Ch3/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.9240 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.725 W/kg

SAR(1 g) = 0.258 W/kg; SAR(10 g) = 0.102 W/kg

Maximum value of SAR (measured) = 0.313 W/kg



0 dB = 0.313 W/kg

Meas.4 Body Plane with Bottom Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Date: 2022.09.04

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5290 MHz;Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.78$ S/m; $\epsilon_r = 36.359$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.5°C Liquid Temperature:21.7°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(5.42, 5.42, 5.42); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch58/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.72 W/kg


Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 3.719 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 5.40 W/kg

SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.286 W/kg

Maximum value of SAR (measured) = 2.42 W/kg



0 dB = 2.42 W/kg

Meas.5 Body Plane with Bottom Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Main

Date: 2022.09.04

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5290 MHz;Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.78$ S/m; $\epsilon_r = 36.359$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.5°C Liquid Temperature:21.7°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(5.42, 5.42, 5.42); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch58/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.91 W/kg


Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 9.101 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 3.75 W/kg

SAR(1 g) = 0.876 W/kg; SAR(10 g) = 0.278 W/kg

Maximum value of SAR (measured) = 1.74 W/kg



0 dB = 1.74 W/kg

Meas.6 Body Plane with Bottom Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna MIMO

Date: 2022.09.04

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5290 MHz; Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5290$ MHz; $\sigma = 4.78$ S/m; $\epsilon_r = 36.359$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.5°C Liquid Temperature: 21.7°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(5.42, 5.42, 5.42); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch58/Area Scan (111x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.17 W/kg


Ch58/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 7.891 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 2.87 W/kg

SAR(1 g) = 0.618 W/kg; SAR(10 g) = 0.178 W/kg

Maximum value of SAR (measured) = 1.24 W/kg



Meas.7 Body Plane with Bottom Side 0mm on 114 Channel in IEEE802.11ac160 mode with Antenna Auxiliary

Date: 2022.09.05

Communication System Band: WLAN(ac) 160Mhz; Frequency: 5570 MHz; Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5570$ MHz; $\sigma = 4.974$ S/m; $\epsilon_r = 35.708$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.2°C Liquid Temperature: 21.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.81, 4.81, 4.81); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch114/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.07 W/kg


Ch114/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.185 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 4.55 W/kg

SAR(1 g) = 0.948 W/kg; SAR(10 g) = 0.241 W/kg

Maximum value of SAR (measured) = 2.06 W/kg



Meas.8 Body Plane with Bottom Side 0mm on 122 Channel in IEEE802.11ac80 mode with Antenna Main

Date: 2022.09.05

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5610 MHz;Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5610$ MHz; $\sigma = 5.011$ S/m; $\epsilon_r = 35.63$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.2°C Liquid Temperature:21.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.81, 4.81, 4.81); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch122/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.79 W/kg


Ch122/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 10.55 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 3.91 W/kg

SAR(1 g) = 0.845 W/kg; SAR(10 g) = 0.255 W/kg

Maximum value of SAR (measured) = 1.74 W/kg



0 dB = 1.74 W/kg

Meas.9 Body Plane with Bottom Side 0mm on 114 Channel in IEEE802.11ac160 mode with Antenna MIMO

Date: 2022.09.05

Communication System Band: WLAN(ac) 160Mhz; Frequency: 5570 MHz; Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5570$ MHz; $\sigma = 4.974$ S/m; $\epsilon_r = 35.708$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.2°C Liquid Temperature: 21.6°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.81, 4.81, 4.81); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch114/Area Scan (111x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.40 W/kg


Ch114/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.447 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 3.08 W/kg

SAR(1 g) = 0.654 W/kg; SAR(10 g) = 0.185 W/kg

Maximum value of SAR (measured) = 1.38 W/kg



0 dB = 1.38 W/kg

Meas.10 Body Plane with Bottom Side 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Date: 2022.09.06

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5775 MHz;Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5775$ MHz; $\sigma = 5.103$ S/m; $\epsilon_r = 35.818$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.8°C Liquid Temperature:21.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.9, 4.9, 4.9); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch155/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.52 W/kg

Ch155/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.456 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.15 W/kg

SAR(1 g) = 0.768 W/kg; SAR(10 g) = 0.198 W/kg

Maximum value of SAR (measured) = 1.66 W/kg



Meas.11 Body Plane with Bottom Side 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Main

Date: 2022.09.06

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5775 MHz; Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5775$ MHz; $\sigma = 5.103$ S/m; $\epsilon_r = 35.818$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.8°C Liquid Temperature: 21.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.9, 4.9, 4.9); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch155/Area Scan (111x111x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.93 W/kg


Ch155/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 4.578 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 4.14 W/kg

SAR(1 g) = 0.866 W/kg; SAR(10 g) = 0.251 W/kg

Maximum value of SAR (measured) = 1.93 W/kg



0 dB = 1.93 W/kg

Meas.12 Body Plane with Bottom Side 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna MIMO

Date: 2022.09.06

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5775 MHz;Duty Cycle: 1:1.01

Medium parameters used (interpolated): $f = 5775$ MHz; $\sigma = 5.103$ S/m; $\epsilon_r = 35.818$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature:22.8°C Liquid Temperature:21.9°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(4.9, 4.9, 4.9); Calibrated: 2021.12.29;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch155/Area Scan (111x161x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.35 W/kg


Ch155/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.271 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 3.30 W/kg

SAR(1 g) = 0.690 W/kg; SAR(10 g) = 0.203 W/kg

Maximum value of SAR (measured) = 1.46 W/kg



Meas.13 Body Plane with Bottom Side 0mm on 78 Channel in Bluetooth mode with Antenna Auxiliary

Date: 2022.09.03

Communication System Band: Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1.301

Medium parameters used (interpolated): $f = 2480$ MHz; $\sigma = 1.869$ S/m; $\epsilon_r = 37.835$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Ambient Temperature: 22.1°C Liquid Temperature: 21.2°C

DASY5 Configuration:

- Probe: EX3DV4 - SN7510; ConvF(7.63, 7.63, 7.63); Calibrated: 2021.12.29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1454; Calibrated: 2021.11.05
- Phantom: SAM (20deg probe tilt) with CRP v5.0 on left 1859; Type: QD000P40CC; Serial: TP:1859
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch78/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0763 W/kg


Ch78/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.125 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.0970 W/kg

SAR(1 g) = 0.044 W/kg; SAR(10 g) = 0.016 W/kg

Maximum value of SAR (measured) = 0.0528 W/kg



0 dB = 0.0528 W/kg

ANNEX D EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2280937-AW.pdf”.

ANNEX E SAR TEST SETUP PHOTOS

Please refer the document “BL-SZ2280937-AS.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “CALIBRATION REPORT.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--