



Connect Display 21"

PoE-powered, 21.5" Full HD touchscreen display designed for UniFi Connect.

The Connect Display 21" (UC Display21) is a PoE-powered, HD touchscreen display designed for UniFi Connect. The UC Display21 offers robust functionality with its two presentation modes: Digital Signage and Protect. In Digital Signage Mode, the UC Display21 showcases your custom, multimedia playlists in either landscape or portrait mode, and gives you the ability to schedule when they are presented. This display is ideal for businesses, hotels, convention centers, and other populated venues that need an intuitive, centrally managed content broadcasting solution to enhance the experience of clients and patrons. In Protect Mode, the UC Display21 provides the same intuitive camera management experience as the UniFi Protect application. With its variety of mounting options, the UC Display21 can be staged virtually anywhere within your space, and can be set up in minutes with the UniFi Connect web application or mobile app.



Mechanical

Dimensions	538.3 x 330 x 37 mm (21.2 x 13 x 1.5")
Weight	4.9 kg (10.8 lb)
Mounting	Table stand (optional) Recessed mount (optional) Surface mount (optional) Arm mount (optional)

Hardware

Display size	546 mm (21.5") diagonal
Resolution	1920 x 1080 FHD (16:9)
Display luminance	250 nits (typical)
Touch screen technology	Capacitive multi-touch
Processor	Octa-core ARM® Cortex®-A53 at 2.2 GHz
Memory	Storage: 32 GB RAM: 2 GB
Power input	802.3bt PoE++
Connectivity	(1) GbE RJ45 port (1) USB-C port (for accessory UC-DisplayCam only) Bluetooth® 4.2 WiFi 2.4G b/g/n/ac, BW 20/40 MHz WiFi 5G a/n/ac, BW 20/40/80 MHz
Button	Factory reset
Sensors	TOF (time of flight), NFC, G sensor (3-axis accelerometer)
NFC reading range	< 10 mm (< 0.4")
NFC standards	ISO 14443A, 14443B, 15693
NFC technology	NFC Tag 1, 2, 3, 4, 5 MIFARE Classic MIFARE Plus MIFARE Ultralight MIFARE DESFire EV1/EV2
Embedded front camera	5 MP
Microphone	Yes
Speaker	Yes
Operating temperature	0 to 40° C (32 to 104° F)



Operating humidity	20 to 90% noncondensing
Certifications	FCC, IC

Software

Application	UniFi Connect
Minimum software requirements	Web browser (Chrome™ recommended)
Mobile apps	UniFi Connect iOS™ and Android™

E-label Access

E-label and warning statements can be found in the device via controller
(Install controller from ui.com/download then select/adopt device) -> overview -> e-label information.



Ubiquiti products are sold with a limited warranty described at ui.com/support/warranty. The limited warranty requires the use of arbitration to resolve disputes on an individual basis, and, where applicable, specifies arbitration instead of jury trials or class actions.

©2021 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, UniFi, and UniFi Connect are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners. 620-00972-04