

FCC Test Report

Report No.: AGC01741231101FR03

FCC ID : 2AYT3-AC200PL

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Portable Power Station

BRAND NAME : BLUETTI

MODEL NAME : AC200P L

APPLICANT: SHENZHEN POWEROAK NEWENER CO., LTD

DATE OF ISSUE : Mar. 04, 2024

STANDARD(S) : FCC Part 15 Subpart C §15.247

REPORT VERSION: V1.0

Attestation of Global Conclance (Shenzhen) Co., Ltd



Page 2 of 97

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar. 04, 2024	Valid	Initial Release



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Table of Carrier Frequency	7
2.3 IEEE 802.11n Modulation Scheme	8
2.4 Related Submittal(S) / Grant (S)	9
2.5 Test Methodology	9
2.6 Special Accessories	9
2.7 Equipment Modifications	9
2.8 Antenna Requirement	9
2.9 Description of Test Software	10
3. Test Environment	11
3.1 Address of The Test Laboratory	11
3.2 Test Facility	11
3.3 Environmental Conditions	12
3.4 Measurement Uncertainty	12
3.5 List of Equipment Used	13
4.System Test Configuration	15
4.1 EUT Configuration	15
4.2 EUT Exercise	15
4.3 Configuration of Tested System	15
4.4 Equipment Used In Tested System	15
4.5 Summary of Test Results	16
5. Description of Test Modes	17
6. Duty Cycle Measurement	
7. RF Output Power Measurement	20
7.1 Provisions Applicable	20
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Result	21
8. 6dB Bandwidth Measurement	22
8.1 Provisions Applicable	22
8.2 Measurement Procedure	22
8.3 Measurement Setup (Block Diagram of Configuration)	22
8.4 Measurement Results	23
9 Power Spectral Density Measurement	36

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Web: http://www.agccert.com/





9.1 Provisions Applicable	36
9.2 Measurement Procedure	36
9.3 Measurement Setup (Block Diagram of Configuration)	37
9.4 Measurement Result	37
10. Conducted Band Edge and Out-of-Band Emissions	44
10.1 Provisions Applicable	44
10.2 Measurement Procedure	44
10.3 Measurement Setup (Block Diagram of Configuration)	44
10.4 Measurement Results	45
11. Radiated Spurious Emission	59
11.1 Measurement Limits	59
11.2 Measurement Procedure	59
11.3 Measurement Setup (Block Diagram of Configuration)	62
11.4 Measurement Result	63
12. AC Power Line Conducted Emission	93
12.1 Measurement Limits	93
12.2 Block Diagram of Line Conducted Emission Test	93
12.3 Preliminary Procedure of Line Conducted Emission Test	94
12.4 Final Procedure of Line Conducted Emission Test	94
12.5 Test Result of Line Conducted Emission Test	94
Appendix I: Photographs of Test Setup	97
Appendix II: Photographs of EUT	97



Page 5 of 97

1. General Information

Applicant	SHENZHEN POWEROAK NEWENER CO., LTD
Address	F19, BLD No.1, Kaidaer Tongsha Rd No.168, Xili Street, Nanshan, Shenzhen, China
Manufacturer	SHENZHEN POWEROAK NEWENER CO., LTD
Address	F19, BLD No.1, Kaidaer Tongsha Rd No.168, Xili Street, Nanshan, Shenzhen, China
Factory	Huizhou PowerOak Innovation Co.,Ltd
Address	(No.1 Workshop)Longsheng 5th Road, Laoshe Village, Dayawan West Zone, Huizhou, Guangdong, China
Product Designation	Portable Power Station
Brand Name	BLUETTI
Test Model	AC200P L
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Jan. 02, 2024
Date of Test	Jan. 02, 2024 – Mar. 01, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-2.4GWLAN-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Alan Duan
(Project Engineer)

Reviewed By

Calvin Liu
(Reviewer)

Mar. 04, 2024



Page 6 of 97

2. Product Information

2.1 Product Technical Description

Equipment Type	WLAN 2.4G
Frequency Band	2400MHz ~ 2483.5MHz
Operation Frequency	2412MHz ~ 2462MHz
Output Power (Average)	IEEE 802.11b:17.45dBm; IEEE 802.11g:15.50dBm;
Output Fower (Average)	IEEE 802.11n(HT20):15.58dBm; IEEE 802.11n(HT40):14.75dBm
Output Power (Peak)	IEEE 802.11b:23.71dBm; IEEE 802.11g:23.15dBm;
Output I Ower (I earl)	IEEE 802.11n(HT20):23.49dBm; IEEE 802.11n(HT40):22.56dBm
Modulation	802.11b:(DQPSK, DBPSK, CCK) DSSS
Wiodalation	802.11g/n:(64-QAM,16-QAM, QPSK, BPSK) OFDM
	802.11b:1/2/5.5/11Mbps
Data Rate	802.11g: 6/9/12/18/24/36/48/54Mbps
	802.11n: up to 300Mbps
Number of channels	11
Hardware Version	V6.0
Software Version	2034
Antenna Designation	PCB Antenna
Antenna Gain	3.42dBi
	AC: 120V~50/60Hz, 20A Max.
Input Rating	DC: 12V-30V=8A PV: 12V-145V=15A Max.
, G	Battery Expansion: 51.2V=60A Max.
	AC: 120V~50/60Hz, 2400W Max.
	Aviation Sockets: 48V=8A
	USB-A: 5V=3A, 9V=2A, 12V=1.5A, 18W Each
Output Rating	USB-C: 5/9/12/15/20V=3A, 20V=5A Cigarette Lighter Port: 12V=10A
	Wireless Charging: 5/7.5/10/15W
	AC and DC Output: 2500W Total
	Battery Expansion: 51.2V=60A Max.



Page 7 of 97

2.2 Table of Carrier Frequency For 2412-2462MHz:

11 channels are provided for 802.11b/g/n(HT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz		

7 channels are provided for 802.11n(HT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency
01		02		03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10		11			



Page 8 of 97

2.3 IEEE 802.11n Modulation Scheme

MCS	I Nss I Modulation I R		Nss	R N _{Bi}	R	n R	N _{BPSC}	N _C	BPS	N _D	BPS	Rate(ata Mbps) nsGI
Index					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz			
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5			
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0			
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5			
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0			
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0			
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0			
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5			
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0			

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval



Page 9 of 97

2.4 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: 2AYT3-AC200PL, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.5 Test Methodology

The tests were performed according to following standards:

	· · · · · · · · · · · · · · · · · · ·	
No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 662911	KDB 662911 D01 Multiple Transmitter Output v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)

2.6 Special Accessories

Refer to section 5.2.

2.7 Equipment Modifications

Not available for this EUT intended for grant.

2.8 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 3.42dBi.



2.9 Description of Test Software

For IEEE 802.11 mode:

Software Setting Diagram



Test Mode	Channel	Power Index
802.11b	L/M/H	0
802.11g	L/M/H	0
802.11n-HT20	L/M/H	0
802.11n-HT40	L/M/H	0



Page 11 of 97

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 12 of 97

3.3 Environmental Conditions

	Normal Conditions
Temperature range (°ℂ)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106

3.4 Measurement Uncertainty

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$		



Page 13 of 97

3.5 List of Equipment Used

• R	RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2023-06-01	2024-05-31		
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2023-03-03	2024-03-02		
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2023-03-03	2024-03-02		
\boxtimes	AGC-EM-A152	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08		
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2023-06-01	2024-05-31		
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A		
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A		

• F	Radiated Spurious Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2023-02-18	2024-02-17		
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31		
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023-06-03	2024-06-02		
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31		
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2022-03-12	2024-03-11		
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10		
\boxtimes	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2023-03-23	2024-03-22		
	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23		
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03		
\boxtimes	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2023-06-01	2024-05-31		
\boxtimes	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08		
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08		

A	AC Power Line Conducted Emission									
Used Equipment No. Test Equipment Manufacturer Model No.		Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)					
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2023-06-03	2024-06-02			
\boxtimes	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2023-06-03	2024-06-02			
\boxtimes	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2024-06-08			



Page 14 of 97

• Te	Test Software								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information				
\boxtimes	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A				
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS ⁺ Ver2.1(JS36-RSE)	4.0.0.0				
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71				
\boxtimes	AGC-ER-S009	BT/WIFI Test System	Tonscend	JS1120-3	2.6.77.0518				



Page 15 of 97

4.System Test Configuration


4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System



4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	AC POWER LINE				1.0m,unshielded

☐ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1					



Page 16 of 97

4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(3)	RF Output Power	Pass
3	§15.247 (a)(2)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
5	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
6	§15.247 (d)&15.209	Radiated Spurious Emission	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



Page 17 of 97

5. Description of Test Modes

	Summary table of Test Cases						
	Data Rate / Modulation						
Test Item	2.4G WLAN - 802.11b/g/n (DSSS/OFDM)						
Radiated & Conducted Test Cases	Mode 1: 802.11b_TX CH01_2412 MHz_1 Mbps(Battery powered or AC input) Mode 2: 802.11b_TX CH06_2437 MHz_1 Mbps(Battery powered or AC input) Mode 3: 802.11b_TX CH11_2462 MHz_1 Mbps(Battery powered or AC input) Mode 4: 802.11g_TX CH01_2412 MHz_6 Mbps(Battery powered or AC input) Mode 5: 802.11g_TX CH06_2437 MHz_6 Mbps(Battery powered or AC input) Mode 6: 802.11g_TX CH11_2462 MHz_6 Mbps (Battery powered or AC input) Mode 7: 802.11n-HT20_TX CH01_2412 MHz_MCS0 Mbps(Battery powered or AC input) Mode 8: 802.11n-HT20_TX CH06_2437 MHz_ MCS0 Mbps(Battery powered or AC input) Mode 9: 802.11n-HT20_TX CH11_2462 MHz_MCS0 Mbps(Battery powered or AC input) Mode 10: 802.11n-HT40_TX CH03_2422 MHz_MCS0 Mbps(Battery powered or AC input) Mode 11: 802.11n-HT40_TX CH06_2437 MHz_ MCS0 Mbps(Battery powered or AC input) Mode 12: 802.11n-HT40_TX CH09_2452 MHz_ MCS0 Mbps(Battery powered or AC input)						
AC Conducted Emission	Mode 1: 2.4G WLAN Link + Battery + Charging from AC input						

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.



Page 18 of 97


6. Duty Cycle Measurement

2.4GHz WLAN (DTS) operation is possible in 20MHz, and 40MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	Data rates (Mbps)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
IEEE 802.11b	1	100			
IEEE 802.11g	6	100			
IEEE 802.11n-HT20	MCS0	100			
IEEE 802.11n-HT40	MCS0	100			


Remark:

- 1. Duty Cycle factor = 10 * log (1/ Duty cycle)
- 2. Average factor = 20 log10 Duty Cycle
- 3. The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value.





The test plots as follows:





Report No.: AGC01741231101FR03 Page 20 of 97

7. RF Output Power Measurement

7.1 Provisions Applicable

For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.

7.2 Measurement Procedure


Method PM is Measurement using an RF Peak power meter. The procedure for this method is as follows:

- 1. The testing follows the ANSI C63.10 Section 11.9.1.3
- 2. The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

☑Method PM is Measurement using an RF average power meter. The procedure for this method is as follows:

- 1. The testing follows the ANSI C63.10 Section 11.9.2.3
- 2. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
- 3. The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
- 4. At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 5. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- 6. Determine according to the duty cycle of the equipment: when it is less than 98%, follow the steps below.
- 7. Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- 8. Adjust the measurement in dBm by adding [10 log (1 / D)], where D is the duty cycle {e.g., [10 log (1 / 0.25)], if the duty cycle is 25%}.
- 9. Record the test results in the report.

7.3 Measurement Setup (Block Diagram of Configuration)





Page 21 of 97

7.4 Measurement Result

	Test Data of Conducted Output Power								
Test Mode	Test Channel (MHz)	Average Power (dBm)	Peak Power (dBm)	Limits (dBm)	Pass or Fail				
	2412	17.45	23.71	≤30	Pass				
802.11b	2437	17.36	23.63	≤30	Pass				
	2462	16.89	23.15	≤30	Pass				
802.11g	2412	15.50	23.15	≤30	Pass				
	2437	14.97	22.60	≤30	Pass				
	2462	14.52	22.13	≤30	Pass				
	2412	15.58	23.49	≤30	Pass				
802.11n20	2437	15.00	22.87	≤30	Pass				
	2462	14.57	22.43	≤30	Pass				
	2422	14.75	22.56	≤30	Pass				
802.11n40	2437	14.39	22.18	≤30	Pass				
	2452	14.07	21.84	≤30	Pass				



Page 22 of 97

8. 6dB Bandwidth Measurement

8.1 Provisions Applicable


The minimum 6dB bandwidth shall be 500 kHz.

8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).

- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss
 was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. For 6dB Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Detector = peak
- 6. Trace mode = max hold.
- 7. Sweep = auto couple.
- 8. Allow the trace to stabilize.
- 9. Measure and record the results in the test report.

8.3 Measurement Setup (Block Diagram of Configuration)






Page 23 of 97


8.4 Measurement Results

	Test Data of Occupied Bandwidth and DTS Bandwidth								
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	DTS Bandwidth (MHz)	DTS Bandwidth Limits (MHz)	Pass or Fail				
	2412	13.115	9.108	≥0.5	Pass				
802.11b	2437	13.149	9.107	≥0.5	Pass				
	2462	13.146	9.100	≥0.5	Pass				
	2412	16.394	16.515	≥0.5	Pass				
802.11g	2437	16.427	16.512	≥0.5	Pass				
	2462	16.429	16.516	≥0.5	Pass				
	2412	17.297	17.322	≥0.5	Pass				
802.11n20	2437	17.319	17.316	≥0.5	Pass				
	2462	17.328	17.326	≥0.5	Pass				
	2422	34.435	33.489	≥0.5	Pass				
802.11n40	2437	34.424	33.438	≥0.5	Pass				
	2452	34.488	33.185	≥0.5	Pass				







Test Graphs of Occupied Bandwidth




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.














































Test Graphs of DTS Bandwidth




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

















Test_Graph_802.11g_ANT1_2462_6Mbps_DTSBW























Page 36 of 97

9. Power Spectral Density Measurement

9.1 Provisions Applicable

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure


For Peak power spectral density test:

- The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 3. Set the RBW = 20 kHz.
- Set the VBW \geq [3 × RBW]. 4.
- Set the Span ≥ [1.5 × DTS bandwidth]. 5.
- 6. Sweep time=Auto couple.
- 7. Detector function=Peak.
- Trace Mode=Max hold. 8.
- When the measurement bandwidth of Maximum PSD is specified in 3 kHz, add a constant factor 10*log(3kHz/20kHz) = -8.23 dB to the measured result.
- 10. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission.
- 11. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- For Average power spectral density test:
- The testing follows the ANSI C63.10 Section 11.10.5 Method AVPSD. 1.
- 2. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator.
- 3. Set Span to at least 1.5 times the OBW.
- Set RBW to:3 kHz ≤ RBW ≤ 100 kHz. 4.
- Set VBW≥[3×RBW]. 5.
- Sweep Time=Auto couple. 6.
- 7. Detector function=RMS (i.e., power averaging).
- 8. Trace average at least 100 traces in power averaging (rms) mode.
- When the measurement bandwidth of Maximum PSD is specified in 3 kHz, add a constant 9. factor 10*log(3kHz/20kHz) = -8.23 dB to the measured result.
- Determine according to the duty cycle of the equipment: when it is less than 98%, follow the steps below.
- 11. Add [10 log (1 / D)], where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add [10 log (1/0.25)] = 6 dB if the duty cycle is 25%.
- 12. Record the test results in the report.




Page 37 of 97

9.3 Measurement Setup (Block Diagram of Configuration)




9.4 Measurement Result


	Test Data of Conducted Output Power Spectral Density						
Test Mode	Test Channel (MHz)			Limit (dBm/3kHz)	Pass or Fail		
	2412	1.528	-6.711	≪8	Pass		
802.11b	2437	1.465	-6.774	≪8	Pass		
	2462	0.989	-7.25	≪8	Pass		
	2412	-3.528	-11.767	≪8	Pass		
802.11g	2437	-4.198	-12.437	≪8	Pass		
	2462	-4.463	-12.702	≪8	Pass		
	2412	-3.108	-11.347	≪8	Pass		
802.11n20	2437	-3.839	-12.078	≪8	Pass		
	2462	-4.229	-12.468	≪8	Pass		
	2422	-6.127	-14.366	≪8	Pass		
802.11n40	2437	-6.452	-14.691	≪8	Pass		
	2452	-6.973	-15.212	≪8	Pass		





Test Graphs of Conducted Output Power Spectral Density






Freq Offset 0 Hz

Scale Type

Log

Span 24.77 MHz Sweep 59.07 ms (1000 pts)






Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11g_ANT1_2412_6Mbps_PSD

#VBW 62 kHz

Center 2.41200 GHz #Res BW 20 kHz





Test_Graph_802.11g_ANT1_2462_6Mbps_PSD

#VBW 62 kHz

Span 24.77 MHz Sweep 59.07 ms (1000 pts)

Log

Center 2.46200 GHz #Res BW 20 kHz


0 Hz

Scale Type

Log

Span 25.97 MHz Sweep 61.94 ms (1000 pts)





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11n20_ANT1_2437_MCS0_PSD

#VBW 62 kHz


Center 2.43700 GHz #Res BW 20 kHz

Scale Type

Log

Span 50.23 MHz Sweep 119.7 ms (1000 pts)





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11n40_ANT1_2422_MCS0_PSD

#VBW 62 kHz

Center 2.42200 GHz #Res BW 20 kHz

4.977750 MHz

Freq Offset 0 Hz

Scale Type


Mar

<u>Auto</u>

Log

Span 49.78 MHz Sweep 118.7 ms (1000 pts)





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11n40_ANT1_2452_MCS0_PSD

#VBW 62 kHz

Center 2.45200 GHz #Res BW 20 kHz



Page 44 of 97

10. Conducted Band Edge and Out-of-Band Emissions

10.1 Provisions Applicable

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

10.2 Measurement Procedure


Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Use the following spectrum analyzer settings:

- Step 1: Measurement Procedure In-Band Reference Level
 - 1. Set instrument center frequency to DTS channel center frequency.
 - 2. Set the span to ≥ 1.5 times the DTS bandwidth.
 - 3. Set the RBW = 100 kHz.
 - 4. Set the VBW \geq 3 x RBW.
 - 5. Detector = peak.
 - 6. Sweep time = auto couple.
 - 7. Trace mode = max hold.
 - 8. Allow trace to fully stabilize.
 - 9. Use the peak marker function to determine the maximum PSD level.
 - 10. Note that the channel found to contain the maximum PSD level can be used to establish the reference level.
- Step 2: Measurement Procedure Out of Band Emission
 - 1. Set RBW = 100 kHz.
 - 2. Set VBW ≥ 300 kHz.
 - 3. Detector = peak.
 - 4. Sweep = auto couple.
 - 5. Trace Mode = max hold.
 - 6. Allow trace to fully stabilize.7. Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

10.3 Measurement Setup (Block Diagram of Configuration)



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




10.4 Measurement Results

Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands





Test_Graph_802.11b_ANT1_2412_1Mbps_Lower Band Emissions










































Test_Graph_802.11g_ANT1_2437_6Mbps_Higher Band Emissions




































































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test_Graph_802.11g_ANT1_2412_6Mbps_Lower Band Edge Emissions





Note: Emissions from 2483.5-2500MHz which fall in the restricted bands had been considered with the radiated emission limits specified.



Page 59 of 97

11. Radiated Spurious Emission

11.1 Measurement Limits

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Any reposphang alternative (provided the funding alternative (provided the funding alternative by the



Page 60 of 97

pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.
- ◆ The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start Stan Fraguency	1GHz~26.5GHz
Start ~Stop Frequency	1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP



Page 61 of 97

Quasi-Peak Measurements below 1GHz

- Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- Detector = CISPR quasi-peak 4.
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- VBW = 3MHz3.
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- Trace was allowed to stabilize 7.


Average Measurements above 1GHz (Method VB)

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.
- If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration. 5.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold




11.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz








11.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.


•	•				
Radiated Emission Test Results at 30MHz-1GHz					
EUT Name	Portable Power Station	Model Name	AC200P L		
Temperature	22.6°C	Relative Humidity	60.5%		
Pressure	960hPa	Test Voltage	AC 120V, 60Hz		
Test Mode	Mode 1	Polarity:	Horizontal		



No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		104.5361	16.87	16.25	33.12	43.50	-10.38	peak
2		199.2855	18.59	14.42	33.01	43.50	-10.49	peak
3		240.8303	21.70	15.38	37.08	46.00	-8.92	peak
4		299.3158	17.23	16.45	33.68	46.00	-12.32	peak
5		403.2500	15.06	20.46	35.52	46.00	-10.48	peak
6	*	942.1304	8.95	28.89	37.84	46.00	-8.16	peak



Radiated Emission Test Results at 30MHz-1GHz					
EUT Name	Portable Power Station	Model Name	AC200P L		
Temperature	22.6°C	Relative Humidity	60.5%		
Pressure	960hPa	Test Voltage	AC 120V, 60Hz		
Test Mode	Mode 1	Polarity:	Vertical		



RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.



Page 65 of 97

Radiated Emissions Test Results above 1 GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 1	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.000	55.69	0.08	55.77	74	-18.23	peak
4824.000	46.91	0.08	46.99	54	-7.01	AVG
7236.000	50.21	2.21	52.42	74	-21.58	peak
7236.000	32.42	2.21	34.63	54	-19.37	AVG
		_				

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 1	Antenna Polarity	Vertical

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
54.29	0.08	54.37	74	-19.63	peak
45.28	0.08	45.36	54	-8.64	AVG
44.19	2.21	46.4	74	-27.6	peak
32.54	2.21	34.75	54	-19.25	AVG
	(dBµV) 54.29 45.28 44.19	(dBµV) (dB) 54.29 0.08 45.28 0.08 44.19 2.21	(dBμV) (dB) (dBμV/m) 54.29 0.08 54.37 45.28 0.08 45.36 44.19 2.21 46.4	(dBμV) (dB) (dBμV/m) (dBμV/m) 54.29 0.08 54.37 74 45.28 0.08 45.36 54 44.19 2.21 46.4 74	(dBμV) (dB) (dBμV/m) (dBμV/m) (dBμV/m) 54.29 0.08 54.37 74 -19.63 45.28 0.08 45.36 54 -8.64 44.19 2.21 46.4 74 -27.6

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: Pass



Page 66 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 2	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4874.000	56.37	0.14	56.51	74	-17.49	peak
4874.000	47.51	0.14	47.65	54	-6.35	AVG
7311.000	50.24	2.36	52.6	74	-21.4	peak
7311.000	41.26	2.36	43.62	54	-10.38	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 2	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4874.000	51.35	0.14	51.49	74	-22.51	peak
4874.000	42.34	0.14	42.48	54	-11.52	AVG
7311.000	46.28	2.36	48.64	74	-25.36	peak
7311.000	34.94	2.36	37.3	54	-16.7	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 67 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 3	Antenna Polarity	Horizontal

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
56.34	0.22	56.56	74	-17.44	peak
45.27	0.22	45.49	54	-8.51	AVG
47.61	2.64	50.25	74	-23.75	peak
38.51	2.64	41.15	54	-12.85	AVG
	(dBµV) 56.34 45.27 47.61	(dBµV) (dB) 56.34 0.22 45.27 0.22 47.61 2.64	(dBμV) (dB) (dBμV/m) 56.34 0.22 56.56 45.27 0.22 45.49 47.61 2.64 50.25	(dBμV) (dB) (dBμV/m) (dBμV/m) 56.34 0.22 56.56 74 45.27 0.22 45.49 54 47.61 2.64 50.25 74	(dBμV) (dB) (dBμV/m) (dBμV/m) (dBμV/m) 56.34 0.22 56.56 74 -17.44 45.27 0.22 45.49 54 -8.51 47.61 2.64 50.25 74 -23.75

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 3	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.000	52.49	0.22	52.71	74	-21.29	peak
4924.000	41.25	0.22	41.47	54	-12.53	AVG
7386.000	48.64	2.64	51.28	74	-22.72	peak
7386.000	39.58	2.64	42.22	54	-11.78	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 68 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 4	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.000	53.42	0.08	53.5	74	-20.5	peak
4824.000	44.91	0.08	44.99	54	-9.01	AVG
7236.000	48.62	2.21	50.83	74	-23.17	peak
7236.000	37.64	2.21	39.85	54	-14.15	AVG
		·		_		

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 4	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Tree
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	─ Value Type
4824.000	53.59	0.08	53.67	74	-20.33	peak
4824.000	48.62	0.08	48.7	54	-5.3	AVG
7236.000	49.35	2.21	51.56	74	-22.44	peak
7236.000	37.52	2.21	39.73	54	-14.27	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 69 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 5	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4874.000	54.26	0.14	54.4	74	-19.6	peak
4874.000	46.28	0.14	46.42	54	-7.58	AVG
7311.000	49.63	2.36	51.99	74	-22.01	peak
7311.000	40.05	2.36	42.41	54	-11.59	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 5	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4874.000	55.39	0.14	55.53	74	-18.47	peak
4874.000	46.38	0.14	46.52	54	-7.48	AVG
7311.000	51.24	2.36	53.6	74	-20.4	peak
7311.000	42.35	2.36	44.71	54	-9.29	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 70 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 6	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Value Type
4924.000	57.62	0.22	57.84	74	-16.16	peak
4924.000	48.25	0.22	48.47	54	-5.53	AVG
7386.000	50.26	2.64	52.9	74	-21.1	peak
7386.000	42.34	2.64	44.98	54	-9.02	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 6	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.000	53.28	0.22	53.5	74	-20.5	peak
4924.000	45.16	0.22	45.38	54	-8.62	AVG
7386.000	48.62	2.64	51.26	74	-22.74	peak
7386.000	40.26	2.64	42.9	54	-11.1	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 71 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 7	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.000	47.64	0.08	47.72	74	-26.28	peak
4824.000	38.91	0.08	38.99	54	-15.01	AVG
7236.000	41.24	2.21	43.45	74	-30.55	peak
7236.000	33.53	2.21	35.74	54	-18.26	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 7	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4824.000	49.63	0.08	49.71	74	-24.29	peak
4824.000	42.34	0.08	42.42	54	-11.58	AVG
7236.000	44.67	2.21	46.88	74	-27.12	peak
7236.000	35.91	2.21	38.12	54	-15.88	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 72 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 8	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4874.000	51.24	0.14	51.38	74	-22.62	peak
4874.000	42.68	0.14	42.82	54	-11.18	AVG
7311.000	48.62	2.36	50.98	74	-23.02	peak
7311.000	38.52	2.36	40.88	54	-13.12	AVG
<u> </u>						

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 8	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4874.000	53.49	0.14	53.63	74	-20.37	peak
4874.000	42.35	0.14	42.49	54	-11.51	AVG
7311.000	48.63	2.36	50.99	74	-23.01	peak
7311.000	40.22	2.36	42.58	54	-11.42	AVG
_		_				

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 73 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 9	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.000	54.29	0.22	54.51	74	-19.49	peak
4924.000	45.36	0.22	45.58	54	-8.42	AVG
7386.000	49.26	2.64	51.9	74	-22.1	peak
7386.000	41.25	2.64	43.89	54	-10.11	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 9	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4924.000	54.29	0.22	54.51	74	-19.49	peak
4924.000	35.52	0.22	35.74	54	-18.26	AVG
7386.000	49.52	2.64	52.16	74	-21.84	peak
7386.000	41.36	2.64	44	54	-10	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 74 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 10	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4844.000	52.34	0.08	52.42	74	-21.58	peak
4844.000	41.26	0.08	41.34	54	-12.66	AVG
7266.000	45.62	2.21	47.83	74	-26.17	peak
7266.000	36.35	2.21	38.56	54	-15.44	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 10	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4844.000	48.62	0.08	48.7	74	-25.3	peak
4844.000	39.65	0.08	39.73	54	-14.27	AVG
7266.000	43.52	2.21	45.73	74	-28.27	peak
7266.000	36.58	2.21	38.79	54	-15.21	AVG
_		•		_		

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 75 of 97

Radiated Emissions Test Results above 1GHz

EUT Name	Portable Power Station	Model Name	AC200P L
Temperature	22.6°C	Relative Humidity	60.5%
Pressure	960hPa	Test Voltage	AC 120V, 60Hz
Test Mode	Mode 11	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4874.000	52.34	0.14	52.48	74	-21.52	peak
4874.000	44.84	0.14	44.98	54	-9.02	AVG
7311.000	47.62	2.36	49.98	74	-24.02	peak
7311.000	38.94	2.36	41.3	54	-12.7	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	Portable Power Station	Model Name	AC200P L	
Temperature	22.6°C	Relative Humidity	60.5%	
Pressure	960hPa	Test Voltage	AC 120V, 60Hz	
Test Mode	Mode 11	Antenna Polarity	Vertical	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4874.000	54.26	0.14	54.4	74	-19.6	peak	
4874.000	36.29	0.14	36.43	54	-17.57	AVG	
7311.000	49.25	2.36	51.61	74	-22.39	peak	
7311.000	40.22	2.36	42.58	54	-11.42	AVG	

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass