

# TEST REPORT

## CERTIFICATE OF CONFORMITY

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

**Report No.:** RFBIBJ-WTW-P22110693-1

**FCC ID:** HBW-VKP1

**Product:** SMART GARAGE VIDEO KEYPAD

**Brand:** myQ

**Model No.:** VKP1-MYQ MC, VKP1-LM MC, VKP1-RJO MC

**Received Date:** 2022/12/2

**Test Date:** 2022/12/2 ~ 2022/12/14

**Issued Date:** 2023/3/13

**Applicant:** The Chamberlain Group Inc

**Address:** 300 Windsor Drive Oakbrook, IL 60523

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location (1):** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan

**FCC Registration /**  
**Designation Number(1):** 788550 / TW0003

**Test Location (2):** No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

**FCC Registration /**  
**Designation Number(2):** 281270 / TW0032

**Approved by:** Jeremy Lin, **Date:** 2023/3/13  
Jeremy Lin / Project Engineer

This test report consists of 50 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Pettie Chen / Senior Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

|                                                                     |           |
|---------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                                 | <b>4</b>  |
| <b>1 Certificate.....</b>                                           | <b>5</b>  |
| <b>2 Summary of Test Results .....</b>                              | <b>6</b>  |
| 2.1 Measurement Uncertainty .....                                   | 6         |
| 2.2 Supplementary Information .....                                 | 6         |
| <b>3 General Information .....</b>                                  | <b>7</b>  |
| 3.1 General Description.....                                        | 7         |
| 3.2 Antenna Description of EUT.....                                 | 8         |
| 3.3 Channel List.....                                               | 8         |
| 3.4 Test Mode Applicability and Tested Channel Detail.....          | 9         |
| 3.5 Duty Cycle of Test Signal.....                                  | 10        |
| 3.6 Test Program Used and Operation Descriptions.....               | 11        |
| 3.7 Connection Diagram of EUT and Peripheral Devices.....           | 11        |
| 3.8 Configuration of Peripheral Devices and Cable Connections ..... | 12        |
| <b>4 Test Instruments .....</b>                                     | <b>13</b> |
| 4.1 RF Output Power.....                                            | 13        |
| 4.2 Power Spectral Density .....                                    | 13        |
| 4.3 6 dB Bandwidth .....                                            | 13        |
| 4.4 Conducted Out of Band Emissions .....                           | 13        |
| 4.5 AC Power Conducted Emissions .....                              | 14        |
| 4.6 Unwanted Emissions below 1 GHz .....                            | 15        |
| 4.7 Unwanted Emissions above 1 GHz.....                             | 16        |
| <b>5 Limits of Test Items.....</b>                                  | <b>17</b> |
| 5.1 RF Output Power.....                                            | 17        |
| 5.2 Power Spectral Density .....                                    | 17        |
| 5.3 6 dB Bandwidth .....                                            | 17        |
| 5.4 Conducted Out of Band Emissions .....                           | 17        |
| 5.5 AC Power Conducted Emissions .....                              | 17        |
| 5.6 Unwanted Emissions below 1 GHz .....                            | 17        |
| 5.7 Unwanted Emissions above 1 GHz.....                             | 18        |
| <b>6 Test Arrangements.....</b>                                     | <b>19</b> |
| 6.1 RF Output Power.....                                            | 19        |
| 6.1.1 Test Setup .....                                              | 19        |
| 6.1.2 Test Procedure.....                                           | 19        |
| 6.2 Power Spectral Density .....                                    | 19        |
| 6.2.1 Test Setup .....                                              | 19        |
| 6.2.2 Test Procedure.....                                           | 19        |
| 6.3 6 dB Bandwidth .....                                            | 20        |
| 6.3.1 Test Setup .....                                              | 20        |
| 6.3.2 Test Procedure.....                                           | 20        |
| 6.4 Conducted Out of Band Emissions .....                           | 20        |
| 6.4.1 Test Setup .....                                              | 20        |
| 6.4.2 Test Procedure.....                                           | 20        |
| 6.5 AC Power Conducted Emissions .....                              | 21        |
| 6.5.1 Test Setup .....                                              | 21        |
| 6.5.2 Test Procedure.....                                           | 21        |
| 6.6 Unwanted Emissions below 1 GHz .....                            | 22        |
| 6.6.1 Test Setup .....                                              | 22        |
| 6.6.2 Test Procedure.....                                           | 23        |
| 6.7 Unwanted Emissions above 1 GHz.....                             | 24        |
| 6.7.1 Test Setup .....                                              | 24        |
| 6.7.2 Test Procedure.....                                           | 24        |
| <b>7 Test Results of Test Item .....</b>                            | <b>25</b> |

|          |                                                      |           |
|----------|------------------------------------------------------|-----------|
| 7.1      | RF Output Power.....                                 | 25        |
| 7.2      | Power Spectral Density .....                         | 26        |
| 7.3      | 6 dB Bandwidth .....                                 | 28        |
| 7.4      | Conducted Out of Band Emissions .....                | 30        |
| 7.5      | AC Power Conducted Emissions .....                   | 33        |
| 7.6      | Unwanted Emissions below 1 GHz .....                 | 35        |
| 7.7      | Unwanted Emissions above 1 GHz.....                  | 37        |
| <b>8</b> | <b>Pictures of Test Arrangements .....</b>           | <b>49</b> |
| <b>9</b> | <b>Information of the Testing Laboratories .....</b> | <b>50</b> |

## Release Control Record

| Issue No.              | Description       | Date Issued |
|------------------------|-------------------|-------------|
| RFBIBJ-WTW-P22110693-1 | Original release. | 2023/3/13   |

## 1 Certificate

**Product:** SMART GARAGE VIDEO KEYPAD

**Brand:** myQ

**Test Model:** VKP1-MYQ MC, VKP1-LM MC, VKP1-RJO MC

**Sample Status:** Engineering sample

**Applicant:** The Chamberlain Group Inc

**Test Date:** 2022/12/2 ~ 2022/12/14

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

**Measurement** ANSI C63.10-2013

**procedure:** KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) |                                 |        |                                                     |
|------------------------------------------------|---------------------------------|--------|-----------------------------------------------------|
| Standard / Clause                              | Test Item                       | Result | Remark                                              |
| 15.247(b)                                      | RF Output Power                 | Pass   | Meet the requirement of limit.                      |
| 15.247(e)                                      | Power Spectral Density          | Pass   | Meet the requirement of limit.                      |
| 15.247(a)(2)                                   | 6 dB Bandwidth                  | Pass   | Meet the requirement of limit.                      |
| 15.247(d)                                      | Conducted Out of Band Emissions | Pass   | Meet the requirement of limit.                      |
| 15.207                                         | AC Power Conducted Emissions    | Pass   | Minimum passing margin is -17.58 dB at 0.26200 MHz  |
| 15.205 /<br>15.209 /<br>15.247(d)              | Unwanted Emissions below 1 GHz  | Pass   | Minimum passing margin is -7.2 dB at 784.91 MHz     |
| 15.205 /<br>15.209 /<br>15.247(d)              | Unwanted Emissions above 1 GHz  | Pass   | Minimum passing margin is -1.0 dB at 2390.00 MHz    |
| 15.203                                         | Antenna Requirement             | Pass   | Antenna connector is IPEX not a standard connector. |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                     | Specification   | Expanded Uncertainty (k=2)<br>(±) |
|---------------------------------|-----------------|-----------------------------------|
| Conducted Out of Band Emissions | 9 kHz ~ 40 GHz  | 2.79 dB                           |
| AC Power Conducted Emissions    | 9 kHz ~ 30 MHz  | 2.99 dB                           |
| Unwanted Emissions below 1 GHz  | 9 kHz ~ 30 MHz  | 3 dB                              |
|                                 | 30 MHz ~ 1 GHz  | 2.93 dB                           |
| Unwanted Emissions above 1 GHz  | 1 GHz ~ 18 GHz  | 1.76 dB                           |
|                                 | 18 GHz ~ 40 GHz | 1.77 dB                           |

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

### 2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

### 3 General Information

#### 3.1 General Description

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Product               | SMART GARAGE VIDEO KEYPAD                                       |
| Brand                 | myQ                                                             |
| Test Model            | VKP1-MYQ MC, VKP1-LM MC, VKP1-RJO MC                            |
| Model Difference      | Marketing purpose                                               |
| Status of EUT         | Engineering sample                                              |
| Power Supply Rating   | 3.7Vdc (From battery)                                           |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM |
| Modulation Technology | DSSS, OFDM                                                      |
| Transfer Rate         | Up to 72.2 Mbps                                                 |
| Operating Frequency   | 2.412 GHz ~ 2.462 GHz                                           |
| Number of Channel     | 802.11b, 802.11g, 802.11n (HT20): 13                            |
| Output Power          | 133.66 mW (21.26 dBm)                                           |

Note:

1. The EUT uses following accessory.

| Battery |               |                     |
|---------|---------------|---------------------|
| Brand   | Model         | Specification       |
| myQ     | 18650MH1-1S2P | Power Rating : 3.7V |

2. The EUT is not capable of simultaneous transmission.
3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 Antenna Description of EUT

1. The antenna information is listed as below.

| Ant. No. | P/N                | Gain (dBi) |          |          |          |          |          | Antenna Type | Connector Type |
|----------|--------------------|------------|----------|----------|----------|----------|----------|--------------|----------------|
|          |                    | 2400 MHz   | 2450 MHz | 2500 MHz | 5150 MHz | 5500 MHz | 5850 MHz |              |                |
| 1        | RFPCA391704IMLB301 | 1.99       | 2.54     | 2.52     | 5.46     | 4.51     | 5.08     | PCB          | IPEX           |
| 2        | RFPCA391707IMLB302 | 2.09       | 2.69     | 2.34     | 4.12     | 5.15     | 5.35     | PCB          | IPEX           |

\* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

\* Ant. 2 with the maximum gain was for the final tests.

2. The EUT provides 1 completed transmitter and 1 receiver.

| 2.4 GHz Band    |                       |     |
|-----------------|-----------------------|-----|
| Modulation Mode | TX & RX Configuration |     |
| 802.11b         | 1TX (Diversity)       | 1RX |
| 802.11g         | 1TX (Diversity)       | 1RX |
| 802.11n (HT20)  | 1TX (Diversity)       | 1RX |

### 3.3 Channel List

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412 MHz  | 7       | 2442 MHz  |
| 2       | 2417 MHz  | 8       | 2447 MHz  |
| 3       | 2422 MHz  | 9       | 2452 MHz  |
| 4       | 2427 MHz  | 10      | 2457 MHz  |
| 5       | 2432 MHz  | 11      | 2462 MHz  |
| 6       | 2437 MHz  |         |           |

### 3.4 Test Mode Applicability and Tested Channel Detail

Following channel(s) was (were) selected for the final test as listed below:

| Test Item                                        | Mode           | Tested Channel | Modulation | Data Rate Parameter |
|--------------------------------------------------|----------------|----------------|------------|---------------------|
| RF Output Power / Power Spectral Density         | 802.11b        | 1, 6, 11       | DBPSK      | 1Mb/s               |
|                                                  | 802.11g        | 1, 6, 11       | BPSK       | 6Mb/s               |
|                                                  | 802.11n (HT20) | 1, 6, 11       | BPSK       | MCS0                |
| 6 dB Bandwidth / Conducted Out of Band Emissions | 802.11b        | 1, 6, 11       | DBPSK      | 1Mb/s               |
|                                                  | 802.11g        | 1, 6, 11       | BPSK       | 6Mb/s               |
|                                                  | 802.11n (HT20) | 1, 6, 11       | BPSK       | MCS0                |
| AC Power Conducted Emissions (Note)              | Battery Charge | -              | -          | -                   |
| Unwanted Emissions below 1 GHz                   | 802.11g        | 6              | BPSK       | 6Mb/s               |
| Unwanted Emissions above 1 GHz                   | 802.11b        | 1, 6, 11       | DBPSK      | 1Mb/s               |
|                                                  | 802.11g        | 1, 6, 11       | BPSK       | 6Mb/s               |
|                                                  | 802.11n (HT20) | 1, 6, 11       | BPSK       | MCS0                |

\* The EUT is designed to be positioned on the Z-plane only.


Note: Battery Charging mode only be performing under AC Power Conducted Emission Test as the EUT has no AC input port.


### 3.5 Duty Cycle of Test Signal

**802.11b:** Duty cycle = 12.44 ms / 12.46 ms x 100% = 99.8%

**802.11g:** Duty cycle = 2.07 ms / 2.31 ms x 100% = 89.6%, duty factor =  $10 \cdot \log(1/\text{Duty cycle}) = 0.48 \text{ dB}$

**802.11n (HT20):** Duty cycle = 1.925 ms / 2.16 ms x 100% = 89.1%, duty factor =  $10 \cdot \log(1/\text{Duty cycle}) = 0.50 \text{ dB}$






### 3.6 Test Program Used and Operation Descriptions


Controlling software AmebaPro2\_mptool\_1V9.6 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

### 3.7 Connection Diagram of EUT and Peripheral Devices

AC Power Conducted Emissions



Unwanted Emissions Test



### 3.8 Configuration of Peripheral Devices and Cable Connections

| ID | Product  | Brand  | Model No. | Serial No. | FCC ID | Remarks               |
|----|----------|--------|-----------|------------|--------|-----------------------|
| A  | Adapter  | ASUS   | AD827M    | NA         | NA     | Provided by Lab       |
| B  | Notebook | Lenovo | L440      | R9-0GFJJK  | NA     | Provided by Lab       |
| C  | Jig      | NA     | NA        | NA         | NA     | Supplied by applicant |

| ID | Cable Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks               |
|----|--------------------|------|------------|--------------------|--------------|-----------------------|
| 1  | USB Cable          | 1    | 1          | Yes                | 0            | Provided by Lab       |
| 2  | Singal Cable       | 1    | 0.1        | No                 | 0            | Supplied by applicant |
| 3  | USB Cable          | 1    | 0.1        | No                 | 0            | Supplied by applicant |

## 4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.1 RF Output Power

| Description<br>Manufacturer       | Model No. | Serial No. | Calibrated<br>Date | Calibrated<br>Until |
|-----------------------------------|-----------|------------|--------------------|---------------------|
| Peak Power Analyzer<br>KEYSIGHT   | 8990B     | MY51000485 | 2022/1/18          | 2023/1/17           |
| Power sensor<br>KEYSIGHT          | U2021XA   | MY55380009 | 2022/3/23          | 2023/3/22           |
| Wideband Power Sensor<br>KEYSIGHT | N1923A    | MY58020002 | 2022/1/17          | 2023/1/16           |

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2022/12/9

### 4.2 Power Spectral Density

| Description<br>Manufacturer          | Model No.                        | Serial No. | Calibrated<br>Date | Calibrated<br>Until |
|--------------------------------------|----------------------------------|------------|--------------------|---------------------|
| Software<br>BV                       | ADT_RF Test Software<br>V6.6.5.4 | N/A        | N/A                | N/A                 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ | FSV40                            | 100979     | 2022/3/25          | 2023/3/24           |

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2022/12/14

### 4.3 6 dB Bandwidth

| Description<br>Manufacturer          | Model No.                        | Serial No. | Calibrated<br>Date | Calibrated<br>Until |
|--------------------------------------|----------------------------------|------------|--------------------|---------------------|
| Software<br>BV                       | ADT_RF Test Software<br>V6.6.5.4 | N/A        | N/A                | N/A                 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ | FSV40                            | 100979     | 2022/3/25          | 2023/3/24           |

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2022/12/9

### 4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get information of the instruments.

#### 4.5 AC Power Conducted Emissions

| Description<br>Manufacturer | Model No.            | Serial No.     | Calibrated<br>Date | Calibrated<br>Until |
|-----------------------------|----------------------|----------------|--------------------|---------------------|
| LISN<br>ROHDE & SCHWARZ     | ESH3-Z5              | 100311         | 2022/9/12          | 2023/9/11           |
| LISN<br>ROHDE & SCHWARZ     | ENV216               | 101826         | 2022/3/14          | 2023/3/13           |
| Receiver<br>ROHDE & SCHWARZ | ESCI                 | 100412         | 2022/8/22          | 2023/8/21           |
| RF Coaxial Cable<br>WOKEN   | 5D-FB                | Cable-cond1-01 | 2022/1/15          | 2023/1/14           |
| Software<br>BVADT           | BVADT_Conc_ V7.3.7.4 | N/A            | N/A                | N/A                 |
| V-LISN<br>Schwarzbeck       | NNBL 8226-2          | 8226-142       | 2022/8/31          | 2023/8/30           |

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2022/12/6

#### 4.6 Unwanted Emissions below 1 GHz

| Description<br>Manufacturer             | Model No.                    | Serial No.    | Calibrated<br>Date | Calibrated<br>Until |
|-----------------------------------------|------------------------------|---------------|--------------------|---------------------|
| Antenna Tower<br>Max-Full               | MFT-151SS-0.5T               | N/A           | N/A                | N/A                 |
| Bi-log Broadband Antenna<br>Schwarzbeck | VULB9168                     | 9168-1213     | 2022/10/20         | 2023/10/19          |
| Loop Antenna<br>EMCI                    | EM-6879                      | 269           | 2022/9/19          | 2023/9/18           |
| Loop Antenna<br>TESEQ                   | HLA 6121                     | 45745         | 2022/7/27          | 2023/7/26           |
| Pre-amplifier<br>EMCI                   | EMC001340                    | 980201        | 2022/9/23          | 2023/9/22           |
| Pre_Amplifier<br>EMCI                   | EMC330N                      | 980782        | 2022/1/17          | 2023/1/16           |
| RF Coaxial Cable<br>EMCI                | 5D-NM-BM                     | 140903+140902 | 2022/1/15          | 2023/1/14           |
|                                         | EMCCFD400-NM-NM-500          | 201233        | 2022/1/17          | 2023/1/16           |
|                                         | EMCCFD400-NM-NM-3000         | 201235        | 2022/1/17          | 2023/1/16           |
|                                         | EMCCFD400-NM-NM-9000         | 201236        | 2022/1/17          | 2023/1/16           |
| Software<br>BV ADT                      | ADT_Radiated_<br>V7.6.15.9.5 | N/A           | N/A                | N/A                 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ    | FSW43                        | 101866        | 2022/1/14          | 2023/1/13           |
| Test Receiver<br>ROHDE & SCHWARZ        | ESR3+                        | 102782        | 2021/12/10         | 2022/12/9           |
| Turn Table<br>Max-Full                  | MF-7802BS                    | N/A           | N/A                | N/A                 |
| Turn Table Controller<br>Max-Full       | MF-7802BS                    | MF780208674   | N/A                | N/A                 |

Notes:

1. The test was performed in WM - 966 chamber 8.
2. Tested Date: 2022/12/6

#### 4.7 Unwanted Emissions above 1 GHz

| Description<br>Manufacturer          | Model No.                    | Serial No.  | Calibrated<br>Date | Calibrated<br>Until |
|--------------------------------------|------------------------------|-------------|--------------------|---------------------|
| Antenna Tower<br>Max-Full            | MFT-151SS-0.5T               | N/A         | N/A                | N/A                 |
| Horn Antenna<br>RFSPIN               | DRH18-E                      | 210103A18E  | 2022/11/13         | 2023/11/12          |
| Horn Antenna<br>Schwarzbeck          | BBHA 9170                    | 9170-1049   | 2022/11/13         | 2023/11/12          |
| Pre_Amplifier<br>EMCI                | EMC118A45SE                  | 980808      | 2021/12/30         | 2022/12/29          |
|                                      | EMC184045SE                  | 980788      | 2022/1/17          | 2023/1/16           |
| RF Coaxial Cable<br>EMCI             | EMC101G-KM-KM-2000           | 201254      | 2022/1/17          | 2023/1/16           |
|                                      | EMC101G-KM-KM-3000           | 201257      | 2022/1/17          | 2023/1/16           |
|                                      | EMC101G-KM-KM-5000           | 201260      | 2022/1/17          | 2023/1/16           |
|                                      | EMC104-SM-SM-1000            | 210102      | 2022/1/17          | 2023/1/16           |
|                                      | EMC104-SM-SM-3000            | 201231      | 2022/1/17          | 2023/1/16           |
|                                      | EMC104-SM-SM-9000            | 201243      | 2022/1/17          | 2023/1/16           |
| Software<br>BV ADT                   | ADT_Radiated_<br>V7.6.15.9.5 | N/A         | N/A                | N/A                 |
| Spectrum Analyzer<br>ROHDE & SCHWARZ | FSW43                        | 101866      | 2022/1/14          | 2023/1/13           |
| Test Receiver<br>ROHDE & SCHWARZ     | ESR3+                        | 102782      | 2021/12/10         | 2022/12/9           |
| Turn Table<br>Max-Full               | MF-7802BS                    | N/A         | N/A                | N/A                 |
| Turn Table Controller<br>Max-Full    | MF-7802BS                    | MF780208674 | N/A                | N/A                 |

Notes:

1. The test was performed in WM - 966 chamber 8.
2. Tested Date: 2022/12/2 ~ 2022/12/5

## 5 Limits of Test Items

### 5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

### 5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

### 5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

### 5.4 Conducted Out of Band Emissions

Below 30 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

### 5.5 AC Power Conducted Emissions

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

## 5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

| Frequencies<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| Above 960            | 500                                  | 3                                |


### Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

## 6 Test Arrangements

### 6.1 RF Output Power

#### 6.1.1 Test Setup




#### 6.1.2 Test Procedure

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

### 6.2 Power Spectral Density

#### 6.2.1 Test Setup




#### 6.2.2 Test Procedure

- a. Measure the duty cycle (x).
- b. Set instrument center frequency to DTS channel center frequency.
- c. Set span to at least 1.5 times the OBW.
- d. Set RBW to: 3 kHz.
- e. Set VBW  $\geq 3 \times$  RBW.
- f. Detector = power averaging (RMS) or sample detector (when RMS not available).
- g. Ensure that the number of measurement points in the sweep  $\geq 2 \times$  span/RBW.
- h. Sweep time = auto couple.
- i. Do not use sweep triggering. Allow sweep to "free run".
- j. Employ trace averaging (RMS) mode over a minimum of 100 traces.
- k. Use the peak marker function to determine the maximum amplitude level.
- l. Note: If Duty cycle < 98%, Add  $10 \log (1/x)$ , where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

### 6.3 6 dB Bandwidth

#### 6.3.1 Test Setup




#### 6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.4 Conducted Out of Band Emissions

#### 6.4.1 Test Setup



#### 6.4.2 Test Procedure

##### MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

##### MEASUREMENT PROCEDURE OOBE

- Set RBW = 100 kHz.
- Set VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

## 6.5 AC Power Conducted Emissions

### 6.5.1 Test Setup



**Note: 1.Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


## 6.6 Unwanted Emissions below 1 GHz

### 6.6.1 Test Setup

#### For Radiated emission below 30 MHz



#### For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 6.6.2 Test Procedure

### For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

#### Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

### For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

#### Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

## 6.7 Unwanted Emissions above 1 GHz

### 6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

#### Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10 Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

## 7 Test Results of Test Item

### 7.1 RF Output Power

|              |                |                           |              |            |           |
|--------------|----------------|---------------------------|--------------|------------|-----------|
| Input Power: | 120 Vac, 60 Hz | Environmental Conditions: | 25°C, 60% RH | Tested By: | Chris Lin |
|--------------|----------------|---------------------------|--------------|------------|-----------|

#### 802.11b

| Chan. | Chan. Freq. (MHz) | Average Power (mW) | Average Power (dBm) | Power Limit (dBm) | Test Result |
|-------|-------------------|--------------------|---------------------|-------------------|-------------|
| 1     | 2412              | 59.156             | 17.72               | 30                | Pass        |
| 6     | 2437              | 67.92              | 18.32               | 30                | Pass        |
| 11    | 2462              | 77.804             | 18.91               | 30                | Pass        |

Note: The antenna gain is 2.69 dBi < 6 dBi, so the output power limit shall not be reduced.

#### 802.11g

| Chan. | Chan. Freq. (MHz) | Average Power (mW) | Average Power (dBm) | Power Limit (dBm) | Test Result |
|-------|-------------------|--------------------|---------------------|-------------------|-------------|
| 1     | 2412              | 48.195             | 16.83               | 30                | Pass        |
| 6     | 2437              | 133.66             | 21.26               | 30                | Pass        |
| 11    | 2462              | 40.926             | 16.12               | 30                | Pass        |

Note: The antenna gain is 2.69 dBi < 6 dBi, so the output power limit shall not be reduced.

#### 802.11n (HT20)

| Chan. | Chan. Freq. (MHz) | Average Power (mW) | Average Power (dBm) | Power Limit (dBm) | Test Result |
|-------|-------------------|--------------------|---------------------|-------------------|-------------|
| 1     | 2412              | 41.115             | 16.14               | 30                | Pass        |
| 6     | 2437              | 121.06             | 20.83               | 30                | Pass        |
| 11    | 2462              | 36.058             | 15.57               | 30                | Pass        |

Note: The antenna gain is 2.69 dBi < 6 dBi, so the output power limit shall not be reduced.

## 7.2 Power Spectral Density

|              |                |                           |              |            |           |
|--------------|----------------|---------------------------|--------------|------------|-----------|
| Input Power: | 120 Vac, 60 Hz | Environmental Conditions: | 25°C, 60% RH | Tested By: | Chris Lin |
|--------------|----------------|---------------------------|--------------|------------|-----------|

### 802.11b

| Chan. | Chan. Freq. (MHz) | PSD (dBm/3kHz) | PSD Limit (dBm/3kHz) | Test Result |
|-------|-------------------|----------------|----------------------|-------------|
| 1     | 2412              | -13.61         | 8.00                 | Pass        |
| 6     | 2437              | -13.64         | 8.00                 | Pass        |
| 11    | 2462              | -12.83         | 8.00                 | Pass        |

Note: The antenna gain is 2.69 dBi < 6 dBi, so the power density limit shall not be reduced.

### 802.11g

| Chan. | Chan. Freq. (MHz) | PSD w/o Duty Factor (dBm/3kHz) | Duty Factor (dB) | PSD (dBm/3kHz) | PSD Limit (dBm/3kHz) | Test Result |
|-------|-------------------|--------------------------------|------------------|----------------|----------------------|-------------|
| 1     | 2412              | -13.63                         | 0.48             | -13.15         | 8.00                 | Pass        |
| 6     | 2437              | -9.16                          | 0.48             | -8.68          | 8.00                 | Pass        |
| 11    | 2462              | -14.81                         | 0.48             | -14.33         | 8.00                 | Pass        |


Note: The antenna gain is 2.69 dBi < 6 dBi, so the power density limit shall not be reduced.

### 802.11n (HT20)


| Chan. | Chan. Freq. (MHz) | PSD w/o Duty Factor (dBm/3kHz) | Duty Factor (dB) | PSD (dBm/3kHz) | PSD Limit (dBm/3kHz) | Test Result |
|-------|-------------------|--------------------------------|------------------|----------------|----------------------|-------------|
| 1     | 2412              | -14.57                         | 0.50             | -14.07         | 8.00                 | Pass        |
| 6     | 2437              | -10.83                         | 0.50             | -10.33         | 8.00                 | Pass        |
| 11    | 2462              | -14.87                         | 0.50             | -14.37         | 8.00                 | Pass        |

Note: The antenna gain is 2.69 dBi < 6 dBi, so the power density limit shall not be reduced.


## Spectrum Plot of Maximum Value



802.11b : CH 11



802.11g : CH 6



802.11n (HT20) : CH 6

### 7.3 6 dB Bandwidth

|              |                |                           |              |            |           |
|--------------|----------------|---------------------------|--------------|------------|-----------|
| Input Power: | 120 Vac, 60 Hz | Environmental Conditions: | 25°C, 60% RH | Tested By: | Chris Lin |
|--------------|----------------|---------------------------|--------------|------------|-----------|

#### 802.11b

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Test Result |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 9.18                | 0.5                 | Pass        |
| 6       | 2437            | 9.16                | 0.5                 | Pass        |
| 11      | 2462            | 9.13                | 0.5                 | Pass        |




#### 802.11g

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Test Result |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 15.06               | 0.5                 | Pass        |
| 6       | 2437            | 15.09               | 0.5                 | Pass        |
| 11      | 2462            | 15.04               | 0.5                 | Pass        |

#### 802.11n (HT20)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Test Result |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 15.15               | 0.5                 | Pass        |
| 6       | 2437            | 15.13               | 0.5                 | Pass        |
| 11      | 2462            | 15.1                | 0.5                 | Pass        |


## Spectrum Plot of Minimum Value



## 7.4 Conducted Out of Band Emissions

|              |                |                           |              |            |           |
|--------------|----------------|---------------------------|--------------|------------|-----------|
| Input Power: | 120 Vac, 60 Hz | Environmental Conditions: | 25°C, 60% RH | Tested By: | Chris Lin |
|--------------|----------------|---------------------------|--------------|------------|-----------|

802.11b



802.11g



## 802.11n (HT20)




## 7.5 AC Power Conducted Emissions

|                 |                  |                                          |                                       |
|-----------------|------------------|------------------------------------------|---------------------------------------|
| Test Mode       | Battery Charge   | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9 kHz |
| Frequency Range | 150 kHz ~ 30 MHz | Input Power                              | 120 Vac, 60 Hz                        |
| Tested By       | Edison Lee       | Environmental Conditions                 | 25°C, 75% RH                          |

| Phase Of Power : Line (L) |                 |                        |                      |              |                       |              |              |              |               |               |
|---------------------------|-----------------|------------------------|----------------------|--------------|-----------------------|--------------|--------------|--------------|---------------|---------------|
| No                        | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |              | Emission Level (dBuV) |              | Limit (dBuV) |              | Margin (dB)   |               |
|                           |                 |                        | Q.P.                 | AV.          | Q.P.                  | AV.          | Q.P.         | AV.          | Q.P.          | AV.           |
| 1                         | 0.15400         | 9.68                   | 36.55                | 19.83        | 46.23                 | 29.51        | 65.78        | 55.78        | -19.55        | -26.27        |
| 2                         | 0.16600         | 9.69                   | 34.89                | 18.23        | 44.58                 | 27.92        | 65.16        | 55.16        | -20.58        | -27.24        |
| 3                         | 0.19780         | 9.72                   | 30.00                | 12.97        | 39.72                 | 22.69        | 63.70        | 53.70        | -23.98        | -31.01        |
| 4                         | <b>0.26200</b>  | <b>9.74</b>            | <b>26.96</b>         | <b>24.05</b> | <b>36.70</b>          | <b>33.79</b> | <b>61.37</b> | <b>51.37</b> | <b>-24.67</b> | <b>-17.58</b> |
| 5                         | 0.65800         | 9.82                   | 22.61                | 17.83        | 32.43                 | 27.65        | 56.00        | 46.00        | -23.57        | -18.35        |
| 6                         | 11.99800        | 10.08                  | 14.36                | 10.24        | 24.44                 | 20.32        | 60.00        | 50.00        | -35.56        | -29.68        |

### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|                        |                  |                                                     |                                       |
|------------------------|------------------|-----------------------------------------------------|---------------------------------------|
| <b>Test Mode</b>       | Battery Charge   | <b>Detector Function &amp; Resolution Bandwidth</b> | Quasi-Peak (QP) / Average (AV), 9 kHz |
| <b>Frequency Range</b> | 150 kHz ~ 30 MHz | <b>Input Power</b>                                  | 120 Vac, 60 Hz                        |
| <b>Tested By</b>       | Edison Lee       | <b>Environmental Conditions</b>                     | 25°C, 75% RH                          |

| Phase Of Power : Neutral (N) |                 |                        |                      |       |                       |       |              |       |             |        |
|------------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                           | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                              |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                            | 0.16600         | 9.69                   | 35.32                | 17.76 | 45.01                 | 27.45 | 65.16        | 55.16 | -20.15      | -27.71 |
| 2                            | 0.20200         | 9.72                   | 30.80                | 14.43 | 40.52                 | 24.15 | 63.53        | 53.53 | -23.01      | -29.38 |
| 3                            | 0.27400         | 9.75                   | 22.89                | 12.43 | 32.64                 | 22.18 | 61.00        | 51.00 | -28.36      | -28.82 |
| 4                            | 0.65800         | 9.83                   | 22.50                | 16.59 | 32.33                 | 26.42 | 56.00        | 46.00 | -23.67      | -19.58 |
| 5                            | 1.49400         | 9.89                   | 13.64                | 8.13  | 23.53                 | 18.02 | 56.00        | 46.00 | -32.47      | -27.98 |
| 6                            | 6.53400         | 10.01                  | 15.65                | 10.24 | 25.66                 | 20.25 | 60.00        | 50.00 | -34.34      | -29.75 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




## 7.6 Unwanted Emissions below 1 GHz

|                 |                |                               |                  |
|-----------------|----------------|-------------------------------|------------------|
| RF Mode         | 802.11g        | Channel                       | CH 6 : 2437 MHz  |
| Frequency Range | 9 kHz ~ 1 GHz  | Detector Function & Bandwidth | (QP) RB = 120kHz |
| Input Power     | 120 Vac, 60 Hz | Environmental Conditions      | 20.9°C, 72.3% RH |
| Tested By       | Edison Lee     |                               |                  |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 41.25           | 26.1 QP                 | 40.0           | -13.9       | 1.00 H             | 123                  | 39.5             | -13.4                    |
| 2                                                    | 142.46          | 29.8 QP                 | 43.5           | -13.7       | 1.00 H             | 88                   | 43.1             | -13.3                    |
| 3                                                    | 222.59          | 28.3 QP                 | 46.0           | -17.7       | 1.50 H             | 29                   | 44.9             | -16.6                    |
| 4                                                    | 337.87          | 29.6 QP                 | 46.0           | -16.4       | 2.00 H             | 111                  | 41.2             | -11.6                    |
| 5                                                    | 607.78          | 26.4 QP                 | 46.0           | -19.6       | 1.50 H             | 321                  | 31.6             | -5.2                     |
| 6                                                    | 784.91          | 38.8 QP                 | 46.0           | -7.2        | 2.00 H             | 93                   | 41.3             | -2.5                     |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




|                 |                |                               |                  |
|-----------------|----------------|-------------------------------|------------------|
| RF Mode         | 802.11g        | Channel                       | CH 6 : 2437 MHz  |
| Frequency Range | 9 kHz ~ 1 GHz  | Detector Function & Bandwidth | (QP) RB = 120kHz |
| Input Power     | 120 Vac, 60 Hz | Environmental Conditions      | 20.6°C, 65.7% RH |
| Tested By       | Edison Lee     |                               |                  |

| Antenna Polarity & Test Distance : Vertical at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|----------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                 | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                  | 42.65           | 28.8 QP                 | 40.0           | -11.2       | 1.50 V             | 99                   | 42.2             | -13.4                    |
| 2                                                  | 101.70          | 26.0 QP                 | 43.5           | -17.5       | 1.00 V             | 246                  | 43.3             | -17.3                    |
| 3                                                  | 256.33          | 24.9 QP                 | 46.0           | -21.1       | 1.00 V             | 242                  | 39.1             | -14.2                    |
| 4                                                  | 354.74          | 25.9 QP                 | 46.0           | -20.1       | 2.00 V             | 171                  | 37.4             | -11.5                    |
| 5                                                  | 588.10          | 30.2 QP                 | 46.0           | -15.8       | 1.00 V             | 116                  | 35.9             | -5.7                     |
| 6                                                  | 742.74          | 28.5 QP                 | 46.0           | -17.5       | 1.00 V             | 66                   | 31.5             | -3.0                     |

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 7.7 Unwanted Emissions above 1 GHz

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11b        | <b>Channel</b>                           | CH 1 : 2412 MHz                                            |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 10 Hz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 23°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 58.7 PK                 | 74.0           | -15.3       | 1.97 H             | 158                  | 26.6             | 32.1                     |
| 2                                                    | 2390.00         | 47.9 AV                 | 54.0           | -6.1        | 1.97 H             | 158                  | 15.8             | 32.1                     |
| 3                                                    | *2412.00        | 104.1 PK                |                |             | 1.97 H             | 158                  | 72.0             | 32.1                     |
| 4                                                    | *2412.00        | 101.6 AV                |                |             | 1.97 H             | 158                  | 69.5             | 32.1                     |
| 5                                                    | 4824.00         | 50.5 PK                 | 74.0           | -23.5       | 1.13 H             | 207                  | 47.4             | 3.1                      |
| 6                                                    | 4824.00         | 49.6 AV                 | 54.0           | -4.4        | 1.13 H             | 207                  | 46.5             | 3.1                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 58.5 PK                 | 74.0           | -15.5       | 1.41 V             | 319                  | 26.4             | 32.1                     |
| 2                                                    | 2390.00         | 49.2 AV                 | 54.0           | -4.8        | 1.41 V             | 319                  | 17.1             | 32.1                     |
| 3                                                    | *2412.00        | 107.8 PK                |                |             | 1.41 V             | 319                  | 75.7             | 32.1                     |
| 4                                                    | *2412.00        | 105.3 AV                |                |             | 1.41 V             | 319                  | 73.2             | 32.1                     |
| 5                                                    | 4824.00         | 55.5 PK                 | 74.0           | -18.5       | 1.05 V             | 326                  | 52.4             | 3.1                      |
| 6                                                    | 4824.00         | 52.6 AV                 | 54.0           | -1.4        | 1.05 V             | 326                  | 49.5             | 3.1                      |

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11b        | <b>Channel</b>                           | CH 6 : 2437 MHz                                            |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 10 Hz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 23°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2437.00        | 104.1 PK                |                |             | 2.26 H             | 168                  | 72.1             | 32.0                     |
| 2                                                    | *2437.00        | 101.6 AV                |                |             | 2.26 H             | 168                  | 69.6             | 32.0                     |
| 3                                                    | 4874.00         | 49.7 PK                 | 74.0           | -24.3       | 1.16 H             | 198                  | 46.8             | 2.9                      |
| 4                                                    | 4874.00         | 46.4 AV                 | 54.0           | -7.6        | 1.16 H             | 198                  | 43.5             | 2.9                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2437.00        | 108.0 PK                |                |             | 1.22 V             | 318                  | 76.0             | 32.0                     |
| 2                                                    | *2437.00        | 105.9 AV                |                |             | 1.22 V             | 318                  | 73.9             | 32.0                     |
| 3                                                    | 4874.00         | 54.1 PK                 | 74.0           | -19.9       | 1.16 V             | 332                  | 51.2             | 2.9                      |
| 4                                                    | 4874.00         | 52.6 AV                 | 54.0           | -1.4        | 1.16 V             | 332                  | 49.7             | 2.9                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11b        | <b>Channel</b>                           | CH 11 : 2462 MHz                                           |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 10 Hz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 23°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2462.00        | 103.4 PK                |                |             | 2.19 H             | 183                  | 71.3             | 32.1                     |
| 2                                                    | *2462.00        | 101.1 AV                |                |             | 2.19 H             | 183                  | 69.0             | 32.1                     |
| 3                                                    | 2483.50         | 59.1 PK                 | 74.0           | -14.9       | 2.19 H             | 183                  | 27.0             | 32.1                     |
| 4                                                    | 2483.50         | 48.9 AV                 | 54.0           | -5.1        | 2.19 H             | 183                  | 16.8             | 32.1                     |
| 5                                                    | 4924.00         | 50.0 PK                 | 74.0           | -24.0       | 1.19 H             | 203                  | 47.0             | 3.0                      |
| 6                                                    | 4924.00         | 46.5 AV                 | 54.0           | -7.5        | 1.19 H             | 203                  | 43.5             | 3.0                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2462.00        | 108.5 PK                |                |             | 1.28 V             | 318                  | 76.4             | 32.1                     |
| 2                                                    | *2462.00        | 105.9 AV                |                |             | 1.28 V             | 318                  | 73.8             | 32.1                     |
| 3                                                    | 2483.50         | 60.1 PK                 | 74.0           | -13.9       | 1.28 V             | 318                  | 28.0             | 32.1                     |
| 4                                                    | 2483.50         | 51.4 AV                 | 54.0           | -2.6        | 1.28 V             | 318                  | 19.3             | 32.1                     |
| 5                                                    | 4924.00         | 55.3 PK                 | 74.0           | -18.7       | 1.00 V             | 324                  | 52.3             | 3.0                      |
| 6                                                    | 4924.00         | 52.9 AV                 | 54.0           | -1.1        | 1.00 V             | 324                  | 49.9             | 3.0                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11g        | <b>Channel</b>                           | CH 1 : 2412 MHz                                            |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 1 kHz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 23°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 66.0 PK                 | 74.0           | -8.0        | 1.84 H             | 173                  | 33.9             | 32.1                     |
| 2                                                    | 2390.00         | 51.3 AV                 | 54.0           | -2.7        | 1.84 H             | 173                  | 19.2             | 32.1                     |
| 3                                                    | *2412.00        | 108.2 PK                |                |             | 1.84 H             | 173                  | 76.1             | 32.1                     |
| 4                                                    | *2412.00        | 101.4 AV                |                |             | 1.84 H             | 173                  | 69.3             | 32.1                     |
| 5                                                    | 4824.00         | 51.5 PK                 | 74.0           | -22.5       | 1.15 H             | 209                  | 48.4             | 3.1                      |
| 6                                                    | 4824.00         | 40.8 AV                 | 54.0           | -13.2       | 1.15 H             | 209                  | 37.7             | 3.1                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 65.8 PK                 | 74.0           | -8.2        | 1.21 V             | 319                  | 33.7             | 32.1                     |
| 2                                                    | 2390.00         | 53.0 AV                 | 54.0           | -1.0        | 1.21 V             | 319                  | 20.9             | 32.1                     |
| 3                                                    | *2412.00        | 111.2 PK                |                |             | 1.21 V             | 319                  | 79.1             | 32.1                     |
| 4                                                    | *2412.00        | 104.6 AV                |                |             | 1.21 V             | 319                  | 72.5             | 32.1                     |
| 5                                                    | 4824.00         | 53.5 PK                 | 74.0           | -20.5       | 1.02 V             | 325                  | 50.4             | 3.1                      |
| 6                                                    | 4824.00         | 43.4 AV                 | 54.0           | -10.6       | 1.02 V             | 325                  | 40.3             | 3.1                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11g        | <b>Channel</b>                           | CH 6 : 2437 MHz                                            |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 1 kHz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 22°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 63.6 PK                 | 74.0           | -10.4       | 1.72 H             | 13                   | 31.5             | 32.1                     |
| 2                                                    | 2390.00         | 48.8 AV                 | 54.0           | -5.2        | 1.72 H             | 13                   | 16.7             | 32.1                     |
| 3                                                    | *2437.00        | 110.3 PK                |                |             | 1.72 H             | 13                   | 78.3             | 32.0                     |
| 4                                                    | *2437.00        | 104.1 AV                |                |             | 1.72 H             | 13                   | 72.1             | 32.0                     |
| 5                                                    | 4874.00         | 53.6 PK                 | 74.0           | -20.4       | 1.16 H             | 190                  | 50.7             | 2.9                      |
| 6                                                    | 4874.00         | 45.0 AV                 | 54.0           | -9.0        | 1.16 H             | 190                  | 42.1             | 2.9                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 67.4 PK                 | 74.0           | -6.6        | 1.17 V             | 320                  | 35.3             | 32.1                     |
| 2                                                    | 2390.00         | 52.6 AV                 | 54.0           | -1.4        | 1.17 V             | 320                  | 20.5             | 32.1                     |
| 3                                                    | *2437.00        | 114.8 PK                |                |             | 1.17 V             | 320                  | 82.8             | 32.0                     |
| 4                                                    | *2437.00        | 107.9 AV                |                |             | 1.17 V             | 320                  | 75.9             | 32.0                     |
| 5                                                    | 4874.00         | 56.6 PK                 | 74.0           | -17.4       | 1.18 V             | 339                  | 53.7             | 2.9                      |
| 6                                                    | 4874.00         | 48.2 AV                 | 54.0           | -5.8        | 1.18 V             | 339                  | 45.3             | 2.9                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11g        | <b>Channel</b>                           | CH 11 : 2462 MHz                                           |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 1 kHz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 22°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2462.00        | 105.3 PK                |                |             | 2.05 H             | 167                  | 73.2             | 32.1                     |
| 2                                                    | *2462.00        | 99.1 AV                 |                |             | 2.05 H             | 167                  | 67.0             | 32.1                     |
| 3                                                    | 2483.50         | 62.2 PK                 | 74.0           | -11.8       | 2.05 H             | 167                  | 30.1             | 32.1                     |
| 4                                                    | 2483.50         | 49.3 AV                 | 54.0           | -4.7        | 2.05 H             | 167                  | 17.2             | 32.1                     |
| 5                                                    | 4924.00         | 51.6 PK                 | 74.0           | -22.4       | 1.17 H             | 185                  | 48.6             | 3.0                      |
| 6                                                    | 4924.00         | 42.5 AV                 | 54.0           | -11.5       | 1.17 H             | 185                  | 39.5             | 3.0                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2462.00        | 110.2 PK                |                |             | 1.97 V             | 318                  | 78.1             | 32.1                     |
| 2                                                    | *2462.00        | 103.8 AV                |                |             | 1.97 V             | 318                  | 71.7             | 32.1                     |
| 3                                                    | 2483.50         | 65.8 PK                 | 74.0           | -8.2        | 1.97 V             | 318                  | 33.7             | 32.1                     |
| 4                                                    | 2483.50         | 52.6 AV                 | 54.0           | -1.4        | 1.97 V             | 318                  | 20.5             | 32.1                     |
| 5                                                    | 4924.00         | 54.5 PK                 | 74.0           | -19.5       | 1.20 V             | 324                  | 51.5             | 3.0                      |
| 6                                                    | 4924.00         | 45.1 AV                 | 54.0           | -8.9        | 1.20 V             | 324                  | 42.1             | 3.0                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11n (HT20) | <b>Channel</b>                           | CH 1 : 2412 MHz                                            |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 1 kHz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 23°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 60.8 PK                 | 74.0           | -13.2       | 2.15 H             | 184                  | 28.7             | 32.1                     |
| 2                                                    | 2390.00         | 50.3 AV                 | 54.0           | -3.7        | 2.15 H             | 184                  | 18.2             | 32.1                     |
| 3                                                    | *2412.00        | 107.2 PK                |                |             | 2.15 H             | 184                  | 75.1             | 32.1                     |
| 4                                                    | *2412.00        | 99.8 AV                 |                |             | 2.15 H             | 184                  | 67.7             | 32.1                     |
| 5                                                    | 4824.00         | 50.0 PK                 | 74.0           | -24.0       | 1.11 H             | 192                  | 46.9             | 3.1                      |
| 6                                                    | 4824.00         | 41.2 AV                 | 54.0           | -12.8       | 1.11 H             | 192                  | 38.1             | 3.1                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 63.1 PK                 | 74.0           | -10.9       | 1.76 V             | 314                  | 31.0             | 32.1                     |
| 2                                                    | 2390.00         | 52.8 AV                 | 54.0           | -1.2        | 1.76 V             | 314                  | 20.7             | 32.1                     |
| 3                                                    | *2412.00        | 111.5 PK                |                |             | 1.76 V             | 314                  | 79.4             | 32.1                     |
| 4                                                    | *2412.00        | 103.8 AV                |                |             | 1.76 V             | 314                  | 71.7             | 32.1                     |
| 5                                                    | 4824.00         | 52.3 PK                 | 74.0           | -21.7       | 1.18 V             | 326                  | 49.2             | 3.1                      |
| 6                                                    | 4824.00         | 43.4 AV                 | 54.0           | -10.6       | 1.18 V             | 326                  | 40.3             | 3.1                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11n (HT20) | <b>Channel</b>                           | CH 6 : 2437 MHz                                            |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 1 kHz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 23°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |

| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 61.0 PK                 | 74.0           | -13.0       | 2.09 H             | 186                  | 28.9             | 32.1                     |
| 2                                                    | 2390.00         | 49.2 AV                 | 54.0           | -4.8        | 2.09 H             | 186                  | 17.1             | 32.1                     |
| 3                                                    | *2437.00        | 111.4 PK                |                |             | 2.09 H             | 186                  | 79.4             | 32.0                     |
| 4                                                    | *2437.00        | 103.9 AV                |                |             | 2.09 H             | 186                  | 71.9             | 32.0                     |
| 5                                                    | 4874.00         | 52.7 PK                 | 74.0           | -21.3       | 1.21 H             | 186                  | 49.8             | 2.9                      |
| 6                                                    | 4874.00         | 43.9 AV                 | 54.0           | -10.1       | 1.21 H             | 186                  | 41.0             | 2.9                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | 2390.00         | 65.6 PK                 | 74.0           | -8.4        | 1.73 V             | 316                  | 33.5             | 32.1                     |
| 2                                                    | 2390.00         | 52.6 AV                 | 54.0           | -1.4        | 1.73 V             | 316                  | 20.5             | 32.1                     |
| 3                                                    | *2437.00        | 116.3 PK                |                |             | 1.73 V             | 316                  | 84.3             | 32.0                     |
| 4                                                    | *2437.00        | 108.7 AV                |                |             | 1.73 V             | 316                  | 76.7             | 32.0                     |
| 5                                                    | 4874.00         | 55.1 PK                 | 74.0           | -18.9       | 1.25 V             | 327                  | 52.2             | 2.9                      |
| 6                                                    | 4874.00         | 47.0 AV                 | 54.0           | -7.0        | 1.25 V             | 327                  | 44.1             | 2.9                      |

**Remarks:**


1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.


|                        |                |                                          |                                                            |
|------------------------|----------------|------------------------------------------|------------------------------------------------------------|
| <b>RF Mode</b>         | 802.11n (HT20) | <b>Channel</b>                           | CH 11 : 2462 MHz                                           |
| <b>Frequency Range</b> | 1 GHz ~ 25 GHz | <b>Detector Function &amp; Bandwidth</b> | (PK) RB = 1 MHz, VB = 3 MHz<br>(AV) RB = 1 MHz, VB = 1 kHz |
| <b>Input Power</b>     | 120 Vac, 60 Hz | <b>Environmental Conditions</b>          | 23°C, 68% RH                                               |
| <b>Tested By</b>       | Edison Lee     |                                          |                                                            |


| Antenna Polarity & Test Distance : Horizontal at 3 m |                 |                         |                |             |                    |                      |                  |                          |
|------------------------------------------------------|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2462.00        | 105.1 PK                |                |             | 2.08 H             | 168                  | 73.0             | 32.1                     |
| 2                                                    | *2462.00        | 97.7 AV                 |                |             | 2.08 H             | 168                  | 65.6             | 32.1                     |
| 3                                                    | 2483.50         | 62.5 PK                 | 74.0           | -11.5       | 2.08 H             | 168                  | 30.4             | 32.1                     |
| 4                                                    | 2483.50         | 48.9 AV                 | 54.0           | -5.1        | 2.08 H             | 168                  | 16.8             | 32.1                     |
| 5                                                    | 4924.00         | 48.2 PK                 | 74.0           | -25.8       | 1.09 H             | 199                  | 45.2             | 3.0                      |
| 6                                                    | 4924.00         | 39.9 AV                 | 54.0           | -14.1       | 1.09 H             | 199                  | 36.9             | 3.0                      |
| Antenna Polarity & Test Distance : Vertical at 3 m   |                 |                         |                |             |                    |                      |                  |                          |
| No                                                   | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1                                                    | *2462.00        | 110.8 PK                |                |             | 1.74 V             | 312                  | 78.7             | 32.1                     |
| 2                                                    | *2462.00        | 103.1 AV                |                |             | 1.74 V             | 312                  | 71.0             | 32.1                     |
| 3                                                    | 2483.50         | 67.1 PK                 | 74.0           | -6.9        | 1.74 V             | 312                  | 35.0             | 32.1                     |
| 4                                                    | 2483.50         | 52.7 AV                 | 54.0           | -1.3        | 1.74 V             | 312                  | 20.6             | 32.1                     |
| 5                                                    | 4924.00         | 51.5 PK                 | 74.0           | -22.5       | 1.22 V             | 321                  | 48.5             | 3.0                      |
| 6                                                    | 4924.00         | 42.8 AV                 | 54.0           | -11.2       | 1.22 V             | 321                  | 39.8             | 3.0                      |

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.







## 8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

## 9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@bureauveritas.com](mailto:service.adt@bureauveritas.com)

**Web Site:** <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---