



## RF EXPOSURE EVALUATION

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range<br>(MHz)                                | Electric Field<br>Strength (V/m) | Magnetic Field<br>Strength (A/m) | Power Density<br>(mW/cm <sup>2</sup> ) | Average Time |
|---------------------------------------------------------|----------------------------------|----------------------------------|----------------------------------------|--------------|
| (A) Limits for Occupational / Control Exposures         |                                  |                                  |                                        |              |
| 300-1,500                                               | --                               | --                               | F/300                                  | 6            |
| 1,500-100,000                                           | --                               | --                               | 5                                      | 6            |
| (B) Limits for General Population / Uncontrol Exposures |                                  |                                  |                                        |              |
| 300-1,500                                               | --                               | --                               | F/1500                                 | 6            |
| 1,500-100,000                                           | --                               | --                               | 1                                      | 30           |

### Friis Formula

Friis transmission formula :  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### EUT Operating Condition

A software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



## Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : RXZ-PC80211G  
Report No. : ER04-04-071FRF  
Page 2 of 3

### Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

### Antenna Gain

Antenna 1 (white) Gain : The maximum Gain measured in fully anechoic chamber is 2dBi linear scale. Cable loss = 1dB.

Antenna 2 (black) Gain : The maximum Gain measured in fully anechoic chamber is 2dBi linear scale.

### Output Power into Antenna & RF Exposure Evaluation Distance

For Antenna 1 (white), Antenna Gain : 2dBi, cable loss : 1dB.

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density at 20cm (mW/cm <sup>2</sup> ) | LIMITS (mW/cm <sup>2</sup> ) |
|---------|-------------------------|-------------------------------|---------------------------------------------|------------------------------|
| CH1     | 2412.00                 | 20.46                         | 0.027844                                    | 1                            |
| CH6     | 2437.00                 | 22.27                         | 0.042241                                    | 1                            |
| CH11    | 2462.00                 | 22.23                         | 0.041853                                    | 1                            |

Note : 1. For Antenna 1 802.11b Mode (11Mbps).

2. The power density Pd (4th column) at a distance of 20cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>. The EUT is classified as mobile product. So, RF exposure limit warning or SAR test are not required.

For Antenna 1 (white), Antenna Gain : 2dBi, cable loss : 1dB.

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density at 20cm (mW/cm <sup>2</sup> ) | LIMITS (mW/cm <sup>2</sup> ) |
|---------|-------------------------|-------------------------------|---------------------------------------------|------------------------------|
| CH1     | 2412.00                 | 16.46                         | 0.011085                                    | 1                            |
| CH6     | 2437.00                 | 18.32                         | 0.017011                                    | 1                            |
| CH11    | 2462.00                 | 18.26                         | 0.016778                                    | 1                            |

Note : 1. For Antenna 1 802.11g Mode (6Mbps).

2. The power density Pd (4th column) at a distance of 20cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>. The EUT is classified as mobile product. So, RF exposure limit warning or SAR test are not required.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C  
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : RXZ-PC80211G

Report No. : ER04-04-071FRF

Page 3 of 3

For Antenna 2 (black), Antenna Gain : 2dBi.

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density at 20cm (mW/cm <sup>2</sup> ) | LIMITS (mW/cm <sup>2</sup> ) |
|---------|-------------------------|-------------------------------|---------------------------------------------|------------------------------|
| CH1     | 2412.00                 | 21.46                         | 0.044130                                    | 1                            |
| CH6     | 2437.00                 | 23.27                         | 0.066947                                    | 1                            |
| CH11    | 2462.00                 | 23.23                         | 0.066333                                    | 1                            |

Note : 1. For Antenna 2 802.11b Mode (11Mbps).

2. The power density Pd (4th column) at a distance of 20cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>. The EUT is classified as mobile product. So, RF exposure limit warning or SAR test are not required.

For Antenna 2 (black), Antenna Gain : 2dBi.

| Channel | Channel Frequency (MHz) | Output Power to Antenna (dBm) | Power Density at 20cm (mW/cm <sup>2</sup> ) | LIMITS (mW/cm <sup>2</sup> ) |
|---------|-------------------------|-------------------------------|---------------------------------------------|------------------------------|
| CH1     | 2412.00                 | 17.46                         | 0.017568                                    | 1                            |
| CH6     | 2437.00                 | 19.32                         | 0.026961                                    | 1                            |
| CH11    | 2462.00                 | 19.26                         | 0.026591                                    | 1                            |

Note : 1. For Antenna 2 802.11g Mode (6Mbps).

2. The power density Pd (4th column) at a distance of 20cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>. The EUT is classified as mobile product. So, RF exposure limit warning or SAR test are not required.