N066_3600W_主机参数贴纸(美规)_V1.01

84mm

Portable Power Station

Model: F3600 Pro

Battery Capacity:3840Wh(80Ah/48V)

AC Charge:1500W Max 100V-120VAC 50/60Hz

DC(XT90)Input:12V-160V-2000W Max

USB-A(×2)Output:5V-3A 9V-2A 12V-1.5A ,Total 36W

Type-C PD 20W(×3)Output:5V-3A, 9V-2.22A,12V-1.67A, Total 60W

Type-C PD 100W Output:(5V/9V/12V/15V)--3A 20V--5A, Total 100W

12V Output:12V--3A(×2)/10A/25A 372W Max

Extra Battery Port(×2):48V--4168W Max

LED:3W

Operating Temperature:-10~40°C

Charging Temperature:0~40°C

AC Output:100V-120VAC 50/60Hz

Off-grid Mode:Rated 3600W

Total DC Output:568W

Total AC and DC Output:4168W

FCC ID: 2BAK2-F3600PRO

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two

This device may not cause harmful interference, and This device must accept any interference received, including interference that may cause undesired operation.

△ CAUTION

This device is not intended for use in a commercial repair facility.Risk of Electric Shock. Refer replacement to qualified service personnel. Do not remove cover. Risk of Injury To Persons. Do not use this product if the power cord or the battery cables are damaged in any way.

△ WARNING

Risk of Electric Shock and Risk of Fire. This device is not to be stored in a vehicle. Do not overcharge the internal battery. See Instruction Manual. Do not smoke, strike a match, or cause a spark in the vicinity of the power pack. Only charge the internal battery in a well ventilated area.

△DANGER

This device is intended to be used indoors only. Do not use outdoors.

Manufacturer: shenzhen Qichang intelligent Technology Co., Ltd









Made in China

贴纸尺寸:84*139mm,公差-0.1mm; 材质工艺:75#合成纸,覆哑膜,防刮, 黑底白字;

注意:产品3600W放电时会达到60℃以上,在这 个温度内不能脱胶。

139mm

Label Location On EUT

