



REPORT No.: SZ23090242W01

TEST REPORT

APPLICANT : Nice North America LLC

PRODUCT NAME : Indoor Window Sensor

MODEL NAME : 2GIG-DW10E-900

BRAND NAME : 2GIG

FCC ID : EF400224

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2023-09-21

TEST DATE : 2023-09-27 to 2023-10-18

ISSUE DATE : 2023-11-15



Edited by:

Su Xiaoxian

Su Xiaoxian (Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	10
2.4. Test Configuration of EUT	11
2.5. Test Conditions	11
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Duty Cycle of Test Signal	15
3.3. Maximum Peak Conducted Output Power	16
3.4. Maximum Average Conducted Output Power	17
3.5. 6 dB Bandwidth	18
3.6. Conducted Spurious Emissions and Band Edge	19
3.7. Power Spectral Density	20
3.8. Conducted Emission	21
3.9. Radiated Emission	22
Annex A Test Data and Result	24



REPORT No.: SZ23090242W01

Change History		
Version	Date	Reason for change
1.0	2023-11-15	First edition

1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Oct. 23, 2023	He Yuyang	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Oct. 23, 2023	He Yuyang	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Oct. 23, 2023	He Yuyang	PASS	No deviation
5	15.247(a)	Bandwidth	Oct. 23, 2023	He Yuyang	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Oct. 23, 2023	He Yuyang	PASS	No deviation
7	15.247(e)	Power Spectral Density	Oct. 23, 2023	He Yuyang	PASS	No deviation
8	15.207	Conducted Emission	Sep. 27, 2023	Wang Deyong	PASS	No deviation
9	15.209, 15.247(d)	Radiated Emission	Oct.09, 2023	Yang Lian	PASS	No deviation

Note 1: Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

Note 2: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB558074 D01 v05r02.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2023.02.27	2024.02.26
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2023.02.09	2024.02.08
LISN	8127449	NSLK 8127	Schwarzbeck	2023.02.21	2024.02.20
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2023.06.27	2024.06.26
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	N/A	N/A

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
Morlab EMCR	Morlab	V1.2
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**1.2.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2023.06.21	2024.06.20
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2022.02.11	2025.02.10
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2022.07.13	2025.07.12
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2022.07.14	2025.07.13
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2023.07.04	2024.07.03
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2023.06.27	2024.06.26
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2023.06.27	2024.06.26
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2023.06.27	2024.06.26
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525
FCC Designation Number	CN1192
FCC Test Firm Registration Number	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant	Nice North America LLC
Applicant Address	5919 Sea Otter Place, Suite 100, Carlsbad, CA 92010
Manufacturer	Nice North America LLC
Manufacturer Address	5919 Sea Otter Place, Suite 100, Carlsbad, CA 92010

2.2. Information of EUT

Product Name:	Indoor Window Sensor	
Sample No.:	3#	
Hardware Version:	X1	
Software Version:	X1	
Modulation Technology:	Non-Hopping	
Equipment Type:	DTS	
Operating Frequency Range:	902MHz-928MHz	
Antenna Type:	Chip Antenna	
Antenna Gain:	-1dBi	
Accessory Information:	Battery	
	Brand Name:	Maxell
	Model No.:	CR2450
	Serial No.:	N/A
	Capacity:	600mAh
	Rated Voltage:	3.0V
	Charge Limit:	N/A
	Manufacturer:	Maxell Asia Ltd.

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	904	5	914
2	906	6	918
3	910	7	920
4	912	8	922

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.5. Test Conditions

Temperature (°C)	15-35
Relative Humidity (%)	30-60
Atmospheric Pressure (kPa)	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.

3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.

3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4. Test Result

Refer to Annex A.8 in this report.

3.9. Radiated Emission

3.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.9.2. Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.9.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4. Test Result

Refer to Annex A.9 in this report.



Annex A Test Data and Result


A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	900M_Non-Hopping	904	Ant1	100	0	0
NVNT	900M_Non-Hopping	912	Ant1	100	0	0
NVNT	900M_Non-Hopping	922	Ant1	100	0	0





Test Graphs

Duty Cycle NVNT 900M_Non-Hopping 904MHz Ant1



Duty Cycle NVNT 900M_Non-Hopping 912MHz Ant1






**A.2. Maximum Peak Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit (dBm)	Verdict
NVNT	900M_ Non-Hopping	904	Ant1	19.33	0	19.33	0.0857	30	Pass
NVNT	900M_ Non-Hopping	912	Ant1	19.38	0	19.38	0.0867	30	Pass
NVNT	900M_ Non-Hopping	922	Ant1	19.41	0	19.41	0.0873	30	Pass





Test Graphs

Peak Power NVNT 900M_Non-Hopping 904MHz Ant1



Peak Power NVNT 900M_Non-Hopping 912MHz Ant1






**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit (dBm)	Verdict
NVNT	900M_ Non-Hopping	904	Ant1	19.24	0	19.24	0.08395	30	Pass
NVNT	900M_ Non-Hopping	912	Ant1	19.35	0	19.35	0.0861	30	Pass
NVNT	900M_ Non-Hopping	922	Ant1	19.23	0	19.23	0.08375	30	Pass





Test Graphs

Average Power NVNT 900M_Non-Hopping 904MHz Ant1



Average Power NVNT 900M_Non-Hopping 912MHz Ant1






**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	900M_Non-Hopping	904	Ant1	0.621	0.5	Pass
NVNT	900M_Non-Hopping	912	Ant1	0.618	0.5	Pass
NVNT	900M_Non-Hopping	922	Ant1	0.625	0.5	Pass





Test Graphs

-6dB Bandwidth NVNT 900M_Non-Hopping 904MHz Ant1



-6dB Bandwidth NVNT 900M_Non-Hopping 912MHz Ant1






**A.5. Conducted Spurious Emissions**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	900M_Non-Hopping	904	Ant1	-48.94	-20	Pass
NVNT	900M_Non-Hopping	912	Ant1	-49.52	-20	Pass
NVNT	900M_Non-Hopping	922	Ant1	-49.04	-20	Pass




Test Graphs

Tx. Spurious NVNT 900M_Non-Hopping 904MHz Ant1 Ref




Tx. Spurious NVNT 900M_Non-Hopping 904MHz Ant1 Emission






Tx. Spurious NVNT 900M_Non-Hopping 912MHz Ant1 Ref




Tx. Spurious NVNT 900M_Non-Hopping 912MHz Ant1 Emission






Tx. Spurious NVNT 900M_Non-Hopping 922MHz Ant1 Ref



Tx. Spurious NVNT 900M_Non-Hopping 922MHz Ant1 Emission





REPORT No.: SZ23090242W01


A.6. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	900M_Non-Hopping	904	Ant1	-53.88	-20	Pass
NVNT	900M_Non-Hopping	922	Ant1	-57.8	-20	Pass




Test Graphs

Band Edge NVNT 900M_Non-Hopping 904MHz Ant1 Ref




Band Edge NVNT 900M_Non-Hopping 904MHz Ant1 Emission






Band Edge NVNT 900M_Non-Hopping 922MHz Ant1 Ref



Band Edge NVNT 900M_Non-Hopping 922MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	900M_ Non-Hopping	904	Ant1	7.89	0	7.89	8	Pass
NVNT	900M_ Non-Hopping	912	Ant1	7.53	0	7.53	8	Pass
NVNT	900M_ Non-Hopping	922	Ant1	7.28	0	7.28	8	Pass




Test Graphs

PSD NVNT 900M_Non-Hopping 904MHz Ant1



PSD NVNT 900M_Non-Hopping 912MHz Ant1





A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT +PC Adapter + PC + 902M TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1716	49.75	39.83	64.88	54.88	Line	PASS
2	0.1985	48.13	38.28	63.67	53.67		PASS
3	0.2302	45.07	34.24	62.44	52.44		PASS
4	0.4567	37.08	30.02	56.75	46.75		PASS
5	3.2607	31.96	22.87	56.00	46.00		PASS
6	18.0725	37.72	30.79	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1733	49.93	38.58	64.80	54.80	Neutral	PASS
2	0.2178	47.25	38.95	62.90	52.90		PASS
3	0.4696	35.58	29.64	56.52	46.52		PASS
4	1.3972	29.29	23.96	56.00	46.00		PASS
5	2.6101	30.21	23.39	56.00	46.00		PASS
6	18.2385	33.62	25.64	60.00	50.00		PASS



A.9. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 3: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.




Plot for Channel 1




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	28.93	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
71.7518	28.96	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
156.2262	38.80	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
179.5295	38.38	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
598.0180	36.28	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
840.7608	39.60	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1655.4617	36.47	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2275.6695	43.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2707.8564	39.33	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4988.9154	42.09	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7221.6635	44.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10629.5422	49.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 12.75GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
35.8258	31.88	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
71.7518	25.22	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
120.3003	27.32	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
167.8779	32.58	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
532.9630	32.24	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
598.9890	34.83	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1818.6743	37.25	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2519.8355	38.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3220.9968	39.31	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4988.9154	47.49	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7182.4925	43.88	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10639.9878	49.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Vertical, 1GHz to 12.75GHz)




Plot for Channel 4




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
71.7518	28.25	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
167.8779	37.36	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
258.1782	31.81	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
559.1792	36.83	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
664.0440	41.85	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
843.6737	37.76	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1655.4617	35.78	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2292.6436	43.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3190.9657	35.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4988.9154	41.31	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7262.1402	44.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10666.1018	49.47	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 12.75GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.5936	25.79	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
120.3003	30.03	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
167.8779	32.43	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
399.9399	30.53	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
599.9600	36.37	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
841.7317	36.79	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Vertical, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1801.7002	37.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2333.1203	40.38	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3192.2714	39.20	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4987.6097	47.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7228.1920	44.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10623.0137	48.97	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Vertical, 1GHz to 12.75GHz)




Plot for Channel 8




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
36.7968	27.52	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
107.6777	34.30	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
156.2262	38.82	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
180.5005	39.19	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
598.0180	38.62	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
839.7898	39.89	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1654.1560	37.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2271.7524	43.73	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2750.9445	39.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4988.9154	41.70	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7281.7257	43.94	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10653.0448	48.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 12.75GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
34.8549	27.63	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
71.7518	24.50	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
144.5746	27.83	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
265.9459	29.66	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
531.9920	34.55	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
840.7608	35.13	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS

(Antenna Vertical, 30MHz to 1GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
1992.3325	38.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2696.1051	39.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3286.2818	46.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4988.9154	46.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7217.7464	44.10	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12239.4711	49.70	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Vertical, 1GHz to 12.75GHz)

END OF REPORT