



TEST REPORT

Report Number. : 14008772-E2V3

Applicant : ENERGOUS CORPORATION
3590 NORTH FIRST STREET,
SUITE 210,
SAN JOSE, CA 95134, U.S.A.

Model : VN25

Brand : ENERGOUS

FCC ID : 2ADNG-VN25

EUT Description : WIRELESS CHARGER

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:

November 24, 2021

Prepared by:

UL VERIFICATION SERVICES

47173 Benicia Street

Fremont, CA 94538 U.S.A.

TEL: (510) 319-4000

FAX: (510) 661-0888



REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	11/22/2021	Initial Issue	--
V2	11/23/2021	Updated Section 6.5, 6.6, 11, 12	Tina Chu
V3	11/24/2021	Updated Section 6.5 to address TCB's question	Tina Chu

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	5
2. TEST RESULTS SUMMARY	7
3. TEST METHODOLOGY	7
4. FACILITIES AND ACCREDITATION	7
5. DECISION RULES AND MEASUREMENT UNCERTAINTY	8
5.1. METROLOGICAL TRACEABILITY	8
5.2. DECISION RULES.....	8
5.3. MEASUREMENT UNCERTAINTY.....	8
5.4. SAMPLE CALCULATION	8
6. EQUIPMENT UNDER TEST	9
6.1. EUT DESCRIPTION	9
6.2. MAXIMUM OUTPUT POWER.....	9
6.3. DESCRIPTION OF AVAILABLE ANTENNAS	9
6.4. SOFTWARE AND FIRMWARE.....	9
6.5. WORST-CASE CONFIGURATION AND MODE.....	10
6.6. DESCRIPTION OF TEST SETUP.....	11
7. MEASUREMENT METHOD.....	15
8. TEST AND MEASUREMENT EQUIPMENT	16
9. ANTENNA PORT TEST RESULTS.....	17
9.1. ON TIME AND DUTY CYCLE.....	17
9.2. 99% BANDWIDTH.....	18
9.3. 6 dB BANDWIDTH.....	20
9.4. OUTPUT POWER.....	22
9.5. AVERAGE POWER.....	23
9.6. POWER SPECTRAL DENSITY	24
9.7. CONDUCTED SPURIOUS EMISSIONS.....	27
10. RADIATED TEST RESULTS	30

10.1.	LIMITS AND PROCEDURE.....	30
10.2.	TRANSMITTER ABOVE 1 GHz.....	32
10.3.	WORST CASE BELOW 30MHZ.....	42
10.4.	WORST CASE BELOW 1 GHZ.....	43
10.5.	WORST CASE 18-26 GHZ.....	45
11.	AC POWER LINE CONDUCTED EMISSIONS	47
11.1.	CONFIGURATION 1	48
11.2.	CONFIGURATION 2	50
12.	SETUP PHOTOS	52

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: ENERGOUS CORPORATION
3590 NORTH FIRST STREET,
SUITE 210,
SAN JOSE, CA 95134, U.S.A.

EUT DESCRIPTION: WIRELESS CHARGER

MODEL: VN25

BRAND: ENERGOUS

SERIAL NUMBER: 2012 and 205B (CONDUCTED); 2060 (RADIATED)

SAMPLE RECEIPT DATE: SEPTEMBER 23, 2021

DATE TESTED: SEPTEMBER 24, 2021 TO NOVEMBER 18, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.


This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:




DAN CORONIA
OPERATIONS LEADER
UL Verification Services Inc.

Prepared By:



JOSE MARTINEZ
TEST ENGINEER
UL Verification Services Inc.

Reviewed By:



TINA CHU
SENIOR PROJECT ENGINEER
UL Verification Services Inc.

2. TEST RESULTS SUMMARY

This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for the validity of results after the integration of the data provided by the customer.

FCC Clause	Requirement	Result	Comment
See Comment	Duty Cycle	Reporting purposes only	ANSI C63.10 Section 11.6.
-	99% OBW	Reporting purposes only	ANSI C63.10 Section 6.9.3.
15.247 (a) (2)	6dB BW	Complies	None.
15.247 (b) (3)	Output Power	Complies	None.
See Comment	Average power	Reporting purposes only	Per ANSI C63.10, Section 11.9.2.3.2.
15.247 (e)	PSD	Complies	None.
15.247 (d)	Conducted Spurious Emissions	Complies	None.
15.209, 15.205	Radiated Emissions	Complies	None.
15.207	AC Mains Conducted Emissions	Complies	None.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01.

4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification #0751.05, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input type="checkbox"/>	Building 1: 47173 Benicia Street, Fremont, CA 94538, USA	US0104	2324A	208313
<input type="checkbox"/>	Building 2: 47266 Benicia Street, Fremont, CA 94538, USA	US0104	22541	208313
<input checked="" type="checkbox"/>	Building 4: 47658 Kato Rd, Fremont, CA 94538, USA	US0104	2324B	208313

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.78 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.40 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.84 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	6.01 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.73 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.51 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.29 dB

Uncertainty figures are valid to a confidence level of 95%.

5.4. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)
 $36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$

MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided:

Final Voltage (dBuV) = Measured Voltage (dBuV) + Cable Loss (dB) + Limiter Factor (dB) + LISN Insertion Loss.
 $36.5 \text{ dBuV} + 0 \text{ dB} + 10.1 \text{ dB} + 0 \text{ dB} = 46.6 \text{ dBuV}$

6. EQUIPMENT UNDER TEST

6.1. EUT DESCRIPTION

The EUT is a stand-alone wireless charger with BLE and MSK tag mode that is mounted on a ceiling or a wall. The wireless charger transmits power via a frequency hopping signal between 917.2MHz to 918.8MHz and a DTS MSK signal between 2402MHz and 2480MHz, and charges multiple receivers at a time.

This report documents test results of the Bluetooth Low Energy radio portion (BLE only supports 1Mbps) of the wireless charger.

6.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402 - 2480	BLE	18.80	75.86

6.3. DESCRIPTION OF AVAILABLE ANTENNAS

The antenna(s) gain and type, as provided by the manufacturer' are as follows:

The radio utilizes two internal PCB cross-polarized dipole antennas, with a maximum gain of 2.5 dBi.

6.4. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was plt_fw_fem_ant0_0dbm_pll96 for maximum power and plt_fw_fem_ant0_-4dbm_pll96 for Lower power setting.

The test utility software used during testing was plt_fw_fem_ant0_0dbm_pll96 for maximum power and plt_fw_fem_ant0_-4dbm_pll96 for Lower power setting.

6.5. WORST-CASE CONFIGURATION AND MODE

Radiated band edge, harmonics, and spurious emissions from 1 GHz to 18GHz were performed with the EUT was set to transmit at the Low/Middle/High channels.

Radiated emission below 30MHz, below 1GHz, above 18GHz, and power line conducted emission were performed with the EUT was set to transmit at the channel with highest output power as worst-case scenario.

The EUT is a wall or ceiling mounted device and it has one USB type C port for power only. The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z1, and Z2, it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation. Due to applicant is only able to exercise the commands via a USB cable that connected to a laptop, therefore all final radiated testing were performed with the EUT in Y orientation powered by laptop via USB cable.

AC powerline was performed in two configurations:

Configuration 1: powered by laptop via USB cable where the BLE Tx continuously

Configuration 2: powered by AC/DC adapter via USB cable where BLE (beaconing mode), MSK tag mode and WPT bands transmit simultaneously as worst case.

Worst-case data rate as provided by the client was:

BLE: 1 Mbps.

The EUT only supports BLE 2 Tx (MIMO) at the same time, it does not support 1 Tx (SISO). All radiated tests are performed on 2 Tx (MIMO) only.

WPT band and BLE (beaconing mode) transmit simultaneously, simultaneous operation result of the radiated emissions is documented in UL document 14008772-E1 WPT report.


6.6. DESCRIPTION OF TEST SETUP

SUPPORT TEST EQUIPMENT						
Description		Manufacturer	Model	Serial Number		FCC ID/ DoC
Laptop		Dell	Latitude E7470	3F94RC2		DoC
Laptop AC/DC adapter		Dell	LA65NM130	CN-03NKWD-72438-38D-0F54-A00		DoC
Faraday Cage		ETS-LINDGREN	Not available (Custom built)	ECSB-001		DoC
AC/DC Switching Adapter		CUI Inc.	SWI5	-		DoC
I/O CABLES (RF CONDUCTED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-shielded	1	AC Mains to AC/DC Adapter
2	DC	1	DC	Un-shielded	1.5	AC/DC Adapter to Laptop
3	USB	1	UART	Shielded	1.5	EUT to Laptop
4	Antenna	1	SMA	Un-shielded	0.15	To spectrum analyzer
I/O CABLES (RF RADIATED TEST/AC LINE CONDUCTED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-shielded	1	AC/DC Adapter to Laptop
2	DC	1	DC	Un-shielded	1.5	
3	USB	1	USB Type C	Shielded	1	

TEST SETUP

The EUT was connected to the test laptop via USB cable. Test software exercised the EUT.


SETUP DIAGRAMS




TEST SETUP- RADIATED TEST / AC LINE CONDUCTED TEST

The EUT was powered by laptop via USB cable. For radiated test, laptop was put inside a Faraday cage. Test software exercised the EUT.

SETUP DIAGRAM





7. MEASUREMENT METHOD

6 dB BW: ANSI C63.10 Subclause -11.8.1 RBW \geq DTS BW

Occupied BW (99%): ANSI C63.10-2013 Section 6.9.3

Output Power: ANSI C63.10 Subclause -11.9.1.3 Method PKPM1 Peak-reading power meter

Output Power: ANSI C63.10 Subclause -11.9.2.3.2 Method AVGPM-G (Measurement using a gated RF average-reading power meter)

PSD: ANSI C63.10 Subclause -11.10.2 Method PKPSD (peak PSD)

Radiated emissions non-restricted frequency bands: ANSI C63.10 Subclause -11.11

Radiated emissions restricted frequency bands: ANSI C63.10 Subclause -11.12.1

Conducted emissions in restricted frequency bands: ANSI C63.10 Subclause -11.12.2

Band-edge: ANSI C63.10 Subclause -11.13.3.4 Integration method -Trace averaging across ON and OFF times DC correction

AC Power Line Conducted Emissions: ANSI C63.10-2013, Section 6.2.

Radiated Spurious Emissions Below 30MHz: ANSI C63.10-2013 Section 6.4

8. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal
Antenna, Passive Loop 30Hz - 1MHz	ELECTRO METRICS	EM-6871	SC-8015	05/24/2022	05/24/2021
Antenna, Passive Loop 100KHz - 30MHz	ELECTRO METRICS	EM-6872	SC-8014	05/24/2022	05/24/2021
Antenna, Horn 1-18GHz	ETS-Lindgren (Cedar Park, Texas)	3117	80404	08/04/2022	08/04/2021
Amplifier, 100MHz-18GHz	AMPLICAL	AMP0.1G18-47-20	PRE0197319	04/08/2022	04/08/2021
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences Corp.	JB1	82258	10/01/2022	10/01/2021
Amplifier, 9KHz to 1GHz, 32dB	SONOMA INSTRUMENT	310	175953	01/21/2022	01/21/2021
EMI TEST RECEIVER	Rohde & Schwarz	ESW44	PRE0179367	02/21/2022	02/21/2021
Antenna, Horn 18 to 26.5GHz	ARA	MWH-1826/B	81139	05/25/2022	05/25/2021
Rf Amplifier, 18-26.5GHz, 60dB gain	AMPLICAL	AMP18G26.5-60	171590	05/21/2022	05/21/2021
Spectrum Analyzer, PSA, 3Hz to 26.5GHz	Keysight Technologies Inc	E4440A	T198	05/13/2022	05/13/2021
Power Meter, P-series single channel	Keysight Technologies Inc	N1911A	T1272	01/21/2022	01/21/2021
Power Sensor, P - series, 50MHz to 18GHz, Wideband	Keysight Technologies Inc	N1921A	T1223	06/17/2022	06/17/2021
AC Line Conducted					
LISN	Fischer Custom Communications, Inc	FCC-LISN-50/250- 25-2-01-480V	PRE0186446	01/20/2022	01/20/2021
EMI TEST RECEIVER	Rohde & Schwarz	ESR	T1436	02/19/2022	02/19/2021
Transient Limiter	TE	TBFL1	207996	06/01/2022	06/01/2021
UL TEST SOFTWARE LIST					
Radiated Software	UL	UL EMC	Rev 9.5, Jan 03, 2020		
Antenna Port Software	UL	UL RF	Ver 2021.08.27		
AC Line Conducted Software	UL	UL EMC	Rev 9.5, 07 Jul 2020		

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.


PROCEDURE

ANSI C63.10 Section 11.6 Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
2.4GHz Band						
BLE	0.396	0.627	0.631	63.15	2.00	2.526

Test Engineer	19498 ER
---------------	----------




9.2. 99% BANDWIDTH



LIMITS

None; for reporting purposes only.

RESULTS

Channel	Frequency (MHz)	99% Bandwidth Antenna 1 (MHz)	99% Bandwidth Antenna 2 (MHz)
Low	2402	1.0393	1.0397
Middle	2440	1.0404	1.043
High	2480	1.0438	1.0438





9.3. 6 dB BANDWIDTH



LIMITS



FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth Antenna 1 (MHz)	6 dB Bandwidth Antenna 2 (MHz)	Minimum Limit (MHz)
Low	2402	0.648	0.630	0.5
Middle	2440	0.666	0.606	0.5
High	2480	0.657	0.693	0.5





9.4. OUTPUT POWER

LIMITS

FCC §15.247 (b) (3)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The power output was measured on the EUT antenna port using SMA cable with 10dB attenuator connected to a power meter via wideband peak power sensor. Peak output power was read directly from power meter.

RESULTS

Tested By:	20756 CW & 23653 DC
Date:	10/1/2021 & 11/18/21

Channel	Frequency (MHz)	Output Power Antenna 1 (dBm)	Output Power Antenna 2 (dBm)	Total Power (dBm)	Limit (dBm)	Margin (dB)
Low	2402	15.48	16.07	18.80	30	-11.20
Middle	2440	15.60	15.98	18.80	30	-11.20
High	2480	12.92	12.74	15.84	30	-14.16

9.5. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The power output was measured on the EUT antenna port using SMA cable with 10dB attenuator connected to a power meter via wideband average power sensor. Gated average output power was read directly from power meter.

RESULTS

Tested By:	20756 CW & 23653 DC
Date:	10/1/2021 & 11/18/21

Channel	Frequency (MHz)	Average Power Antenna 1 (dBm)	Average Power Antenna 2 (dBm)	Total Power (dBm)
Low	2402	15.35	15.96	18.68
Middle	2440	15.47	15.87	18.68
High	2480	12.86	12.69	15.79

9.6. POWER SPECTRAL DENSITY

LIMITS


FCC §15.247 (e)



The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

PSD Results

Channel	Frequency (MHz)	Antenna 1 Meas (dBm/ 3kHz)	Antenna 2 Meas (dBm/ 3kHz)	Total Corr'd PSD (dBm/ 3kHz)	Limit (dBm/ 3kHz)	Margin (dB)
Low	2402	0.629	1.306	3.99	8.0	-4.0
Mid	2440	0.573	0.977	3.79	8.0	-4.2
High	2480	-1.297	-1.833	1.45	8.0	-6.5






9.7. CONDUCTED SPURIOUS EMISSIONS


LIMITS

FCC §15.247 (d)


Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dBc.

RESULTS







LOW CHANNEL BANDEDGE ANTENNA 2




OUT-OF-BAND LOW CHANNEL ANTENNA 2




IN-BAND REFERENCE LEVEL ANTENNA 2



OUT-OF-BAND MID CHANNEL ANTENNA 2



HIGH CHANNEL BANDEDGE ANTENNA 2



OUT-OF-BAND HIGH CHANNEL ANTENNA 2

10. RADIATED TEST RESULTS

10.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
0.009-0.490	2400/F(kHz) @ 300 m	-
0.490-1.705	24000/F(kHz) @ 30 m	-
1.705 - 30	30 @ 30m	-
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements in the 30-1000MHz range, 9kHz for peak and/or quasi-peak detection measurements in the 0.15-30MHz range and 200Hz for peak and/or quasi-peak detection measurements in the 9 to 150kHz range. Peak detection is used unless otherwise noted as quasi-peak or average (9-90kHz and 110-490kHz).

For pre-scans above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

For final measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and as applicable for average measurements.

The spectrum from 1 GHz to 18 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band. Below 1GHz and above 18GHz emissions, the channel with the highest output power was tested.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

For below 30MHz testing, investigation was done on three antenna orientations (parallel, perpendicular, and ground-parallel), parallel and perpendicular are the worst orientations, therefore testing was performed on these two orientations only. Blue color trace on plots: Parallel orientation. Green color trace on plots: Perpendicular orientation.

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.


KDB 414788 Open Field Site(OFS) and Chamber Correlation Justification

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

10.2. TRANSMITTER ABOVE 1 GHz

BANDEDGE (LOW CHANNEL)

HORIZONTAL RESULT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 80404 (dBm)	Amp/Ch/Tr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Altitude (Degs)	Height (cm)	Polarity
1	* 2.39	41.31	PK	32.1	-11.2	0	62.21	-	-	74	-11.79	23	101	H
2	* 2.38969	42.01	PK	32.1	-11.2	0	62.91	-	-	74	-11.09	23	101	H
3	* 2.39	22.46	RMS	32.1	-11.2	2	45.36	54	-8.64	-	-	23	101	H
4	* 2.38902	23.98	RMS	32.1	-11.2	2	46.88	54	-7.12	-	-	23	101	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 80404 (dB/m)	Amp/Chl/Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.55	Pk	32.1	-11.2	0	60.45	-	-	74	-13.55	22	195	V
2	* 2.38984	40.02	Pk	32.1	-11.2	0	61.82	-	-	74	-12.18	22	195	V
3	* 2.39	21.62	RMS	32.1	-11.2	2	44.52	54	-9.48	-	-	22	195	V
4	* 2.38857	22.83	RMS	32.1	-11.2	2	45.73	54	-8.27	-	-	22	195	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

BANDEDGE (HIGH CHANNEL)

HORIZONTAL RESULT




Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 80484 (dBm)	AmpChnFiltorPad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Altitude (Degs)	Height (cm)	Polarity
1	* 2.4835	47.05	Pk	32.7	-10.9	0	68.95	-	-	74	-5.15	27	145	H
2	* 2.4835	47.05	Pk	32.7	-10.9	0	68.95	-	-	74	-5.15	27	145	H
3	* 2.4835	28.4	RMS	32.7	-10.9	2	52.2	54	-1.8	-	-	27	145	H
4	* 2.4835	29.83	RMS	32.7	-10.9	2	53.63	54	-3.7	-	-	27	145	H

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL RESULT



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 80404 (dBm)	Amp/Chl/Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.4835	46.92	PK	32.7	-10.9	0	68.72	-	-	74	-5.28	28	163	V
2	* 2.48351	47.26	PK	32.7	-10.9	0	69.06	-	-	74	-4.94	28	163	V
3	* 2.4835	28.86	RMS	32.7	-10.9	2	52.66	54	-1.34	-	-	28	163	V
4	* 2.4839	29.36	RMS	32.7	-10.9	2	53.16	54	-1.34	-	-	28	163	V



* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK - Peak detector

RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL RESULTS



RADIATED EMISSIONS



Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF 85404 (dBm)	Amp/Ctx/Ftr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.8034	57.4	PK2	34.2	-40	0	51.6	-	-	74	-22.4	26	213	H
	* 4.80371	50.47	MAv1	34.2	-40	2	46.67	54	-7.33	-	-	26	213	H
2	7.20664	59.19	PK2	35.9	-37.8	0	57.29	-	-	-	-	313	99	H
3	* 12.01085	47.24	PK2	38.8	-33.8	0	52.24	-	-	74	-21.76	72	210	H
	* 12.00856	37.29	MAv1	38.8	-33.8	2	44.29	54	-9.71	-	-	72	210	H
4	16.81244	41.27	Pk	41.7	-31.8	0	51.17	-	-	-	-	0-360	199	H
5	* 4.8035	61.34	PK2	34.2	-40	0	55.54	-	-	74	-18.46	48	118	V
	* 4.80373	55.08	MAv1	34.2	-40	2	51.28	54	-2.72	-	-	48	118	V
6	7.20625	59.44	PK2	35.9	-37.8	0	57.54	-	-	-	-	56	272	V
7	* 12.01108	48.29	PK2	38.8	-33.8	0	53.29	-	-	74	-20.71	13	194	V
	* 12.00873	38.31	MAv1	38.8	-33.8	2	45.31	54	-8.69	-	-	13	194	V
8	16.81244	39.96	Pk	41.7	-31.8	0	49.96	-	-	-	-	0-360	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

MID CHANNEL RESULTS



RADIATED EMISSIONS



Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 80404 (dB/m)	Amp/Cbl/Filt/ Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.88032	55.21	PK2	34.1	-39.8	0	49.51	-	-	74	-24.49	32	217	H
	* 4.87976	47.73	MAv1	34.1	-39.8	2	44.03	54	-9.97	-	-	32	217	H
2	* 7.31921	58.46	PK2	35.8	-37.4	0	56.86	-	-	74	-17.14	349	298	H
	* 7.31923	51.62	MAv1	35.8	-37.4	2	52.02	54	-1.98	-	-	349	298	H
3	* 12.20131	45.66	PK2	39	-33.9	0	50.76	-	-	74	-23.24	351	149	H
	* 12.19861	34.72	MAv1	39	-33.9	2	41.82	54	-12.18	-	-	351	149	H
4	* 4.88045	61.12	PK2	34.1	-39.8	0	55.42	-	-	74	-18.58	50	137	V
	* 4.87969	55.21	MAv1	34.1	-39.8	2	51.51	54	-2.49	-	-	50	137	V
5	* 7.31922	58.71	PK2	35.8	-37.4	0	57.11	-	-	74	-16.89	56	267	V
	* 7.31928	51.98	MAv1	35.8	-37.4	2	52.38	54	-1.62	-	-	56	267	V
6	* 12.19861	47.28	PK2	39	-33.9	0	52.38	-	-	74	-21.62	10	191	V
	* 12.19862	37	MAv1	39	-33.9	2	44.1	54	-9.9	-	-	10	191	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

HIGH CHANNEL RESULTS



RADIATED EMISSIONS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 80404 (dB/m)	Amp/Cbl/Filt/P ad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.95947	60.37	PK2	34.1	-39.9	0	54.57	-	-	74	-19.43	23	99	H
	* 4.96026	53.68	MAv1	34.1	-39.9	2	49.88	54	-4.12	-	-	23	99	H
2	6.55445	47.85	PK2	35.9	-38.1	0	45.65	-	-	-	-	146	192	H
3	10.04552	47.12	PK2	37.3	-35.7	0	48.72	-	-	-	-	81	141	H
4	* 4.96005	60	PK2	34.1	-39.9	0	54.2	-	-	74	-19.8	68	145	V
	* 4.95958	53.69	MAv1	34.1	-39.9	2	49.89	54	-4.11	-	-	68	145	V
5	6.53706	47.74	PK2	35.9	-38.1	0	45.54	-	-	-	-	11	201	V
6	10.07036	46.63	PK2	37.4	-35.6	0	48.43	-	-	-	-	228	119	V


* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

10.3. WORST CASE BELOW 30MHZ

SPURIOUS EMISSIONS BELOW 30 MHz (WORST-CASE CONFIGURATION)



ANTENNA- TWO ORIENTATIONS FACE ON/FACE OFF

Below 30MHz Data

Marker	Frequency (MHz)	Meter Reading (dBUV)	Det	Loop Antenna (ACF)	Amp/Cbl (dB)	Dist Corr 300m	Corrected Reading (dBUV/m)	Peak Limit (dBUV/m)	Margin (dB)	Avg Limit (dBUV/m)	Margin (dB)	Azimuth (Degs)
1	.01214	23.01	Pk	60	-31.1	-80	-28.09	65.9	-93.99	45.9	-73.99	0-360
4	.01225	11.93	Pk	60	-31.1	-80	-39.17	65.82	-104.99	45.82	-84.99	0-360



Pk - Peak detector

Marker	Frequency (MHz)	Meter Reading (dBUV)	Det	Loop Antenna (ACF)	Amp/Cbl (dB)	Dist Corr 30m (dB)	Corrected Reading (dBUV/m)	QP Limit (dBUV/m)	Margin (dB)	Azimuth (Degs)
2	.67851	19.66	Pk	56.2	-32.1	-40	3.76	30.98	-27.22	0-360
3	.81109	24.79	Pk	56.2	-32.1	-40	8.89	29.43	-20.54	0-360
5	.67906	20.48	Pk	56.2	-32.1	-40	4.58	30.97	-26.39	0-360
6	.80747	22.13	Pk	56.2	-32.1	-40	6.23	29.47	-23.24	0-360
7	1.0935	17.09	Pk	46.4	-32.1	-40	-8.61	26.85	-35.46	0-360
8	1.91565	14.66	Pk	42	-32.1	-40	-15.44	29.5	-44.94	0-360
9	1.10252	16.88	Pk	46.4	-32.1	-40	-8.82	26.78	-35.6	0-360
10	1.90936	16.93	Pk	42.1	-32.1	-40	-13.07	29.5	-42.57	0-360

Pk - Peak detector

10.4. WORST CASE BELOW 1 GHZ

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)



Below 1GHz Data



Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	82258 ACF (dB)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	80.5456	38.71	Pk	13.6	-31	21.31	40	-18.69	0-360	197	H
4	37.37238	41.16	Pk	22.2	-31.4	31.96	40	-8.04	251	97	V
	37.37238	35.47	Qp	22.2	-31.4	26.27	40	-13.73	251	97	V
5	79.2702	49.48	Pk	13.8	-30.9	32.38	40	-7.62	0-360	97	V
6	* 168.8834	38.78	Pk	18.1	-30.3	26.58	43.52	-16.94	0-360	97	V
2	209.5012	35.36	Pk	17.1	-30.2	22.26	43.52	-21.26	0-360	299	H
3	709.5662	31.55	Pk	26.7	-28.3	29.95	46.02	-16.07	0-360	299	H

Pk - Peak detector

Qp - Quasi-Peak detector

10.5. WORST CASE 18-26 GHZ

SPURIOUS EMISSIONS 18-26 GHz (WORST-CASE CONFIGURATION)



18 – 26GHz DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF 81139 (dB/m)	Amp/Cbl (dB)	Dist Corr (dB)	Corrected Reading (dBuVolts)	Peak Limit (dBuV/m)	PK Margin (dB)	Average Limit dBuV/m	Margin (dB)
1	19.33689	68.91	Pk	33.5	-57	-9.5	35.91	74	-38.09	54	-18.09
2	21.49067	67.05	Pk	33.9	-57.3	-9.5	34.15	74	-39.85	54	-19.85
3	23.27022	68.42	Pk	34.4	-57.1	-9.5	36.22	74	-37.78	54	-17.78
4	19.30578	68.13	Pk	33.5	-57	-9.5	35.13	74	-38.87	54	-18.87
5	21.48	67.41	Pk	33.9	-57.1	-9.5	34.71	74	-39.29	54	-19.29
6	23.26489	68.42	Pk	34.4	-57.1	-9.5	36.22	74	-37.78	54	-17.78

Pk - Peak detector

11. AC POWER LINE CONDUCTED EMISSIONS

LIMITS


FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

RESULTS


11.1. CONFIGURATION 1 LINE 1 RESULTS



Range 1: Line-L1 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	PRE018644 6 L1	C1&C3 cable calibration factor	TekBox Limiter TBFL1 Model 207	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	QP Margin (dB)	CFR 47 Part 15 Class B Avg	Av(CISPR)M argin (dB)
2	.16125	16.87	Ca	0	0	9.4	26.27	-	-	55.4	-29.13
4	.26925	11.48	Ca	0	0	9.3	20.78	-	-	51.14	-30.36
6	.48975	11.99	Ca	0	0	9.3	21.29	-	-	46.17	-24.88
8	1.7385	11.8	Ca	0	.1	9.3	21.2	-	-	46	-24.8
10	3.43275	13.48	Ca	0	.1	9.3	22.88	-	-	46	-23.12
12	5.66925	8.91	Ca	0	.1	9.3	18.31	-	-	50	-31.69
1	.1635	36.5	Qp	0	0	9.4	45.9	65.28	-19.38	-	-
3	.2715	25.55	Qp	0	0	9.3	34.85	61.07	-26.22	-	-
5	.48975	24.88	Qp	0	0	9.3	34.18	56.17	-21.99	-	-
7	1.74075	24.28	Qp	0	.1	9.3	33.68	56	-22.32	-	-
9	3.43275	24.21	Qp	0	.1	9.3	33.61	56	-22.39	-	-
11	5.676	18.05	Qp	0	.1	9.3	27.45	60	-32.55	-	-

Qp - Quasi-Peak detector
Ca - CISPR average detection

LINE 2 RESULTS




Range 2: Line-L2 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	PRE018644 6 L2	C2&C3 cable	TekBox Limiter TBFL1 Model 207	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	QP Margin (dB)	CFR 47 Part 15 Class B Avg	Av(CISPR)Margin (dB)
14	.17475	23.84	Ca	0	0	9.4	33.24	-	-	54.73	-21.49
16	.23325	15.2	Ca	0	0	9.3	24.5	-	-	52.33	-27.83
18	.4875	13.39	Ca	0	0	9.3	22.69	-	-	46.21	-23.52
20	1.419	9.81	Ca	0	.1	9.3	19.21	-	-	46	-26.79
22	3.318	10.87	Ca	0	.1	9.3	20.27	-	-	46	-25.73
24	4.9965	7.48	Ca	0	.1	9.3	16.88	-	-	46	-29.12
13	.1725	34.94	Qp	0	0	9.4	44.34	64.84	-20.5	-	-
15	.231	27.43	Qp	0	0	9.3	36.73	62.41	-25.68	-	-
17	.492	27.49	Qp	0	0	9.3	36.79	56.13	-19.34	-	-
19	1.419	20.29	Qp	0	.1	9.3	29.69	56	-26.31	-	-
21	3.32025	19.56	Qp	0	.1	9.3	28.96	56	-27.04	-	-
23	5.001	14.7	Qp	0	.1	9.3	24.1	60	-35.9	-	-

Qp - Quasi-Peak detector

Ca - CISPR average detection

11.2. CONFIGURATION 2 LINE 1 RESULTS




Range 1: Line-L1 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	PRE018644 6 L1	LC Cables C1&C3 dB	TekBox Limiter TBFL1 Model 207	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	QP Margin (dB)	CFR 47 Part 15 Class B Avg	Av(CISPR)M argin (dB)
2	.1905	4.3	Ca	0	0	9.3	13.6	-	-	54.01	-40.41
4	.4785	17.07	Ca	0	0	9.3	26.37	-	-	46.37	-20
6	1.05225	14.98	Ca	0	.1	9.3	24.38	-	-	46	-21.62
8	2.10525	17.31	Ca	0	.1	9.3	26.71	-	-	46	-19.29
10	4.209	16.91	Ca	0	.1	9.3	26.31	-	-	46	-19.69
12	7.8135	1.72	Ca	0	.1	9.3	11.12	-	-	50	-38.88
1	.1905	16.14	Qp	0	0	9.3	25.44	64.01	-38.57	-	-
3	.47625	25.23	Qp	0	0	9.3	34.53	56.4	-21.87	-	-
5	1.05225	23.84	Qp	0	.1	9.3	33.24	56	-22.76	-	-
7	2.0985	27.73	Qp	0	.1	9.3	37.13	56	-18.87	-	-
9	4.1955	28.3	Qp	0	.1	9.3	37.7	56	-18.3	-	-
11	7.8675	17.85	Qp	0	.1	9.3	27.25	60	-32.75	-	-

Qp - Quasi-Peak detector

Ca - CISPR average detection

LINE 2 RESULTS



Range 2: Line-L2 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	PRE018644 6 L2	LC Cables C2&C3 dB	TekBox Limiter TBFL1 Model 207	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	QP Margin (dB)	CFR 47 Part 15 Class B Avg	Av(CISPR)M argin (dB)
14	.1905	-.34	Ca	0	0	9.3	8.96	-	-	54.01	-45.05
16	.4785	11.19	Ca	0	0	9.3	20.49	-	-	46.37	-25.88
18	1.005	9.87	Ca	0	.1	9.3	19.27	-	-	46	-26.73
20	2.63175	14.53	Ca	0	.1	9.3	23.93	-	-	46	-22.07
22	4.16625	11.58	Ca	0	.1	9.3	20.98	-	-	46	-25.02
24	16.20038	2.39	Ca	0	.2	9.3	11.89	-	-	50	-38.11
13	.159	13.66	Qp	0	0	9.4	23.06	65.52	-42.46	-	-
15	.48075	17.15	Qp	0	0	9.3	26.45	56.33	-29.88	-	-
17	1.00725	17.34	Qp	0	.1	9.3	26.74	56	-29.26	-	-
19	2.58675	24.66	Qp	0	.1	9.3	34.06	56	-21.94	-	-
21	4.1685	23.21	Qp	0	.1	9.3	32.61	56	-23.39	-	-
23	16.19925	14.97	Qp	0	.2	9.3	24.47	60	-35.53	-	-

Qp - Quasi-Peak detector

Ca - CISPR average detection