


### Test result for band edge emission at restricted bands

EUT	Mini PC	Model Name	Mini IT12
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

#### Test Graph for Peak Measurement



Test Graph for Average Measurement



**RESULT: PASS** 




EUT	Mini PC	Model Name	Mini IT12
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement




**RESULT: PASS** 




EUT	Mini PC	Model Name	Mini IT12
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




**RESULT: PASS** 



EUT	Mini PC	Model Name	Mini IT12
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



### **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer. The GFSK modulation is the worst case and recorded in the report.



### 11. NUMBER OF HOPPING FREQUENCY

#### 11.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- 2. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 3. VBW > RBW. Sweep: Auto. Detector function: Peak. Trace: Max hold.
- 4. Allow the trace to stabilize.

### 11.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

#### 11.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6

#### 11.4. LIMITS AND MEASUREMENT RESULT

Test Data of Number of Hopping Frequency					
Test Mode Number of Hopping Frequency Limits Pass or Fa					
GFSK Hopping	>=15	Pass			

# **Test Graphs of Number of Hopping Frequency**



Note: The GFSK modulation is the worst case and recorded in the report.



Report No.: AGC12060221001FE03

Page 72 of 85

# 12. TIME OF OCCUPANCY (DWELL TIME)

#### 12.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span: Zero span, centered on a hopping channel.
- 2. RBW shall be ≤channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- 4. Detector function: Peak. Trace: Max hold.
- 5. Use the marker-delta function to determine the transmit time per hop.
- 6. Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) = (number of hops on spectrum analyzer)  $\times$  (period specified in the requirements / analyzer sweep time)

7. The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements.

### 12.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 8.2

### 12.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6


#### 12.4. LIMITS AND MEASUREMENT RESULT

Test Data of Dwell Time						
Channel	Time of Pulse for DH5 (ms)	Number of hops in the period specified in the requirements	Sweep Time (ms)	Limit (ms)	Pass or Fail	
2402	2.883	31.0*4	357.492	400	Pass	
2441	2.883	25.0*4	288.300	400	Pass	
2480	2.882	25.0*4	288.200	400	Pass	

Note: The GFSK modulation is the worst case and recorded in the report.



### **Test Graphs of Dwell Time**





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_BR\_HOP\_ANT1\_NA\_1Mbps\_2402\_Time per Burst

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/








Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/







Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



### 13. FREQUENCY SEPARATION

#### 13.1. MEASUREMENT PROCEDURE

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span: Wide enough to capture the peaks of two adjacent channels.
- 2. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- 3. Video (or average) bandwidth (VBW) ≥ RBW.
- 4. Sweep: Auto. e) Detector function: Peak. f) Trace: Max hold. g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

### 13.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION)

Same as described in section 6.2


#### 13.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.3

#### 13.4. LIMITS AND MEASUREMENT RESULT

Test Data of Frequency Separation						
Test Mode Channel Separation (MHz) Limits Pass or F						
GFSK Hopping	1.001	>= 2/3 -20dB BW	Pass			

#### **Test Graphs of Number of Hopping Frequency**



Note: The GFSK modulation is the worst case and recorded in the report.



### 14. LINE CONDUCTED EMISSION TEST


### 14.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage				
	Q.P. (dBμV)	Average (dBμV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

#### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 14.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Report No.: AGC12060221001FE03 Page 78 of 85

#### 14.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


#### 14.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

#### 14.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Adapter 2
Line Conducted Emission Test Line 1-L



### MEASUREMENT RESULT: "agc fin"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.154000	57.90	6.9	66	7.9	OP	L1
0.182000	51.60	6.7	64	12.8	_	L1
0.218000	46.50	6.4	63	16.4		L1
3.574000	32.10	6.5	56	23.9	QP	L1
3.666000	32.70	6.5	56	23.3	OP	L1
3.806000	31.30	6.5	56	24.7	QP	L1

### MEASUREMENT RESULT: "agc\_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.158000	41.20	6.8	56	14.4	AV	L1
0.182000	33.40	6.7	54	21.0	AV	L1
0.494000	28.50	5.4	46	17.6	AV	L1
0.658000	27.70	5.4	46	18.3	AV	L1
4.998000	24.70	6.6	46	21.3	AV	L1
5.894000	28.70	6.6	50	21.3	AV	L1



#### Line Conducted Emission Test Line 2-N



### MEASUREMENT RESULT: "agc\_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.154000	58.60	6.9	66	7.2	QP	N
3.542000	33.90	6.5	56	22.1	QP	N
3.578000	33.50	6.5	56	22.5	QP	N
3.638000	32.20	6.5	56	23.8	QP	N
3.710000	34.40	6.5	56	21.6	QP	N
3.822000	31.80	6.5	56	24.2	QP	N


# MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.158000	41.20	6.8	56	14.4	AV	N
0.186000	37.40	6.6	54	16.8	AV	N
0.494000	28.10	5.4	46	18.0	AV	N
0.658000	27.50	5.4	46	18.5	AV	N
4.998000	25.40	6.6	46	20.6	AV	N
5.866000	29.60	6.6	50	20.4	AV	N

#### **RESULT: PASS**



Adapter 3
Line Conducted Emission Test Line 1-L



# MEASUREMENT RESULT: "agc\_fin"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	
0.450000	30.00	5.5	57	26.9	QP	L1	
19.330000	31.20	8.7	60	28.8	QP	L1	
20.082000	31.50	8.8	60	28.5	QP	L1	
20.802000	34.60	8.9	60	25.4	QP	L1	
21.038000	36.60	8.9	60	23.4	QP	L1	
21.518000	35.80	8.9	60	24.2	QP	L1	

### MEASUREMENT RESULT: "agc\_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	
0.446000	27.90	5.5	47	19.0	AV	L1	
19.366000	32.20	8.7	50	17.8	AV	L1	
20.562000	30.90	8.8	50	19.1	AV	L1	
20.802000	29.70	8.9	50	20.3	AV	L1	
21.042000	33.10	8.9	50	16.9	AV	L1	
21.518000	32.30	8.9	50	17.7	AV	L1	



#### Line Conducted Emission Test Line 2-N



### MEASUREMENT RESULT: "agc\_fin"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
19.362000 20.682000 20.722000 20.742000 21.042000 21.158000	34.10 31.90 31.30 31.70 37.00 33.00	8.7 8.9 8.9 8.9 8.9	60 60 60 60 60	25.9 28.1 28.7 28.3 23.0 27.0	QP QP	N N N N N


### MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.446000	27.50	5.5	47	19.4	AV	N
19.366000	32.50	8.7	50	17.5	AV	N
20.562000	31.00	8.8	50	19.0	AV	N
20.802000	29.50	8.9	50	20.5	AV	N
21.038000	33.10	8.9	50	16.9	AV	N
21.518000	32.50	8.9	50	17.5	AV	N

#### **RESULT: PASS**



Adapter 5
Line Conducted Emission Test Line 1-L



### MEASUREMENT RESULT: "agc\_fin"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.166000 0.190000 2.350000 21.574000 21.690000 23.042000	50.00 48.80 31.70 39.10 38.40 38.60	6.8 6.6 6.5 8.9 8.9 9.0	65 64 56 60 60	15.2 15.2 24.3 20.9 21.6 21.4	QP QP QP QP	L1 L1 L1 L1 L1 L1

# MEASUREMENT RESULT: "agc\_fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
14.858000 19.414000 21.090000 21.570000 22.050000 22.526000	33.60 31.50 35.20 35.30 33.70 33.60	8.3 8.8 8.9 9.0 9.0	50 50 50 50 50	16.4 18.5 14.8 14.7 16.3 16.4	AV AV AV	L1 L1 L1 L1 L1



#### Line Conducted Emission Test Line 2-N



### MEASUREMENT RESULT: "agc fin"


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.162000	52.40	6.8	65	13.0	QP	N
0.190000	48.10	6.6	64	15.9	QP	N
0.206000	40.50	6.5	63	22.9	QP	N
0.294000	37.30	6.1	60	23.1	QP	N
21.138000	38.40	8.9	60	21.6	QP	N
21.518000	38.80	8.9	60	21.2	QP	N

### MEASUREMENT RESULT: "agc fin2"

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
14.870000	34.30	8.3	50	15.7	AV	N
19.430000	28.80	8.8	50	21.2	AV	N
19.670000	27.70	8.8	50	22.3	AV	N
21.110000	29.50	8.9	50	20.5	AV	N
21.586000	34.10	8.9	50	15.9	AV	N
22.066000	32.40	9.0	50	17.6	AV	N

#### **RESULT: PASS**

Note: All the test modes had been tested, the mode 3 was the worst case. Only the data of the worst case would be record in this test report.





### **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

Refer to the Report No.: AGC12060221001AP02

**APPENDIX B: PHOTOGRAPHS OF EUT** 

Refer to the Report No.: AGC12060221001AP03

----END OF REPORT----



# Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.