



FCC RF Test Report

APPLICANT : TCL Communication Ltd.
EQUIPMENT : GSM/UMTS/LTE/NR Mobile phone
BRAND NAME : TCL
MODEL NAME : T803E
FCC ID : 2ACCJH183
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Mar. 16, 2024 ~ Mar. 27, 2024

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

Revision History	3
Summary of Test RESULT	4
1 General Description	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software	7
1.8 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test.....	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode	9
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	11
3 Test Result	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	30
3.6 AC Conducted Emission Measurement.....	34
3.7 Antenna Requirements.....	36
4 List of Measuring Equipment.....	37
5 Measurement Uncertainty	38
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR422702C	Rev. 01	Initial issue of report	Apr. 07, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.91 dB at 2389.52 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 3.41 dB at 13.56 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

TCL Communication Ltd.

5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong

1.2 Manufacturer

TCL Communication Ltd.

5/F, Building 22E, 22 Science Park East Avenue, Hong Kong Science Park, Shatin, NT, Hong Kong

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM/UMTS/LTE/NR Mobile phone
Brand Name	TCL
Model Name	T803E
FCC ID	2ACCJH183
IMEI Code/SN	Conducted: YTDMEIJZFYYTTOWK Conduction: 353318350121777/353318350121785 Radiation: 353318350121819/353318350121827
HW Version	05
SW Version	AGS7
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 20.02 dBm (0.1005 W) 802.11g : 23.89 dBm (0.2449 W) 802.11n HT20 : 24.21 dBm (0.2636 W) 802.11n HT40 : 24.30 dBm (0.2692 W)
99% Occupied Bandwidth	802.11b : 13.09MHz 802.11g : 16.93MHz 802.11n HT20 : 17.98MHz 802.11n HT40 : 36.76MHz
Antenna Type / Gain	FPC Antenna type with gain -1.5 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH03-SZ	CN1256	421272



1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.


Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Co-location mode
WLAN 2.4G 11n HT40 CH03 Tx + LTE Band 48 Link


Test Cases	
AC Conducted Emission	Mode 1 :GSM850 Idle + WLAN Link(2.4G) + NFC TX + Earphone + Battery 1 + USB Cable(Charging from Adapter 2)
Remark: For Radiated Test Cases, the tests were performed with Adapter 1, Earphone and USB Cable.	

2.3 Connection Diagram of Test System

For Conducted Emission:



For Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	NFC Card	N/A	N/A	N/A	N/A	N/A
5.	Earphone	apple	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuous transmit.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 3.3 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 3.3 + 20 = 23.3 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Jack Liu	Temperature :	21~25°C
		Relative Humidity :	51~54%


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----


100kHz PSD reference Level




Spurious Emission Plot-1



Spurious Emission Plot-2




Test Mode :	802.11b	Test Channel :	11
--------------------	---------	-----------------------	----






Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----


100kHz PSD reference Level



Spurious Emission Plot-1




Spurious Emission Plot-2






Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	01
-------------	--------------	----------------	----


100kHz PSD reference Level




Channel Plot



Spurious Emission Plot-1




Spurious Emission Plot-2






Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----


100kHz PSD reference Level



Spurious Emission Plot-1




Spurious Emission Plot-2






Test Mode :	802.11n HT20	Test Channel :	11
-------------	--------------	----------------	----






Test Mode :	802.11n HT40	Test Channel :	03
-------------	--------------	----------------	----






Test Mode :	802.11n HT40	Test Channel :	06
-------------	--------------	----------------	----


100kHz PSD reference Level



Spurious Emission Plot-1




Spurious Emission Plot-2





Test Mode :	802.11n HT40	Test Channel :	09
-------------	--------------	----------------	----



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 06, 2023	Mar. 16, 2024	Apr. 05, 2024	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 29, 2023	Mar. 16, 2024	Dec. 28, 2024	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Aug. 21, 2023	Mar. 16, 2024	Aug. 20, 2024	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 04, 2023	Mar. 23, 2024~Mar. 27, 2024	Apr. 03, 2024	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 04, 2023	Mar. 23, 2024~Mar. 27, 2024	Apr. 03, 2024	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jul. 28, 2022	Mar. 23, 2024~Mar. 27, 2024	Jul. 27, 2024	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Aug. 20, 2023	Mar. 23, 2024~Mar. 27, 2024	Aug. 19, 2025	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 08, 2023	Mar. 23, 2024~Mar. 27, 2024	Apr. 07, 2024	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 07, 2023	Mar. 23, 2024~Mar. 27, 2024	Jul. 06, 2024	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 08, 2023	Mar. 23, 2024~Mar. 27, 2024	Apr. 07, 2024	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz~3000MHz	Oct. 18, 2023	Mar. 23, 2024~Mar. 27, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 18, 2023	Mar. 23, 2024~Mar. 27, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 27, 2023	Mar. 23, 2024~Mar. 27, 2024	Dec. 26, 2024	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002729	N/A	Oct. 18, 2023	Mar. 23, 2024~Mar. 27, 2024	Oct. 17, 2024	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 23, 2024~Mar. 27, 2024	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 23, 2024~Mar. 27, 2024	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Jul. 06, 2023	Mar. 22, 2024	Jul. 05, 2024	Conduction (CO01-SZ)
AC LISN	R&S	ENV216	100063	9kHz~30MHz	Aug. 21, 2023	Mar. 22, 2024	Aug. 20, 2024	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 16, 2023	Mar. 22, 2024	Oct. 15, 2024	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 07, 2023	Mar. 22, 2024	Jul. 06, 2024	Conduction (CO01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Conducted Power Spectral Density	±1.32 dB
Frequency	±1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.0 dB
---	--------

----- THE END -----



Appendix A. Conducted Test Results

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Jack LIU	Temperature:	21~25	°C
Test Date:	2024/3/16	Relative Humidity:	51~54	%

TEST RESULTS DATA
Peak Output Power

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
					Ant 7	Ant 7	Ant 7	Ant 7	Ant 7	
11b	1Mbps	1	1	2412	19.45	30.00	-1.50	17.95	36.00	Pass
11b	1Mbps	1	6	2437	19.58	30.00	-1.50	18.08	36.00	Pass
11b	1Mbps	1	11	2462	20.02	30.00	-1.50	18.52	36.00	Pass
11g	6Mbps	1	1	2412	23.68	30.00	-1.50	22.18	36.00	Pass
11g	6Mbps	1	6	2437	23.72	30.00	-1.50	22.22	36.00	Pass
11g	6Mbps	1	11	2462	23.89	30.00	-1.50	22.39	36.00	Pass
HT20	MCS0	1	1	2412	23.79	30.00	-1.50	22.29	36.00	Pass
HT20	MCS0	1	6	2437	24.15	30.00	-1.50	22.65	36.00	Pass
HT20	MCS0	1	11	2462	24.21	30.00	-1.50	22.71	36.00	Pass
HT40	MCS0	1	3	2422	24.25	30.00	-1.50	22.75	36.00	Pass
HT40	MCS0	1	6	2437	24.11	30.00	-1.50	22.61	36.00	Pass
HT40	MCS0	1	9	2452	24.30	30.00	-1.50	22.80	36.00	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
					Ant 7	Ant 7	Ant 7	Ant 7	Ant 7	
11b	1Mbps	1	1	2412	17.90	30.00	-1.50	16.40	36.00	Pass
11b	1Mbps	1	6	2437	17.70	30.00	-1.50	16.20	36.00	Pass
11b	1Mbps	1	11	2462	18.20	30.00	-1.50	16.70	36.00	Pass
11g	6Mbps	1	1	2412	17.10	30.00	-1.50	15.60	36.00	Pass
11g	6Mbps	1	6	2437	17.30	30.00	-1.50	15.80	36.00	Pass
11g	6Mbps	1	11	2462	17.50	30.00	-1.50	16.00	36.00	Pass
HT20	MCS0	1	1	2412	17.30	30.00	-1.50	15.80	36.00	Pass
HT20	MCS0	1	6	2437	17.40	30.00	-1.50	15.90	36.00	Pass
HT20	MCS0	1	11	2462	17.50	30.00	-1.50	16.00	36.00	Pass
HT40	MCS0	1	3	2422	16.50	30.00	-1.50	15.00	36.00	Pass
HT40	MCS0	1	6	2437	16.30	30.00	-1.50	14.80	36.00	Pass
HT40	MCS0	1	9	2452	16.60	30.00	-1.50	15.10	36.00	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
					Ant 7	Ant 7		
11b	1Mbps	1	1	2412	12.99	8.08	0.50	Pass
11b	1Mbps	1	6	2437	13.09	7.60	0.50	Pass
11b	1Mbps	1	11	2462	13.04	8.08	0.50	Pass
11g	6Mbps	1	1	2412	16.93	15.38	0.50	Pass
11g	6Mbps	1	6	2437	16.88	15.16	0.50	Pass
11g	6Mbps	1	11	2462	16.93	15.36	0.50	Pass
HT20	MCS0	1	1	2412	17.88	15.16	0.50	Pass
HT20	MCS0	1	6	2437	17.93	15.16	0.50	Pass
HT20	MCS0	1	11	2462	17.98	15.14	0.50	Pass
HT40	MCS0	1	3	2422	36.46	35.16	0.50	Pass
HT40	MCS0	1	6	2437	36.76	35.24	0.50	Pass
HT40	MCS0	1	9	2452	36.76	35.16	0.50	Pass


TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)	DG (dBi)	Peak PSD Limit (dBm/3kHz)	Pass/Fail
					Ant 7	Ant 7	Ant 7	
11b	1Mbps	1	1	2412	-4.34	-1.50	8.00	Pass
11b	1Mbps	1	6	2437	-4.41	-1.50	8.00	Pass
11b	1Mbps	1	11	2462	-4.22	-1.50	8.00	Pass
11g	6Mbps	1	1	2412	-5.70	-1.50	8.00	Pass
11g	6Mbps	1	6	2437	-7.53	-1.50	8.00	Pass
11g	6Mbps	1	11	2462	-7.14	-1.50	8.00	Pass
HT20	MCS0	1	1	2412	-7.86	-1.50	8.00	Pass
HT20	MCS0	1	6	2437	-6.03	-1.50	8.00	Pass
HT20	MCS0	1	11	2462	-7.81	-1.50	8.00	Pass
HT40	MCS0	1	3	2422	-10.10	-1.50	8.00	Pass
HT40	MCS0	1	6	2437	-10.93	-1.50	8.00	Pass
HT40	MCS0	1	9	2452	-11.16	-1.50	8.00	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Yuki Tang	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
Condition: FCC 15C QP AC LISN 100063 N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.19	23.50	-30.34	53.84	2.90	10.45	10.15	Average
2	0.19	45.60	-18.24	63.84	25.00	10.45	10.15	QP
3	0.27	28.45	-22.71	51.16	8.21	10.09	10.15	Average
4	0.27	40.35	-20.81	61.16	20.11	10.09	10.15	QP
5	0.33	19.42	-29.98	49.40	-0.90	10.16	10.16	Average
6	0.33	37.82	-21.58	59.40	17.50	10.16	10.16	QP
7	0.39	19.66	-28.42	48.08	-0.91	10.41	10.16	Average
8	0.39	38.76	-19.32	58.08	18.19	10.41	10.16	QP
9	0.48	22.06	-24.30	46.36	1.60	10.30	10.16	Average
10	0.48	39.36	-17.00	56.36	18.90	10.30	10.16	QP
11	0.99	23.92	-22.08	46.00	3.50	10.26	10.16	Average
12	0.99	37.22	-18.78	56.00	16.80	10.26	10.16	QP
13 *	13.56	46.49	-3.51	50.00	25.80	10.23	10.46	Average
14	13.56	48.89	-11.11	60.00	28.20	10.23	10.46	QP

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

Test Engineer :	Reid Huang	Relative Humidity :	50%
		Temperature :	20-24℃

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	7	802.11b	01	2412	1Mbps	-	-
Mode 2	2400-2483.5	7	802.11b	06	2437	1Mbps	-	-
Mode 3	2400-2483.5	7	802.11b	11	2462	1Mbps	-	-
Mode 4	2400-2483.5	7	802.11g	01	2412	6Mbps	-	-
Mode 5	2400-2483.5	7	802.11g	06	2437	6Mbps	-	-
Mode 6	2400-2483.5	7	802.11g	11	2462	6Mbps	-	-
Mode 7	2400-2483.5	7	802.11n HT20	01	2412	MCS0	-	-
Mode 8	2400-2483.5	7	802.11n HT20	06	2437	MCS0	-	-
Mode 9	2400-2483.5	7	802.11n HT20	11	2462	MCS0	-	-
Mode 10	2400-2483.5	7	802.11n HT40	03	2422	MCS0	-	-
Mode 11	2400-2483.5	7	802.11n HT40	09	2452	MCS0	-	-
Mode 12	2400-2483.5	7	802.11n HT40	03	2422	MCS0	-	LF
Mode 13	CO-TX	7	802.11n HT40	03	2422	MCS0	-	-
		2	LTE Band 48 Link	-	-	-	-	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	802.11b	01	2344.06	39.20	54.00	-14.80	H	AVERAGE	Pass	Band Edge
1	802.11b	01	4824.00	43.81	74.00	-30.19	V	Peak	Pass	Harmonic
2	802.11b	06	-	-	-	-	-	-	-	Band Edge
2	802.11b	06	4874.00	45.98	74.00	-28.02	V	Peak	Pass	Harmonic
3	802.11b	11	2487.00	39.64	54.00	-14.36	V	AVERAGE	Pass	Band Edge
3	802.11b	11	4924.00	45.33	54.00	-8.67	V	Average	Pass	Harmonic
4	802.11g	01	-	-	-	-	-	-	-	Band Edge
4	802.11g	01	4824.00	41.72	74.00	-32.28	H	Peak	Pass	Harmonic
5	802.11g	06	-	-	-	-	-	-	-	Band Edge
5	802.11g	06	7311.00	44.04	74.00	-29.96	V	Peak	Pass	Harmonic
6	802.11g	11	-	-	-	-	-	-	-	Band Edge
6	802.11g	11	7386.00	44.70	74.00	-29.30	V	Peak	Pass	Harmonic
7	802.11n HT20	01	2389.82	43.30	54.00	-10.70	V	AVERAGE	Pass	Band Edge
7	802.11n HT20	01	4824.00	42.00	74.00	-32.00	V	Peak	Pass	Harmonic
8	802.11n HT20	06	-	-	-	-	-	-	-	Band Edge
8	802.11n HT20	06	7311.00	43.49	74.00	-30.51	V	Peak	Pass	Harmonic
9	802.11n HT20	11	2483.51	49.14	54.00	-4.86	V	AVERAGE	Pass	Band Edge
9	802.11n HT20	11	7386.00	43.72	74.00	-30.28	V	Peak	Pass	Harmonic
10	802.11n HT40	03	2389.52	49.89	54.00	-4.11	V	AVERAGE	Pass	Band Edge
10	802.11n HT40	03	7266.00	44.63	74.00	-29.37	H	Peak	Pass	Harmonic
11	802.11n HT40	09	2484.50	48.42	54.00	-5.58	V	AVERAGE	Pass	Band Edge
11	802.11n HT40	09	-	-	-	-	-	-	-	Harmonic
12	802.11n HT40	03	869.05	31.12	46	-14.88	H	Peak	Pass	LF
13	Co-TX	03	2389.52	50.09	54.00	-3.91	H	AVERAGE	Pass	Band Edge
13		03	7266.00	43.96	74.00	-30.04	H	Peak	Pass	Harmonic



Mode	1																																																																																										
	Band Edge																																																																																										
	2400-2483.5_802.11b_CH01_2412MHz																																																																																										
ANT	7																																																																																										
Pol.	Horizontal						Fundamental																																																																																				
Peak	Level (dBuV/m) Date: 2024-03-24 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2312.60</td><td>49.47</td><td>74.00</td><td>-24.53</td><td>47.60</td><td>30.76</td><td>4.72</td><td>33.61</td><td>324</td><td>233</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2312.60	49.47	74.00	-24.53	47.60	30.76	4.72	33.61	324	233	PEAK	Level (dBuV/m) Date: 2024-03-24 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>96.16</td><td>-----</td><td>-----</td><td>94.25</td><td>30.64</td><td>4.82</td><td>33.55</td><td>324</td><td>233</td><td>PEAK_74</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	96.16	-----	-----	94.25	30.64	4.82	33.55	324	233	PEAK_74
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2312.60	49.47	74.00	-24.53	47.60	30.76	4.72	33.61	324	233	PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2412.00	96.16	-----	-----	94.25	30.64	4.82	33.55	324	233	PEAK_74																																																																																
Avg	Level (dBuV/m) Date: 2024-03-24 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2344.06</td><td>39.20</td><td>54.00</td><td>-14.80</td><td>37.34</td><td>30.70</td><td>4.75</td><td>33.59</td><td>324</td><td>233</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2344.06	39.20	54.00	-14.80	37.34	30.70	4.75	33.59	324	233	AVERAGE	Level (dBuV/m) Date: 2024-03-24 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>93.83</td><td>-----</td><td>-----</td><td>91.92</td><td>30.64</td><td>4.82</td><td>33.55</td><td>324</td><td>233</td><td>AVERAGE_54</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	93.83	-----	-----	91.92	30.64	4.82	33.55	324	233	AVERAGE_54
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2344.06	39.20	54.00	-14.80	37.34	30.70	4.75	33.59	324	233	AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2412.00	93.83	-----	-----	91.92	30.64	4.82	33.55	324	233	AVERAGE_54																																																																																



Mode	1																																																																																											
	Band Edge																																																																																											
	2400-2483.5_802.11b_CH01_2412MHz																																																																																											
ANT	7																																																																																											
Pol.	Vertical						Fundamental																																																																																					
Peak	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2336 2362 2388 2414 2440 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2377.86</td><td>50.27</td><td>74.00</td><td>-23.73</td><td>48.43</td><td>30.63</td><td>4.78</td><td>33.57</td><td>134</td><td>236</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2377.86	50.27	74.00	-23.73	48.43	30.63	4.78	33.57	134	236	PEAK	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>97.34</td><td>-----</td><td>-----</td><td>95.43</td><td>30.64</td><td>4.82</td><td>33.55</td><td>134</td><td>236</td><td>PEAK_74</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	97.34	-----	-----	95.43	30.64	4.82	33.55	134	236	PEAK_74
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2377.86	50.27	74.00	-23.73	48.43	30.63	4.78	33.57	134	236	PEAK																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2412.00	97.34	-----	-----	95.43	30.64	4.82	33.55	134	236	PEAK_74																																																																																	
Avg	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2336 2362 2388 2414 2440 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2385.40</td><td>39.02</td><td>54.00</td><td>-14.98</td><td>37.18</td><td>30.62</td><td>4.79</td><td>33.57</td><td>134</td><td>236</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2385.40	39.02	54.00	-14.98	37.18	30.62	4.79	33.57	134	236	AVERAGE	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2412.00</td><td>95.21</td><td>-----</td><td>-----</td><td>93.30</td><td>30.64</td><td>4.82</td><td>33.55</td><td>134</td><td>236</td><td>AVERAGE_AVG_54</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	95.21	-----	-----	93.30	30.64	4.82	33.55	134	236	AVERAGE_AVG_54
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2385.40	39.02	54.00	-14.98	37.18	30.62	4.79	33.57	134	236	AVERAGE																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2412.00	95.21	-----	-----	93.30	30.64	4.82	33.55	134	236	AVERAGE_AVG_54																																																																																	







Mode	1																																																																																										
	Harmonic																																																																																										
	2400-2483.5_802.11b_CH01_2412MHz																																																																																										
ANT	7																																																																																										
Pol.	Horizontal										Vertical																																																																																
Peak Avg	Level (dBuV/m) Date: 2024-03-24 PEAK_74 AVG_54 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>41.63</td><td>74.00</td><td>-32.37</td><td>57.10</td><td>34.26</td><td>7.75</td><td>57.48</td><td>--</td><td>-- Peak</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	41.63	74.00	-32.37	57.10	34.26	7.75	57.48	--	-- Peak	Level (dBuV/m) Date: 2024-03-24 PEAK_74 AVG_54 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4824.00</td><td>43.81</td><td>74.00</td><td>-30.19</td><td>59.28</td><td>34.26</td><td>7.75</td><td>57.48</td><td>--</td><td>-- Peak</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	43.81	74.00	-30.19	59.28	34.26	7.75	57.48	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																	
1	4824.00	41.63	74.00	-32.37	57.10	34.26	7.75	57.48	--	-- Peak																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																	
1	4824.00	43.81	74.00	-30.19	59.28	34.26	7.75	57.48	--	-- Peak																																																																																	



Mode	2																																																																																																																				
	Harmonic																																																																																																																				
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																																				
ANT	7																																																																																																																				
Pol.	Horizontal										Vertical																																																																																																										
Peak Avg	Level (dBuV/m) Date: 2024-03-26 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>42.53</td><td>74.00</td><td>-31.47</td><td>57.95</td><td>34.33</td><td>7.77</td><td>57.52</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>43.67</td><td>74.00</td><td>-30.33</td><td>58.22</td><td>35.44</td><td>8.93</td><td>58.92</td><td>--</td><td>--</td><td>Peak</td></tr></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	42.53	74.00	-31.47	57.95	34.33	7.77	57.52	--	--	Peak	2	7311.00	43.67	74.00	-30.33	58.22	35.44	8.93	58.92	--	--	Peak	Level (dBuV/m) Date: 2024-03-26 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4874.00</td><td>45.98</td><td>74.00</td><td>-28.02</td><td>61.40</td><td>34.33</td><td>7.77</td><td>57.52</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>43.42</td><td>74.00</td><td>-30.58</td><td>57.97</td><td>35.44</td><td>8.93</td><td>58.92</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4874.00	45.98	74.00	-28.02	61.40	34.33	7.77	57.52	--	--	Peak	2	7311.00	43.42	74.00	-30.58	57.97	35.44	8.93	58.92	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																													
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																											
1	4874.00	42.53	74.00	-31.47	57.95	34.33	7.77	57.52	--	--	Peak																																																																																																										
2	7311.00	43.67	74.00	-30.33	58.22	35.44	8.93	58.92	--	--	Peak																																																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																											
1	4874.00	45.98	74.00	-28.02	61.40	34.33	7.77	57.52	--	--	Peak																																																																																																										
2	7311.00	43.42	74.00	-30.58	57.97	35.44	8.93	58.92	--	--	Peak																																																																																																										



Mode	3																																																																																										
	Band Edge																																																																																										
	2400-2483.5_802.11b_CH11_2462MHz																																																																																										
ANT	7																																																																																										
Pol.	Horizontal						Fundamental																																																																																				
Peak	Level (dBuV/m) Date: 2024-03-24  PEAK_BE_74						Level (dBuV/m) Date: 2024-03-24  PEAK_74																																																																																				
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2487.19</td><td>50.87</td><td>74.00</td><td>-23.13</td><td>48.58</td><td>30.87</td><td>4.93</td><td>33.51</td><td>338</td><td>229</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2487.19	50.87	74.00	-23.13	48.58	30.87	4.93	33.51	338	229	PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>94.07</td><td>-----</td><td>-----</td><td>91.94</td><td>30.77</td><td>4.89</td><td>33.53</td><td>338</td><td>229</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	94.07	-----	-----	91.94	30.77	4.89	33.53	338	229
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2487.19	50.87	74.00	-23.13	48.58	30.87	4.93	33.51	338	229	PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	94.07	-----	-----	91.94	30.77	4.89	33.53	338	229	PEAK																																																																																
Avg	Level (dBuV/m) Date: 2024-03-24  AVG_BE_54						Level (dBuV/m) Date: 2024-03-24  AVG_54																																																																																				
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2496.96</td><td>39.36</td><td>54.00</td><td>-14.64</td><td>37.01</td><td>30.91</td><td>4.94</td><td>33.50</td><td>338</td><td>229</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2496.96	39.36	54.00	-14.64	37.01	30.91	4.94	33.50	338	229	AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>91.65</td><td>-----</td><td>-----</td><td>89.52</td><td>30.77</td><td>4.89</td><td>33.53</td><td>338</td><td>229</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	91.65	-----	-----	89.52	30.77	4.89	33.53	338	229
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2496.96	39.36	54.00	-14.64	37.01	30.91	4.94	33.50	338	229	AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	91.65	-----	-----	89.52	30.77	4.89	33.53	338	229	AVERAGE																																																																																



Mode	3																																																																																										
	Band Edge																																																																																										
	2400-2483.5_802.11b_CH11_2462MHz																																																																																										
ANT	7																																																																																										
Pol.	Vertical						Fundamental																																																																																				
Peak	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2462 2469.6 2477.2 2484.8 2492.4 2500 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2486.85</td><td>50.52</td><td>74.00</td><td>-23.48</td><td>48.25</td><td>30.86</td><td>4.92</td><td>33.51</td><td>169</td><td>287</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2486.85	50.52	74.00	-23.48	48.25	30.86	4.92	33.51	169	287	PEAK	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>100.83</td><td>-----</td><td>-----</td><td>98.70</td><td>30.77</td><td>4.89</td><td>33.53</td><td>169</td><td>287</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	100.83	-----	-----	98.70	30.77	4.89	33.53	169	287	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2486.85	50.52	74.00	-23.48	48.25	30.86	4.92	33.51	169	287	PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	100.83	-----	-----	98.70	30.77	4.89	33.53	169	287	PEAK																																																																																
Avg	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2462 2469.6 2477.2 2484.8 2492.4 2500 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.00</td><td>39.64</td><td>54.00</td><td>-14.36</td><td>37.37</td><td>30.86</td><td>4.92</td><td>33.51</td><td>169</td><td>287</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2487.00	39.64	54.00	-14.36	37.37	30.86	4.92	33.51	169	287	AVERAGE	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>98.43</td><td>-----</td><td>-----</td><td>96.30</td><td>30.77</td><td>4.89</td><td>33.53</td><td>169</td><td>287</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	98.43	-----	-----	96.30	30.77	4.89	33.53	169	287	AVERAGE
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2487.00	39.64	54.00	-14.36	37.37	30.86	4.92	33.51	169	287	AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	98.43	-----	-----	96.30	30.77	4.89	33.53	169	287	AVERAGE																																																																																



Mode	3																																																																																																																		
	Harmonic																																																																																																																		
	2400-2483.5_802.11b_CH11_2462MHz																																																																																																																		
ANT	7																																																																																																																		
Pol.	Horizontal								Vertical																																																																																																										
Peak Avg	Level (dBuV/m) Date: 2024-03-24 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>43.85</td><td>74.00</td><td>-30.15</td><td>59.21</td><td>34.40</td><td>7.79</td><td>57.55 -- Peak</td></tr><tr><td>2</td><td>7386.00</td><td>43.55</td><td>74.00</td><td>-30.45</td><td>57.91</td><td>35.42</td><td>9.17</td><td>58.95 -- Peak</td></tr></table>									Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB		1	4924.00	43.85	74.00	-30.15	59.21	34.40	7.79	57.55 -- Peak	2	7386.00	43.55	74.00	-30.45	57.91	35.42	9.17	58.95 -- Peak	Level (dBuV/m) Date: 2024-03-24 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>49.64</td><td>74.00</td><td>-24.36</td><td>65.00</td><td>34.40</td><td>7.79</td><td>57.55 352 77 Peak</td></tr><tr><td>2</td><td>4924.00</td><td>45.33</td><td>54.00</td><td>-8.67</td><td>60.69</td><td>34.40</td><td>7.79</td><td>57.55 352 77 Average</td></tr><tr><td>3</td><td>7386.00</td><td>43.44</td><td>74.00</td><td>-30.56</td><td>57.80</td><td>35.42</td><td>9.17</td><td>58.95 -- Peak</td></tr></table>									Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB		1	4924.00	49.64	74.00	-24.36	65.00	34.40	7.79	57.55 352 77 Peak	2	4924.00	45.33	54.00	-8.67	60.69	34.40	7.79	57.55 352 77 Average	3	7386.00	43.44	74.00	-30.56	57.80	35.42	9.17	58.95 -- Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																											
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																												
1	4924.00	43.85	74.00	-30.15	59.21	34.40	7.79	57.55 -- Peak																																																																																																											
2	7386.00	43.55	74.00	-30.45	57.91	35.42	9.17	58.95 -- Peak																																																																																																											
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																												
1	4924.00	49.64	74.00	-24.36	65.00	34.40	7.79	57.55 352 77 Peak																																																																																																											
2	4924.00	45.33	54.00	-8.67	60.69	34.40	7.79	57.55 352 77 Average																																																																																																											
3	7386.00	43.44	74.00	-30.56	57.80	35.42	9.17	58.95 -- Peak																																																																																																											





Mode	4																																																																																										
	Harmonic																																																																																										
	2400-2483.5_802.11g_CH01_2412MHz																																																																																										
ANT	7																																																																																										
Pol.	Horizontal						Vertical																																																																																				
Peak Avg	Level (dBuV/m) Date: 2024-03-26 PEAK_74 AVG_54 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>41.72</td><td>74.00</td><td>-32.28</td><td>57.19</td><td>34.26</td><td>7.75</td><td>57.48</td><td>--</td><td>-- Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	41.72	74.00	-32.28	57.19	34.26	7.75	57.48	--	-- Peak	Level (dBuV/m) Date: 2024-03-26 PEAK_74 AVG_54 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>40.82</td><td>74.00</td><td>-33.18</td><td>56.29</td><td>34.26</td><td>7.75</td><td>57.48</td><td>--</td><td>-- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	40.82	74.00	-33.18	56.29	34.26	7.75	57.48	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																	
1	4824.00	41.72	74.00	-32.28	57.19	34.26	7.75	57.48	--	-- Peak																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																	
1	4824.00	40.82	74.00	-33.18	56.29	34.26	7.75	57.48	--	-- Peak																																																																																	



Mode	5																																																																																																																							
	Harmonic																																																																																																																							
	2400-2483.5_802.11g_CH06_2437MHz																																																																																																																							
ANT	7																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2024-03-26 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4874.00</td><td>42.09</td><td>74.00</td><td>-31.91</td><td>57.51</td><td>34.33</td><td>7.77</td><td>57.52</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>43.40</td><td>74.00</td><td>-30.60</td><td>57.95</td><td>35.44</td><td>8.93</td><td>58.92</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4874.00	42.09	74.00	-31.91	57.51	34.33	7.77	57.52	--	--	Peak	2	7311.00	43.40	74.00	-30.60	57.95	35.44	8.93	58.92	--	--	Peak	Level (dBuV/m) Date: 2024-03-26 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4874.00</td><td>42.32</td><td>74.00</td><td>-31.68</td><td>57.74</td><td>34.33</td><td>7.77</td><td>57.52</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>44.04</td><td>74.00</td><td>-29.96</td><td>58.59</td><td>35.44</td><td>8.93</td><td>58.92</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4874.00	42.32	74.00	-31.68	57.74	34.33	7.77	57.52	--	--	Peak	2	7311.00	44.04	74.00	-29.96	58.59	35.44	8.93	58.92	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4874.00	42.09	74.00	-31.91	57.51	34.33	7.77	57.52	--	--	Peak																																																																																																													
2	7311.00	43.40	74.00	-30.60	57.95	35.44	8.93	58.92	--	--	Peak																																																																																																													
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4874.00	42.32	74.00	-31.68	57.74	34.33	7.77	57.52	--	--	Peak																																																																																																													
2	7311.00	44.04	74.00	-29.96	58.59	35.44	8.93	58.92	--	--	Peak																																																																																																													



Mode	6																																																														
	Harmonic																																																														
	2400-2483.5_802.11g_CH11_2462MHz																																																														
ANT	7																																																														
Pol.	Horizontal						Vertical																																																								
Peak Avg																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>42.64</td><td>74.00</td><td>-31.36</td><td>58.00</td><td>34.40</td><td>7.79</td><td>57.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7386.00</td><td>43.43</td><td>74.00</td><td>-30.57</td><td>57.79</td><td>35.42</td><td>9.17</td><td>58.95</td><td>--</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	4924.00	42.64	74.00	-31.36	58.00	34.40	7.79	57.55	--	--	Peak	2	7386.00	43.43	74.00	-30.57	57.79	35.42	9.17	58.95	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																								
1	4924.00	42.64	74.00	-31.36	58.00	34.40	7.79	57.55	--	--	Peak																																																				
2	7386.00	43.43	74.00	-30.57	57.79	35.42	9.17	58.95	--	--	Peak																																																				
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>42.34</td><td>74.00</td><td>-31.66</td><td>57.70</td><td>34.40</td><td>7.79</td><td>57.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7386.00</td><td>44.70</td><td>74.00</td><td>-29.30</td><td>59.06</td><td>35.42</td><td>9.17</td><td>58.95</td><td>--</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB		1	4924.00	42.34	74.00	-31.66	57.70	34.40	7.79	57.55	--	--	Peak	2	7386.00	44.70	74.00	-29.30	59.06	35.42	9.17	58.95	--	--	Peak	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																								
1	4924.00	42.34	74.00	-31.66	57.70	34.40	7.79	57.55	--	--	Peak																																																				
2	7386.00	44.70	74.00	-29.30	59.06	35.42	9.17	58.95	--	--	Peak																																																				



Mode	7																																																																																											
	Band Edge																																																																																											
	2400-2483.5_802.11n HT20_CH01_2412MHz																																																																																											
ANT	7																																																																																											
Pol.	Horizontal						Fundamental																																																																																					
Peak	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2336 2362 2388 2414 2440 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.39</td><td>57.77</td><td>74.00</td><td>-16.23</td><td>55.94</td><td>30.61</td><td>4.79</td><td>33.57</td><td>324</td><td>228</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2388.39	57.77	74.00	-16.23	55.94	30.61	4.79	33.57	324	228	PEAK	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>97.16</td><td>-----</td><td>-----</td><td>95.27</td><td>30.63</td><td>4.82</td><td>33.56</td><td>324</td><td>228</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	97.16	-----	-----	95.27	30.63	4.82	33.56	324	228	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2388.39	57.77	74.00	-16.23	55.94	30.61	4.79	33.57	324	228	PEAK																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2412.00	97.16	-----	-----	95.27	30.63	4.82	33.56	324	228	PEAK																																																																																	
Avg	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2336 2362 2388 2414 2440 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>41.80</td><td>54.00</td><td>-12.20</td><td>39.96</td><td>30.61</td><td>4.80</td><td>33.57</td><td>324</td><td>228</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.95	41.80	54.00	-12.20	39.96	30.61	4.80	33.57	324	228	AVERAGE	Level (dBuV/m) Date: 2024-03-24 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>89.93</td><td>-----</td><td>-----</td><td>88.02</td><td>30.64</td><td>4.82</td><td>33.55</td><td>324</td><td>228</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	89.93	-----	-----	88.02	30.64	4.82	33.55	324	228	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2389.95	41.80	54.00	-12.20	39.96	30.61	4.80	33.57	324	228	AVERAGE																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2412.00	89.93	-----	-----	88.02	30.64	4.82	33.55	324	228	AVERAGE																																																																																	



Mode	7																																																																																											
	Band Edge																																																																																											
	2400-2483.5_802.11n_HT20_CH01_2412MHz																																																																																											
ANT	7																																																																																											
Pol.	Vertical						Fundamental																																																																																					
Peak	Level (dBuV/m) Date: 2024-03-24 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.65</td><td>59.54</td><td>74.00</td><td>-14.46</td><td>57.71</td><td>30.61</td><td>4.79</td><td>33.57</td><td>284</td><td>283</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2388.65	59.54	74.00	-14.46	57.71	30.61	4.79	33.57	284	283	PEAK	Level (dBuV/m) Date: 2024-03-24 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>97.85</td><td>-----</td><td>-----</td><td>95.94</td><td>30.64</td><td>4.82</td><td>33.55</td><td>284</td><td>283</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	97.85	-----	-----	95.94	30.64	4.82	33.55	284	283	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2388.65	59.54	74.00	-14.46	57.71	30.61	4.79	33.57	284	283	PEAK																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2412.00	97.85	-----	-----	95.94	30.64	4.82	33.55	284	283	PEAK																																																																																	
Avg	Level (dBuV/m) Date: 2024-03-24 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.82</td><td>43.30</td><td>54.00</td><td>-10.70</td><td>41.46</td><td>30.61</td><td>4.80</td><td>33.57</td><td>284</td><td>283</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.82	43.30	54.00	-10.70	41.46	30.61	4.80	33.57	284	283	AVERAGE	Level (dBuV/m) Date: 2024-03-24 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>91.00</td><td>-----</td><td>-----</td><td>89.09</td><td>30.64</td><td>4.82</td><td>33.55</td><td>284</td><td>283</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2412.00	91.00	-----	-----	89.09	30.64	4.82	33.55	284	283	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2389.82	43.30	54.00	-10.70	41.46	30.61	4.80	33.57	284	283	AVERAGE																																																																																	
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																					
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																			
1	2412.00	91.00	-----	-----	89.09	30.64	4.82	33.55	284	283	AVERAGE																																																																																	







Mode	7																																																																																																
	Harmonic																																																																																																
	2400-2483.5_802.11n HT20_CH01_2412MHz																																																																																																
ANT	7																																																																																																
Pol.	Horizontal										Vertical																																																																																						
Peak Avg	Level (dBuV/m) Date: 2024-03-26 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4824.00</td><td>40.67</td><td>74.00</td><td>-33.33</td><td>56.14</td><td>34.26</td><td>7.75</td><td>57.48</td><td>--</td><td>-- Peak</td></tr></table>												Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4824.00	40.67	74.00	-33.33	56.14	34.26	7.75	57.48	--	-- Peak	Level (dBuV/m) Date: 2024-03-26 <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4824.00</td><td>42.00</td><td>74.00</td><td>-32.00</td><td>57.47</td><td>34.26</td><td>7.75</td><td>57.48</td><td>--</td><td>-- Peak</td></tr></table>			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4824.00	42.00	74.00	-32.00	57.47	34.26	7.75	57.48	--	-- Peak
			Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																						
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	4824.00	40.67	74.00	-33.33	56.14	34.26	7.75	57.48	--	-- Peak																																																																																							
		Limit		Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	4824.00	42.00	74.00	-32.00	57.47	34.26	7.75	57.48	--	-- Peak																																																																																							



Mode	8																																																																																																																							
	Harmonic																																																																																																																							
	2400-2483.5_802.11n HT20_CH06_2437MHz																																																																																																																							
ANT	7																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2024-03-26 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 3000 6000 9000 12000 15000 18000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4874.00</td><td>41.23</td><td>74.00</td><td>-32.77</td><td>56.65</td><td>34.33</td><td>7.77</td><td>57.52</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>42.95</td><td>74.00</td><td>-31.05</td><td>57.50</td><td>35.44</td><td>8.93</td><td>58.92</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4874.00	41.23	74.00	-32.77	56.65	34.33	7.77	57.52	--	--	Peak	2	7311.00	42.95	74.00	-31.05	57.50	35.44	8.93	58.92	--	--	Peak	Level (dBuV/m) Date: 2024-03-26 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 3000 6000 9000 12000 15000 18000 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4874.00</td><td>41.66</td><td>74.00</td><td>-32.34</td><td>57.08</td><td>34.33</td><td>7.77</td><td>57.52</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>43.49</td><td>74.00</td><td>-30.51</td><td>58.04</td><td>35.44</td><td>8.93</td><td>58.92</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4874.00	41.66	74.00	-32.34	57.08	34.33	7.77	57.52	--	--	Peak	2	7311.00	43.49	74.00	-30.51	58.04	35.44	8.93	58.92	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4874.00	41.23	74.00	-32.77	56.65	34.33	7.77	57.52	--	--	Peak																																																																																																													
2	7311.00	42.95	74.00	-31.05	57.50	35.44	8.93	58.92	--	--	Peak																																																																																																													
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4874.00	41.66	74.00	-32.34	57.08	34.33	7.77	57.52	--	--	Peak																																																																																																													
2	7311.00	43.49	74.00	-30.51	58.04	35.44	8.93	58.92	--	--	Peak																																																																																																													



Mode	9																																																																																										
	Band Edge																																																																																										
	2400-2483.5_802.11n_HT20_CH11_2462MHz																																																																																										
ANT	7																																																																																										
Pol.	Horizontal						Fundamental																																																																																				
Peak	 Level (dBuV/m) Date: 2024-03-24 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2484.15</td><td>59.69</td><td>74.00</td><td>-14.31</td><td>57.43</td><td>30.85</td><td>4.92</td><td>33.51</td><td>303</td><td>229</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2484.15	59.69	74.00	-14.31	57.43	30.85	4.92	33.51	303	229	PEAK	 Level (dBuV/m) Date: 2024-03-24 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>95.96</td><td>-----</td><td>-----</td><td>93.83</td><td>30.77</td><td>4.89</td><td>33.53</td><td>303</td><td>229</td><td>PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	95.96	-----	-----	93.83	30.77	4.89	33.53	303	229	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2484.15	59.69	74.00	-14.31	57.43	30.85	4.92	33.51	303	229	PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	95.96	-----	-----	93.83	30.77	4.89	33.53	303	229	PEAK																																																																																
Avg	 Level (dBuV/m) Date: 2024-03-24 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2483.55</td><td>44.42</td><td>54.00</td><td>-9.58</td><td>42.16</td><td>30.85</td><td>4.92</td><td>33.51</td><td>303</td><td>229</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2483.55	44.42	54.00	-9.58	42.16	30.85	4.92	33.51	303	229	AVERAGE	 Level (dBuV/m) Date: 2024-03-24 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2462.00</td><td>89.01</td><td>-----</td><td>-----</td><td>86.87</td><td>30.77</td><td>4.89</td><td>33.52</td><td>303</td><td>229</td><td>AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	89.01	-----	-----	86.87	30.77	4.89	33.52	303	229	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2483.55	44.42	54.00	-9.58	42.16	30.85	4.92	33.51	303	229	AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	89.01	-----	-----	86.87	30.77	4.89	33.52	303	229	AVERAGE																																																																																



Mode	9																																																																																										
	Band Edge																																																																																										
	2400-2483.5_802.11n HT20_CH11_2462MHz																																																																																										
ANT	7																																																																																										
Pol.	Vertical						Fundamental																																																																																				
Peak	Level (dBuV/m) Date: 2024-03-24 PEAK_BE_74						Level (dBuV/m) Date: 2024-03-24 PEAK_74																																																																																				
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.66</td><td>65.04</td><td>74.00</td><td>-8.96</td><td>62.78</td><td>30.85</td><td>4.92</td><td>33.51</td><td>247</td><td>284</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2483.66	65.04	74.00	-8.96	62.78	30.85	4.92	33.51	247	284	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>100.75</td><td>-----</td><td>-----</td><td>98.62</td><td>30.77</td><td>4.89</td><td>33.53</td><td>247</td><td>284</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	100.75	-----	-----	98.62	30.77	4.89	33.53	247	284
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2483.66	65.04	74.00	-8.96	62.78	30.85	4.92	33.51	247	284	PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	100.75	-----	-----	98.62	30.77	4.89	33.53	247	284	PEAK																																																																																
Avg	Level (dBuV/m) Date: 2024-03-24 AVG_BE_54						Level (dBuV/m) Date: 2024-03-24 AVG_54																																																																																				
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.51</td><td>49.14</td><td>54.00</td><td>-4.86</td><td>46.88</td><td>30.85</td><td>4.92</td><td>33.51</td><td>247</td><td>284</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2483.51	49.14	54.00	-4.86	46.88	30.85	4.92	33.51	247	284	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>94.10</td><td>-----</td><td>-----</td><td>91.97</td><td>30.77</td><td>4.89</td><td>33.53</td><td>247</td><td>284</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2462.00	94.10	-----	-----	91.97	30.77	4.89	33.53	247	284
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2483.51	49.14	54.00	-4.86	46.88	30.85	4.92	33.51	247	284	AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2462.00	94.10	-----	-----	91.97	30.77	4.89	33.53	247	284	AVERAGE																																																																																



Mode	9																																																																																																																							
	Harmonic																																																																																																																							
	2400-2483.5_802.11n HT20_CH11_2462MHz																																																																																																																							
ANT	7																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2024-03-26 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>41.73</td><td>74.00</td><td>-32.27</td><td>57.09</td><td>34.40</td><td>7.79</td><td>57.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7386.00</td><td>43.47</td><td>74.00</td><td>-30.53</td><td>57.83</td><td>35.42</td><td>9.17</td><td>58.95</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4924.00	41.73	74.00	-32.27	57.09	34.40	7.79	57.55	--	--	Peak	2	7386.00	43.47	74.00	-30.53	57.83	35.42	9.17	58.95	--	--	Peak	Level (dBuV/m) Date: 2024-03-26 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4924.00</td><td>42.04</td><td>74.00</td><td>-31.96</td><td>57.40</td><td>34.40</td><td>7.79</td><td>57.55</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7386.00</td><td>43.72</td><td>74.00</td><td>-30.28</td><td>58.08</td><td>35.42</td><td>9.17</td><td>58.95</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4924.00	42.04	74.00	-31.96	57.40	34.40	7.79	57.55	--	--	Peak	2	7386.00	43.72	74.00	-30.28	58.08	35.42	9.17	58.95	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4924.00	41.73	74.00	-32.27	57.09	34.40	7.79	57.55	--	--	Peak																																																																																																													
2	7386.00	43.47	74.00	-30.53	57.83	35.42	9.17	58.95	--	--	Peak																																																																																																													
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4924.00	42.04	74.00	-31.96	57.40	34.40	7.79	57.55	--	--	Peak																																																																																																													
2	7386.00	43.72	74.00	-30.28	58.08	35.42	9.17	58.95	--	--	Peak																																																																																																													



Mode	10																																																																																							
	Band Edge - L																																																																																							
	2400-2483.5_802.11n_HT40_CH03_2422MHz																																																																																							
ANT	7																																																																																							
Pol.	Horizontal					Fundamental																																																																																		
Peak	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.86</td><td>61.55</td><td>74.00</td><td>-12.45</td><td>59.71</td><td>30.61</td><td>4.80</td><td>33.57</td><td>113</td><td>238 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.86	61.55	74.00	-12.45	59.71	30.61	4.80	33.57	113	238 PEAK	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2422.00</td><td>94.79</td><td>-----</td><td>-----</td><td>92.86</td><td>30.65</td><td>4.83</td><td>33.55</td><td>113</td><td>238 PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2422.00	94.79	-----	-----	92.86	30.65	4.83	33.55	113	238 PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2389.86	61.55	74.00	-12.45	59.71	30.61	4.80	33.57	113	238 PEAK																																																																														
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2422.00	94.79	-----	-----	92.86	30.65	4.83	33.55	113	238 PEAK																																																																														
Avg	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.52</td><td>46.86</td><td>54.00</td><td>-7.14</td><td>45.02</td><td>30.61</td><td>4.80</td><td>33.57</td><td>113</td><td>238 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.52	46.86	54.00	-7.14	45.02	30.61	4.80	33.57	113	238 AVERAGE	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2422.00</td><td>87.92</td><td>-----</td><td>-----</td><td>85.99</td><td>30.65</td><td>4.83</td><td>33.55</td><td>113</td><td>238 AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2422.00	87.92	-----	-----	85.99	30.65	4.83	33.55	113	238 AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2389.52	46.86	54.00	-7.14	45.02	30.61	4.80	33.57	113	238 AVERAGE																																																																														
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																															
1	2422.00	87.92	-----	-----	85.99	30.65	4.83	33.55	113	238 AVERAGE																																																																														



Mode	10	
	Band Edge - R	
	2400-2483.5_802.11n HT40_CH03_2422MHz	
ANT	7	
Pol.	Horizontal	Fundamental
Peak		



		10																																																																																								
Mode		Band Edge - L																																																																																								
		2400-2483.5_802.11n HT40_CH03_2422MHz																																																																																								
ANT		7																																																																																								
Pol.		Vertical					Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2024-03-23 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2332.4 2354.8 2377.2 2399.6 2422 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.97</td><td>64.76</td><td>74.00</td><td>-9.24</td><td>62.92</td><td>30.61</td><td>4.80</td><td>33.57</td><td>298</td><td>283</td><td>PEAK</td></tr></tbody></table> Level (dBuV/m) Date: 2024-03-23 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2422.00</td><td>96.53</td><td>-----</td><td>-----</td><td>94.58</td><td>30.66</td><td>4.84</td><td>33.55</td><td>298</td><td>283</td><td>PEAK</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.97	64.76	74.00	-9.24	62.92	30.61	4.80	33.57	298	283	PEAK		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2422.00	96.53	-----	-----	94.58	30.66	4.84	33.55	298	283	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2389.97	64.76	74.00	-9.24	62.92	30.61	4.80	33.57	298	283	PEAK																																																																															
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2422.00	96.53	-----	-----	94.58	30.66	4.84	33.55	298	283	PEAK																																																																															
Avg	Level (dBuV/m) Date: 2024-03-23 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2332.4 2354.8 2377.2 2399.6 2422 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.52</td><td>49.89</td><td>54.00</td><td>-4.11</td><td>48.05</td><td>30.61</td><td>4.80</td><td>33.57</td><td>298</td><td>283</td><td>AVERAGE</td></tr></tbody></table> Level (dBuV/m) Date: 2024-03-23 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2422.00</td><td>89.62</td><td>-----</td><td>-----</td><td>87.67</td><td>30.66</td><td>4.84</td><td>33.55</td><td>298</td><td>283</td><td>AVERAGE</td></tr></tbody></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.52	49.89	54.00	-4.11	48.05	30.61	4.80	33.57	298	283	AVERAGE		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2422.00	89.62	-----	-----	87.67	30.66	4.84	33.55	298	283	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2389.52	49.89	54.00	-4.11	48.05	30.61	4.80	33.57	298	283	AVERAGE																																																																															
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line Margin	Level Factor	Loss Factor				Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																	
1	2422.00	89.62	-----	-----	87.67	30.66	4.84	33.55	298	283	AVERAGE																																																																															



Mode	10									
	Band Edge - R									
	2400-2483.5_802.11n HT40_CH03_2422MHz									
ANT	7									
Pol.	Vertical					Fundamental				
Peak	<									



Mode	10																																																																																																																																			
	Harmonic																																																																																																																																			
	2400-2483.5_802.11n HT40_CH03_2422MHz																																																																																																																																			
ANT	7																																																																																																																																			
Pol.	Horizontal								Vertical																																																																																																																											
Peak Avg	Level (dBuV/m) Date: 2024-03-26 <table><thead><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4844.00</td><td>41.86</td><td>74.00</td><td>-32.14</td><td>57.30</td><td>34.29</td><td>7.76</td><td>57.49</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7266.00</td><td>44.63</td><td>74.00</td><td>-29.37</td><td>59.30</td><td>35.45</td><td>8.79</td><td>58.91</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>										Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4844.00	41.86	74.00	-32.14	57.30	34.29	7.76	57.49	--	--	Peak	2	7266.00	44.63	74.00	-29.37	59.30	35.45	8.79	58.91	--	--	Peak	Level (dBuV/m) Date: 2024-03-26 <table><thead><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>4844.00</td><td>41.60</td><td>74.00</td><td>-32.40</td><td>57.04</td><td>34.29</td><td>7.76</td><td>57.49</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7266.00</td><td>43.96</td><td>74.00</td><td>-30.04</td><td>58.63</td><td>35.45</td><td>8.79</td><td>58.91</td><td>--</td><td>--</td><td>Peak</td></tr></tbody></table>										Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4844.00	41.60	74.00	-32.40	57.04	34.29	7.76	57.49	--	--	Peak	2	7266.00	43.96	74.00	-30.04	58.63	35.45	8.79	58.91	--	--	Peak
			Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																								
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																										
1	4844.00	41.86	74.00	-32.14	57.30	34.29	7.76	57.49	--	--	Peak																																																																																																																									
2	7266.00	44.63	74.00	-29.37	59.30	35.45	8.79	58.91	--	--	Peak																																																																																																																									
		Limit		Read		Ant	Cable	Preamp	APos	TPos	Remark																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																										
1	4844.00	41.60	74.00	-32.40	57.04	34.29	7.76	57.49	--	--	Peak																																																																																																																									
2	7266.00	43.96	74.00	-30.04	58.63	35.45	8.79	58.91	--	--	Peak																																																																																																																									

Note: Only the worst case has assessed 18G ~26GHz to test.







Mode	11																																																																													
	Band Edge - L																																																																													
	2400-2483.5_802.11n HT40_CH09_2452MHz																																																																													
ANT	7																																																																													
Pol.	Horizontal	Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.81</td><td>50.25</td><td>74.00</td><td>-23.75</td><td>48.42</td><td>30.61</td><td>4.79</td><td>33.57</td><td>382 217 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2388.81	50.25	74.00	-23.75	48.42	30.61	4.79	33.57	382 217 PEAK	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2452.00</td><td>89.59</td><td>-----</td><td>-----</td><td>87.53</td><td>30.72</td><td>4.87</td><td>33.53</td><td>382 217 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2452.00	89.59	-----	-----	87.53	30.72	4.87	33.53	382 217 PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																					
1	2388.81	50.25	74.00	-23.75	48.42	30.61	4.79	33.57	382 217 PEAK																																																																					
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																					
1	2452.00	89.59	-----	-----	87.53	30.72	4.87	33.53	382 217 PEAK																																																																					
Avg	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2388.95</td><td>39.74</td><td>54.00</td><td>-14.26</td><td>37.91</td><td>30.61</td><td>4.79</td><td>33.57</td><td>382 217 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2388.95	39.74	54.00	-14.26	37.91	30.61	4.79	33.57	382 217 AVERAGE	Level (dBuV/m) Date: 2024-03-23 Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2452.00</td><td>83.01</td><td>-----</td><td>-----</td><td>80.92</td><td>30.74</td><td>4.88</td><td>33.53</td><td>382 217 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2452.00	83.01	-----	-----	80.92	30.74	4.88	33.53	382 217 AVERAGE
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																					
1	2388.95	39.74	54.00	-14.26	37.91	30.61	4.79	33.57	382 217 AVERAGE																																																																					
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																					
1	2452.00	83.01	-----	-----	80.92	30.74	4.88	33.53	382 217 AVERAGE																																																																					



Mode	11																																																		
	Band Edge - R																																																		
	2400-2483.5_802.11n HT40_CH09_2452MHz																																																		
ANT	7																																																		
Pol.	Horizontal						Fundamental																																												
Peak	Date: 2024-03-23 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.02</td><td>60.07</td><td>74.00</td><td>-13.93</td><td>57.81</td><td>30.85</td><td>4.92</td><td>33.51</td><td>382</td><td>217</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2484.02	60.07	74.00	-13.93	57.81	30.85	4.92	33.51	382	217	PEAK	Blank				
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	2484.02	60.07	74.00	-13.93	57.81	30.85	4.92	33.51	382	217	PEAK																																								
Avg	Date: 2024-03-23 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.64</td><td>44.85</td><td>54.00</td><td>-9.15</td><td>42.58</td><td>30.86</td><td>4.92</td><td>33.51</td><td>382</td><td>217</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2484.64	44.85	54.00	-9.15	42.58	30.86	4.92	33.51	382	217	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	2484.64	44.85	54.00	-9.15	42.58	30.86	4.92	33.51	382	217	AVERAGE																																								





Mode	11																																																																																										
	Band Edge - L																																																																																										
	2400-2483.5_802.11n_HT40_CH09_2452MHz																																																																																										
ANT	7																																																																																										
Pol.	Vertical						Fundamental																																																																																				
Peak	 Level (dBuV/m) Date: 2024-03-23 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.95</td><td>53.48</td><td>74.00</td><td>-20.52</td><td>51.64</td><td>30.61</td><td>4.80</td><td>33.57</td><td>246</td><td>282</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.95	53.48	74.00	-20.52	51.64	30.61	4.80	33.57	246	282	PEAK	 Level (dBuV/m) Date: 2024-03-23 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2452.00</td><td>97.62</td><td>-----</td><td>-----</td><td>95.53</td><td>30.74</td><td>4.88</td><td>33.53</td><td>246</td><td>282</td><td>PEAK</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2452.00	97.62	-----	-----	95.53	30.74	4.88	33.53	246	282	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2389.95	53.48	74.00	-20.52	51.64	30.61	4.80	33.57	246	282	PEAK																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2452.00	97.62	-----	-----	95.53	30.74	4.88	33.53	246	282	PEAK																																																																																
Avg	 Level (dBuV/m) Date: 2024-03-23 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2389.80</td><td>40.41</td><td>54.00</td><td>-13.59</td><td>38.57</td><td>30.61</td><td>4.80</td><td>33.57</td><td>246</td><td>282</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2389.80	40.41	54.00	-13.59	38.57	30.61	4.80	33.57	246	282	AVERAGE	 Level (dBuV/m) Date: 2024-03-23 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2452.00</td><td>90.98</td><td>-----</td><td>-----</td><td>88.89</td><td>30.74</td><td>4.88</td><td>33.53</td><td>246</td><td>282</td><td>AVERAGE</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2452.00	90.98	-----	-----	88.89	30.74	4.88	33.53	246	282	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2389.80	40.41	54.00	-13.59	38.57	30.61	4.80	33.57	246	282	AVERAGE																																																																																
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																																																																		
1	2452.00	90.98	-----	-----	88.89	30.74	4.88	33.53	246	282	AVERAGE																																																																																







Mode	11																																																		
	Band Edge - R																																																		
	2400-2483.5_802.11n HT40_CH09_2452MHz																																																		
ANT	7																																																		
Pol.	Vertical						Fundamental																																												
Peak	Date: 2024-03-23 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2484.26</td><td>63.82</td><td>74.00</td><td>-10.18</td><td>61.56</td><td>30.85</td><td>4.92</td><td>33.51</td><td>246</td><td>282</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2484.26	63.82	74.00	-10.18	61.56	30.85	4.92	33.51	246	282	PEAK	Blank				
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	2484.26	63.82	74.00	-10.18	61.56	30.85	4.92	33.51	246	282	PEAK																																								
Avg	Date: 2024-03-23 <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2484.50</td><td>48.42</td><td>54.00</td><td>-5.58</td><td>46.16</td><td>30.85</td><td>4.92</td><td>33.51</td><td>246</td><td>282</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2484.50	48.42	54.00	-5.58	46.16	30.85	4.92	33.51	246	282	AVERAGE	Blank				
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																										
1	2484.50	48.42	54.00	-5.58	46.16	30.85	4.92	33.51	246	282	AVERAGE																																								



Mode	12																																																																																																																																							
	LF																																																																																																																																							
	2400-2483.5_802.11n HT40_CH03_LF_2422MHz																																																																																																																																							
ANT	7																																																																																																																																							
Pol.	Horizontal					Vertical																																																																																																																																		
Peak																																																																																																																																								
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>47.46</td><td>21.37</td><td>40.00</td><td>-18.63</td><td>36.06</td><td>19.62</td></tr><tr><td>2</td><td>143.49</td><td>23.41</td><td>43.50</td><td>-20.09</td><td>38.44</td><td>18.43</td></tr><tr><td>3</td><td>198.78</td><td>22.67</td><td>43.50</td><td>-20.83</td><td>39.84</td><td>16.05</td></tr><tr><td>4</td><td>349.13</td><td>25.89</td><td>46.00</td><td>-20.11</td><td>38.35</td><td>20.20</td></tr><tr><td>5</td><td>741.98</td><td>29.50</td><td>46.00</td><td>-16.50</td><td>33.46</td><td>27.51</td></tr><tr><td>6</td><td>869.05</td><td>31.12</td><td>46.00</td><td>-14.88</td><td>33.57</td><td>28.73</td></tr></table>						Limit	Read	Ant	Cable	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	47.46	21.37	40.00	-18.63	36.06	19.62	2	143.49	23.41	43.50	-20.09	38.44	18.43	3	198.78	22.67	43.50	-20.83	39.84	16.05	4	349.13	25.89	46.00	-20.11	38.35	20.20	5	741.98	29.50	46.00	-16.50	33.46	27.51	6	869.05	31.12	46.00	-14.88	33.57	28.73	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>33.88</td><td>26.20</td><td>40.00</td><td>-13.80</td><td>42.04</td><td>18.46</td></tr><tr><td>2</td><td>140.58</td><td>23.85</td><td>43.50</td><td>-19.65</td><td>39.13</td><td>18.20</td></tr><tr><td>3</td><td>194.90</td><td>23.34</td><td>43.50</td><td>-20.16</td><td>40.29</td><td>16.28</td></tr><tr><td>4</td><td>282.20</td><td>22.09</td><td>46.00</td><td>-23.91</td><td>36.42</td><td>18.57</td></tr><tr><td>5</td><td>601.33</td><td>26.99</td><td>46.00</td><td>-19.01</td><td>32.89</td><td>26.09</td></tr><tr><td>6</td><td>933.07</td><td>30.17</td><td>46.00</td><td>-15.83</td><td>31.87</td><td>29.38</td></tr></table>						Limit	Read	Ant	Cable	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	33.88	26.20	40.00	-13.80	42.04	18.46	2	140.58	23.85	43.50	-19.65	39.13	18.20	3	194.90	23.34	43.50	-20.16	40.29	16.28	4	282.20	22.09	46.00	-23.91	36.42	18.57	5	601.33	26.99	46.00	-19.01	32.89	26.09	6	933.07	30.17	46.00	-15.83	31.87	29.38
		Limit	Read	Ant	Cable	APos	TPos																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																																																		
1	47.46	21.37	40.00	-18.63	36.06	19.62																																																																																																																																		
2	143.49	23.41	43.50	-20.09	38.44	18.43																																																																																																																																		
3	198.78	22.67	43.50	-20.83	39.84	16.05																																																																																																																																		
4	349.13	25.89	46.00	-20.11	38.35	20.20																																																																																																																																		
5	741.98	29.50	46.00	-16.50	33.46	27.51																																																																																																																																		
6	869.05	31.12	46.00	-14.88	33.57	28.73																																																																																																																																		
	Limit	Read	Ant	Cable	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																																																		
1	33.88	26.20	40.00	-13.80	42.04	18.46																																																																																																																																		
2	140.58	23.85	43.50	-19.65	39.13	18.20																																																																																																																																		
3	194.90	23.34	43.50	-20.16	40.29	16.28																																																																																																																																		
4	282.20	22.09	46.00	-23.91	36.42	18.57																																																																																																																																		
5	601.33	26.99	46.00	-19.01	32.89	26.09																																																																																																																																		
6	933.07	30.17	46.00	-15.83	31.87	29.38																																																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>47.46</td><td>21.37</td><td>40.00</td><td>-18.63</td><td>36.06</td><td>19.62</td></tr><tr><td>2</td><td>143.49</td><td>23.41</td><td>43.50</td><td>-20.09</td><td>38.44</td><td>18.43</td></tr><tr><td>3</td><td>198.78</td><td>22.67</td><td>43.50</td><td>-20.83</td><td>39.84</td><td>16.05</td></tr><tr><td>4</td><td>349.13</td><td>25.89</td><td>46.00</td><td>-20.11</td><td>38.35</td><td>20.20</td></tr><tr><td>5</td><td>741.98</td><td>29.50</td><td>46.00</td><td>-16.50</td><td>33.46</td><td>27.51</td></tr><tr><td>6</td><td>869.05</td><td>31.12</td><td>46.00</td><td>-14.88</td><td>33.57</td><td>28.73</td></tr></table>						Limit	Read	Ant	Cable	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	47.46	21.37	40.00	-18.63	36.06	19.62	2	143.49	23.41	43.50	-20.09	38.44	18.43	3	198.78	22.67	43.50	-20.83	39.84	16.05	4	349.13	25.89	46.00	-20.11	38.35	20.20	5	741.98	29.50	46.00	-16.50	33.46	27.51	6	869.05	31.12	46.00	-14.88	33.57	28.73	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>33.88</td><td>26.20</td><td>40.00</td><td>-13.80</td><td>42.04</td><td>18.46</td></tr><tr><td>2</td><td>140.58</td><td>23.85</td><td>43.50</td><td>-19.65</td><td>39.13</td><td>18.20</td></tr><tr><td>3</td><td>194.90</td><td>23.34</td><td>43.50</td><td>-20.16</td><td>40.29</td><td>16.28</td></tr><tr><td>4</td><td>282.20</td><td>22.09</td><td>46.00</td><td>-23.91</td><td>36.42</td><td>18.57</td></tr><tr><td>5</td><td>601.33</td><td>26.99</td><td>46.00</td><td>-19.01</td><td>32.89</td><td>26.09</td></tr><tr><td>6</td><td>933.07</td><td>30.17</td><td>46.00</td><td>-15.83</td><td>31.87</td><td>29.38</td></tr></table>						Limit	Read	Ant	Cable	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	33.88	26.20	40.00	-13.80	42.04	18.46	2	140.58	23.85	43.50	-19.65	39.13	18.20	3	194.90	23.34	43.50	-20.16	40.29	16.28	4	282.20	22.09	46.00	-23.91	36.42	18.57	5	601.33	26.99	46.00	-19.01	32.89	26.09	6	933.07	30.17	46.00	-15.83	31.87	29.38
	Limit	Read	Ant	Cable	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																																																		
1	47.46	21.37	40.00	-18.63	36.06	19.62																																																																																																																																		
2	143.49	23.41	43.50	-20.09	38.44	18.43																																																																																																																																		
3	198.78	22.67	43.50	-20.83	39.84	16.05																																																																																																																																		
4	349.13	25.89	46.00	-20.11	38.35	20.20																																																																																																																																		
5	741.98	29.50	46.00	-16.50	33.46	27.51																																																																																																																																		
6	869.05	31.12	46.00	-14.88	33.57	28.73																																																																																																																																		
	Limit	Read	Ant	Cable	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																																																		
1	33.88	26.20	40.00	-13.80	42.04	18.46																																																																																																																																		
2	140.58	23.85	43.50	-19.65	39.13	18.20																																																																																																																																		
3	194.90	23.34	43.50	-20.16	40.29	16.28																																																																																																																																		
4	282.20	22.09	46.00	-23.91	36.42	18.57																																																																																																																																		
5	601.33	26.99	46.00	-19.01	32.89	26.09																																																																																																																																		
6	933.07	30.17	46.00	-15.83	31.87	29.38																																																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>47.46</td><td>21.37</td><td>40.00</td><td>-18.63</td><td>36.06</td><td>19.62</td></tr><tr><td>2</td><td>143.49</td><td>23.41</td><td>43.50</td><td>-20.09</td><td>38.44</td><td>18.43</td></tr><tr><td>3</td><td>198.78</td><td>22.67</td><td>43.50</td><td>-20.83</td><td>39.84</td><td>16.05</td></tr><tr><td>4</td><td>349.13</td><td>25.89</td><td>46.00</td><td>-20.11</td><td>38.35</td><td>20.20</td></tr><tr><td>5</td><td>741.98</td><td>29.50</td><td>46.00</td><td>-16.50</td><td>33.46</td><td>27.51</td></tr><tr><td>6</td><td>869.05</td><td>31.12</td><td>46.00</td><td>-14.88</td><td>33.57</td><td>28.73</td></tr></table>						Limit	Read	Ant	Cable	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	47.46	21.37	40.00	-18.63	36.06	19.62	2	143.49	23.41	43.50	-20.09	38.44	18.43	3	198.78	22.67	43.50	-20.83	39.84	16.05	4	349.13	25.89	46.00	-20.11	38.35	20.20	5	741.98	29.50	46.00	-16.50	33.46	27.51	6	869.05	31.12	46.00	-14.88	33.57	28.73	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>33.88</td><td>26.20</td><td>40.00</td><td>-13.80</td><td>42.04</td><td>18.46</td></tr><tr><td>2</td><td>140.58</td><td>23.85</td><td>43.50</td><td>-19.65</td><td>39.13</td><td>18.20</td></tr><tr><td>3</td><td>194.90</td><td>23.34</td><td>43.50</td><td>-20.16</td><td>40.29</td><td>16.28</td></tr><tr><td>4</td><td>282.20</td><td>22.09</td><td>46.00</td><td>-23.91</td><td>36.42</td><td>18.57</td></tr><tr><td>5</td><td>601.33</td><td>26.99</td><td>46.00</td><td>-19.01</td><td>32.89</td><td>26.09</td></tr><tr><td>6</td><td>933.07</td><td>30.17</td><td>46.00</td><td>-15.83</td><td>31.87</td><td>29.38</td></tr></table>						Limit	Read	Ant	Cable	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	1	33.88	26.20	40.00	-13.80	42.04	18.46	2	140.58	23.85	43.50	-19.65	39.13	18.20	3	194.90	23.34	43.50	-20.16	40.29	16.28	4	282.20	22.09	46.00	-23.91	36.42	18.57	5	601.33	26.99	46.00	-19.01	32.89	26.09	6	933.07	30.17	46.00	-15.83	31.87	29.38
	Limit	Read	Ant	Cable	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																																																		
1	47.46	21.37	40.00	-18.63	36.06	19.62																																																																																																																																		
2	143.49	23.41	43.50	-20.09	38.44	18.43																																																																																																																																		
3	198.78	22.67	43.50	-20.83	39.84	16.05																																																																																																																																		
4	349.13	25.89	46.00	-20.11	38.35	20.20																																																																																																																																		
5	741.98	29.50	46.00	-16.50	33.46	27.51																																																																																																																																		
6	869.05	31.12	46.00	-14.88	33.57	28.73																																																																																																																																		
	Limit	Read	Ant	Cable	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB																																																																																																																																		
1	33.88	26.20	40.00	-13.80	42.04	18.46																																																																																																																																		
2	140.58	23.85	43.50	-19.65	39.13	18.20																																																																																																																																		
3	194.90	23.34	43.50	-20.16	40.29	16.28																																																																																																																																		
4	282.20	22.09	46.00	-23.91	36.42	18.57																																																																																																																																		
5	601.33	26.99	46.00	-19.01	32.89	26.09																																																																																																																																		
6	933.07	30.17	46.00	-15.83	31.87	29.38																																																																																																																																		



		13																																																																																																			
Mode		Band Edge - L																																																																																																			
		2400-2483.5_802.11n HT40_CH03_2422MHz& LTE Band 48Link																																																																																																			
Pol.		Horizontal					Fundamental																																																																																														
Peak		Level (dBuV/m) Date: 2024-03-26  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.74</td><td>64.70</td><td>74.00</td><td>-9.30</td><td>62.86</td><td>30.61</td><td>4.80</td><td>33.57</td><td>354</td><td>61</td><td>PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.74	64.70	74.00	-9.30	62.86	30.61	4.80	33.57	354	61	PEAK	Level (dBuV/m) Date: 2024-03-26  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2422.00</td><td>94.62</td><td>-----</td><td>-----</td><td>92.69</td><td>30.65</td><td>4.83</td><td>33.55</td><td>354</td><td>61</td><td>PEAK</td></tr></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2422.00	94.62	-----	-----	92.69	30.65	4.83	33.55	354	61	PEAK
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																												
1	2389.74	64.70	74.00	-9.30	62.86	30.61	4.80	33.57	354	61	PEAK																																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																												
1	2422.00	94.62	-----	-----	92.69	30.65	4.83	33.55	354	61	PEAK																																																																																										
Avg		Level (dBuV/m) Date: 2024-03-26  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.52</td><td>50.09</td><td>54.00</td><td>-3.91</td><td>48.25</td><td>30.61</td><td>4.80</td><td>33.57</td><td>354</td><td>61</td><td>AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.52	50.09	54.00	-3.91	48.25	30.61	4.80	33.57	354	61	AVERAGE	Level (dBuV/m) Date: 2024-03-26  Frequency (MHz) <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2422.00</td><td>87.37</td><td>-----</td><td>-----</td><td>85.44</td><td>30.65</td><td>4.83</td><td>33.55</td><td>354</td><td>61</td><td>AVERAGE</td></tr></table>											Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2422.00	87.37	-----	-----	85.44	30.65	4.83	33.55	354	61	AVERAGE
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																												
1	2389.52	50.09	54.00	-3.91	48.25	30.61	4.80	33.57	354	61	AVERAGE																																																																																										
	Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																												
1	2422.00	87.37	-----	-----	85.44	30.65	4.83	33.55	354	61	AVERAGE																																																																																										



Mode	13																																									
	Band Edge - R																																									
	2400-2483.5_802.11n HT40_CH03_2422MHz<E Band 48Link																																									
Pol.	Horizontal	Fundamental																																								
Peak	Date: 2024-03-26 PEAK_BE_74 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2486.19</td><td>51.06</td><td>74.00</td><td>-22.94</td><td>48.79</td><td>30.86</td><td>4.92</td><td>33.51</td><td>354</td><td>61</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2486.19	51.06	74.00	-22.94	48.79	30.86	4.92	33.51	354	61	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																	
1	2486.19	51.06	74.00	-22.94	48.79	30.86	4.92	33.51	354	61	PEAK																															
Avg	Date: 2024-03-26 AVG_BE_54 <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.13</td><td>40.56</td><td>54.00</td><td>-13.44</td><td>38.27</td><td>30.87</td><td>4.93</td><td>33.51</td><td>354</td><td>61</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg	1	2487.13	40.56	54.00	-13.44	38.27	30.87	4.93	33.51	354	61	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	cm	deg																																	
1	2487.13	40.56	54.00	-13.44	38.27	30.87	4.93	33.51	354	61	AVERAGE																															



		13																																																																																							
Mode	Band Edge - L																																																																																								
	2400-2483.5_802.11n HT40_CH03_2422MHz& LTE Band 48Link																																																																																								
Pol.	Vertical										Fundamental																																																																														
Peak	Level (dBuV/m) Date: 2024-03-26 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2332.4 2354.8 2377.2 2399.6 2422 Frequency (MHz) <table><tr><th colspan="2"></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2389.74</td><td>64.43</td><td>74.00</td><td>-9.57</td><td>62.59</td><td>30.61</td><td>4.80</td><td>33.57</td><td>100</td><td>90 PEAK</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2389.74	64.43	74.00	-9.57	62.59	30.61	4.80	33.57	100	90 PEAK	Level (dBuV/m) Date: 2024-03-26 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th colspan="2"></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2422.00</td><td>97.98</td><td>-----</td><td>-----</td><td>96.05</td><td>30.65</td><td>4.83</td><td>33.55</td><td>100</td><td>90 PEAK</td></tr></table>			Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2422.00	97.98	-----	-----	96.05	30.65	4.83	33.55	100	90 PEAK
			Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2389.74	64.43	74.00	-9.57	62.59	30.61	4.80	33.57	100	90 PEAK																																																																																
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2422.00	97.98	-----	-----	96.05	30.65	4.83	33.55	100	90 PEAK																																																																																
Avg	Level (dBuV/m) Date: 2024-03-26 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 2310 2332.4 2354.8 2377.2 2399.6 2422 Frequency (MHz) <table><tr><th colspan="2"></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2389.41</td><td>49.58</td><td>54.00</td><td>-4.42</td><td>47.74</td><td>30.61</td><td>4.80</td><td>33.57</td><td>100</td><td>90 AVERAGE</td></tr></table>												Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2389.41	49.58	54.00	-4.42	47.74	30.61	4.80	33.57	100	90 AVERAGE	Level (dBuV/m) Date: 2024-03-26 130 113.8 97.5 81.3 65.0 48.8 32.5 16.3 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th colspan="2"></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 2422.00</td><td>91.04</td><td>-----</td><td>-----</td><td>89.11</td><td>30.65</td><td>4.83</td><td>33.55</td><td>100</td><td>90 AVERAGE</td></tr></table>			Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 2422.00	91.04	-----	-----	89.11	30.65	4.83	33.55	100	90 AVERAGE
			Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2389.41	49.58	54.00	-4.42	47.74	30.61	4.80	33.57	100	90 AVERAGE																																																																																
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1 2422.00	91.04	-----	-----	89.11	30.65	4.83	33.55	100	90 AVERAGE																																																																																



Mode	13																																											
	Band Edge - R																																											
	2400-2483.5_802.11n HT40_CH03_2422MHz& LTE Band 48Link																																											
Pol.	Vertical	Fundamental																																										
Peak	Date: 2024-03-26 <table><tr><th colspan="2"></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2485.26</td><td>51.03</td><td>74.00</td><td>-22.97</td><td>48.76</td><td>30.86</td><td>4.92</td><td>33.51</td><td>100</td><td>90</td><td>PEAK</td></tr></table>			Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2485.26	51.03	74.00	-22.97	48.76	30.86	4.92	33.51	100	90	PEAK	Blank
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																		
1	2485.26	51.03	74.00	-22.97	48.76	30.86	4.92	33.51	100	90	PEAK																																	
Avg	Date: 2024-03-26 <table><tr><th colspan="2"></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.95</td><td>41.67</td><td>54.00</td><td>-12.33</td><td>39.40</td><td>30.86</td><td>4.92</td><td>33.51</td><td>100</td><td>90</td><td>AVERAGE</td></tr></table>			Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2484.95	41.67	54.00	-12.33	39.40	30.86	4.92	33.51	100	90	AVERAGE	Blank
		Limit	Read	Ant	Cable	Preamp	APos	TPos	Remark																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																		
1	2484.95	41.67	54.00	-12.33	39.40	30.86	4.92	33.51	100	90	AVERAGE																																	




Mode	13																																																																																																																							
	Harmonic																																																																																																																							
	2400-2483.5_802.11n HT40_CH03_2422MHz& LTE Band 48Link																																																																																																																							
Pol.	Horizontal						Vertical																																																																																																																	
Peak Avg	Level (dBuV/m) Date: 2024-03-27 Frequency (MHz)						Level (dBuV/m) Date: 2024-03-27 Frequency (MHz)																																																																																																																	
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4844.00</td><td>41.72</td><td>74.00</td><td>-32.28</td><td>57.16</td><td>34.29</td><td>7.76</td><td>57.49</td><td>189</td><td>176</td><td>Peak</td></tr><tr><td>2</td><td>7266.00</td><td>43.96</td><td>74.00</td><td>-30.04</td><td>58.63</td><td>35.45</td><td>8.79</td><td>58.91</td><td>215</td><td>312</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4844.00	41.72	74.00	-32.28	57.16	34.29	7.76	57.49	189	176	Peak	2	7266.00	43.96	74.00	-30.04	58.63	35.45	8.79	58.91	215	312	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4844.00</td><td>41.15</td><td>74.00</td><td>-32.85</td><td>56.59</td><td>34.29</td><td>7.76</td><td>57.49</td><td>196</td><td>266</td><td>Peak</td></tr><tr><td>2</td><td>7266.00</td><td>43.02</td><td>74.00</td><td>-30.98</td><td>57.69</td><td>35.45</td><td>8.79</td><td>58.91</td><td>275</td><td>312</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg		1	4844.00	41.15	74.00	-32.85	56.59	34.29	7.76	57.49	196	266	Peak	2	7266.00	43.02	74.00	-30.98	57.69	35.45	8.79	58.91	275	312	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4844.00	41.72	74.00	-32.28	57.16	34.29	7.76	57.49	189	176	Peak																																																																																																													
2	7266.00	43.96	74.00	-30.04	58.63	35.45	8.79	58.91	215	312	Peak																																																																																																													
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																														
1	4844.00	41.15	74.00	-32.85	56.59	34.29	7.76	57.49	196	266	Peak																																																																																																													
2	7266.00	43.02	74.00	-30.98	57.69	35.45	8.79	58.91	275	312	Peak																																																																																																													

Note: For all plots above, the over limit line signals are Fundamental signal which can be ignored.

Appendix D. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	100	-	-	10Hz
802.11g	97.57	1.3971	0.7158	1kHz
802.11n HT20	97.39	1.2986	0.7701	1kHz
802.11n HT40	94.92	0.6493	1.5402	3kHz

802.11b






802.11g



802.11n HT20



802.11n HT40

