

Page: 1 of 27

Appendix F - DAE & Probe Calibration Certificate

Calibration Laboratory of Schmid & Partner Engineering AG eughausstrasse 43, 8004 Zurich, Switzerland



Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

SGS Client

Certificate No: DAE4-1751_Mar24

Taoyuan City CALIBRATION CERTIFICATE DAE4 - SD 000 D04 BP - SN: 1751 Calibration procedure(s) QA CAL-06.v30 Calibration procedure for the data acquisition electronics (DAE) Calibration date: March 13, 2024 This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate. All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70% Calibration Equipment used (M&TE critical for calibration) Cal Date (Certificate No.) Primary Standards Scheduled Calibration Keithley Multimeter Type 2001 SN: 0810278 29-Aug-23 (No:37421) Check Date (in house) Scheduled Check SE UWS 053 AA 1001 23-Jan-24 (in house check) SE UMS 006 AA 1002 23-Jan-24 (in house check) Auto DAE Calibration Unit Calibrator Box V2 1 In house check: Jan-25 Name Calibrated by: Dominique Steffen Laboratory Technician Approved by: Sven Kühn This calibration certificate shall not be reproduced except in full without written approval of the laboratory

Certificate No: DAE4-1751_Mar24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format

documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 2 of 27

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Glossary

DAE data acquisition electronics

Connector angle information used in DASY system to align probe sensor X to the robot

coordinate system.

Methods Applied and Interpretation of Parameters

- DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - DC Voltage Measurement Linearity: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement
 - Common mode sensitivity: Influence of a positive or negative common mode voltage on the differential measurement.
 - Channel separation: Influence of a voltage on the neighbor channels not subject to an input voltage.
 - AD Converter Values with inputs shorted: Values on the internal AD converter corresponding to zero input voltage
 - Input Offset Measurement: Output voltage and statistical results over a large number of zero voltage measurements.
 - Input Offset Current: Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - Input resistance: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - Low Battery Alarm Voltage: Typical value for information. Below this voltage, a battery alarm signal is generated.
 - Power consumption: Typical value for information. Supply currents in various operating modes.

Certificate No: DAE4-1751 Mar24

Page 2 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非早有治明,此数华廷田属影测过了样具有者,同时此样具属是例如于。太极生土概太公司隶而连订,因可以必拘制。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 3 of 27

DC Voltage Measurement

A/D - Converter Resolution nominal High Range: 1LSB =

High Range: 1LSB = 6.1µV , full range = -100...+300 mV Low Range: 1LSB = 61nV , full range = -1......+3mV DASY measurement parameters: Auto Zero Time: 3 sec: Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	404.302 ± 0.02% (k=2)	404.262 ± 0.02% (k=2)	404.527 ± 0.02% (k=2)
Low Range	3.98545 ± 1.50% (k=2)	4.00007 ± 1.50% (k=2)	4.00889 ± 1.50% (k=2)

Connector Angle

Connector Angle to be used in DASY system	340.0 ° ± 1 °

Certificate No: DAE4-1751_Mar24

Page 3 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 4 of 27

Appendix (Additional assessments outside the scope of SCS0108)

High Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	200004.24	2.04	0.00
Channel X + Input	20012.21	2.36	0.01
Channel X - Input	-19991.98	2.30	-0.01
Channel Y + Input	200003.93	1.59	0.00
Channel Y + Input	20008.65	-1.27	-0.01
Channel Y - Input	-19993.86	0,47	-0.00
Channel Z + Input	200002.71	0.78	0.00
Channel Z + Input	20006.16	-3.77	-0.02
Channel Z - Input	-19994.26	0.07	-0.00

Low Range	Reading (μV)	Difference (µV)	Error (%)
Channel X + Input	2009.98	1.17	0.06
Channel X + Input	208.49	-0.63	-0,30
Channel X - Input	-190.51	0.27	-0.14
Channel Y + Input	2009.15	0.31	0.02
Channel Y + Input	208.94	-0.18	-0.08
Channel Y - Input	-191.11	-0.35	0.18
Channel Z + Input	2008.91	0.14	0.01
Channel Z + Input	208.43	-0.60	-0.29
Channel Z - Input	-192.33	-1.42	0.74

Common mode sensitivity
 DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	9.27	7.52
	- 200	-7.71	-8.70
Channel Y	200	12.87	12.77
	- 200	-14.29	-14,57
Channel Z	200	3.15	3.40
	- 200	-5.72	-5.94

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (µV)	Channel Y (μV)	Channel Z (μV)
Channel X	200	1 10 10 11	1.78	-3.96
Channel Y	200	6.24		2.54
Channel Z	200	7.70	4.26	

Certificate No: DAE4-1751_Mar24

Page 4 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 5 of 27

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	15782	13277
Channel Y	16207	15182
Channel Z	16262	14305

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec Input 10M Ω

	Average (μV)	min. Offset (μV)	max. Offset (μV)	Std. Deviation (µV)
Channel X	0.39	-1.17	2.70	0.53
Channel Y	-0.25	-1.19	0,54	0.33
Channel Z	-0.57	-1.68	0.44	0.38

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

9. Power Consumption (Typical values for info

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9

Certificate No: DAE4-1751_Mar24

Page 5 of 5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司




Page: 6 of 27

Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland







Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

SGS Taoyuan City

EX-7823 Jul24

CALIBRATION CERTIFICATE

Object

EX3DV4 - SN:7823

Calibration procedure(s)

QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,

QA CAL-25.v8

Calibration procedure for dosimetric E-field probes

Calibration date

July 31, 2024

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (St). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate. All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3) °C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP2	SN: 104778	26-Mar-24 (No. 217-04036/04037)	Mar-25
Power sensor NRP-Z91	SN: 103244	26-Mar-24 (No. 217-04036)	Mar-25
OCP DAK-3.5 (weighted)	SN: 1249	05-Oct-23 (OCP-DAK3.5-1249 Oct23)	Oct-24
OCP DAK-12	SN: 1016	05-Oct-23 (OCP-DAK12-1016 Oct23)	Oct-24
Reference 20 dB Attenuator	SN: CC2552 (20x)	26-Mar-24 (No. 217-04046)	Mar-25
DAE4	SN: 660	23-Feb-24 (No. DAE4-660 Feb24)	Feb-25
Reference Probe EX3DV4	SN: 7349	03-Jun-24 (No. EX3-7349 Jun24)	Jun-25

Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-24)	In house check: Jun-26
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-24)	In house check: Jun-26
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-24)	In house check: Jun-26
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-24)	In house check: Jun-26
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-22)	In house check: Oct-24

Name Function Calibrated by Jeffrey Katzman Laboratory Technician

Approved by Technical Manager

This calibration certificate shall not be reproduced except in full without written approval of the laboratory

Certificate No: EX-7823_Jul24

Page 1 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司



Page: 7 of 27

Calibration Laboratory of Schmid & Partner

Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland

Ilac-MRA



S Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura Swiss Calibration Service C

Accreditation No.: SCS 0108

Glossary

tissue simulating liquid sensitivity in free space sensitivity in TSL / NORMx.y.z diode compression point crest factor (1/duty_cycle) of the RF signal modulation dependent linearization parameters NORMx,y,z ConvF DCP CF

A. B. C. D

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

o rotation around probe axis

We retain around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\psi = 0$ is normal to probe axis Polarization ()

information used in DASY system to align probe sensor X to the robot coordinate system Connector Angle

Calibration is Performed According to the Following Standards:

- a) IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- b) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORMx,y,z: Assessed for E-field polarization θ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E2-field uncertainty inside TSL (see
- below convert.

 NORM(f)x,y,z = NORMx,y,z * Irequency_response (see Frequency Response Chart). This linearization is implemented in DASY4(s,x,z = NORMx,y,z * Irequency_response (see Frequency response is included in the stated uncertainty of
- DCPx,y,z; DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A A.Y., If S. If is Peak to Average Hatto that is not calibrated but determine based on the signal distance state.
 A A.Y., If S. W., If S. C.Y., If Y.Y., If Y.Y., If Y.Y. A. B. C. D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for 1 ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for t > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from +50 MHz to +100 MHz
- · Spherical isotropy (3D deviation from isotropy): In a field of low gradients realized using a flat phantom exposed by a patch
- . Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis).
- + Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).

Certificate No: EX-7823_Jul24

Page 2 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 8 of 27

July 31, 2024 EX3DV4 - SN:7823

Parameters of Probe: EX3DV4 - SN:7823

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc $(k=2)$
Norm $(\mu V/(V/m)^2)^A$	0.60	0.61	0.58	±10.1%
DCP (mV) B	107.6	106.0	107.1	±4.7%

Calibration Results for Modulation Response

UID	Communication System Name		A dB	$dB\sqrt{\mu V}$	С	D dB	VR mV	Max dev.	Max Unc ^E k=2
0	CW	X	0.00	0.00	1.00	0.00	130.0	±1.6%	±4.7%
		Y	0.00	0.00	1.00		133.8	-	
		Z	0.00	0.00	1.00		125.8		
10352	Pulse Waveform (200Hz, 10%)	X	1.38	60.00	6.14	10.00	60.0	±2.5%	±9.6%
		Y	1.49	60.59	6,41		60.0		
		Z	1.72	61.48	6.81		60.0		
10353	Pulse Waveform (200Hz, 20%)	X	10.00	72.00	9.00	6.99	80.0	±2.3%	±9.6%
	Name of the State	Y	0.81	60.00	4,96		80.0		
		Z	0.81	60.00	4.95		80.0		
10354	Pulse Waveform (200Hz, 40%)	X	0.16	138.07	0.23	3.98	95.0	±2.8%	±9.69
	(2000)	Y	22.00	72.00	7.00	95.0	95.0		
		Z	22.00	72.00	7.00		95.0		
10355	Pulse Waveform (200Hz, 60%)	X	11.33	93.62	0.05	2.22	120.0	±1.7%	±9.69
		Y	11.42	154.30	11.24	10000	120.0		94.17
		Z	9.72	86.24	0.07		120.0		
10387	QPSK Waveform, 1 MHz	X	0.65	66.31	14.06	1.00	00 150.0	±3.1%	±9.69
		Y	0.49	62.40	11.65	-	150.0		
		Z	0.59	66.20	14.31		150.0		
10388	QPSK Waveform, 10 MHz	X	1.47	67.44	14.78	0.00	150.0	±1.0%	±9.69
		Y	1.23	65.05	13.10		150.0		
		Z	1.45	67.94	14.87		150.0		
10396	64-QAM Waveform, 100 kHz	X	1.75	65.20	16.26	3.01	150.0	±0.8%	±9.69
		Y	1.66	64.00	15.53		150.0		1
		Z	1.73	65.11	16.18		150.0		
10399	64-QAM Waveform, 40 MHz	X	2.93	66.97	15.49	0.00	150.0 150.0	±1.5%	±9.69
	The state of the s	Y	2.76	66.09	14.89	1			
		Z	2.88	67.11	15.56		150.0	7	
10414	WLAN CCDF, 64-QAM, 40 MHz	X	3.90	66.50	15.55	0.00	150.0	±2.6%	±9,69
	weeks a state of the form	Y	3.68						
		Z	3.79	66,60	15.54		150.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: EX-7823_Jul24

Page 3 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

A The uncertainties of Norm X.Y.Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

§ Unearization parameter uncertainty for maximum specified field strength:

Elementarity is determined using the max, deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Page: 9 of 27

July 31, 2024 EX3DV4 - SN:7823

Parameters of Probe: EX3DV4 - SN:7823

Sensor Model Parameters

	C1 fF	C2 fF	α V-1	T1 msV ⁻²	T2 ms V ⁻¹	T3 ms	T4 V-2	T5 V ⁻¹	T6
X	9.4	67.56	33.00	3.15	0.00	4.90	0.47	0.00	1.00
У	8.3	60.37	33.74	2.92	0.00	4.90	0.37	0.00	1,00
Z	8.3	59.27	32,77	2.85	0.00	4.90	0.47	0.00	1.00

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle	29.5°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	.337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1_4 mm

Note: Measurement distance from surface can be increased to 3-4 mm for an Area Scan job,

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Certificate No: EX-7823_Jul24

所非另有說明・此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Page 4 of 22



Page: 10 of 27

July 31, 2024 EX3DV4 - SN:7823

Parameters of Probe: EX3DV4 - SN:7823

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc ^H (k = 2)
750	41.9	0.89	9.75	8.90	9.05	0.35	1.27	±11.0%
835	41.5	0.90	9.60	8.76	8.90	0.35	1.27	±11.0%
900	41.5	0.97	9.36	8.55	8.68	0.35	1.27	±11.0%
1450	40.5	1.20	8.60	7.85	7.98	0.35	1.27	±11.0%
1750	40.1	1.37	8.34	7.61	7.73	0.36	1.27	±11.0%
1900	40.0	1.40	7.85	7.16	7.28	0.36	1.27	±11.0%
2000	40.0	1.40	7,81	7.13	7.24	0.36	1.27	±11.0%
2300	39.5	1.67	7.64	6.97	7.09	0.36	1,27	±11.0%
2450	39.2	1.80	7.29	6,66	6.76	0.36	1.27	±11.0%
2600	39.0	1.96	7.22	6.59	6.69	0.36	1.27	±11.0%
3300	38.2	2.71	6.83	6.23	6.33	0.37	1.27	±13.1%
3500	37,9	2.91	6.63	6.05	6.15	0.37	1.27	±13.1%
3700	37.7	3.12	6.55	5,98	6.08	0.37	1.27	±13.1%
3900	37.5	3.32	6.49	5.92	6.02	0.37	1.27	±13.1%
4100	37.2	3.53	6.44	5.88	5.98	0.37	1.27	±13.1%
4200	37.1	3.63	6.38	5.83	5.92	0.37	1.27	±13.1%
4400	36.9	3.84	6.24	5.70	5.79	0.37	1.27	±13.1%
4600	36.7	4.04	6.07	5.54	5,63	0.37	1.27	±13.19
4800	36.4	4.25	5.99	5.46	5.55	0.38	1.27	±13.19
4950	36,3	4.40	5.87	5.35	5.44	0,36	1.27	±13.19
5250	35.9	4.71	5.57	5.08	5.16	0.33	1.27	±13.19
5600	35.5	5.07	5.05	4.61	4.69	0.29	1.27	±13.19
5750	35.4	5.22	5,19	4.74	4.81	0.28	1.27	±13.19
5850	35.2	5.32	4.99	4.55	4.62	0.27	1,27	±13.19

C Frequency validity above 300 MHz of ±100 MHz only applies for DASY v4.4 and higher (see Page 2), else in its restricted to ±60 MHz. The uncertainty is the RSs of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity blow 300 MHz is ±10, 25, 40, 50 and 70 MHz for ±00 MHz is ±10, 25, 40, 50 and 70 MHz for ±00 MHz is ±10, 25, 40, 50 and 70 MHz is ±10 MHz. Above 5GHz frequency validity can be extended to 11 to MHz.

The probes are calibrated using tissue simulating liquids (TSL) that deviate for and or by less than ±5% from the target values (typically better than ±3%) and 24 Alpha/Deght are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3GHz and below ±2% for frequencies between 3–5 GHz at any distance larger than half the probe tip diameter from the boundary.

H The stated uncertainty is the total calibration uncertainty (k = 2) of Norm ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.

Certificate No: EX-7823_Jul24

Page 5 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 11 of 27

July 31, 2024 EX3DV4 - SN:7823

Parameters of Probe: EX3DV4 - SN:7823

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc ^H (k = 2)
6500	34.5	6.07	5.34	4.87	4.95	0.20	1.27	±18.6%
7000	33.9	6.65	5.47	4.99	5.07	0.20	1.27	±18.6%

Certificate No: EX-7823_Jul24

Page 6 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

C Prequency validity at 6.5 GHz is -600 i 700 MHz, and ±700 MHz at or above 7 GHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

The probos are calibrated using tissue simulating illusid (TSL) that deviate for ε and σ by less than ±10% from the target values (typically better than ±6%) and are valid for TSL with deviations of up to ±10%.

Apha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz, below ±26 for frequencies between 3-6 GHz; and below ±4% for frequencies between 6-10 GHz at any distance larger than half the probe tig diameter from the boundary.

The stated uncertainty is the total calibration uncertainty (k = 2) of Norm ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.




Page: 12 of 27

July 31, 2024 EX3DV4 - SN:7823

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide:R22)



Uncertainty of Frequency Response of E-field: ±6.3% (k=2)

Certificate No: EX-7823_Jul24

Page 7 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 13 of 27

July 31, 2024 EX3DV4 - SN:7823

Receiving Pattern (ϕ), $\vartheta = 0^{\circ}$



Certificate No: EX-7823_Jul24

Page 8 of 22

Uncertainty of Axial Isotropy Assessment: ±0.5% (k=2)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.




Page: 14 of 27

EX3DV4 - SN:7823 July 31, 2024

Dynamic Range f(SARhead)





Uncertainty of Linearity Assessment: ±0.6% (k=2)

Certificate No: EX-7823_Jul24

Page 9 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.


除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.




Page: 15 of 27

July 31, 2024 EX3DV4 - SN:7823

Conversion Factor Assessment



Deviation from Isotropy in Liquid



Certificate No: EX-7823_Jul24

Page 10 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 16 of 27

July 31, 2024 EX3DV4 - SN:7823

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k =
0		CW	CW	0.00	±4,7
0010	CAB	SAR Validation (Square, 100 ms, 10 ms)	Test	10.00	±9.6
0.011	CAC	UMTS-FDD (WCDMA)	WCDMA.	2.91	±9.6
0012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	19.6
0013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9,46	£9.6
0021	DAG	GSM-FDD (TDMA, GMSK)	GSM	9.39	=9.6
0.023	DAG	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	±9.6
0024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	±9.6
0025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	±9.6
10.026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	±9.6
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	±9.6
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-8)	GSM	3.55	=9.6
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	±9.6
10025	CAA	IEEE 802,15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	±9.6
10031	CAA	IEEE 802,15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	+9.6
		IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluelooth	1,16	9.6
10032	CAA		Bluetooth	7.74	±9.6
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	4.53	19.6
10034	CAA	IEEE 802.15.1 Blustooth (PI/4-DQPSK, DH3)			±9.6
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	±9.6
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	4.77	=9.6
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth		
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10 4.57	±9.6
10039	CAB	GBMA2000 (1xRTT, RC1)	CDMA2000	3.41	±9.6
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	±9.6
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0,00	±9.6
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	-9.6
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	±9.6
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	±9.6
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	±9.6
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	±9.6
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	±9.6
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	9.6
10062	CAE	IEEE 802.11a/h WIF: 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	=9.6
10063	CAE	IEEE 802.11a/h WIFI 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	±9.6
10064	CAE	IEEE 802,11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	±9.6
10065	CAE	IEEE 802,11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	±9.6
10066	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mops)	WLAN	9,38	19.6
10067	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	±9.6
10068	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	+9.6
10.069	CAE	IEEE 802.11a/h WiFl 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	=9.6
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	±9.6
10072	CAB	IEEE 802,11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	±9.6
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	±9,6
10074	CAB	IEEE 802.11g WiFi 2,4GHz (DSSS/OFDM, 24Mbps)	WLAN	10.30	19.6
10074	CAB	IEEE 802,11g WiFi 2.4 GHz (DSSS/OFDM, 24 NOps)	WLAN	10.77	±9.6
10075	CAB	IEEE 802,11g WIFI 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.94	±9.6
10076	CAB	IEEE 802,11g WIFI 2,4 GHz (DSSS/OFDM, 48 M0ps)	WLAN	11.00	=9.6
10077	CAB		CDMA2000	3,97	±9.6
		CDMA2000 (1xRTT, RC3)	AMPS	4.77	±9.6
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	GSM	6.56	19.0
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)			
10097	CAC	UMTS-FDD (HSDPA)	WCDMA	3.98	±9.6
10098		UMTS-FDD (HSUPA, Subtest 2)	WGDMA		±9.6
10099		EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	±9.6
10100		LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	±9.
10101	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	+9.
10102		LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9,
10103		LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TOD	9,29	±9,0
10104			LTE-TOD	9.97	±9.
10105	CAH		LTE-TDD	10.01	±9,6
10108	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	±9.8
10109	CAH		LTE-FOD:	6.43	±93
10110			LTE-FDD	5.75	=9.8
10111			LTE-FDD	6.44	±9.

Certificate No: EX-7823 Jul24

Page 11 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Onless otherwise stated the results shown in this test report reter only to the sample(s) leader and such sample(s) leader and sample(s) leader and such sample(s) leader and such sample(s) leader and such sample(s) leader and sample(s) le Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 17 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k =
10112	CAH	LTE-FDD (SC-FDMA, 100% RB, 10MHz, 64-QAM)	LTE-FDD	6.59	±9.6
0113	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
0114	CAE	IEEE 802.11n (HT Greenfield, 13.5 Mops, BPSK)	WLAN	8.10	±9.6
0115	CAE	IEEE 802,11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	±9,6
0116	CAE	IEEE 802,11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8,15	±9.6
0117	CAE	IEEE 802,11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	±9.6
0118	CAE	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	19.6
0119	CAE	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	±9.6
0140	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FDD	6.49	±9,6
0141	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	±9.6
		LTE-FDD (SG-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
0142	CAF		LTE-FDD	6.35	±9.6
0143	- Ser. 11	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6,65	±9.6
0144	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	5.76	±9.6
0145	CAG	LTE-FDB (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	6.41	±9.6
0146	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4MHz, 16-QAM)		6.72	±9.6
0147	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD		
0149	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FD0	6.42	±9.6
0150	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9,6
0151	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-TOD	9,28	#9.6
0152	CAH	LTE-TDD (SG-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
0153	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-TDD	10.05	19.6
0154	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD.	5.75	±9.6
0155	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
0156	CAH	LTE-FDD (SC-FDMA, 50% RB, 5MHz, QPSK)	LTE-FDD	5.79	=9.6
0157	CAH	LTE-FDD (SC-FDMA, 50% RB, 5MHz, 16-QAM)	LTE-FDD	6.49	±9.6
0158	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
0159	CAH	LTE-FDD (SC-FDMA, 50% RB, 5MHz, 64-QAM)	LTE-FOD	6.56	±9.6
10160	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FOD	5.82	±9.6
0161	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10162	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, 64-QAM)	LTE-FDD	6,58	-9.6
10166	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	19.6
10167	CAG	LTE-FDD (SC-FDMA, 50% RB. 1.4 MHz, 16-QAM)	LTE-FDD	6.21	±9.6
10188	CAG	LTE-FDD (SC-FDMA, 50% RB. 1.4 MHz, 64-QAM)	LTE-FDD	6,79	±9.6
10169	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	±9.6
10170	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	+9.6
10171	AAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	+9.6
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TDD	9,21	±9.6
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9,48	±9.6
	CAH	LTE-TDD (SC-FDMA, 1 RB. 20 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10174	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, OPSK)	LTE-FDD	5,72	±9.6
			LTE-FDD	6.52	±9.6
10176	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)			-
10177	CAJ	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-FDD	5.73	±9.6
10178	CAH	LTE-FDD (SC-FDMA, 1 RB, 5MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10179	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-FDD	6.50	±9,6
10180	CAH	LTE-FDD (SC-FDMA, 1 RB, 5MHz, 64-QAM)	LTE-FOD	6.50	±9.6
10181	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-FDD	5.72	±9.6
10182	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	=9.6
10183	AAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	+9.6
10184	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10185	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.51	±9.6
10186	AAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-FDD	6.50	±9,6
10187	CAG	LTE-FDD (SC-FDMA, 1 RB, 1,4 MHz, QPSK)	LTE-FDD	5,73	19,6
10188	CAG	LTE-FDD (SC-FDMA, 1 RB, 1,4 MHz, 16-QAM)	LTE-FDD	6.52	19,€
10189	AAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10193	CAE	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	±9,6
10194	CAE	IEEE 802,11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	±9.6
10195	CAE	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	B.21	±9.6
10196	CAE	IEEE 802,T1n (HT Mixed, 6,5 Mbps, BPSK)	WLAN	8.10	±9.6
10197	CAE	IEEE 802,11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8,13	±9.6
10198	CAE	IEEE 802,11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	=9.6
10219	CAE	IEEE 802,11n (HT Mixed, 53 Mbps, 64 GAW)	WLAN	8.03	±9.5
10220	CAE	IEEE 802,11n (HT Mixed, 7,2 Mbps, 5FSK)	WLAN	8.13	-9.6
10220	CAE	IEEE 802,11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.27	±9.6
10221	CAE	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.06	+9,6
10223	CAE	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8,48	±9.6
10224	CAE	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	80.8	±9.6

Certificate No: EX-7823_Jul24

Page 12 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 18 of 27

EX3DV4 - SN:7823

July 31, 2024

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k =
0225	GAC	UMTS-FDD (HSPA+)	WCDMA	5.97	±9,6
0226	CAC	LTE-TDD (SG-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	9,49	-9,6
0227	CAC	LTE-TDD (SG-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TOD	10.26	±9.6
0228	CAC	LTE-TDD (SC-FDMA, 1 RB, 1,4 MHz, QPSK)	LTE-TOD	9.22	±9.6
0229	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz. 16-QAM)	LTE-TDD	9,48	±9.6
0.230	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-TDD	10,25	±9.6
0231	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TDD	9,19	±9.6
0232	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	±9,6
0233	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10,25	±9.6
10234	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	±9.6
0235	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz. 16-QAM)	LTE-TDD	9.48	±9.6
0236	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
0237	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TDD	9.21	±9.6
0238	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TDD	9,48	=9.6
0239	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TOD	10.25	±9.6
0240	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TOO	9.21	±9.6
0241	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.82	±9.6
0242	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4MHz, 64-QAM)	LTE-TDD	9.86	±9.6
0248	CAC	LTE-TDD (SC-FDMA, 50% RB, 1,4 MHz, QPSK)	LTE-TDD	9.46	=9.6
0244	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
0245	CAE	LTE-TDD (SC-FDMA, 50% RB, 3MHz, 64-QAM)	LTE-TDD	10.06	±9.6
0246	CAE	LTE-TDD (SC-FDMA, 50% RB, 3MHz, QPSK)	LTE-TOD	9.30	±9.6
0.247	CAH	LTE-TDD (SC-FDMA, 50% RB, 5MHz, 16-QAM)	LTE-TDD	9.91	±9,6
0248	CAH	LTE-TDD (SC-FDMA, 50% RB, 5MHz, 64-QAM)	LTE-TDD	10.09	±9,6
0249	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	±9.6
10250	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TOD	9,81	±9.6
10251	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-TOD	10.17	±9.6
10252	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	±9.6
0253	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-TDD	9.90	±9.6
0254	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	±9.6
10255	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	±9.6
10256	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TOD	9.96	±9,6
10257	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-OAM)	LTE-TDD	10.08	+9.6
10258	CAC	LTE-TDD (SC-FDMA, 100% RB, 1,4 MHz, QPSK)	LTE-TDD	9.34	±9.6
10259	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	±9.6
10260	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	±9.8
10261	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	±9,6
10262	CAH	LTE-TDB (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	±9,6
10263	CAH	LTE-TDD (SC-FDMA, 100% RB, 5MHz, 64-QAM)	LTE-TDD	10.16	±9.6
10264	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	±9.€
10265	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10266	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	±9.6
10267	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TDD	9.30	±9.6
10268	CAG	LTE-TDD (SC-FDMA, 100% RB, 15.MHz, 16-QAM)	LTE-TDD	10:06	±9,€
10269	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	±9.6
10270	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-TOD	9.58	±9.6
10274	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8,10)	WCDMA	4.87	±9.6
10275	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	±9.6
10277	CAA	PHS (QPSK)	PHS	11,81	±9.6
10278	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.5)	PHS	11,81	= 9,6
10279	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.38)	PHS	12.18	±9.6
10290	AAB	CDMA2000, RC1, SO55, Full Rate	CDMA2000	3.91	±9.6
10291	AAB	CDMA2000, RC3, SO55, Full Rate	CDMA2000	3,46	±9.6
10292	AAB	CDMA2000, RC3, SO32, Full Rate	GDMA2000	3.39	±9.6
10293	AAB	GDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	19.6
10295		CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	CDMA2000	12.49	+9,6
10297	AAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	±9.0
10298		LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	±9.0
10299		LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	±9.0
10300		LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6,60	19.0
10300	AAA	IEEE 802 15e WIMAX (29:18, 5 ms. 10 MHz, QPSK, PUSC)	WiMAX	12,03	+9.
10302		IEEE 802,16e WIMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	±9.0
10302		IEEE 802.16e WIMAX (23:18, 5 ms, 10 MHz, 64QAM, PUSC)	WIMAX	12.52	±9)
10303		IEEE 802.16e WIMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)	WIMAX	11.86	±9.8
10304		IEEE 802.168 WIMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC) IEEE 802.168 WIMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)	WIMAX	15.24	+9.
10305	AAA				

Certificate No: EX-7823_Jul24

Page 13 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 19 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k =
10307	AAA	IEEE 802.16e WIMAX (29:18, 10 ms, 10 MHz, QPSK, PUSC, 18 symbols)	WiMAX	14.49	±9.6
0308	AAA	IEEE 802.16e WIMAX (29:18, 10 ms, 10 MHz, 16QAM, PUSC)	WIMAX	14.46	±9.6
0309	AAA	IEEE 802.16e WIMAX (29:18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 18 symbols)	WiMAX	14.58	±9.6
0310	AAA	IEEE 802.16e WIMAX (29:18, 10 ms. 10 MHz, QPSK, AMC 2x3, 18 symbols)	WIMAX	14.57	19.6
0311	AAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	±9.6
0313	AAA	IDEN 1:3	IDEN	10.51	=9.6
0314	AAA	IDEN 1:6	IDEN	13.48	=9.6
0315	AAB	IEEE 802,11b WiFi 2,4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	±9.6
0316	AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
0317	AAE	IEEE 802,11a WIFI 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
0352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	±9.6
0353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	±9.6
0353	AAA	Pulse Waveform (200Hz, 20%)	Generic	3.98	±9.6
0355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	+9.6
		Pulse Waveform (200Hz, 80%)	Generic	0.97	+9.6
0356	AAA	QPSK Waveform, 1 MHz	Generic	5.10	±9.6
	AAA	QPSK Wavelorm, 10 MHz	Generic	5,22	-9.6
0388			Generic	6.27	-9.6
0396	AAA	64-QAM Waveform, 100 kHz	Generic	6,27	19.6
0399	AAA	64-QAM Waveform, 40 MHz	WLAN	8.37	19.6
0400	AAF	IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.60	19.6
0401	AAF	IEEE 802.11ac WiFI (40 MHz. 64-QAM, 99pc duty cycle)		8.53	±9.6
0402	AAF	IEEE 802.11ac WiFr (80 MHz, 64-QAM, 99pc duty cycle)	WLAN	3.76	±9.6
0403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000 CDMA2000	3.76	±9.6
0404	AAB	CDMA2000 (1xEV-DO, Rev. A)			±9.6
0406	AAB	CDMA2000, RC3, SC32, SCH0, Full Rate	CDMA2000	5.22	
10410	AAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subtrame Conf=4)	LTE-TDD	7.82	±9,6
10414	AAA	WLAN CCDF, 64-QAM, 40 MHz	Generic	8.54	±9.6
0415	AAA	IEEE 802.11b WIFI 2.4 GHz (DSSS. 1 Mbps, 99pc duty cycle)	WLAN	1,54	1.9.6
0416	AAA	IEEE 802.11g WIFI 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	-9.6
10417	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8,23	±9.€
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preambule)	WLAN	8.14	19.8
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 8 Mbps, 99pc duty cycle, Short preambule)	WLAN	8.19	±9.6
10422	AAD	IEEE 802.11n (HT Greenfield, 7,2Mbps, BPSK)	WLAN	8.32	±9.6
10423	AAD	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	±9.6
10424	AAD	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	19.6
10425	AAD	IEEE 802,11n (HT Greentield, 15 Mbps, BPSK)	WLAN	8,41	1.9.8
10426		IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	±9.6
10427	CAA	IEEE 802,11n (HT Greenfield, 150 Mbps, 64-QAM)	WLAN	8.41	±9.6
10430	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FOD	8.28	±9.6
10431	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	±9.6
10432	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3,1)	LTE-FDD	8.34	=9.6
10433	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FDD	8,34	±9.6
10434	AAB	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	±9.6
10435	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10447	AAE	LTE-FDD (OFDMA, 5MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	±9.6
10448	AAE	LTE-FDD (OFDMA, 10 MHz; E-TM 3.1, Clippin 44%)	LTE-FD0	7.53	±9.6
10449	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Cliping 44%)	LTE-FDD	7.51	19.0
10450	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	±9.6
10.451		W-CDMA (BS Test Model 1, 64 DPCH. Clipping 44%)	WCDMA	7.59	±9.
10453	AAE	Validation (Square, 10 ms. 1 ms)	Test	10.00	=9)
10456		IEEE 802,11ac WiFi (160 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.63	±9.
10457		UMTS-FDD (DC-HSDPA)	WCDMA	6.62	1.9.
10458		CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	GDMA2000	6.55	±9.
10459		CDMA2000 (1xEV-DO: Rev. B, 3 carriers)	CDMA2000	8.25	±9.
10.460		UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	±9.
10461		LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2.3,4,7,8,9)	LTE-TDD	7.82	±9.
10462		LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-OAM, UL Subframe 2.3.4.7,8,9)	LTE-TDD	8.30	19.
10463		LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.
10464		LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4.7.8.9)	LTE-TDD	7.82	±9.
10465		LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8.9)	LTE-TOD	8,32	±9.
10466		LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2.3.4,7,8.9)	LTE-TDD	8.57	±9.
10.467		LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	19.
10467		LTE-TDD (SC-FDMA, 1 RB, 5 MHz, GFSK, GL Stoframe=2,3,4,7,6,5)	LTE-TDD	8.32	19.
10468		LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, DL Subtrame=2,3,4,7,8,9)	LTE-TOD	8,56	±9.
			LTE-TOD	7,82	±9.
10470					-9.
10471	AAG	LTE-TDD (SC-FDMA, 1 RB. 10 MHz, 16-QAM, UL Subframe=2,3.4,7.8,9)	LTE-TDD	8.32	-9.

Certificate No: EX-7823_Jul24

Page 14 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Onless otherwise stated the results shown in this test report reter only to the sample(s) leader and such sample(s) leader and sample(s) leader and such sample(s) leader and such sample(s) leader and such sample(s) leader and sample(s) le Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 20 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k =
0472	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
0473	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7.8.9)	LTE-TDD	7.82	1.9.6
0474	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3.4.7.8,9)	LTE-TDD	8.32	+9.6
3475	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8.9)	LTE-TDD	8.57	±9.6
3477	AAG	LTE-TDD (SC-FDMA, 1 RB. 20 MHz. 16-QAM, UL Subframe=2,3;4,7,8,9)	LTE-TDD	8.32	=9.6
3478	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8,57	±9,6
0479	AAC	LTE-TDD (SC-FDMA, 50% RB. 1.4 MHz, QPSK, UL Subtrame=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
0480	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3.4,7.8,9)	LTE-TOD	8.18	±9.6
0481	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2.3.4,7.8,9)	LTE-TDD	8.45	±9.6
0482	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2.3,4,7.8,9)	LTE-TDD	7.71	±9.6
	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-OAM, UL Subtrame=2,3,4,7,8,9)	LTE-TDD	8,39	±9.6
0483	AAD	LTE-TDD (SC-FDMA, 50 % RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	±9.6
0484		LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7,59	±9.6
10485	AAG	LTE-TDD (SC-FDMA, 50% RB, 5MHz, 16-QAM, UL Subframe=2,3,4 7,8.9)	LTE-TOD	8.38	49,6
0486	AAG	LTE-TOD (SC-FDMA, 50% RB, 5MFZ, 16-QAM, OL SQUIRAINS=2,5,4 7,6.5)	LTE-TDD	8.60	19,6
10487	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3.4,7,8,9)	LTE-TOD	7,70	±9.6
10488	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subtrame=2.3,4,7,8.9)		8,31	±9.6
10489	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8.9)	LTE-TDD		
0490	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4.7,8,9)	LTE-TOD	8,54	±9.6
10491	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	=9.6
10492	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3.4,7.8,9)	LTE-TDD	8.41	±9.6
10493	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2.3,4,7,8,9)	LTE-TDD	8.55	±9.6
10494	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10495	AAG	I.TE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subtrame=2.3,4,7,8.9)	LTE-TDD	8.37	±9.6
10496	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10497	AAC	LTE-TDD (SC-FDMA, 100% RB, 1,4MHz, QPSK, UL Subframe=2,3,4.7.8,9)	LTE-TDD	7.67	±9.6
10498	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3.4,7,8,9)	LTE-TDD	8,40	±9.6
10499	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.68	±9.€
10500	AAD	LTE-TDD (SG-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2.3,4,7,8,9)	LTE-TDD	7.67	+9.6
10501	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TOD	8.44	±9.6
10502	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8,52	+9.6
10502	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.72	=9.6
10504	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE/TDD	8,31	±9.8
	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subtrame=2,3,4,7,8,9)	LTE-TDD	8,54	±9.8
10505		LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2.3,4,7,8.9)	LTE-TDD	7.74	+9.6
10506		LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TOD	8.36	+9.1
10507	AAG		LTE-TOD	8.55	±9.1
10508	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7.8,9)	LTE-TDD	7.99	±9.6
10509	AAF	LTE-TDD (SC-FDMA, 100% RB, 15MHz, QPSK, UL Subframe=2,3.4,7,8,9)		8.49	
10510		LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4.7,8.9)	LTE-TDD		±9.6
10511	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2.3,4,7,8,9)	LTE-TDD	8.51	±9.6
10512		LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9,6
10513		LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TOD	8.42	=9.8
10514		LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3.4.7.8,9)	LTE-TDD	8.45	±9.
10515	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	WLAN	1.58	+9.
10516	AAA	IEEE 802,11b WiFi 2,4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	WLAN	1.57	±9.
10517	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	WLAN	1.58	±9.0
10518	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.23	±9.
10519		IEEE 802,11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8,39	-9.
10520		IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.12	€9.
10521		IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	WLAN	7.97	±9.
10522		IEEE 802,11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.45	±9.
10523		IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8,08	19,
10524		IEEE 802,11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.27	1.9.
10525		IEEE 802.11ac WiFi (20 MHz. MCS0, 99pc duty cycle)	WLAN	8.36	19
10525		IEEE 802.11ac WiFi (20 MHz. MCS1, 99pc duty cycle)	WLAN	8.42	±9.
10525		IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.21	=9.
	-		WLAN	8.36	±9
10528		IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)		0.00	
10529		IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.36	±9
10531		IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)	WLAN		±9.
10532		IEEE 802,11ac WiFi (20 MHz, MGS7, 99pc duty cycle)	WLAN	8,29	±9.
10533		IEEE 802,11ac WiFi (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.38	±9.
10534	AAD	IEEE 802,11ac WiFi (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.45	±9
10535	AAD	IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)	WLAN	8,45	19
10536	AAD	IEEE 802,11ac WiFi (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.32	±9.
10537	AAD.	IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	+9
10538			WLAN	8.54	±9
			WLAN	8,39	±9.

Certificate No: EX-7823 Jul24

Page 15 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 21 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k =
10541	AAD	IEEE 802,11ac WiFi (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.46	±9.6
0542	AAD	IEEE 802,11ac WiFi (40 MHz. MCS8, 99pc duty cycle)	WLAN	8.65	±9.6
0543	AAD	IEEE 802,11ac WiFi (40 MHz, MGS3, 99pc duty cycle)	WLAN	8,65	±9.6
0544	AAD	IEEE 802,11ac WiFi (80 MHz, MCS0, 99pc duty cycle)	WLAN	8,47	19.6
0545	AAD	IEEE 802,11ac WiFi (80 MHz, MCS1, 99pc duty cycle)	WLAN	8,55	±9.6
0546	AAD	IEEE 802,11ac WiFi (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.35	=9.6
0547	AAD	IEEE 802.11ac WiFi (80 MHz. MCS3, 99pc duty cycle)	WLAN	8.49	±9.6
0548	AAD	IEEE 802.11ac WIFi (80 MHz, MCS4, 99pc duty cycle)	WLAN	8,37	±9.6
	AAD	IEEE 802.11ac WiFi (80 MHz. MCS6, 99pc duty cycle)	WLAN	8.38	±9.6
0550		IEEE 802.11ac WiFI (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.50	±9.6
10551	AAD		WLAN	8.42	±9.6
0552	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.45	±9.6
0553	AAD	IEEE 802.11ac WiFi (80 MHz, MGS9, 99pc duty cycle)	WLAN	8.48	±9.6
10554	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)	WLAN	8,47	±9.6
10555	AAE	IEEE 802.11ac WiFi (160 MHz, MGS1, 99pc duty cycle)	WLAN	8.50	+9.6
10556	AAE	IEEE 802,11ac WiFi (160 MHz, MCS2, 99pc duty cycle)		8.52	±9.6
10557	AAE	(EEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)	WLAN		
10558	AAE	IEEE 802,11 ac WIFI (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.61	±9,6
10560	AAE	IEEE 802.11ac WIFI (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.73	±9.6
10561	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.56	±9.6
10562	AAE	IEEE 802;11ac WiFi (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.69	±9,6
10563	AAE	IEEE 802.11ac WiFi (160 MHz. MCS9, 99pc duty cycle)	WLAN	8.77	±9.8
10564	AAA	IEEE 802.11g WIFI 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	±9.6
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	19.6
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	±9.5
10568	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.37	±9,€
10.569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.10	±9,6
1.0570	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM: 54 Mbps, 99pc duty cycle)	WLAN	8,30	±9.6
10571	AAA	IEEE 802.11b WIFI 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	WLAN	1,99	±9.6
10.572	AAA	IEEE 802,11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	WLAN	1.99	+9.6
10573	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	WLAN	1.98	19.0
10574	AAA	IEEE 802.11b WIFI 2.4 GHz (DSSS, 3.3 Wops, 30pc duty cycle)	WLAN	1.98	1.9.6
	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10575			WLAN	8.60	±9.6
10576	AAA	IEEE 802,11g WiFl 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)			
10577	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10578	AAA	IEEE 802,11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8,49	±9.6
10579	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	1,9,6
10580	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10581	AAA	IEEE 802,11g WiFi 2,4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10582	AAA	IEEE 802,11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.5
10583	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8,59	±9.6
10584	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8,60	±9.6
10585	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10586	AAD	IEEE 802.11a/h WIFI 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9,6
10587	AAD	IEEE 802.11a/h WIFI 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	+9.8
10588	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.8
10589	AAD	IEEE 802,11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	-9.0
10590	AAD	IEEE 802.11a/h WIFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10591	AAD	IEEE 802,11n (HT Mixed, 20 MHz, MCS0, 90pc duty cycle)	WLAN	8.63	+91
10592	AAD	IEEE 802,11n (HT Mixed, 20 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	19,
10593	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MGS2, 90pc duty cycle)	WLAN	8.64	±9.
10594		IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.
10595		IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 90pc duty cycle)	WLAN	8.74	±9.
			WLAN	8.71	±9.
10596		IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 90pc duty cycle)		8.72	19.
10597	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 90pc duty cycle)	WLAN		
10598		IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 90pc duty cycle)	WLAN	8.50	±9.
10.599		IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 90pc duty cycle)	WLAN	8,79	±9.
10600		IEEE 802,11n (HT Mixed. 40 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.
10601	AAD	IEEE 802,11n (HT Mixed: 40 MHz, MCS2, 90pc duty cycle)	WLAN	8.82	±9,
10602		IEEE 802,11π (HT Mixed, 40 MHz, MCS3, 90pc duty cycle)	WLAN	8,94	+9.
10603	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 90pc duty cycle)	WLAN	9.03	±9,
10604	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 90pc duty cycle)	WLAN	8.76	±9,
10605	AAD	IEEE 802,11n (HT Mixed, 40 MHz, MCS6, 90pc duty cycle)	WLAN	8.97	=9,
10606		IEEE 802.11n (HT Mixed, 40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.
10607		IEEE 802.11ac WiFi (20 MHz, MCS0, 90pc duty cycle)	WLAN	8.64	119.
10608	0.075		WLAN	8.77	1.9.

Certificate No: EX-7823 Jul24

Page 16 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 22 of 27

July 31, 2024 FX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k =
0609	AAD	IEEE 802.11ac WiFi (20 MHz, MGS2, 90pc duty cycle)	WLAN	8.57	±9.6
0610	AAD	IEEE 802.11ac WiFi (20 MHz. MGS3, 90pc duty cycle)	WLAN	8.78	19.6
0611	AAD	IEEE 802.11ac WiFi (20 MHz, MGS4, 90pc duty cycle)	WLAN	8.70	19.6
0612	AAD	IEEE 802,11ac WiFi (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9,6
0613	AAD	IEEE 802.11ac WiFi (20 MHz, MGS6, 90pc duty cycle)	WLAN	8.94	±9.6
0614	AAD	IEEE 802, 11 ac WiFr (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.59	±9.6
0615	AAD	IEEE 802,TTac WiFi (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	=9.6
0616	AAD	IEEE 802,17ac WiFi (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.82	±9.6
0617	AAD	IEEE 802,11gc WiFi (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.81	±9.6
0618	AAD	IEEE 802,11ac WiFi (40 MHz, MCS2, 90pc duty cycle).	WLAN	8.58	±9.6
0619	AAD	IEEE 802,11ac WiFi (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.86	±9.6
0620	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.87	±9.6
0621	AAD	IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
0622	AAD	IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)	WLAN	8,68	=9,6
0623	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
0624	AAD	IEEE 802,11ac WiFi (40 MHz. MCS8, 90pc duty cycle)	WLAN	8.96	±9.6
0625	AAD	IEEE 802,11ac WiFi (40 MHz, MCS9, 90pc duty cycle)	WLAN	8,96	±9.6
0626	AAD	IEEE 802,11ac WiFi (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
0627	AAD	IEEE 802.11ac WiFi (80 MHz. MCS1, 90pc duty cycle)	WLAN	8.88	19.6
0628	AAD	IEEE 802,11ac WiFi (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.71	19.6
0629	AAD	IEEE 802.11ac WIFI (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.85	+9.6
0630	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duly cycle)	WLAN	8.72	19.6
0631		IEEE 802.11ac WiFi (80 MHz. MCS4, 90pc duty cycle)	WLAN	8.81	=9.6
0.632	AAD	IEEE 802,11ac WiFi (80 MHz, MCSS, 90pc duty cycle)	WLAN	B,74	±9.6
		IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.83	±9.6
0633	AAD		WLAN	8.80	±9.6
0634	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)	WLAN	8,81	±9.6
0635	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)	WLAN	8,83	±9.6
10636	AAE	IEEE 802,11ac WiFi (160 MHz, MCS0, 90pc duty cycle)		8.79	=9.6
0637	AAE	[EEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)	WLAN	8.86	-9.6
0638	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.85	-9.6
10,639	AAE	IEEE 802.11as WiFi (160 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10640	AAE	IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)	11.50,000.00	0.00	
10641	AAE	IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)	WLAN	9.06	±9.6
10642	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)	WLAN	9.06	±9.6
10643	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.89	±9.6
10644	AAE	IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duly cycle)	WLAN	9.05	9.6
10645	AAE	IEEE 802,11ac WiFi (160 MHz, MCS9, 90pc duty cycle)	WLAN	9.11	1.9.6
10646	AAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	=9.6
10647	AAG	LTE-TDD (SG-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2.7)	LTE-TDD	11.96	±9.6
10648	AAA	CDMA2000 (1x Advanced)	CDMA2000	3.45	±9.6
10652	AAF	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.91	±9.6
10653	AAF	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	±9.6
10654	AAE	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.96	±9.6
10655	AAF	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.21	+9.6
10658	AAB	Pulse Waveform (200Hz, 10%)	Test	10.00	±9.6
10659	AAB	Pulse Waveform (200Hz, 20%)	Test	6.99	=9.6
10660	AAB	Pulse Waveform (200Hz, 40%)	Test	3.98	±9.8
10661	AAB	Pulse Waveform (200Hz, 60%)	Test	2:22	±9.6
10662	AAB	Pulse Waveform (200Hz, 80%)	Test	0.97	±9.6
10670		Bluetooth Low Energy	Bluetooth	2.19	₹9.6
10671	AAC	IEEE 802,11ax (20 MHz, MCS0, 90pc duty cycle)	WLAN	9.09	±9.€
10672	AAC	JEEE 802,11ax (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.57	±9.6
10673	AAC	IEEE 802,11ax (20 MHz, MCS2, 90pc duly cycle)	WLAN	8.78	±9.6
10674		IEEE 802:11ax (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9,€
10675	AAC	IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)	WLAN	8,90	19.6
10676		IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10.677	AAC	IEEE 802,11ax (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.73	±9.6
10678	AAC	IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.78	±9.6
10679	AAC	IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.89	1.9.6
10680	AAC	IEEE 802.11ax (20MHz, MCS9, 90pc duty cycle)	WLAN	8.80	+9.6
10681	AAC	JEEE 802.11ax (20 MHz, MOS10, 90pc duty cycle)	WLAN	8.62	±9.6
10.001	AAC	IEEE 802,11ax (20 MHz, MGS11, 90pc duty cycle)	WLAN	8.83	±9.6
10682			WLAN.	8.42	±9.6
	AAC	IEEE 802,11ax (20 MHz; MCS0, 99pc duty cycle)	AAT SIA		
10682 10683		IEEE 802,11ax (20 MHz, MCS0, 99pc duty cycle) IEEE 802,11ax (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.26	±9.6
10682	AAC				±9.6

Certificate No: EX-7823 Jul24

Page 17 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279

www.sgs.com.tw



Page: 23 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k =
0687	AAC	IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.45	±9.6
		IEEE 802,11ax (20 MHz, MCS5, 99pc duty cycle)	WLAN	8.29	±9.6
0688	AAC		WLAN	8.55	19.6
0689	AAC	IEEE 802.11ax (20 MHz, MCS6, 99pc duly cycle)	WLAN	8.29	(9,6
0690	AAC	IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.25	±9.6
0691	AAC	IEEE 802,11ax (20 MHz, MCS8, 99pc duty cycle)			
0692	AAC	IEEE 802,11ax (20 MHz; MCS9, 99pc duty cycle)	WLAN	8.29	±9.6
10693	AAC	IEEE 802,11ax (20 MHz, MCS10, 99pc duty cycle)	WLAN	8.25	±9.6
10694	AAC	IEEE 802.11ax (20 MHz, MCS11, 99pc duly cycle)	WLAN	8,57	±9.6
10695	AAC	IEEE 802.11ax (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.78	±9.6
10696	AAC	IEEE 802.11ax (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.91	±9.6
	AAC	IEEE 802,11ax (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.61	-9.6
10697			WLAN	8.89	±9.6
10698	AAC	IEEE 802.11ax (40 MHz, MCS3, 90pc duly cycle)	WLAN	8,82	±9.6
10699	AAC	IEEE 802,11ax (40 MHz, MCS4, 90pc duty cycle)			
10700	AAC	IEEE 802.11ax (40 MHz, MCS5, 90pc duty cycle)	WLAN	8,73	±9.6
10701	AAC	IEEE 802.11ax (40 MHz, MCS6, 90pc duty cycle)	WLAN.	8.86	±9,6
10702	AAC	IEEE 802.11ax (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.70	±9.6
10703	AAC	IEEE 802,11ax (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10704	AAC	IEEE 802,11ax (40 MHz, MCS9, 90pc duty cycle)	WLAN	8,56	+9.6
10705	AAC	IEEE 802.11ax (40 MHz, MCS10, 90oc duty cycle)	WLAN	8.69	±9.6
			WLAN	8.66	±9.6
10706	AAC	IEEE 802.11ax (40 MHz, MCS11, 90pc duty cycle)	WLAN	8.32	±9.6
10707	AAC	IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)			
10708	AAC	IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10709	AAC	IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	19.6
10710	AAC	IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.29	9.6
10711	AAC	IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.39	±9.6
10712	AAC	IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)	WLAN	8.67	±9.6
10713	AAC	IEEE 802,11ax (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.33	±9.6
	AAC	IEEE 802,11ax (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.26	±9,6
10714			WLAN	8,45	±9.6
10715	AAC	IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)			
10716	AAC	IEEE 802,11ax (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.30	±9.6
10717	AAC	IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle)	WLAN	8.48	±9.6
10718	AAC	IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle)	WLAN	B.24	19.6
10.719	AAC	IEEE 802.11ax (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.81	1.9.6
10720	AAC	IEEE 802,11ax (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.87	±9.6
10721	AAG	IEEE 802,11ax (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.76	±9.6
		IEEE 802,11ax (80 MHz, MCS3, 90pc duty cycle)	WLAN	8,55	±9,6
10722	AAC				±9.6
10723	AAC	IEEE 802,11ax (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	
10724	AAC	IEEE 802.11ax (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.90	=9.6
10725	AAC	IEEE 802.11ax (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10726	AAC	IEEE 802.11ax (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.72	±9.6
10727	AAC	IEEE 802.11ax (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.66	±9.6
10728	AAC	IEEE 802.11ax (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.65	±9,6
10729	AAC	IEEE 802.11ax (80 MHz, MCS10, 90pc duty cycle)	WLAN	8.64	±9.6
10729	AAC	IEEE 802.11ax (80 MHz, MCS10, 30pc duty cycle)	WLAN	8.67	+9.6
10731	AAC	IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	-9.6
10732	AAC	IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.46	±9.6
10733	AAC	IEEE 802.11ax (80 MHz, MGS2 99pc duty cycle)	WLAN	8.40	±9.6
10734	AAC	IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)	WLAN	8,25	±9.6
10735	AAC	IEEE 802,11ax (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.33	±9,6
10736		IEEE 802,11ax (80 MHz, MCS5, 99pc duty cycle)	WLAN	8.27	9,6
10737		(EEE 802,11ax (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.36	19.6
10738		IEEE 802:11ax (80 MHz, MCS7, 99oc duty cycle)	WLAN	8.42	±9,8
				8.29	
10739		IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)	WLAN		±9,
10740		IEEE 802,11ax (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.48	±9.
10741	AAC	IEEE 802.11ax (80 MHz, MCS10, 39pc duty cycle)	WLAN	8.40	±9.
10742		IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle)	WLAN	8.43	L9.
10743	AAC	IEEE 802,11ax (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.94	±9.
10744	AAC	IEEE 802,11ax (160 MHz, MGS1, 90pc duty cycle)	WLAN	9.16	±9,
10745		IEEE 802,11ax (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.93	±9.
10746		IEEE 802,11ax (160 MHz, MCS3, 90pc duty cycle)	WLAN	9.11	+9.
				9.04	
10747		IEEE 802.11ax (160 MHz, MCS4, 90pc duty cycle)	WLAN		+90
10748		IEEE 802,11ax (160 MHz, MCS5, 90pc duty cycle)	WLAN	8.93	±9,
10749		IEEE 802,11ax (160 MHz, MCS6, 90pc duty cycle)	WLAN	8,90	±9.
10.750	AAC	IEEE 802.11ax (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.79	±9.
10751	AAG	IEEE 802,11ax (160 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	9.
10752		IEEE 802,11ax (160 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.

Certificate No: EX-7823 Jul24

Page 18 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 24 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k =
0.753	AAC	IEEE 802,11ax (160 MHz, MCS10, 90pc duty cycle)	WLAN	9.00	=9.6
0.754	AAC	IEEE 802,11ax (160 MHz, MCS11, 90pc duty cycle)	WLAN	8.94	±9.6
0.755	AAC	IEEE 802,11ax (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.64	19.6
	AAC	IEEE 802,11ax (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.77	£9.6
0756	1000		WLAN	8.77	±9.6
0757	AAC	IEEE 802.11ax (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.69	±9.6
0.758	AAC	IEEE 802.11ax (160 MHz, MCS3, 99pc duty cycle)		8.58	±9.6
0759	AAC	IEEE 802,11ax (160 MHz, MCS4, 99pc duty cycle)	WLAN	7.15-5-1	
0760	AAC	IEEE 802.11ax (160 MHz, MCS5, 99pc duty cycle)	WLAN	8.49	±9,6
0761	AAC	IEEE 802,11ax (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.58	±9.6
10762	AAC	IEEE 802.11ax (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.49	±9,6
0763	AAC	IEEE 802.11ax (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.53	±9.6
0764	AAC	IEEE 802.11ax (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.54	±9.6
0.765	AAC	IEEE 802.11ax (160 MHz, MCS10, 99pc duty cycle)	WLAN	8.54	4.9.6
0766	AAC	IEEE 802.11ax (160 MHz, MCS11, 99pc duty cycle)	WLAN	8.51	+9.6
	AAG	5G NR (CP-OFDM, 1 RB, SMHz, QPSK, 15kHz)	5G NR FR1 TDD	7.99	9.6
10767			5G NR FR1 TDD	8.01	+9.6
10768	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)		.561.00.1	-0.0
10769	AAD	5G NR (CP-OFDM, 1 RB, 15MHz, QPSK, 15kHz)	5G NR FR1 TDD	8,01	±9.6
10770	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10771	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8:02	±9.6
10772	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.23	±9,6
10773	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.03	±9.6
10774	AAE	5G NR (CP-OFDM, 1 RB, 50MHz, QPSK, 15kHz)	5G NR FR1 TDD	8.02	±9,6
10775	AAF	5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10776	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8,30	+9.6
	AAC	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	+9.6
10777			5G NR FR1 TDD	8.34	+9.6
10778	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)		8.42	
10779	AAC	5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	74,71.0	+9.6
10780	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	19.6
10781	AAF	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	+9.6
10782	AAE	5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8,43	±9.6
10783	AAG	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	=9.6
10784	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	50 NR FR1 TDD	8.29	=9.6
10785	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FRI TDD	8.40	±9.6
10786	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.35	±9.6
	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15kHz)	5G NR FR1 TDD	8,44	+9.6
10787			5G NR FR1 TDD	8.39	
10.788	AAE	5G NR (CP-OFDM, 100% RB. 30 MHz, QPSK, 15 kHz)			±9.6
10789	AAF	5G NR (CP-OFDM, 100% RB. 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.37	±9.6
10790		5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	=9.6
10791	AAG	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.83	±9.6
10792	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7,92	19.6
10793	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.95	+9,6
10794	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	19.6
10795		5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.84	±9.6
10796		5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
-	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.01	±9.6
10797					
10798		5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7,89	±9.6
10799		5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		+9.6
10801		5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10802		5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.87	±9.6
10803		5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7,93	±9,6
10805	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10806	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.37	1.93
10809		5G NR (CP-OFDM: 50% RB; 30 MHz, QPSK; 30 kHz)	5G NR FR1 TDD	8.34	49.6
10810		5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.8
10.812		5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FRI TOD		±9.0
10817		5G NR (CP-OFDM, 100% RB, 5MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.
			SG NR FR1 TDD		±9.6
10818		5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)			
10.819		5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.6
10820		5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		=93
10821	AAD	5G NR (CP-OFDM, 100% RB, 25MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9,0
10822	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8,41	±9.
10823	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.1
10824		5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		193
10825		5G NR (CP-OFDM, 100% RB, 60 MHz, OPSK, 30 kHz)	SG NR FR1 TDD		1.9.1
10827		5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 KHz)	5G NR FRI TDD		±9.0
					±9.1
10828	AAE	5G NR (CP-OFDM, 100% RB. 90 MHz, QPSK, 30 kHz)	5G.NR FR1 TDD	8.43	- 2

Certificate No: EX-7823 Jul24

Page 19 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

所非另有說明・此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 25 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k =
10829	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.40	19.6
0830	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.63	±9.6
0.831	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.73	±9.6
0832	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.74	+9.6
0833	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, OPSK, 50 kHz)	5G NR FR1 TDD	7.70	19.6
8834	AAF	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7,75	±9.6
0835	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
0836	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.66	±9.6
0837	AAF	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.68	±9.6
0839	AAF	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7,70	±9.6
10840	AAE	5G NR (CP-OFDM, 1 RB, 90MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.67	±9.6
			5G NR FR1 TDD	7.71	+9.6
10841	AAF	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.49	19.6
10843	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 60 kHz)		8.49	±9.6
10844	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD		
10846	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10854	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10855	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8,36	±9,6
10856	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9,6
10857	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8,35	±9,6
10858	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8,36	=9.6
10859	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	+9.6
10860	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10861	AAF	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.40	±9.6
10863	AAF	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10864	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, OPSK, 60 kHz)	5G NR FR1 TDD	8.37	=9.6
10865	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8,41	±9.6
10866	AAF	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9,6
10.868	AAF	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.89	±9.6
10869	AAE	5G NR (DFTs-OFDM, 100% RB, 100 MHz, QFSK, 30 KHz)	5G NR FR2 TDD	5.75	±9.6
0,000			5G NR FR2 TDD	5.86	±9.6
10870	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)		5,75	
10871	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD		±9.8
10872	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.52	±9.6
10873	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6,61	±9.€
10874	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	+9.6
10875	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10876	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.39	±9.6
10877	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	7.95	±9.6
10878	AAE	5G NR (CP-OFDM, 100% RB. 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8,41	±9.6
10879	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8,12	±9,6
10880	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 64OAM, 120 kHz)	5G NR FR2 TDD	8.38	+9.6
10881	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TD0	5.75	±9.6
10882	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.96	±9,6
10883	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.57	±9.6
10884	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.53	±9.8
10885		5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.8
10886		5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 KHz)	5G NR FR2 TDD	6.65	+9.6
				7,78	
10887		5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.35	±9.6
10888		5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD		±9,1
10889		5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.02	±9.0
10890		5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.40	±9,1
10891		5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.13	±9.0
10892		5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD		±9.
10897		5G NR (DFT/s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.
10898	AAC	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9,
10.899	AAB	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.
10900	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.
10901		5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.
10902		5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.
10903		5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.
10904		5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.
10905			5G NR FR1 TDD		1-9.
10905			5G NR FR1 TDD		±9.
-		5G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)			
10907		5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.
10908		5G NR (DFTs-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		=9.
10909		5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		±9.
10910	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	+9.

Certificate No: EX-7823 Jul24

Page 20 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 26 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k = 2
10911	AAB	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5,93	±9.6
10912	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5,84	±9.6
0913	AAD	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
0914	AAC	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 KHz)	5G NR FR1 TDD	5.85	19.6
0915	AAD	5G NR (DFT-s-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6
0916	AAD	5G NR (DFT-s-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
0917	AAD	5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9,6
0918	AAE	5G NR (DFT-s-OFDM, 100% RB, 5MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
0919	AAC	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
0920	AAB	5G NR (DFT-s-OFDM, 100% RB, 15MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
0921	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
0922	AAB	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.82	±9.6
0923	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
0924	AAD	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.B4	±9.6
0925	AAC	5G NR (DFT-s-OFDM, 100% RB, 50MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.95	±9.6
0926	AAD	5G NR (DET-s-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9,6
0927	AAD	5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	1:9.6
0928	AAD	5G NR (DFT-s-OFDM, 1 RB, 5MHz, QPSK, 15kHz)	5G NR FR1 FDD	5.52	±9.6
0929	AAD	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9,6
0930	AAC	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
0931	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	=9.6
10932	AAC	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10933	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9,6
10934	AAC-	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10935	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10936	AAD	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10937	AAD	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.77	±9.6
10938	AAC	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10939	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.82	+9.6
10940	AAC	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.89	±9.6
10941	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10942	AAC	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10943	AAD	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.95	±9.6
10944	AAD	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.81	±9,6
10945	AAD	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10946	AAC	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	19.6
10947	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.€
10948	AAC	5G NR (DFT-s-OFDM, 100% RB, 25 MHz. QPSK, 15 kHz)	5G NR FR1 FDD	5,94	±9.8
10949	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5,87	±9.6
10950	AAC	5G NR (DFT-s-OFDM, 100% RB, 40 MHz. QPSK, 15 kHz)	5G NR FR1 FDD	5,94	±9,6
10951	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.92	±9,6
10952	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.25	±9.6
10953	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-OAM, 15 kHz)	5G NR FR1 FDD	8.15	±9.6
10954	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.23	+9.6
10955	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.42	±9.6
10956	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.14	±9.f
10957	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.31	±9.6
10958	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.61	±9.6
10959	AAA	5G NR DL (CP-OFDM, TM 8.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.33	= 9.6
10960	AAE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.32	=9.6
10961	AAC	5G NR DL (CP-OFDM, TM 3,1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD		±9.6
10962	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD		±9.8
10963	AAC	5G NR DL (CP-OFDM: TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD		±9.6
10964	AVE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD		王9.
10965	AAC	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD		1.9.
10966	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD		=9,
10967	AAC	5G NR DI, (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD		±9.
10968	AAD	5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD		±9,
10972		5G NR (CP-OFDM: 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD		±9.0
10973		5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD		+9.
10974	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)	5G NR FR1 TDD		±9.
10978		ULLA BDR	ULLA	1.16	±9,
10979		ULLA HDR4	ULLA	8,58	±9.
10980	AAA	ULLA HDR8	ULLA	10.32	±9.
10981	AAA	ULLA HDRp4	ULLA	3.19	±9.
10982	AAA	ULLA HDRp8	ULLA	3,43	±9.

Certificate No: EX-7823 Jul24

Page 21 of 22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

Onless otherwise stated the results shown in this test report reter only to the sample(s) leader and such sample(s) leader and sample(s) leader and such sample(s) leader and such sample(s) leader and such sample(s) leader and sample(s) le Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 27 of 27

July 31, 2024 EX3DV4 - SN:7823

UID	Rev	Communication System Name	Group	PAR (dB)	UncE k = 2
10983	AAC	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.31	19.6
10984	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.42	±9.6
10985	AAG	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.54	±9.6
10986	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 KHz)	5G NR FR1 TDD	9.50	±9.6
10987	AAC	5G NR DL (CP-OFDM, TM 3.1, 60 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.53	±9.6
10988	AAB	5G NR DL (CP-OFDM, TM 3.1, 70 MHz, 64-QAM, 30 kHz)	5G NR FRI TDD	9.38	: 9.6
10989	AAC	5G NR DL (CP-OFDM, TM 3.1, 80 MHz, 64-QAM, 30 kHz)	5G NR FRI TDD	9.33	±9.6
10990	AAB	5G NR DL (CP-OFDM, TM 3.1, 90 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.52	±9.6
11003	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	10.24	±9.6
11004	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	10.73	±9.6
11005	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.70	±9,6
11006	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8,55	±9.6
11007	AAA	5G NR DL (CP-OFDM, TM 3.1, 48 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8,46	=9,6
11008	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.51	±9.6
11009	AAA	5G NR DL (CP-OFDM, TM 3,1, 25 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8,76	±9.6
11010	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.95	±9.6
11011	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5g NR FR1 FDD	8,96	±9.6
11012	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.68	-9.6
11013	AAB	IEEE 802,11be (320 MHz, MCS1, 99pc duty cycle)	WLAN	8,47	±9.6
11014	AAB	IEEE 802,11be (320 MHz, MCS2, 99pc duty cycle)	WLAN	B:45	19.6
11015	AAB	IEEE 802,11be (320 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
11016	AAB	IEEE 802,11be (320 MHz, MCS4, 99pc duty cycle)	WLAN	8.44	±9.6
11017	AAB	IEEE 802,11be (320 MHz, MCS5, 99pc duty cycle)	WLAN	8.41	±9.6
11018	AAB	IEEE 802.11be (320 MHz, MCS6, 99pc duty cycle)	WLAN	8.40	±9.6
11019	AAB	IEEE 802.11be (320 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
11020	AAB	IEEE 802.11be (320 MHz, MCS8, 99pc duty cycle)	WLAN	8.27	=9.6
11021	AAB	IEEE 802,11be (320 MHz, MCS9, 99pc duty cycle)	WLAN	8.46	+9.6
11022	AAB	(EEE 802.11be (320 MHz, MCS10, 99pc duty cycle)	WLAN	8.36	±9.6
11023	AAB	IEEE 802.11be (320 MHz, MCS11, 99pc duty cycle)	WLAN	8.09	±9.6
11024	AAB	IEEE 802,11be (320 MHz, MCS12, 99pc duty cycle)	WLAN	8.42	±9,6
11 025	AAB	IEEE 802.11be (320 MHz, MCS13, 99pc duty cycle)	WLAN	8.37	±9.6
11026	AAB	IEEE 802.11be (320 MHz, MCS0, 99pc duty cycle)	WLAN	8.39	9.6

E Uncertainty is determined using the max, deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Certificate No: EX-7823_Jul24

Page 22 of 22

- End of report -

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。 This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.