

Power measurements for
B8QACSCCT1
2 button transmitter

Scan /Div Mhz	Res. Bandwidth KHz	DUT Frequency (Mhz)	Meter Frequency (Mhz)	Meter Reading (dBm)	Antenna Factor (dB)	Coax Factor (dB)	Amplifier Gain (dB)	Measurement Distance (Meters)	Duty Cycle Correction (dB)	3 Meter Limit (uV/M)	Field Strength (uV/M)	Delta Limit (dB)
0.5	100	390	390	-24.6	21	4	26	3	-10.7	9170	3,427.68	-8.55
0.5	100	390	780	-46.3	27	5.8	28	3	-10.7	917	549.54	-4.45
0.5	1000	390	1170	-45.8	23.7	7.9	36	3	-10.7	500	201.84	-7.88
0.5	1000	390	1560	-53.4	25	9.42	37.4	3	-10.7	500	99.08	-14.06
0.5	1000	390	1950	-60.2	27.3	10.78	37.3	3	-10.7	917	69.82	-22.37
0.5	1000	390	2340	-66.4	28	12	35.4	3	-10.7	500	53.09	-19.48
0.5	1000	390	2730	-66	29.5	13.2	35.5	3	-10.7	500	74.99	-16.48
0.5	1000	390	3120	-66.6	31.29	14.3	35.6	3	-10.7	917	96.49	-19.56
0.5	1000	390	3510	-67.1	31.4	15.4	35.6	3	-10.7	917	104.71	-18.85
0.5	1000	390	3900	-67.6	32.85	16.4	35.4	3	-10.7	500	134.12	-11.43