

RADIO TEST REPORT


The device described below is tested by Dongguan Nore Testing Center Co., Ltd. to determine the maximum emission levels emanating from the device, the severe levels which the device can endure and E.U.T.'s performance criterion. The test results, data evaluation, test procedures, and equipment of configurations shown in this report were made in accordance with the procedures in ANSI C63.10(2013).

Applicant : DONGGUAN TOGRAN ELECTRONICS TECHNOLOGY CO.,LTD.
Address : 262 shidan Rd., 3rd industrial Area, Juzhou, Shijie Town, Dongguan city, China
Manufacturer /Factory : DONGGUAN TOGRAN ELECTRONICS TECHNOLOGY CO.,LTD.
Address : 262 shidan Rd., 3rd industrial Area, Juzhou, Shijie Town, Dongguan city, China
E.U.T. : Wireless Dongle
Brand Name : Togran
Model No. : TM173G-Dongle
FCC ID : 2AGLG-TM173GDONGLE
Measurement Standard : FCC PART 15.249: 2017
Date of Receiver : October 31, 2018
Date of Test : October 31, 2018 to November 15, 2018
Date of Report : November 15, 2018

This Test Report is Issued Under the Authority of :

Prepared by

Approved & Authorized Signer


-Rose Hu / Engineer


Lori Fan / Authorized Signatory



This test report is for the customer shown above and their specific product only. This report applies to above tested sample only and shall not be reproduced in part without written approval of Dongguan Nore Testing Center Co., Ltd.

Table of Contents

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	4
1.2 RELATED SUBMITTAL(S) / GRANT (S)	6
1.3 TEST METHODOLOGY	6
1.4 EQUIPMENT MODIFICATIONS	6
1.5 SUPPORT DEVICE	6
1.6 TEST FACILITY AND LOCATION	7
1.7 SUMMARY OF TEST RESULTS	8
2. SYSTEM TEST CONFIGURATION	9
2.1 EUT CONFIGURATION	9
2.2 SPECIAL ACCESSORIES	9
2.3 DESCRIPTION OF TEST MODES	9
2.4 EUT EXERCISE	9
3. CONDUCTED EMISSIONS TEST	10
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	10
3.2 TEST CONDITION	10
3.3 MEASUREMENT RESULTS	10
4. RADIATED EMISSION TEST	13
4.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
4.2 MEASUREMENT PROCEDURE	14
4.3 LIMIT	15
4.4 MEASUREMENT RESULTS	16
5. 20DB BANDWIDTH	20
5.1 MEASUREMENT PROCEDURE	20
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	20
5.3 MEASUREMENT RESULTS	20
6. BAND EDGE	23
6.1 MEASUREMENT PROCEDURE	23
6.2 LIMIT	23
6.3 MEASUREMENT RESULTS	23
7. ANTENNA REQUIREMENT	24
7.1 MEASUREMENT PROCEDURE	26
7.2 MEASUREMENT RESULTS	26
8. TEST EQUIPMENT LIST	27

Revision History of This Test Report

Report Number	Description	Issued Date
NTC1810334FV00	Initial Issue	2018-11-15

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

Product Name	: Wireless Dongle
Main model number	: TM173G-Dongle
Additional Model number	: N/A
Brand Name	: Togran
Power Supply	: DC 5V come from PC
Adapter	: N/A
Test voltage	: AC 120V 60Hz PC input
Model Difference Description	: N/A
Hardware version	: A1
Software version	: V01
Note	: N/A
Remark	: N/A

Technical Specification:

2.4G Function:

Frequency Range	: 2403~2480MHz
Modulation Type	: GFSK
Number of Channel	: 16
Antenna Type	: PCB
Antenna Gain	: 0 dBi (Declaration by manufacturer)

Channel List

Channel	Frequency MHz	Channel	Frequency MHz
1	2403	9	2414
2	2426	10	2436
3	2441	11	2459
4	2463	12	2473
5	2407	13	2419
6	2422	14	2439
7	2445	15	2453
8	2466	16	2480

Note: The Lowest, middle, and the Highest frequency of channel were selected to perform the test. The frequency selected see below:

The Lowest frequency: 2403MHz

The middle frequency: 2441MHz

The Highest frequency: 2480MHz

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: 2AGLG-TM173GDONGLE filing to comply with Section 15.249 of the FCC Part 15 (2017), Subpart C Rule.

1.3 Test Methodology

The radiated emission measurement was performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

Monitor	:	Manufacturer: LENOVO M/N: L2061wD S/N: 3M04769B1102083
PC	:	P/N: QG570PA#AB2 Power Cord: 1.8m Unshielded, with core CE, FCC: DOC
Notebook	:	Manufacturer: IBM Model: 1834 P/N: 13N5615
Adapter (For Notebook)	:	Manufacturer: Huntkey Model: HKA09019047-6D I/P: AC 100-240V 50-60Hz, 1.5A O/P: DC 19V 4.74A
Printer	:	Manufacturer: Lenovo M/N: 3518
Keyboard	:	Manufacturer: DELL M/N: KB216d CE, FCC: DOC, IC, VCCI, RCM
Wireless Mouse	:	Manufacturer: TOGRAN M/N: TM173G-QI

1.6 Test Facility and Location

Site Description

EMC Lab : Listed by CNAS, August 13, 2018
The certificate is valid until August 13, 2024
The Laboratory has been assessed and proved to
be in compliance with CNAS/CL01
The Certificate Registration Number is L5795.

Listed by A2LA, November 01, 2017
The certificate is valid until December 31, 2019
The Laboratory has been assessed and proved to
be in compliance with ISO17025
The Certificate Registration Number is 4429.01

Listed by FCC, November 06, 2017
The Designation Number is CN1214
Test Firm Registration Number: 907417

Listed by Industry Canada, June 08, 2017
The Certificate Registration Number. Is 46405-9743
Name of Firm : Dongguan Nore Testing Center Co., Ltd.
(Dongguan NTC Co., Ltd.)

Site Location : Building D, Gaosheng Science & Technology Park,
Zhouxi Longxi Road, Nancheng District, Dongguan
City, Guangdong Province, China

1.7 Summary of Test Results

FCC Rules	Description Of Test	Uncertainty	Result
§15.207(a)	AC Power Conducted Emission	±1.06dB	Compliant
§15.249(a)/ 15.209	Radiated Emissions	±3.70dB	Compliant
§15.249(d)/ 15.205	Band Edge	±1.70dB	Compliant
§15.215(c)	20dB Bandwidth	±1.42 x10 ⁻⁴ %	Compliant
§15.203	Antenna Requirement	---	Compliant

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.


2.3 Description of test modes

The EUT has been tested under operating condition. The Lowest, middle and highest frequencies were chosen for testing.

2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

3.1 Test SET-UP (Block Diagram of Configuration)





Dongguan NTC Co., Ltd.
Tel:+86-769-22022444 Fax:+86-769-22022799
Web: [Http://www.ntc-c.com](http://www.ntc-c.com)


Conducted Emission Measurement

File :TM173G-Dongle

Data :#5

Date: 2018-11-7

Time: 12:24:57



Site

Phase: **L1**

Temperature: 26

Limit: FCC PART 15_Class B_QP

Power: AC120V/60Hz

Humidity: 50 %

EUT: Wireless Dongle

M/N: TM173G-Dongle

Mode: TX Mode

Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.2467	30.79	10.61	41.40	61.87	-20.47	QP	
2	0.2467	17.19	10.61	27.80	51.87	-24.07	AVG	
3	0.4580	30.28	10.62	40.90	56.73	-15.83	QP	
4	0.4580	18.28	10.62	28.90	46.73	-17.83	AVG	
5	0.8336	26.96	10.64	37.60	56.00	-18.40	QP	
6	0.8336	19.26	10.64	29.90	46.00	-16.10	AVG	
7	1.0220	27.05	10.65	37.70	56.00	-18.30	QP	
8 *	1.0220	20.75	10.65	31.40	46.00	-14.60	AVG	
9	3.2418	27.45	10.65	38.10	56.00	-17.90	QP	
10	3.2418	17.65	10.65	28.30	46.00	-17.70	AVG	
11	17.9859	31.33	10.67	42.00	60.00	-18.00	QP	
12	17.9859	20.13	10.67	30.80	50.00	-19.20	AVG	



Dongguan NTC Co., Ltd.
Tel:+86-769-22022444 Fax:+86-769-22022799
Web: [Http://www.ntc-c.com](http://www.ntc-c.com)


Conducted Emission Measurement

File : TM173G-Dongle

Data : #6

Date: 2018-11-7

Time: 12:33:37



Site

Phase: **N**

Temperature: 26

Limit: FCC PART 15_Class B_QP

Power: AC120V/60Hz

Humidity: 50 %

EUT: Wireless Dongle

M/N: TM173G-Dongle

Mode: TX Mode


Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2787	29.69	10.61	40.30	60.85	-20.55	QP	
2		0.2787	22.39	10.61	33.00	50.85	-17.85	AVG	
3	*	0.4660	32.28	10.62	42.90	56.58	-13.68	QP	
4		0.4660	20.98	10.62	31.60	46.58	-14.98	AVG	
5		1.0300	30.55	10.65	41.20	56.00	-14.80	QP	
6		1.0300	20.45	10.65	31.10	46.00	-14.90	AVG	
7		2.1459	30.25	10.65	40.90	56.00	-15.10	QP	
8		2.1459	20.85	10.65	31.50	46.00	-14.50	AVG	
9		2.8620	28.65	10.65	39.30	56.00	-16.70	QP	
10		2.8620	17.75	10.65	28.40	46.00	-17.60	AVG	
11		16.8379	28.43	10.67	39.10	60.00	-20.90	QP	
12		16.8379	14.43	10.67	25.10	50.00	-24.90	AVG	


4. Radiated Emission Test

4.1 Test SET-UP (Block Diagram of Configuration)

4.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz



4.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



4.2 Measurement Procedure

- Blow 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- For the radiated emission test above 1GHz:
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Level	Resolution Bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

4.3 Limit

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)	
		$\mu\text{V/m}$	
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	
88 ~ 216	3	150	
216 ~ 960	3	200	
Above 960	3	500	
Frequency range MHz	Distance Meters	Field Strengths Limit (15.249)	
		mV/m (Field strength of fundamental)	$\mu\text{V/m}$ (Field strength of Harmonics)
902 ~ 928	3	50	500
2400 ~ 2483.5	3	50	500
5725 ~ 5875	3	50	500
24000 ~ 2425000	3	250	2500

- Remark: (1) Emission level (dB) μV = 20 log Emission level $\mu\text{V/m}$
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
(4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
(5) Sample of data calculate:
Level=Reading + Factor; Margin= Level-Limit
Factor=CF+AF+AG
Where CF=Cable attenuation factor in dB
AF= Antenna factor in dB
AG=Amplifier Gain in dB

4.4 Measurement Results

PASS

Please refer to following the test plots of the worst case: Low channel.



Dongguan NTC Co., Ltd.
 Tel:+86-769-22022444 Fax:+86-769-22022799
 Web: [Http://www.ntc-c.com](http://www.ntc-c.com)


Radiated Emission Measurement

File : TM173G-Dongle

Data : #1

Date: 2018-11-6

Time: 10:10:11



Site: 3m Chamber

Polarization: **Horizontal**

Temperature: 26

Limit: FCC Part 15_ClassB_3M

Power: AC 120V/60Hz

Humidity: 47 %

EUT: Wireless Dongle

Distance: 3m

M/N: TM173G-Dongle

Mode: TX

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		206.5399	35.52	-13.32	22.20	43.50	-21.30	QP		
2		358.8299	24.74	-9.14	15.60	46.00	-30.40	QP		
3		399.5700	31.01	-9.11	21.90	46.00	-24.10	QP		
4		510.1500	25.25	-6.75	18.50	46.00	-27.50	QP		
5		598.4200	26.83	-5.03	21.80	46.00	-24.20	QP		
6	*	898.1500	28.62	-1.22	27.40	46.00	-18.60	QP		

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.



Dongguan NTC Co., Ltd.
Tel: +86-769-22022444 Fax: +86-769-22022799
Web: [Http://www.ntc-c.com](http://www.ntc-c.com)

Radiated Emission Measurement

File : TM173G-Dongle

Data : #2

Date: 2018-11-6

Time: 10:18:36

80.0 dBuV/m



Site: 3m Chamber

Polarization: **Vertical**

Temperature: 26

Limit: FCC Part 15_ClassB_3M

Power: AC 120V/60Hz

Humidity: 47 %

EUT: Wireless Dongle

Distance: 3m

M/N: TM173G-Dongle

Mode: TX

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		106.6300	34.22	-16.02	18.20	43.50	-25.30	QP		
2		142.5200	33.40	-18.60	14.80	43.50	-28.70	QP		
3		211.3900	34.01	-16.21	17.80	43.50	-25.70	QP		
4		250.1900	30.89	-13.69	17.20	46.00	-28.80	QP		
5	*	389.8700	35.05	-11.15	23.90	46.00	-22.10	QP		
6		480.0800	28.31	-9.21	19.10	46.00	-26.90	QP		

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

Frequency Range: 1-25GHz
Test Result: PASS
Measured Distance: 3m
Test By: Sance

Test Date : November 13, 2018
Temperature : 21 °C
Humidity : 55 %

Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
Operation Mode: TX Mode (Low)										
2403	V	76.73	33.52	0.13	76.86	33.65	114.00	94.00	-37.14	-60.35
4806	V	59.52	32.03	6.32	65.84	38.35	74.00	54.00	-8.16	-15.65
7209	V	44.59	30.79	10.44	55.03	41.23	74.00	54.00	-18.97	-12.77

2403	H	85.67	33.42	0.13	85.80	33.55	114.00	94.00	-28.20	-60.45
4806	H	52.8	31.78	6.32	59.12	38.10	74.00	54.00	-14.88	-15.90
7209	H	46.22	30.71	10.44	56.66	41.15	74.00	54.00	-17.34	-12.85

Operation Mode: TX Mode (Mid)										
2441	V	84.79	33.12	0.24	85.03	33.36	114.00	94.00	-28.97	-60.64
4882	V	58.8	31.39	6.60	65.40	37.99	74.00	54.00	-8.60	-16.01
7323	V	52.2	31.23	10.55	62.75	41.78	74.00	54.00	-11.25	-12.22

2441	H	81.28	33.19	0.24	81.52	33.43	114.00	94.00	-32.48	-60.57
4882	H	54.32	31.11	6.60	60.92	37.71	74.00	54.00	-13.08	-16.29
7323	H	50.19	31.05	10.55	60.74	41.60	74.00	54.00	-13.26	-12.4

Operation Mode: TX Mode (High)										
2480	V	85.28	33.2	0.34	85.62	33.54	114.00	94.00	-28.38	-60.46
4960	V	51.63	30.88	6.89	58.52	37.77	74.00	54.00	-15.48	-16.23
7440	V	50.86	31.32	10.6	61.46	41.92	74.00	54.00	-12.54	-12.08

2480	H	82.5	33.28	0.34	82.84	33.62	114.00	94.00	-31.16	-60.38
4960	H	57.85	31.06	6.89	64.74	37.95	74.00	54.00	-9.26	-16.05
7440	H	47.33	31.47	10.6	57.93	42.07	74.00	54.00	-16.07	-11.93

- Note:** (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level + Factor
(3) Factor= Antenna Gain + Cable Loss – Amplifier Gain
(4) Data of measurement within this frequency range shown “ ---” in the table above means the reading of emissions are attenuated more than 10dB below the permissible limits.
(5) Measurement uncertainty : ± 3.7 dB.
(6) Horn antenna used for the emission over 1000MHz.
(7) Due to the highest Peak emission level below AVG limit, therefore, the AVG emission level is deemed to meet the requirements, no AVG result record.


5. 20dB Bandwidth

5.1 Measurement Procedure

The 20dB bandwidth of the emission was contained within the frequency band designated which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered, FCC Rule 15.215(c):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Results

Refer to attached data chart.

RBW:	30KHz	VBW:	100KHz
Spectrum Detector:	PK	Temperature :	22 °C
Test By:	Sance	Humidity :	54 %
Test Result:	PASS	Test Date :	November 12, 2018

Channel frequency (MHz)	20dB Down BW(kHz)
2403	1833
2441	1818
2480	1828



Highest Channel



6. Band Edge

6.1 Measurement Procedure

Same as Radiated Emission Test.

6.2 Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

6.3 Measurement Results


Operation Mode:	TX Mode	Test Date :	November 13, 2018
Temperature :	21 °C	Humidity :	55 %
Test Result:	PASS	Test By:	Sance
Measured Distance:	3m		

Freq. (MHz)	Ant.Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
2390.0	H	57.22	33.65	0.09	57.31	33.74	74.00	54.00	-16.69	-20.26
2390.0	V	64.85	32.66	0.09	64.94	32.75	74.00	54.00	-9.06	-21.25
2483.5	H	60.93	33.28	0.35	61.28	33.63	74.00	54.00	-12.72	-20.37
2483.5	V	50.91	33.38	0.35	51.26	33.73	74.00	54.00	-22.74	-20.27


Note: (1) Emission Level= Reading Level + Factor
 (2) Factor= Antenna Gain + Cable Loss – Amplifier Gain
 (3) Horn antenna used for the emission over 1000MHz.

Low channel

Horizontal




Vertical



High channel


Horizontal

120.0 dBuV/m



Vertical

120.0 dBuV/m



7. Antenna requirement

7.1 Measurement Procedure

According to of FCC part 15C section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.2 Measurement Results

The antenna is PCB antenna and no consideration of replacement, and the best case gain of the antenna is 0dBi. So, the antenna is consider meet the requirement.

8. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Characteristics	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	9KHz~7GHz	Mar. 14, 2018	Mar. 13, 2019
Antenna	Schwarzbeck	VULB9162	9162-010	30MHz~7GHz	Mar. 15, 2018	Mar. 14, 2019
Cable	Huber+Suhner	CBL2-NN-1M	22390001	9KHz~7GHz	Mar. 14, 2018	Mar. 13, 2019
Cable	Huber+Suhner	CIL02	N/A	9KHz~7GHz	Mar. 14, 2018	Mar. 13, 2019
RF Cable	Huber+Suhner	SF-104	MY16559/4	9KHz~25GHz	Apr. 25, 2018	Apr. 24, 2019
Power Amplifier	HP	HP 8447D	1145A00203	100KHz~1.3GHz	Mar. 14, 2018	Mar. 13, 2019
Horn Antenna	Schwarzbeck	BBHA9170	9170-242	15GHz~40GHz	Mar. 14, 2018	Mar. 13, 2019
Horn Antenna	Com-Power	AH-118	071078	1GHz~18GHz	Mar. 15, 2018	Mar. 14, 2019
RF Cable	Huber+Suhner	SF-104	N/A	9KHz~40GHz	Apr. 25, 2018	Apr. 24, 2019
Loop antenna	Daze	ZA30900A	0708	9KHz~30MHz	Apr. 25, 2018	Apr. 24, 2019
Spectrum Analyzer	Rohde & Schwarz	FSU26	200409/026	20Hz~26.5GHz	Apr. 25, 2018	Apr. 24, 2019
Spectrum Analyzer	Rohde & Schwarz	FSV40	101003	10Hz~40GHz	Apr. 06, 2018	Apr. 05, 2019
Pre-Amplifier	EMCI	EMC 184045	980102	18GHz~40GHz	Nov. 03, 2018	Nov. 02, 2019
Pre-Amplifier	Agilent	8449B	3008A02964	1GHz~26.5GHz	Apr. 25, 2018	Apr. 24, 2019
L.I.S.N.	Rohde & Schwarz	ENV 216	101317	9KHz~30MHz	Mar. 14, 2018	Mar. 13, 2019
Temporary antenna connector	TESCOM	SS402	N/A	9KHz-25GHz	N/A	N/A
Power Meter	Anritsu	ML2495A	1139001	100k-65GHz	Nov. 03, 2018	Nov. 02, 2019
Power Sensor	Anritsu	MA2411B	100345	300M-40GHz	Nov. 03, 2018	Nov. 02, 2019

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

---End---