



Report No.: TW2103437E File reference No.: 2021-04-27

Applicant: LEADER PREMIUMS LTD

Product: BLUETOOTH SPEAKER

Model No.: AE0151

Brand Name: N/A

Test Standards: FCC Part 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10 &FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: April 27, 2021

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: TW2103437E Page 2 of 46

Date: 2021-04-27



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Report No.: TW2103437E

Date: 2021-04-27



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment.	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT.	12
6.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit.	13
6.5	Test Result.	14
7.0	Band Edge	23
7.1	Test Method and Test Procedure.	23
7.2	Radiated Test Setup.	23
7.3	Configuration of the EUT.	23
7.4	EUT Operating Condition.	23
7.5	Band Edge Limit.	23
7.6	Band Edge Test Result.	24
8.0	Antenna Requirement	28
9.0	20dB bandwidth measurement.	29
10.0	FCC ID Label	38
11.0	Photo of Test Setup and EUT View	39

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2103437E Page 4 of 46

Date: 2021-04-27



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189 For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: LEADER PREMIUMS LTD

Address: 9/F., Hengfu Mansion B building, NO.858. Fuming Road, Ningbo, China

Telephone: -Fax: --

1.3 Description of EUT

Product: BLUETOOTH SPEAKER

Manufacturer: LEADER PREMIUMS LTD

Address: 9/F., Hengfu Mansion B building, NO.858. Fuming Road, Ningbo, China

Brand Name: N/A
Model Number: AE0151
Additional Model Name N/A

Hardware Version: Bluetooth-AE0151 V1.0

Software Version: 2021.02 V1.0 Serial No.: AE0151

Rating: DC5V, 1A or Built-in DC3.7V, 300mAh, 1.11Wh Li-ion battery

Modulation Type: GFSK, Pi/4D-QPSK, 8DPSK (Bluetooth)

Operation Frequency: 2402-2480MHz

Channel Separate: 1MHz Channel Number: 79

Antenna Designation PCB antenna with gain 1.2dBi Max (Get from the antenna specification

provided by the applicant)

1.4 Submitted Sample: 1 pc

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2103437E Page 5 of 46

Date: 2021-04-27



1.5 Test Duration

2021-03-29 to 2021-04-27

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty =6.0dB

Occupied Channel Bandwidth Uncertainty = 5%

Conducted Emissions Uncertainty =3.6dB

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 46

Report No.: TW2103437E

Date: 2021-04-27



2.0 Test Equipment							
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date		
ESPI Test Receiver	R&S	ESPI 3	100379	2020-06-23	2021-06-22		
LISN	R&S	EZH3-Z5	100294	2020-06-23	2021-06-22		
LISN	R&S	EZH3-Z5	100253	2020-06-23	2021-06-22		
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2020-06-23	2021-06-22		
Loop Antenna	EMCO	6507	00078608	2018-06-25	2021-06-24		
Spectrum	R&S	FSIQ26	100292	2020-06-23	2021-06-22		
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2020-06-23	2021-06-22		
Horn Antenna	R&S	BBHA 9120D	9120D-631	2018-07-09	2021-07-08		
Power meter	Anritsu	ML2487A	6K00003613	2020-06-23	2021-06-22		
Power sensor	Anritsu	MA2491A	32263	2020-06-23	2021-06-22		
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2018-07-04	2021-07-03		
9*6*6 Anechoic			N/A	2020-07-06	2021-07-05		
EMI Test Receiver	RS	ESVB	826156/011	2020-06-23	2021-06-22		
EMI Test Receiver	RS	ESH3	860904/006	2020-06-23	2021-06-22		
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2020-06-23	2021-06-22		
Spectrum	HP/Agilent	E4407B	MY50441392	2020-06-23	2021-06-22		
Spectrum	RS	FSP	1164.4391.38	2021-01-16	2022-01-15		
RF Cable	Zhengdi	ZT26-NJ-NJ-8M/FA		2020-06-23	2021-06-22		
RF Cable	Zhengdi	7m		2020-06-23	2021-06-22		
RF Switch	EM	EMSW18	060391	2020-06-23	2021-06-22		
Pre-Amplifier	Schwarebeck	BBV9743	#218	2020-06-23	2021-06-22		
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2020-06-23	2021-06-22		
LISN	SCHAFFNER	NNB42	00012	2021-01-06	2022-01-05		

2.2 Automation Test Software

For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

For Radiated Emissions

Name	Version		
EMI Test Software BL410-EV18.91	V18.905		
EMI Test Software BL410-EV18.806 High Frequency	V18.06		

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 7 of 46

Date: 2021-04-27



3.0 Technical Details

3.1 Summary of test results

Report No.: TW2103437E

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	PASS	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	PASS	Complies

3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249, ANSI C63.4:2014 and ANSI C63.10:2013

4.0 EUT Modification

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES


Report No.: TW2103437E

Date: 2021-04-27



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum from 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10 –2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

One channels are provided to the EUT

A. EUT

Device	Manufacturer	Model	FCC ID
BLUETOOTH SPEAKER	LEADER PREMIUMS LTD	AE0151	2APYY-AE0151

Report No.: TW2103437E Page 9 of 46

Date: 2021-04-27



B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	KEYU	KA23-0502000DEU	Input: 100-240V~, 50/60Hz, 0.35A;
			Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (dB μ V)			
(MHz)	Quasi-peak Level	Average Level		
$0.15 \sim 0.50$	66.0~56.0*	56.0~46.0*		
$0.50 \sim 5.00$	56.0	46.0		
5.00 ~ 30.00	60.0	50.0		

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The tighter limit shall apply at the transition frequencies

5.6 Test Results:

Pass

Report No.: TW2103437E

Date: 2021-04-27



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa


EUT set Condition: Charging and Communication by BT

Model: AE0151

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1578	20.76	9.78	30.54	65.58	-35.04	QP	Р
2	0.1578	6.30	9.78	16.08	55.58	-39.50	AVG	Р
3	0.6492	31.36	9.78	41.14	56.00	-14.86	QP	Р
4	0.6492	30.55	9.78	40.33	46.00	-5.67	AVG	Р
5	3.2379	27.41	9.85	37.26	56.00	-18.74	QP	Р
6	3.2379	24.52	9.85	34.37	46.00	-11.63	AVG	Р
7	4.5327	24.25	9.91	34.16	56.00	-21.84	QP	Р
8	4.5327	19.60	9.91	29.51	46.00	-16.49	AVG	Р
9	9.3375	22.34	10.13	32.47	60.00	-27.53	QP	Р
10	9.3375	17.59	10.13	27.72	50.00	-22.28	AVG	Р
11	18.5961	15.63	10.60	26.23	60.00	-33.77	QP	Р
12	18.5961	7.49	10.60	18.09	50.00	-31.91	AVG	Р

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2103437E

Date: 2021-04-27



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa


EUT set Condition: Charging and Communication by BT

Model: AE0151

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1578	20.50	9.78	30.28	65.58	-35.30	QP	Р
2	0.1578	8.39	9.78	18.17	55.58	-37.41	AVG	Р
3	0.6453	32.07	9.78	41.85	56.00	-14.15	QP	Р
4	0.6453	32.00	9.78	41.78	46.00	-4.22	AVG	Р
5	1.9401	31.02	9.80	40.82	56.00	-15.18	QP	Р
6	1.9401	30.05	9.80	39.85	46.00	-6.15	AVG	Р
7	3.2340	25.95	9.85	35.80	56.00	-20.20	QP	Р
8	3.2340	23.72	9.85	33.57	46.00	-12.43	AVG	Р
9	4.5288	23.28	9.91	33.19	56.00	-22.81	QP	Р
10	4.5288	18.94	9.91	28.85	46.00	-17.15	AVG	Р
11	8.7915	23.55	10.10	33.65	60.00	-26.35	QP	Р
12	8.7915	18.39	10.10	28.49	50.00	-21.51	AVG	Р

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2103437E Page 12 of 46

Date: 2021-04-27




6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz (Note: for Fundamental frequency radiated emission measurement, RBW=3MHz, VBW=10MHz). Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup

For radiated emissions from 9kHz to 30MHz




Page 13 of 46

Report No.: TW2103437E


Date: 2021-04-27



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition

 Same as section 5.4 of this report.

Report No.: TW2103437E Page 14 of 46

Date: 2021-04-27



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency	Field Strength of Fundamental (3m)			Field Strength of Harmonics (3m)		
(MHz)	mV/m	dBuV/m		uV/m	dBuV/m	
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note:

- 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK. For fundamental measurement, PK detector used.
- 6. Battery full charged during tests.
- 7. The three modulation modes of GFSK, Pi/4D-QPSK, and 8DPSK were tested. And only the worst case was recorded in the test report. GFSK was the worst case.

Report No.: TW2103437E Page 15 of 46

Date: 2021-04-27




6.5 Test result

A Fundamental & Harmonics Radiated Emission Data

Please refer to the following test plots for details: Low Channel-2402MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2402.500	88.73	-3.57	114.0	-25.27	Peak	246.00	100	Horizontal	Pass
2	4803.500	50.43	3.12	74.0	-23.57	Peak	286.00	100	Horizontal	Pass

Report No.: TW2103437E Page 16 of 46

Date: 2021-04-27



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2402.500	80.13	-3.57	114.0	-33.87	Peak	250.00	100	Vertical	Pass
2	4803.500	48.43	3.12	74.0	-25.57	Peak	275.00	100	Vertical	Pass


Report No.: TW2103437E Page 17 of 46

Date: 2021-04-27



Please refer to the following test plots for details: Middle Channel-2441MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2440.750	87.78	-3.57	114.0	-26.22	Peak	233.00	100	Horizontal	Pass
2	4880.250	52.53	3.20	74.0	-21.47	Peak	246.00	100	Horizontal	Pass

Report No.: TW2103437E Page 18 of 46

Date: 2021-04-27



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2440.750	81.62	-3.57	114.0	-32.38	Peak	234.00	100	Vertical	Pass
2	4880.250	49.16	3.20	74.0	-24.84	Peak	275.00	100	Vertical	Pass


Report No.: TW2103437E Page 19 of 46

Date: 2021-04-27



Please refer to the following test plots for details: High Channel-2480MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2479.750	89.39	-3.57	114.0	-24.61	Peak	246.00	100	Horizontal	Pass
2	4961.000	52.05	3.36	74.0	-21.95	Peak	250.00	100	Horizontal	Pass

Report No.: TW2103437E Page 20 of 46

Date: 2021-04-27



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2479.750	77.87	-3.57	114.0	-36.13	Peak	176.00	100	Vertical	Pass

Note: (2) Emission Level = Reading Level + Antenna Factor + Cable Loss-Amplifier

- (3) Margin=Emission-Limits
- (4) According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) For test purpose, keep EUT continuous transmitting
- (5) For emission above 18GHz and Below 30MHz, It is only the floor noise. No necessary to take down.
- (6) the measured PK value less than the AV limit.

Report No.: TW2103437E Page 21 of 46

Date: 2021-04-27




B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	143.947	34.15	-17.10	43.5	-9.35	Peak	179.00	100	Horizontal	Pass
2	166.978	31.89	-16.08	43.5	-11.61	Peak	27.00	100	Horizontal	Pass
3	231.952	33.16	-12.56	46.0	-12.84	Peak	63.00	100	Horizontal	Pass
4	299.835	40.95	-11.03	46.0	-5.05	Peak	121.00	100	Horizontal	Pass
5	341.777	42.47	-9.71	46.0	-3.53	Peak	121.00	100	Horizontal	Pass
6	479.968	23.10	-7.40	46.0	-22.90	Peak	308.00	100	Horizontal	Pass

Report No.: TW2103437E Page 22 of 46

Date: 2021-04-27




Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	36.788	35.48	-13.31	40.0	-4.52	Peak	221.00	100	Vertical	Pass
2	50.850	33.84	-11.40	40.0	-6.16	Peak	360.00	100	Vertical	Pass
3	84.791	24.81	-16.57	40.0	-15.19	Peak	280.00	100	Vertical	Pass
4	140.552	33.70	-17.24	43.5	-9.80	Peak	91.00	100	Vertical	Pass
5	226.376	32.00	-12.81	46.0	-14.00	Peak	109.00	100	Vertical	Pass
6	340.807	36.93	-9.76	46.0	-9.07	Peak	53.00	100	Vertical	Pass

Date: 2021-04-27




7. Band Edge

7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) Set Spectrum as RBW=1MHz, VBW=3MHz and Peak detector used for PK value. RBW=1MHz, VBW=10Hz and Peak detector used for AV value.
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

7.3 Configuration of The EUT

Same as section 5.3 of this report

7.4 EUT Operating Condition

Same as section 5.4 of this report.

7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No.: TW2103437E Page 24 of 46

Date: 2021-04-27



7.6 Test Result

Product:	BLUETOOTH SPEAKER	Polarity	Horizontal
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2399.315	50.93	-3.56	74.0	-23.07	Peak	237.00	100	Horizontal	Pass
2	2389.405	44.91	-3.53	74.0	-29.09	Peak	237.00	100	Horizontal	Pass

Report No.: TW2103437E Page 25 of 46

Date: 2021-04-27

2390.935

39.64

-3.53

74.0



Product:	В	LUETO	OTH SPEA	KER	Detect	or		Vertical	
Mode		Keeping	g Transmitti	ng	Test Volt	tage		DC3.7V	
emperature		24	l deg. C,		Humidi	ity		56% RH	
est Result:			Pass						
15C Class B 1GHz-18GH:	: -2								
90-									
80-								\wedge	
70-									
60-							M1	/	
50-						M2	7		
40-	والمساعدين المساعدين المساعدين	بالمتعدد والمعاددات	handra is being a below by	A STATE OF THE PARTY OF THE PAR	Maadalalahaan qooqoolii aaabaaa ka sa		Walder Waller		Market Krayer Ma
30-	and Language and have to the fall of the second of the fall of	And heart of a distribution of	addition of a state of a	- ''					
20-									
20-									
				Frequency (MH:	2)				2410
0.0-	Results	Factor	Limit	Frequency (MH:	z) Detector	Table (o)	Height	ANT	2410 Verdic
0.0-	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)			Table (o)	Height (cm)	ANT	_
	Mode emperature eest Result: 15C Class B 1GHz-18GHz +2- 90- 60- 50- 40-	Mode emperature est Result: 15C Class B 1GHz-18GHz -2 +2- 90- 80- 70- 60- 50- 40- 40- 40- 40- 40- 40- 4	Mode Keeping emperature 24 est Result: 15C Class B 1GHz-18GHz -2 1-2 90 60 60 40	Mode Keeping Transmitti emperature 24 deg. C, est Result: Pass 15C Class B 1GHz-18GHz -2 170- 170- 170- 170- 170- 170- 170- 170	Mode Keeping Transmitting emperature 24 deg. C, lest Result: Pass 15C Class B 1GHz-18GHz -2 150- 150- 150- 150- 150- 150- 150- 150	Mode Keeping Transmitting Test Voltemperature 24 deg. C, Humiditest Result: Pass 15C Class B 1GHz-18GHz -2 170- 180- 180- 180- 180- 180- 180- 180- 18	Mode Keeping Transmitting Test Voltage emperature 24 deg. C, Humidity est Result: Pass 15C Class B 1GHz-18GHz -2 170- 180- 180- 180- 180- 180- 180- 180- 18	Mode Keeping Transmitting Test Voltage emperature 24 deg. C, Humidity est Result: Pass 15C Class B 1GHz-18GHz -2 170- 60- 50- 60- 60- 60- 60- 60- 60- 60- 60- 60- 6	Mode Keeping Transmitting Test Voltage DC3.7V emperature 24 deg. C, Humidity 56% RH est Result: Pass 15C Class B 1GHz-18GHz -2 +- 2 60

-34.36

Peak

220.00

100

Vertical

Pass

Page 26 of 46 Report No.: TW2103437E



P	roduct:	BI	LUETOC	TH SPEAK	ER	Polarit	.y	Но	rizontal	
	Mode		Keeping	Transmittin	g	Test Volt	age	D	C3.7V	
Ten		24	deg. C,		Humidi	ity	56% RH			
Tes										
CC Part 15	C Class B 1GHz-18GHz	-2								
90-										
80-					-/-					
70-										
60-										
50-										
40-	In the property and their and their	the same and the little same		and the same of the same		-	instituted the original	ntales publicate the second	ni alon ilikuwa ilipi ili	din din di
30-										
50										
20-										
10-										
0.0-					Frequency (MH	2483.5 z)				250
0.0-		Results	Factor	Limit	Frequency (MH		Table (o)	Height	ANT	2500
0.0 - 24	460	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	1	z)	Table (o)	Height (cm)	ANT	I

Report No.: TW2103437E Page 27 of 46

Date: 2021-04-27



Pı	roduct:	B !	LUETO	OTH SPEA	KER	Detec	tor	,	Vertical	
]	Mode		Keeping	g Transmitti	ng	Test Vo	ltage]	DC3.7V	
Ten	nperature		24	l deg. C,		Humio	dity	5	56% RH	
Tes	st Result:			Pass						
CC Part 150	C Class B 1GHz-18GHz	: -2								
90 - 80 -										
70-										
					/ \					
60-										
		ir 4 1 tirible (41 tiris)	مارين المناب	المعادية المالية المالية المالية			o las sa a mel i dessi sas din		المام المام المام	John Dalling
	And with the state of the state	المعارض والمعارض والم	hiladaje aj vojes adalitik	المتعادية فالمتعادية والمتعادية و		Hart date land land	n levy a nak do do de la garal la	isa-delendrichen der Albertike	hadhariani babayahdahad	
(w/\ngg) 40-	Autodopo artikaki di Antopologia arti	handardakilateneensekitakistoo	ident disk op e forsjon besking	وعالية والمطابق والمراجع والم		Hartistingly	icheria de palde de Marcella	iva-plaba, desconder del Albertila	hat having in the stay of the blad	44.65.44.11.50
(W/Anggr) 40-4	· · · · · · · · · · · · · · · · · · ·	tendentelijkenserverskijdelijken	ishiringkaya, kasambadan	ind distribution while distributions with		Haridalahlah	isher, said Addendiy	ina-dados, el sencido de Albertida	helden von den de	of the American Life American
30 20 10		tendulati til deneman kit dilatina	identeles en la constante de l	reddinadedd ywynoled og bynnaeth	Frequency (MH:	2483.5	tikery kalik Alleberghy	ira-padeba, d _{ala} an qabii _t abbaqiibba	dest landonista de adopuelo de destrib	2500
30- 20- 10- 244		Results	Factor	Limit	Frequency (MH:	2483.5	Table (o)	Height	ANT	
(W/Ango) 40 - 40 - 40 - 40 - 40 - 40 - 40 - 40	60				T	2483.5 z)				2500

Note: 1. The PK emission level less than the AV limit. No necessary to record the AV emission level.

- 2. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 3. The three modulation modes of GFSK, Pi/4D-QPSK, and 8DPSK were tested. And only the worst case was recorded in the test report. GFSK was the worst case.

Report No.: TW2103437E Page 28 of 46

Date: 2021-04-27



8.0 Antenna Requirement

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a PCB antenna. The antenna gain is 1.2dBi Max. It fulfills the requirement of this section. Test Result: Pass

Report No.: TW2103437E Page 29 of 46



FSK Modulation	Dittem	OTH OP	EAVED		T	4 M 1		IZ ·			
Product:		OOTH SP				est Mode:		Keep transmitting DC3.7V			
Mode		ng Transm				est Voltage					
Temperature		24 deg. C,			Humidity			56%			
Test Result:		Pass			_	Detector		Pl	<u>K</u>		
OdB Bandwidth	8	83.77kHz	2						-		
Ref Lvl	Marker ndB		ndB] .00 dB		3W 3W	30 ki	Hz	F Att	20 (dВ	
10 dBm	BW 883	.767535	507 kHz	SI	TV	8.5 m	s U	nit	(dBm	
10						v ₁	[T1]	- 4	1.99 d	dBm	
								2.40182	866 6	Hz	
0			1			ndB	0.4	20	0.00	lB 	
			$\wedge \wedge \wedge$	\cap		BW ▼ _T 1	87 [T1]	3.76753 -24		dBm	
-10			Ĵ	8	\			2.40154			
		<i>f</i>	\mathcal{N}		7	$ abla_{\mathrm{T2}}$	[T1]	-24	.76	lBm	
1MAX		Til				T2		2.40242	385 0	Hz:	
-30		,				V	<u> </u>				
-40	~ /						1	M			
-50	V						V		٠.٧٠		
-60								**	**************************************	M	
-70											
-80											
-90 Center 2.402			300						n 3 N		

Page 30 of 46 Report No.: TW2103437E



GFSK Modula	tion							W		
Product:		BLUETO	OTH SPE	AKER		Test Mode		Keep tra	ansmitting	
Mode		Keepin	g Transmi	tting		Test Voltage	e	DC	C3.7V	
Temperature		24	4 deg. C,			Humidity		569	% RH	
Test Result:			Pass			Detector]	PK	
20dB Bandwidth		88	3.77kHz							
₩.		Marker	1 [T1 r	ndB]	RB	W 30 k	Hz R	F Att	20 dB	
Ref Lvl		ndB	20.	.00 dB	VB	W 100 k	XHZ			
10 dBm		BW 883	.767535	07 kHz	SW'	r 8.5 m	ns U	nit	dBm	
10						v ₁	[T1]	_ 5	.56 dBm	
								2.44082	866 GHz	A
0				1		ndl	8	20	0.00 dB	
				12	_	BW		3.76753	507 kHz	
-10				0 0	V \	lacksquare	[T1]	-25	.21 dBm	
				\sim)	$\nabla_{\mathbf{T}}$	2 [T1]	2.44054		
-20						4		2.44142	385 GHz	
1MAX						MT2				1MA
-30		\	/			V	ή.			
-40	m							Λ Λ		
-50	1	V					W	hy,		
-60									WWW	
-70										
-80										
-90 Center 2	.441 GF	łz		300	kHz/			Spa	an 3 MHz	
Date: 13	.APR.2	021 00	:25:46							

Page 31 of 46

Report No.: TW2103437E



Product:		BLUETO	OTH SPE	AKER		T	est Mode:		Keep tra	ansmitting	
Mode		Keepin	g Transmi	tting		Te	est Voltage		DC	23.7V	
Temperature		2	4 deg. C,]	Humidity		569	% RH	
Test Result:			Pass				Detector]	PK	
20dB Bandwidth		88	83.77kHz								
R		Marker	1 [T1 r	ndB]	RE	ЗW	30 kHz	: R	F Att	20 dB	
Ref Lvl		ndB		00 dB	VE	ЗW	100 kHz				
10 dBm		BW 883	3.767535	07 kHz	SV	TV	8.5 ms	Uı	nit	dBm	1
10							▼ 1 [г1]	-6	.80 dBm	A
									2.47982	866 GHz	
0				1			ndB		20	0.00 dB	
				10.0			BW ▼ _{T1}	88 [T1]	3.76753	507 kHz	
-10				1494	74		· I I		2.47954		
				$\sqrt{}$		لم	$oldsymbol{ abla}_{\mathrm{T}2}$	[T1]	-26		
-20			<i></i>			\neg	ATTO		2.48042	385 GHz	1.00
1MAX			TAU Y				VIEW I				1M2
-30			7				\ <u>\</u>				
		<i></i>	<i>(</i> *				1				
-40							1	<u></u>			
	A1	/									
-50	- And the second	-/						\	\sim		
\ _u	N	V						V	\		
-60	,								704	WWW.	
										. /II/W	
-70											
-80											
-90											
Center 2	Center 2.48 GHz			300	kHz/				Spa	an 3 MHz	

Report No.: TW2103437E Page 32 of 46



Pi/4D-QPSK M Product:	Iodulation	ı								
Product:	В	BLUETO	OTH SPE	AKER	,	Test Mode	:	Keep tra	nsmitting	
Mode		Keepin	g Transmi	tting	Г	est Voltag	je e	DC	3.7V	
Temperature		24	4 deg. C,			Humidity		569	6 RH	
Test Result:			Pass			Detector]	PK	
20dB Bandwidth		1.	232MHz							
r)	M	Marker	1 [T1 r	ndB]	RBW	30]	kHz R	F Att	20 dB	
Ref Lvl	n	ndB	20.	00 dB	VBW	100 }	кНz			
10 dBm	E	3W 1	.232464	193 MHz	SWT	8.5 r	ns U	nit	dBm	
10						v ₁	[T1]	- 5	.00 dBm	A
								2.40182	866 GHz	
0				1		nd		20	.00 dB	
				\bigwedge \bigwedge		BW ∇ _T		1.23246	493 MHz	
-10			^	14	L. / ~	√ 1.	TTTT	2.40135	.71 dBm 972 GHz	
			\ww/	· س	W.	T	2 [T1]	-25	.20 dBm	
-20		T /	J				Γ2	2.40259	218 GHz	
1MAX		7				,	1			1MA
-30										
-40	. ^ /	w								
-50	√ √ √						, u	W	Mulli	
-60									1,000	
-70										
-80										
-90 Center 2	.402 GHz	z		300	kHz/			Spa	n 3 MHz	
	.APR.20		:21:05		•					

Report No.: TW2103437E Page 33 of 46



Product:		BLUETO	OTH SPE	AKER	T	T	est Mode:		Keep tra	ansmitting	_
Mode		Keepin	g Transmi	tting		Т	est Voltage		DC	C3.7V	
Temperature		2	4 deg. C,]	Humidity		569	% RH	
Test Result:			Pass				Detector	PK			
0dB Bandwidth		1.	.257MHz								
Ŕ		Marker	1 [T1 r	ndB]	RI	ЗW	30 kI	Iz R	F Att	20 dB	
Ref Lvl		ndB	20.	00 dB	VI	ЗW	100 kH				
10 dBm		BW 1	L.256513	303 MHz	SI	TV	8.5 ms	S U	nit	dBm	ı
10							v ₁	[T1]	_ 5	.56 dBm	A
									2.44082	866 GHz	
0				<u>1</u>			ndB		20	0.00 dB	
				$\Lambda \wedge$			BW ▼ _{T1}	[T1]	1.25651	303 MHz $3.08 dBm$	
-10			^	14/	M		٨		2.44035		
			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	، سر	(' ~ \ ∀ _{T2}	[T1]	-25	5.52 dBm	
-20		т1	/					2	2.44161	623 GHz	
1MAX		7					Y	7			1M2
-30								}			
-40								_			
	м	m						\ M	A		
-50	~\\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \							\ \ 	√ [₩] _		
-60 www									NV.	May	
-60										1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
-70											
-80											
-90	445	_			1 :				_	2]
Center 2	.441 GF	12		300	kHz/				Spa	an 3 MHz	

Page 34 of 46

Report No.: TW2103437E



Product:		BLUETO	OTH SPE	AKER		Test Mode:		Keep tra	ansmitting	
Mode		Keepin	g Transmi	tting	7	Test Voltage	2	DC	23.7V	
Temperature		2	4 deg. C,			Humidity		56% RH		
Test Result:			Pass			Detector]	PK	
20dB Bandwidth		1.	.257MHz							
Ŕ		Marker	1 [T1 r	ndB]	RBW	30 k	Hz R	F Att	20 dB	
Ref Lvl		ndB		00 dB	VBW					
10 dBm		BW 1	L.256513	803 MHz	SWT	8.5 m	ıs U	nit	dBn	n
10						v ₁	[T1]	- 6	.73 dBm	A
								2.47982	866 GHz	
0				1		ndI	8	20	0.00 dB	
				\ \bar{\bar{\chi}}		BW V _T	[T1]	1.25651	303 MHz	
-10				1/2/	\	^		2.47935		İ
			\sim	۷۰ کسم	, C	V WYT:	2 [T1]	-26		
-20		m 1	/			1	_	2.48061	623 GHz	
1MAX		7				([2 Y			1M2
- 30										
-40	/H	W					M			
-50 -60	may 1						*\	wally was	Wh n	
-70										
-80										
-90 Center 2	90 Center 2.48 GHz		I	300	kHz/	1	I	Spa	ın 3 MHz	8
Date: 1	3.APR.2	2021 00								

Page 35 of 46 Report No.: TW2103437E



8QPSK Modu	lation									
Product:		BLUETO	OTH SPE	AKER		Test Mode	::	Keep tra	ansmitting	
Mode		Keepin	g Transmi	tting		Test Voltag	ge ge	DC	3.7V	
Temperature		2	4 deg. C,			Humidity		56%	6 RH	
Test Result:			Pass			Detector		I	PK	
20dB Bandwidth		1.	251MHz							
<u>ka</u>		Marker	1 [T1 n	idB]	RB	W 30 I	kHz R	F Att	20 dB	
Ref Lvl		ndB		00 dB	VB					
10 dBm		BW 1	.250501	.00 MHz	SW	T 8.5 1	ms U	nit	dBm	
						v ₁	[T1]	- 5	.02 dBm	A
0								2.40182	866 GHz	
				1		nd		20	.00 dB	
				Λ Λ		BW $oldsymbol{ abla}_{\mathrm{T}}$		1.25050	100 MHz .93 dBm	
-10				74	\mathbb{A}	~		2.40135		
			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	~	W	$_{\text{L}}$	'2 [T1]	-24	.39 dBm	
-20		т/	_			1	T2	2.40261	022 GHz	1
-30		1					\			1MA
-40	\wedge						\mathcal{A}	\wedge		
-60	M O						i i	The Many	Maria II	
-70										
-80										
-90 Center 2	2.402 G	Hz		300	kHz/			Spa	n 3 MHz	
Date: 1	3.APR.2	021 00	:23:01							

Page 36 of 46

Report No.: TW2103437E



Product:		BLUETO	OTH SPE	AKER		Test Mod	le:	Keep transmitting			
Mode		Keepin	g Transmi	tting		Test Volta	ige		DC	3.7V	
Temperature		2	4 deg. C,			Humidit	y	56% RH			
Test Result:			Pass			Detecto	r		l	PK	
OdB Bandwidth		1.	.257MHz								
		Marker	1 [T1 r	ndB]	RBI	W 30	kHz	R	F Att	20 dB	
Ref Lvl		ndB		00 dB	VBV		kHz				
10 dBm		BW 1	L.256513	303 MHz	SW	г 8.5	ms	Uı	nit	dBn	1
						_	1 [T	1]	- 5	.58 dBm	A
0									2.44082	866 GHz	
				1		n			20	.00 dB	
1.0				\ \ \ \	_		W T1 []	r1 l	1.25651 -25	303 MHz	
-10			- ^	JW	$\backslash M \backslash M$	~/\			2.44035		
			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	т2 [:	r1]	-25	.59 dBm	
-20 1MAX		Ţ)	7				T2		2.44161	623 GHz	1M2
-30											
-50	Λ (Ma						\m	Д		
-60	m v							\ .	W.	W. W. W. C. C.	
										* (10)	
-70											
-80											
-90 Center 2	2.441 G	Hz	I	300	kHz/	I			Spa	ın 3 MHz	
Date: 1		021 00							-		

Report No.: TW2103437E Page 37 of 46



Product:		BLUETO	OTH SPE	AKER		Test Mode:			Keep transmitting		
Mode		Keepin	g Transmi	tting		Te	est Voltage		DC3.7V		
Temperature		2	4 deg. C,			F	Humidity		56%	% RH	
Test Result:			Pass]	Detector]	PK	
dB Bandwidth		1.	257MHz								
r)		Marker	1 [T1 n	ndB]	RE	ВW	30 kH	z R	F Att	20 dB	
Ref Lvl		ndB		00 dB	VE	3W	100 kH				
10 dBm		BW 1	.256513	303 MHz	SW	T	8.5 ms	U:	nit	dBm	l -
							V 1 [T1]	-6	.79 dBm	A
0				_					2.47982	866 GHz	
				1			ndB BW	· · ·	20 1.25651	.00 dB	
1.0				/ /			$oldsymbol{ abla}_{ ext{T1}}^{ ext{BW}}$	[T1]	-26	303 MHz	
-10			_		M	/	٦ - ا		2.47935		
			\w\	۷ کر		\sim	VT2	[T1]	-26	.77 dBm	
-20		T./	J				TZ	!	2.48061	623 GHz	1M2
-30							1				
-40	/h							\anu			
-50 -60 -60 -60 -60 -60 -60 -60 -60 -60 -6	W\\							An .d	May	. A A	
										A.A.C.	
-70											
-80											
-90 Center 2	.48 GHz	3		300	kHz/				Spa	ın 3 MHz	

Report No.: TW2103437E Page 38 of 46

Date: 2021-04-27




10.0 FCC ID Label

FCC ID: 2APYY-AE0151

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 39 of 46

Report No.: TW2103437E

Date: 2021-04-27



11.0 Photo of testing

11.1 Conducted test View--




Page 40 of 46

Report No.: TW2103437E

Date: 2021-04-27



Radiated emission test view



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2103437E

Date: 2021-04-27



11.2 Photographs – EUT



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No.: TW2103437E

Date: 2021-04-27



Photographs - EUT

Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Report No.: TW2103437E Page 43 of 46



Outside View




Page 44 of 46

Report No.: TW2103437E

Date: 2021-04-27



Inside view



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


Page 45 of 46

Report No.: TW2103437E

Date: 2021-04-27



Inside view



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

Page 46 of 46

Report No.: TW2103437E

Date: 2021-04-27





-- End of the report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES.

will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to