



## RF Exposure Evaluation

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>,  $P_{out}$  = output power to antenna in mW;

G = gain of antenna in linear scale,  $\pi = 3.1416$ ;

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



## Test Result of RF Exposure Evaluation

### BLE

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
GFSK	0.83	1.21	0.0007	1.0	PASS

### BR+EDR

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
GFSK	1.37	1.37	0.0008	1.0	PASS

### 2.4G Wi-Fi

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11b	12.72	18.71	0.0084	1.0	PASS

### 5.2G Wi-Fi

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11ac	10.69	11.72	0.0083	1.0	PASS

### 5.3G Wi-Fi

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11a	9.1	8.13	0.0057	1.0	PASS

### 5.6G Wi-Fi

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11a	10.96	12.47	0.0088	1.0	PASS

## 5.8G Wi-Fi

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11a	11.28	13.43	0.0095	1.0	PASS

Remark: BT antenna gain: 4.68dBi, Wi-Fi antenna gain: 2.4GHz=3.52dBi, 5GHz=5.49dBi.

The device cannot transmit with 2.4GHz Wi-Fi and 5.2GHz, 5.3GHz, 5.6GHz, 5.8GHz Wi-Fi simultaneously, can transmit with 2.4G Wi-Fi, 5.2GHz, 5.3GHz, 5.6GHz, 5.8GHz Wi-Fi and BT simultaneously.

### Calculations for simultaneously transmit

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0008	0.0099	1	PASS
BLE	0.0007			
2.4G Wi-Fi	0.0084			

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0008	0.0098	1	PASS
BLE	0.0007			
5.2G Wi-Fi	0.0083			

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0008	0.0072	1	PASS
BLE	0.0007			
5.3G Wi-Fi	0.0057			

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0008	0.0103	1	PASS
BLE	0.0007			
5.6G Wi-Fi	0.0088			

Mode	Ratios	Result	Limit	Result
BR+EDR	0.0008	0.011	1	PASS
BLE	0.0007			
5.8G Wi-Fi	0.0095			

Ratios = Power Density / Power density Limit

So a SAR test is not required