Report No: 68.910.24.0004.01-S

RF exposure Estimation



1. Introduction

Product: Etekcity Smart Fitness Scale

Models no.: ESF93 FCC ID: 2AB22-ESF932

The EUT is an Etekcity Smart Fitness Scale, supports BLE-1Mbps function, operates at 2402 – 2480MHz.

2. **Limit and Guidelines on Exposure to Electromagnetic Fields**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r01, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation25
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

3. Calculation method

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \leq 3.0$

Conducted Power + tune up tolerance =3.30dBm= 2.14mW Distance = 5 mmf = 2.440 GHz

[2.14/5] * SQRT (2.440) =0.669 $0.669 \le 3.0$ Therefore, excluded from SAR testing.

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:

Jessie He / Project Manage

Date: 2024-03-19

Prepared By:

Myron Yu / Project Engineer

Date: 2024-03-19