



FCC Maximum Permissible Exposure(MPE) Estimation Report

Product Name: HSPA+ Module

Model: MU709s-6

Report No.: SYBH(Z-SAR)018112014-2

FCC ID: QISMU709S-6

	APPROVED (Lab Manager)	PREPARED (Test Engineer)
BY	<i>Wei Huanbin</i>	<i>Pan Man</i>
DATE	2014-12-08	2014-12-08

The test results of this test report relate exclusively to the item(s) tested. The HUAWEI does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of HUAWEI.

Reliability Laboratory of Huawei Technologies Co., Ltd.

Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian,
Longgang District, Shenzhen, 518129, P.R.C

Tel: +86 755 28780808 Fax: +86 755 89652518



※ ※ Modified History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	2014-12-08	Pan Man



Table of Contents

1	EUT Description	4
1.1	General Description	4
2	Test specification(s).....	5
3	Testing laboratory	5
4	Applicant and Manufacturer	5
5	Application details.....	5
6	Ambient Condition	5
7	RF Exposure Requirements	6
8	RF Exposure Evaluation.....	9
8.1	Operation in GSM850.....	9
8.2	Operation in GSM1900.....	9
8.3	Operation in UMTS Band V	10
8.4	Operation in UMTS Band II	10



1 EUT Description

Device Information:			
DUT Name:	HSPA+ Module		
Type Identification:	MU709s-6		
Device Type :	Mobile device		
FCC ID:	QISMU709S-6		
Device Phase:	Identical Prototype		
Exposure Category:	Uncontrolled environment/general population		
Hardware Version :	MD1MU709M01		
Software Version :	25.651.66.00.02		
Antenna Type :	External Antenna		
Device Operating Configurations:			
Supporting Mode(s)	GSM850/1900,UMTS Band V/II		
Test Modulation	GSM(GMSK/8PSK),UMTS(QPSK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824-849	869-894
	GSM1900	1850-1910	1930-1990
	UMTS Band V	824-849	869-894
	UMTS Band II	1850-1910	1930-1990

1.1 General Description

MU709s-6 WCDMA/HSDPA/HSUPA/HSPA+/GSM/GPRS/EDGE mode Wireless Module is subscriber equipment in the system. MU709s-6 implement such functions as RF signal receiving/transmitting,WCDMA/HSDPA/HSUPA/HSPA/GSM/GPRS/EDGE protocol processing, data service etc.



2 Test specification(s)

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz – 300 GHz.(IEEE Std C95.1-1991)
KDB 447498 D01	General RF Exposure Guidance v05r02

3 Testing laboratory

Test Site	The Reliability Laboratory of Huawei Technologies Co., Ltd.
Test Location	Zone K3,Huawei Industrial Base, Bantian Industry Area, Longgang District, Shenzhen, Guangdong, China
Telephone	+86 755 28780808
Fax	+86 755 89652518
State of accreditation	The Test laboratory (area of testing) is accredited according to ISO/IEC 17025. CNAS Registration number: L0310 A2LA TESTING CERT #2174.01

4 Applicant and Manufacturer

Company Name	HUAWEI TECHNOLOGIES CO., LTD
Address	Administration Building, Headquarters of Huawei Technologies Co., Ltd., Bantian, Longgang District, Shenzhen, 518129, P.R.C

5 Application details

Start Date of test	2014-12-08
End Date of test	2014-12-08

6 Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

7 RF Exposure Requirements

An estimation of MPE in this application for product is used to ensure if it complies to the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC's MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

Table: Limits For Maximum Permissible Exposure (MPE)

(A) Limits for Occupational/controlled Exposure				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm ²)	Averaging Time (minute) E ² , H ² or S
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/uncontrolled Exposure				
Frequency Range(MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength(H)(A/m)	Power Density (S)(mW/cm ²)	Averaging Time (minute) E ² , H ² or S
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30
f=frequency in MHz			*Plane-wave equivalent power density	

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator



R = distance to the centre of radiation of the antenna

$$EIRP = P \cdot G$$

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with $R=20\text{cm}$, and if it is below the limit S , then we can conclude the device complies with the rules.



8 RF Exposure Evaluation

8.1 Operation in GSM850

(uplink: 824-849MHz, downlink: 869-894MHz)

Mode	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
1TS*(1/8)	33.5	2.5	36	497.63	20	0.099	0.549	PASS
2TS*(2/8)	31.5	2.5	34	627.97	20	0.125	0.549	PASS
3TS*(3/8)	30.5	2.5	33	748.22	20	0.149	0.549	PASS
4TS*(4/8)	28.5	2.5	31	629.46	20	0.125	0.549	PASS

Note: *- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.149mW/cm², which is below the uncontrolled exposure limit of 0.549mW/cm² at 824MHz, so we can conclude it is into compliance.

8.2 Operation in GSM1900

(uplink: 1850-1910MHz, downlink: 1930-1990MHz)

Mode	Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
1TS*(1/8)	30.5	2.5	33	249.41	20	0.050	1.000	PASS
2TS*(2/8)	28.5	2.5	31	314.73	20	0.063	1.000	PASS
3TS*(3/8)	27.5	2.5	30	375.00	20	0.075	1.000	PASS
4TS*(4/8)	25.5	2.5	28	315.48	20	0.063	1.000	PASS

Note: *- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.075mW/cm², which is below the uncontrolled exposure limit of 1.000mW/cm² at 1850MHz, so we can conclude it is into compliance.



8.3 Operation in UMTS Band V

(uplink: 824-849MHz, downlink: 869-894MHz)

Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
24.5	2.5	27	501.19	20	0.100	0.549	PASS

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.100mW/cm², which is below the uncontrolled exposure limit of 0.549mW/cm² at 824MHz, so we can conclude it is into compliance.

8.4 Operation in UMTS Band II

(uplink: 1850-1910MHz, downlink: 1930-1990MHz)

Tune-up limit (dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R(cm)	S (mW/cm ²)	MPE Limit (mW/cm ²)	Conclusion
24.5	2.5	27	501.19	20	0.100	1.000	PASS

Note:*- based on the maximum tune-up tolerance limit declared by manufacturer

According to the Table, we can conclude the max power density level at 20 cm is 0.100mW/cm², which is below the uncontrolled exposure limit of 1.000mW/cm² at 1850MHz, so we can conclude it is into compliance.

End