

Straubing, November 24, 1998

## **TEST - REPORT**

**No. 51940-80919**

**for**

**ZB 001**

**Hand Held Verifier**

Applicant: Sensormatic GmbH

Purpose of testing: To show compliance with  
I-ETS 300 330 (December 1994)  
Product Class 1

Radio Equipment and Systems (RES);  
Short Range Devices (SRDs);  
Technical characteristics and test methods  
for radio equipment in the frequency range  
9 kHz to 25 MHz and inductive loop systems  
in the frequency range 9 kHz to 30 MHz

---

Note:

The test data of this report relate only to the individual item which have been tested.  
This report shall not be reproduced except in full extent without the written approval of  
the testing laboratory.

---

## Table of Contents

|     |                                                              |    |
|-----|--------------------------------------------------------------|----|
| 1.  | Identification of the Test Laboratory.....                   | 3  |
| 2.  | Administrative Data.....                                     | 4  |
| 3.  | Deviations from the Test Specifications.....                 | 6  |
| 4.  | Summary of Test Results.....                                 | 7  |
| 5.  | Additional References.....                                   | 8  |
| 6.  | Test Results.....                                            | 9  |
| 7.  | Test Equipment and Ancillaries used for Tests.....           | 14 |
| 8.  | Measurement Uncertainty Values.....                          | 18 |
| 9.  | Photographs of the Equipment Under Test.....                 | 21 |
| 10. | Additional Information supplementary to the Test Report..... | 33 |

## 1. Identification of the Test Laboratory

### DETAILS OF THE TEST LABORATORY

|                                |                                                                                  |
|--------------------------------|----------------------------------------------------------------------------------|
| COMPANY NAME:                  | Senton GmbH EMI/EMC Test Center                                                  |
| ADDRESS:                       | Aeussere Fruehlingstrasse 45<br>D-94315 Straubing<br>Germany                     |
| LABORATORY ACCREDITATION:      | DAR-Registration No. TTI-P-G 062/94-30<br>DAR-Registration No. TTI-P-G 109/95-20 |
| NAME FOR CONTACT PURPOSES:     | Mr. Johann Roidt                                                                 |
| TELEPHONE: (+49) 09421 55 22-0 | FAX: (+49) 09421 55 22 99                                                        |

### PERSONNEL INVOLVED IN THIS TEST REPORT

|                              |                           |
|------------------------------|---------------------------|
| TECHNICAL DIRECTOR:          | .....<br>Mr. Johann Roidt |
| RESPONSIBLE FOR TESTING:     | .....<br>Mr. Thomas Eberl |
| RESPONSIBLE FOR TEST REPORT: | Mr. Thomas Eberl          |

## 2. Administrative Data

| IDENTIFICATION OF EUT                                                        |                                                   |
|------------------------------------------------------------------------------|---------------------------------------------------|
| TYPE DESIGNATION OF EUT (i.e. system if EUT consists of more than one part): | ZB 001                                            |
| PARTS OF THE SYSTEM (including appropriate type designations)                | 1                                                 |
| SERIAL NUMBER(S):                                                            | --                                                |
| FREQUENCY RANGE:                                                             | 1 kHz - 135 kHz<br>(according to BAPT 222 ZV 122) |
| OPERATING FREQUENCY:                                                         | 57.6 kHz                                          |
| CHANNEL SPACING:                                                             | --                                                |
| ITU DESIGNATION:                                                             | 1H00 NON                                          |
| NUMBER OF RF-CHANNELS:                                                       |                                                   |
| NUMBER OF CONTROL FUNCTIONS:                                                 |                                                   |
| POWER SUPPLY:                                                                | Accu 12 V                                         |
| TYPE OF ANTENNA:                                                             | Printed antenna                                   |
| SIZE / LENGTH OF ANTENNA:                                                    | 0.0176 m <sup>2</sup>                             |
| INTERFACE(S):                                                                | --                                                |

## ADMINISTRATIVE DATA

|                           |                                                                      |
|---------------------------|----------------------------------------------------------------------|
| APPLICANT (full address): | Sensormatic GmbH<br>Am Schimmersfeld 7<br>40880 Ratingen ( Germany ) |
| CONTACT PERSON:           | Mr. Zinke                                                            |
| TELEPHONE NO.:            | 02102/431326                                                         |
| FAX NO.:                  | 02102/431250                                                         |
| RECEIPT OF EUT:           | Oct. 98                                                              |
| DATE(S) OF TEST:          | Nov. 98                                                              |
| VERSION OF EUT:           | series version                                                       |
| NOTE:                     |                                                                      |

### **3. Deviations from the Test Specifications**

All tests were performed without deviations from the test specifications.

#### 4. Summary of Test Results

| REFERENCE FOR PERFORMED TESTS |                                                                                                                                                                                                                                                    |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reference:                    | I-ETS 300 330 (December 1994)                                                                                                                                                                                                                      |
| Title:                        | Radio Equipment and Systems (RES);<br>Short Range Devices (SRDs);<br>Technical characteristics and test methods for radio equipment in<br>the frequency range 9 kHz to 25 MHz and inductive loop systems in<br>the frequency range 9 kHz to 30 MHz |
| Result:                       | The tested sample fully complies with the requirements set forth in<br>I-ETS 300 330 (December 1994) for equipment belonging to<br>product class 1                                                                                                 |

| LIST OF MEASUREMENTS   |                                                       |                |      |
|------------------------|-------------------------------------------------------|----------------|------|
| Sub-<br>clause         | Parameter to be measured                              | Test           | Page |
| Transmitter parameters |                                                       |                |      |
| 7.2.1                  | H-field (Class 1)                                     | Passed         |      |
| 7.2.2                  | RF carrier current (Classes 2 and 3)                  | Not applicable |      |
| 7.2.3                  | Radiated E-field (Class 4)                            | Not applicable |      |
| 7.3.2                  | Frequency error                                       | Not applicable |      |
| 7.3.3                  | Modulation bandwidth                                  | Passed         |      |
| 7.4.2.1<br>7.4.2.2     | Spurious emissions conducted - transmitter operating  | Not applicable |      |
| 7.4.2.1<br>7.4.2.2     | Spurious emissions conducted - transmitter on standby | Not applicable |      |
| 7.4.3<br>7.4.4         | Spurious emissions radiated - transmitter operating   | Passed         |      |
| 7.4.3<br>7.4.4         | Spurious emissions radiated - transmitter on standby  | Not applicable |      |

## 5. Additional References

| ADDITIONAL REFERENCES                                                                                                                                                                                                                                                                                                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>[ X ] The EUT meets the requirements of BAPT 222 ZV 122</li><li>[ ] The EUT complies with performance specification MPT 1337 published by Radiocommunications Agency</li><li>[ ] The EUT complies with performance specification MPT 1339 published by Radiocommunications Agency</li></ul> |



## **6. Test Results**

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

## H-FIELD FIELD STRENGTH (CLASS 1)

### SUBCLAUSE 7.2.1

Rated field strength (maximum) 28.4 dBµA/m at 10 metres

Antenna size 0.0176 m²

| Test conditions                                                       |                         | Transmitter field strength (dBµA/m) |      |      |
|-----------------------------------------------------------------------|-------------------------|-------------------------------------|------|------|
|                                                                       |                         | CH 1                                | CH 2 | CH 3 |
| $T_{\text{nom}}$ +20.0 °C                                             | $V_{\text{nom}}$ 12.0 V | 28.4                                | --   | --   |
| Maximum deviation from rated output under normal test conditions (dB) |                         | 1.5                                 |      |      |
| Measurement uncertainty (dBµA/m)                                      |                         | ± 3                                 |      |      |

## LIMIT:

### SUBCLAUSE 7.2.1.3

| Frequency range (MHz)                                                                | H-field field strength limit (H <sub>f</sub> ) dBµA/m at 10 m                                                |
|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| For loop coil antennas with area ≥ 0.16 m <sup>2</sup>                               |                                                                                                              |
| 0.009 ≤ f < 0.03                                                                     | 72                                                                                                           |
| 0.03 ≤ f < 0.135                                                                     | 72 at 0.03 MHz descending 3.5 dB/oct                                                                         |
| 0.135 ≤ f < 4.78                                                                     | 38 at 0.135 MHz descending 3.5 dB/oct                                                                        |
| 4.78 ≤ f < 30                                                                        | 20                                                                                                           |
| 6.765 ≤ f ≤ 6.795 (ISM)                                                              | 42                                                                                                           |
| 13.553 ≤ f ≤ 13.567 (ISM)                                                            |                                                                                                              |
| 26.957 ≤ f ≤ 27.283 (ISM)                                                            |                                                                                                              |
| For loop coil antennas< 0.05 m <sup>2</sup>                                          |                                                                                                              |
| 0.009 ≤ f < 0.03                                                                     | 62                                                                                                           |
| 0.03 ≤ f < 0.135                                                                     | 62 at 0.03 MHz descending 3.5 dB/oct                                                                         |
| For loop coil antennas with area between 0.05 m <sup>2</sup> and 0.16 m <sup>2</sup> |                                                                                                              |
| 0.009 ≤ f < 0.135                                                                    | H <sub>f</sub> table values for loop coils ≥ 0.16 m <sup>2</sup><br>+ 10 * log( area / 0.16 m <sup>2</sup> ) |

Reference number(s) of test equipment used (for reference see test equipment listing):  
001, 012, 103, 123, 140

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

**PERMITTED RANGE OF OPERATING FREQUENCIES  
FOR WIDEBAND EQUIPMENT (>25 KHZ)**

**SUBCLAUSE 7.3**

Applicants declared operating frequency band:

Lowest frequency: ..... kHz

Highest frequency: ..... kHz

| Test conditions              |                         | Limit                   |
|------------------------------|-------------------------|-------------------------|
|                              |                         | Frequency (kHz)         |
| T <sub>nom</sub> +20.0 °C    | V <sub>nom</sub> 12.0 V | F <sub>L</sub> = 53.089 |
|                              |                         | F <sub>H</sub> = 63.422 |
| T <sub>min</sub> -20.0 °C    | V <sub>min</sub> 10.8 V | F <sub>L</sub> = 53.200 |
|                              |                         | F <sub>H</sub> = 62.844 |
|                              | V <sub>max</sub> 13.2 V | F <sub>L</sub> = 52.467 |
|                              |                         | F <sub>H</sub> = 64.111 |
| T <sub>max</sub> +55.0 °C    | V <sub>min</sub> 10.8 V | F <sub>L</sub> = 53.756 |
|                              |                         | F <sub>H</sub> = 62.178 |
|                              | V <sub>max</sub> 13.2 V | F <sub>L</sub> = 52.956 |
|                              |                         | F <sub>H</sub> = 63.600 |
| Measurement uncertainty (Hz) |                         |                         |

Where F<sub>L</sub> Lowest frequency at the appropriate spurious emission level  
F<sub>H</sub> Highest frequency at the appropriate spurious emission level

Band edge limits

F<sub>LM</sub> Lowest F<sub>L</sub> (measured): 53.089 kHz  
F<sub>HM</sub> Highest F<sub>H</sub> (measured): 63.600 kHz

Reference number(s) of test equipment used (for reference see test equipment listing):  
007, 008, 020, 022, 102

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

## TRANSMITTER SPURIOUS EMISSIONS RADIATED (<30 MHz)

### SUBCLAUSE 7.4.3

Rated carrier output 28.4 dBμA/m  
Transmitter operating/standby\*

Modulated/Unmodulated\*  
\*(Delete whichever is inappropriate)

| Spurious Emissions Level (dBμA/m) |                           |                   |            |                           |                   |            |                           |                   |
|-----------------------------------|---------------------------|-------------------|------------|---------------------------|-------------------|------------|---------------------------|-------------------|
| CH 1                              |                           |                   | CH 2       |                           |                   | CH 3       |                           |                   |
| f<br>(MHz)                        | Band-<br>width**<br>(kHz) | Level<br>(dBμA/m) | f<br>(MHz) | Band-<br>width**<br>(kHz) | Level<br>(dBμA/m) | f<br>(MHz) | Band-<br>width**<br>(kHz) | Level<br>(dBμA/m) |
| *                                 |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
|                                   |                           |                   |            |                           |                   |            |                           |                   |
| Measurement uncertainty (dBμA/m)  |                           |                   |            |                           |                   | ± 3        |                           |                   |

\*\*Bandwidth = the measuring receiver bandwidth

\*Note ∴ No values above noise level of the appropriate test receiver

### LIMIT:

### SUBCLAUSE 7.4.3.2

| State     | Frequency $9 \text{ kHz} \leq f < 4.78 \text{ MHz}$ | Frequency $4.78 \text{ MHz} \leq f < 30 \text{ MHz}$ |
|-----------|-----------------------------------------------------|------------------------------------------------------|
| Operating | 24.5 dBμA/m descending 3 dB/oct                     | -2.8 dBμA/m                                          |
| Standby   | 3.5 dBμA/m descending 3 dB/oct                      | -23.7 dBμA/m                                         |

Reference number(s) of test equipment used (for reference see test equipment listing):  
001, 003, 012, 014, 103, 104, 140

Ambiente temperature: +20.0 °C

Relative humidity: 50 %

## TRANSMITTER SPURIOUS EMISSIONS RADIATED (>30 MHz)

### SUBCLAUSE 7.4.4

Rated carrier output 28.4 dBμA/m

Transmitter operating/~~standby~~\*

Modulated/~~Unmodulated~~\*  
\*(Delete whichever is inappropriate)

| Spurious Emissions Level (nW) |                           |               |            |                           |               |            |                           |               |
|-------------------------------|---------------------------|---------------|------------|---------------------------|---------------|------------|---------------------------|---------------|
| CH 1                          |                           |               | CH 2       |                           |               | CH 3       |                           |               |
| f<br>(MHz)                    | Band-<br>width**<br>(kHz) | Level<br>(nW) | f<br>(MHz) | Band-<br>width**<br>(kHz) | Level<br>(nW) | f<br>(MHz) | Band-<br>width**<br>(kHz) | Level<br>(nW) |
| *                             |                           |               |            |                           |               |            |                           |               |
|                               |                           |               |            |                           |               |            |                           |               |
|                               |                           |               |            |                           |               |            |                           |               |
|                               |                           |               |            |                           |               |            |                           |               |
|                               |                           |               |            |                           |               |            |                           |               |
|                               |                           |               |            |                           |               |            |                           |               |
|                               |                           |               |            |                           |               |            |                           |               |
|                               |                           |               |            |                           |               |            |                           |               |
| Measurement uncertainty (dB)  |                           |               |            |                           |               | ± 3        |                           |               |

\*\*Bandwidth = the measuring receiver bandwidth

\*Note .: No values above noise level of the appropriate test receiver

### LIMIT:

### SUBCLAUSE 7.4.4.2

| State     | 47 MHz to 74 MHz<br>87.5 MHz to 118 MHz<br>174 MHz to 230 MHz<br>470 MHz to 862 MHz | Other frequencies between<br>30 MHz to 1000 MHz |
|-----------|-------------------------------------------------------------------------------------|-------------------------------------------------|
| Operating | 4 nW                                                                                | 250 nW                                          |
| Standby   | 2 nW                                                                                | 2 nW                                            |

Reference number(s) of test equipment used (for reference see test equipment listing):  
001, 004, 012, 015, 101, 106, 141, 142, 143, 144

## 7. Test Equipment and Ancillaries used for Tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the test laboratory (version 11/20/1995).

### General Test Equipment and Ancillaries

| No. | Instrument/Ancillary     | Type       | Serial Number | Manufacturer       |
|-----|--------------------------|------------|---------------|--------------------|
| 001 | Open area test site      | EG 1       |               | Senton             |
| 002 | Shielded room            | No. 1      | 1451          | Senton             |
| 003 | Shielded room            | No. 2      | 1452          | Senton             |
| 004 | Semi-anechoic room       | No. 3      | 1453          | Siemens            |
| 005 | Shielded room            | No. 4      | 3FD 100 544   | Euroshield         |
| 006 | Shielded room            | No. 5      | 5468          | Ray Proof Division |
| 007 | Temperature test chamber | HT4010     | 07065550      | Heraeus            |
| 008 | Cable                    | RG214      | 1309          | Senton             |
| 009 | Cable                    | 200CM_001  | 1357          | Rosenberger        |
| 010 | Cable                    | 150CM_001  | 1479          | Rosenberger        |
| 011 | Cable                    | 150CM_002  | 1480          | Rosenberger        |
| 012 | Cable set EG1            | RG214      | 1189 - 1191   | Senton             |
| 013 | Cable set cabin no. 1    | RG214      |               | Senton             |
| 014 | Cable set cabin no. 2    | RG214      |               | Senton             |
| 015 | Cable set cabin no. 3    | RG214      |               | Senton             |
| 016 | Cable set cabin no. 4    | RG214      |               | Senton             |
| 017 | DC power supply          | NGSM 32/10 | 203           | Rohde & Schwarz    |
| 018 | DC power supply          | NGB        | 2455          | Rohde & Schwarz    |
| 019 | DC power supply          | NGA        | 386           | Rohde & Schwarz    |
| 020 | Isolating transformer    | RT 5A      | 10387         | Grundig            |
| 021 | Isolating transformer    | RT 5A      | 10416         | Grundig            |
| 022 | Digital multimeter       | 199        | 463386        | Keithley           |
| 023 | Multimeter               | HP E2373A  | 2927J03345    | Hewlett Packard    |

## Test Equipment and Ancillaries used for Emission Tests

| No. | Instrument/Ancillary                | Type         | Serial Number            | Manufacturer    |
|-----|-------------------------------------|--------------|--------------------------|-----------------|
| 101 | EMI test receiver                   | ESMI         | 839379/013<br>839587/006 | Rohde & Schwarz |
| 102 | Spectrum analyzer                   | R 3271       | 05050023                 | Advantest       |
| 103 | Test receiver                       | ESH 3        | 880112/032               | Rohde & Schwarz |
| 104 | Test receiver                       | ESHS 10      | 860043/016               | Rohde & Schwarz |
| 105 | Test receiver                       | ESV          | 881414/009               | Rohde & Schwarz |
| 106 | Test receiver                       | ESVP         | 881120/024               | Rohde & Schwarz |
| 107 | Audio analyzer                      | UPA          | 862954                   | Rohde & Schwarz |
| 108 | Radio communication service monitor | CMS 54       | 838384/030               | Rohde & Schwarz |
| 109 | Power meter                         | NRVS         | 836856/015               | Rohde & Schwarz |
| 110 | Power sensor                        | NRV-Z52      | 837901/030               | Rohde & Schwarz |
| 111 | Power sensor                        | NRV-Z4       | 863828/015               | Rohde & Schwarz |
| 112 | Preamplifier                        | ESV-Z3       | 860907/004               | Rohde & Schwarz |
| 113 | Preamplifier                        | R14601       |                          | Advantest       |
| 114 | Preamplifier                        | ACX/080-3030 | 32640                    | CTT             |
| 115 | Preamplifier                        | ACO/180-3530 | 32641                    | CTT             |
| 116 | Signal generator                    | SMS          | 872166/039               | Rohde & Schwarz |
| 117 | Signal generator                    | HP 8673 D    | 2930A00966               | Hewlett Packard |
| 118 | Waveform generator                  | HP 33120 A   | US34005375               | Hewlett Packard |
| 119 | UHF attenuator set                  | DPU          | 300771/075               | Rohde & Schwarz |
| 120 | UHF attenuator set                  | DPU          | 300788/006               | Rohde & Schwarz |
| 121 | Attenuator                          | 4776-10      | 9412                     | Narda           |
| 122 | Attenuator                          | 4776-20      | 9503                     | Narda           |
| 123 | Pulse limiter                       | ESH 3-Z2     | 1144                     | Rohde & Schwarz |
| 124 | Pulse limiter                       | 11947 A      | 3107A00566               | Hewlett Packard |
| 125 | V-network                           | ESH 3-Z5     | 862770/018               | Rohde & Schwarz |
| 126 | V-network                           | ESH 3-Z5     | 894785/005               | Rohde & Schwarz |
| 127 | V-network                           | ESH 3-Z5     | 830952/025               | Rohde & Schwarz |
| 128 | V-network                           | ESH 3-Z6     | 830722/010               | Rohde & Schwarz |
| 129 | V-network                           | NSLK 8127    | 8127152                  | Schwarzbeck     |
| 130 | Artificial mains network            | ESH 2-Z5     | 842966/004               | Rohde & Schwarz |
| 131 | T-network                           | ESH 3-Z4     | 890602/011               | Rohde & Schwarz |
| 132 | T-network                           | ESH 3-Z4     | 890602/012               | Rohde & Schwarz |
| 133 | Diode detector negative             | 8473D        | 01492                    | Hewlett Packard |

## Test Equipment and Ancillaries used for Emission Tests (continued)

| No. | Instrument/Ancillary  | Type     | Serial Number | Manufacturer    |
|-----|-----------------------|----------|---------------|-----------------|
| 134 | High impedance probe  | TK 9416  | 01            | Schwarzbeck     |
| 135 | High impedance probe  | TK 9416  | 02            | Schwarzbeck     |
| 136 | Current probe         | ESH 2-Z1 | 863366/18     | Rohde & Schwarz |
| 137 | Current probe         | ESV-Z1   | 862553/3      | Rohde & Schwarz |
| 138 | Absorbing clamp       | MDS 21   | 80911         | Lüthi           |
| 139 | Absorbing clamp       | MDS 21   | 79690         | Lüthi           |
| 140 | Loop antenna          | HFH2-Z2  | 882964/1      | Rohde & Schwarz |
| 141 | Biconical antenna     | HK 116   | 836239/02     | Rohde & Schwarz |
| 142 | Biconical antenna     | HK 116   | 842204/001    | Rohde & Schwarz |
| 143 | Log. periodic antenna | HL 223   | 834408/12     | Rohde & Schwarz |
| 144 | Log. periodic antenna | HL 223   | 841516/023    | Rohde & Schwarz |
| 145 | Horn antenna          | 3115     | 9508-4553     | Emco            |
| 146 | Horn antenna          | 3160-03  | 9112-1003     | Emco            |
| 147 | Horn antenna          | 3160-04  | 9112-1001     | Emco            |
| 148 | Horn antenna          | 3160-05  | 9112-1001     | Emco            |
| 149 | Horn antenna          | 3160-06  | 9112-1001     | Emco            |
| 150 | Horn antenna          | 3160-07  | 9112-1008     | Emco            |
| 151 | Horn antenna          | 3160-08  | 9112-1002     | Emco            |
| 152 | Horn antenna          | 3160-09  | 9403-1025     | Emco            |
| 153 | Stub tuner            | 904N     | 04            | Narda           |
| 154 | Mains analyzer        | DPA 503  | 496 - 02      | EM Test         |
| 155 | Controller            | HIS 500  | X71010        | EM Test         |
| 156 | AC Amplifier          | ACS 500  | HK51736       | EM Test         |
| 157 | Mains impedance       | AIF 500  | X71062        | EM Test         |



## Test Equipment and Ancillaries used for Immunity Tests

| No. | Type                    | Model            | Serial Number            | Manufacturer       |
|-----|-------------------------|------------------|--------------------------|--------------------|
| 201 | ESD simulator           | NSG 435          | 000290                   | Schaffner          |
| 202 | EFT generator           | NSG 1025         | 3020                     | Schaffner          |
| 203 | Ultra compact simulator | UCS              | 1195-30                  | EM Test            |
| 204 | Coupling clamp          | CDN 8014         | 131                      | Schaffner          |
| 205 | Coupling clamp          | SL 400-071D      | 007                      | Schaffner          |
| 206 | Coupling filter         | FP 16            | 080554-14-84             | Haefely            |
| 207 | Oscilloscope            | 2225             | 203550                   | Tektronix          |
| 208 | Signal generator        | SMT 03           | 838129/029<br>837533/032 | Rohde & Schwarz    |
| 209 | Power amplifier         | 150 L            | 8835                     | Amplifier Research |
| 210 | Power amplifier         | 200 W 1000       | 12904                    | Amplifier Research |
| 211 | Power meter             | NRVS             | 838624/016               | Rohde & Schwarz    |
| 212 | E-field generator       | 3107 B           | 2302                     | Emco               |
| 213 | Biconical antenna       | VHBA 9123        | 1018                     | Schwarzbeck        |
| 214 | Log. periodic antenna   | AT 1080          | 12834                    | Amplifier Research |
| 215 | Isotropic field probe   | FP 2000          | 12847                    | Amplifier Research |
| 216 | Isotropic field monitor | FM 2004          | 12632                    | Amplifier Research |
| 217 | Ultra compact simulator | UCS              | 1195-30                  | EM Test            |
| 218 | Surge generator         | NSG 650          | 1679204                  | Schaffner          |
| 219 | Coupling network        | CDN 110          | 1649135                  | Schaffner          |
| 220 | Coupling network        | CDN 115          | 132                      | Schaffner          |
| 221 | Dropping resistor       | INA 110-40       | 121                      | Schaffner          |
| 222 | Oscilloscope            | HM 408           | 9005 F 3144              | Hameg              |
| 223 | Signal generator        | SMX              | 883184/018               | Rohde & Schwarz    |
| 224 | Power amplifier         | 411 LA           | 299                      | ENI                |
| 225 | Power amplifier         | HVV 250          | 836956/004               | Rohde & Schwarz    |
| 226 | Power meter             | NRV              | 863825/018               | Rohde & Schwarz    |
| 227 | Coupling network        | FCC - 801- M3-25 | 117                      | FCC                |
| 228 | Coupling network        | FCC - 801- M4-25 | 17                       | FCC                |
| 229 | Coupling network        | FCC - 801- M5-25 | 16                       | FCC                |
| 230 | Coupling network        | FCC - 801- AF4   | 47                       | FCC                |
| 231 | Coupling network        | FCC - 801- AF4   | 48                       | FCC                |
| 232 | Coupling network        | FCC - 801-T4     | 68                       | FCC                |
| 233 | Coupling network        | FCC - 801- C1    | 64                       | FCC                |
| 234 | Coupling network        | CDN 801-M3       | --                       | Senton             |
| 235 | Coupling network        | CDN 801-S37      | --                       | Senton             |
| 236 | Current clamp           | FCC-120-9B       | 15                       | FCC                |
| 237 | EM injection clamp      | EM 101           | 35354                    | Lüthi              |
| 238 | Ultra compact simulator | UCS 500          | 1195-30                  | EM Test            |
| 239 | Transformer             |                  |                          | Senton             |
| 240 | Oscilloscope            | 54602B           | US35060304               | Hewlett Packard    |

## 8. Measurement Uncertainty Values

### 8.1. Radio Interference Emission Testing

#### 8.1.1. Conducted Emission 9 kHz - 30 MHz

| Used measuring instrument                                | Maximum value     |
|----------------------------------------------------------|-------------------|
| Test receiver ESHS 10 (CISPR-detector, $S/N \geq 16$ dB) | $< \pm 1.5$ dB    |
| Test receiver ESH 3 (CISPR-detector, $S/N \geq 16$ dB)   | $< \pm 1.5$ dB    |
| Pulse Limiter ESH 3-Z2                                   | $\leq \pm 0.3$ dB |
| Network ESH 3-Z4, ESH 3-Z5 or ESH 3-Z6                   | $\leq \pm 1.0$ dB |
| High impedance probe TK 9416                             | $\leq \pm 1.0$ dB |
| Cable attenuation (determined with power meter NRV)      | $< \pm 0.2$ dB    |

#### 8.1.2. Radiated Emission 9 kHz - 30 MHz

| Used measuring instrument                                | Maximum value  |
|----------------------------------------------------------|----------------|
| Test receiver ESHS 10 (CISPR-detector, $S/N \geq 16$ dB) | $< \pm 1.5$ dB |
| Test receiver ESH 3 (CISPR-detector, $S/N \geq 16$ dB)   | $< \pm 1.5$ dB |
| Loop Antenna HFH 2-Z2                                    | $< \pm 1.0$ dB |
| Cable attenuation (determined with power meter NRV)      | $< \pm 0.2$ dB |

#### 8.1.3. Radiated Emission / Equivalent Radiated Power 30 MHz - 1000 MHz

| Used measuring instrument                                     | Maximum value         |
|---------------------------------------------------------------|-----------------------|
| Spectrum analyzer R3261A                                      | $\leq \pm 1.5$ dB     |
| Spectrum analyzer R3271                                       | $\leq \pm 1.5$ dB     |
| Test receiver ESVP (CISPR-detector, $S/N > 15$ dB)            | $< \pm 1.5$ dB        |
| Test receiver ESV (CISPR-detector, $S/N \geq 10$ dB)          | $< \pm 1.5$ dB        |
| Preamplifier ESV-Z3                                           | max. $+2.0 / -1.0$ dB |
| Biconical antenna EMCO 3110                                   | $\leq \pm 1.5$ dB     |
| Biconical antenna HK 116                                      | $\leq \pm 1.0$ dB     |
| Log.-per. antenna EMCO 3147                                   | $\leq \pm 1.5$ dB     |
| Log.-per. antenna HL 223                                      | $\leq \pm 1.0$ dB     |
| Open area test site (related to theoretical site attenuation) | $< \pm 3.0$ dB        |
| Cable attenuation (determined with power meter NRV)           | $< \pm 0.2$ dB        |

#### 8.1.4. Interference Power 30 MHz - 1000 MHz

| Used measuring instrument                            | Maximum value       |
|------------------------------------------------------|---------------------|
| Spectrum analyzer R3261A                             | $\leq \pm 1.5$ dB   |
| Spectrum analyzer R3271                              | $\leq \pm 1.5$ dB   |
| Test receiver ESVP (CISPR-detector, S/N > 15 dB)     | $< \pm 1.5$ dB      |
| Test receiver ESV (CISPR-detector, S/N $\geq$ 10 dB) | $< \pm 1.5$ dB      |
| Preamplifier ESV-Z3                                  | max. +2.0 / -1.0 dB |
| Absorbing clamp MDS 21                               | $\leq \pm 1.0$ dB   |
| Cable attenuation (determined with power meter NRV)  | $< \pm 0.2$ dB      |

## 8.2. Immunity Testing

### 8.2.1. Electrostatic Discharge

Used measuring instrument

Maximum value

ESD simulator NSG 435

$\leq \pm 5\%$  of selected discharge voltage

ESD simulator PSD 25

max.  $+20\%$  /  $- 0\%$  of selected discharge voltage

### 8.2.2. Electromagnetic Fields (RF-Fields)

Used measuring instrument

Maximum value

Field probe FP 2000 / field monitor FM 2004

Selected range up to 10 V/m

$\leq \pm 0.7$  V/m

Selected range up to 30 V/m

$\leq \pm 1.9$  V/m

Selected range up to 100 V/m

$\leq \pm 6.1$  V/m

Selected range up to 300 V/m

$\leq \pm 18.1$  V/m

### 8.2.3. Electrical Fast Transients (Burst)

Used measuring instrument

Maximum value

EFT generator NSG 1025

$\leq \pm 10\%$  of selected pulse amplitude

### 8.2.4. Surge Immunity

Used measuring instrument

Maximum value

Surge generator NSG 650

$\leq \pm 10\%$  of selected pulse amplitude

## **9. Photographs of the Equipment Under Test**

**Photo No. 1**

**Antenna**

**Photo No. 2**

**Front of unit**

**Photo No. 3**

**Rear of unit**



**Photo No. 4**

**Label or identifying mark**

**Photo No. 5**

**Top view - Antenna - PCB**

**Photo No. 6**

**Bottom view - Antenna - PCB**

**Photo No. 7**

**Unit disassembled**

**Photo No. 8**

**Top view - printed board**

**Photo No. 9**

**Bottom view - printed board**

**Photo No. 10**

**Top view - Accu - pack**

**Photo No. 11**

**Bottom view - Accu - pack**



## 10. Additional Information supplementary to the Test Report

| Item | Description                                                                                      | No. of Pages |
|------|--------------------------------------------------------------------------------------------------|--------------|
| 1    | Technical documents including data sheet, circuit diagrams, positioning of components and layout | 12           |
| 2    | Application form for testing to I-ETS 300 330                                                    | 18           |