

PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



HEARING AID COMPATIBILITY

Applicant Name:

LG Electronics MobileComm U.S.A. Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 United States Date of Testing: 04/30/2018 - 05/09/2018 Test Site/Location: PCTEST Lab, Columbia, MD, USA Test Report Serial No.: 1M1803280056-10-R1.ZNF

FCC ID: ZNFQ710CS

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A. INC.

Scope of Test: Audio Band Magnetic Testing (T-Coil)

Application Type: Certification
FCC Rule Part(s): CFR §20.19(b)
HAC Standard: ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

DUT Type: Portable Handset **Model:** LM-Q710CS

Additional Model(s): LMQ710CS, Q710CS

Test Device Serial No.: Pre-Production Sample [S/N: 02185, 02235]

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

Note: This revised Test Report (S/N: 1M1803280056-10-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.







FCC ID: ZNFQ710CS	PCTEST VICINITIAN LABORATIVA INC.	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 1 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 1 of 74

TABLE OF CONTENTS

1.	INTRODUCTION	
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	6
4.	METHOD OF MEASUREMENT	8
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	18
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	20
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	23
8.	FCC 3G MEASUREMENTS	26
9.	T-COIL TEST SUMMARY	27
10.	MEASUREMENT UNCERTAINTY	37
11.	EQUIPMENT LIST	38
12.	TEST DATA	39
13.	CALIBRATION CERTIFICATES	62
14.	CONCLUSION	69
15.	REFERENCES	70
16.	TEST SETUP PHOTOGRAPHS	72

FCC ID: ZNFQ710CS	HAC (T-COIL) TEST REPORT		LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 2 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 2 of 74

INTRODUCTION 1.

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-86581 to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 3 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 3 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

2. DUT DESCRIPTION



FCC ID: ZNFQ710CS

Applicant: LG Electronics MobileComm U.S.A. Inc.

1000 Sylvan Avenue

Englewood Cliffs, NJ 07632

United States

Model: LM-Q710CS

Additional Model(s): LMQ710CS, Q710CS

Serial Number: 02185, 02235

HW Version: Rev.1.0
SW Version: Q710CS06g
Antenna: Internal Antenna
DUT Type: Portable Handset

I. Device Serial Numbers

Several samples with identical hardware were used to support HAC testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical, and thermal characteristics are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 9.

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 4 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 4 of 74

Table 2-1 ZNFQ710CS HAC Air Interfaces

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service
	850	VO	Yes	Yes: WIFI or BT	CMRS Voice*
GSM	1900	VO	163	res. Wiri di Bi	CIVINS VOICE
	GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo**
	850				
UMTS	1700	VD	Yes	Yes: WIFI or BT	CMRS Voice*
UIVITS	1900				
	HSPA	VD	Yes	Yes: WIFI or BT	Google Duo**
	700 (B12)	VD	Yes	Yes: WIFI or BT	VoLTE*, Google Duo**
	790 (B14)				
LTE (FDD)	850 (B5)				
LIE (FDD)	1700 (B4)				
	1900 (B2)				
	2300 (B30)				
	2450				
	5200 (U-NII 1)			Yes Yes: GSM, UMTS, or LTE	VoWIFI**, Google Duo**
WIFI	5300 (U-NII 2A)	VD	Yes		
	5500 (U-NII 2C)				
	5800 (U-NII 3)				
ВТ	2450	DT	No	Yes: GSM, UMTS, or LTE	N/A
Type Transport VO = Voice Only The Digital Data - Not intended for CMRS Service VD = CMRS and IP Voice over Data Transport Notes: * Reference level in accordance with 7.4.2.1 of ANSI C63.19-2011 and July 2012 C63 VoLTE Interpretation. ** Reference level is -20dBm0 in accordance with FCC KDB 285076 D02			,		

FCC ID: ZNFQ710CS	HAC (T-COIL) TEST REPORT		1 LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg F of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 5 of 74

3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

I. MAGNETIC COUPLING

Axial and Radial Field Intensity

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be \geq -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz




Figure 3-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds
-15 dB(A/m) at 1 kHz

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Dogo 6 of 74	
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 6 of 74	

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

Signal Quality

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Catamani	Telephone RF Parameters		
Category	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]		
T1	0 to 10 dB		
T2	10 to 20 dB		
Т3	20 to 30 dB		
T4	> 30 dB		
Table 3-1 Magnetic Coupling Parameters			

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFQ710CS	PCTEST*			Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 7 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 7 of 74

4. METHOD OF MEASUREMENT

I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 4-1
Validation Setup with Helmholtz Coil




Figure 4-2 T-Coil Test Setup

FCC ID: ZNFQ710CS	PCTEST INCHES ASSESSED IN NO.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 8 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		rage o oi 74

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size:

0.1 mm

Maximum speed
6.1 cm/sec

Line Voltage:
115 VAC

Line Frequency:
60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T

Active Frequency 100 Hz – 8 kHz

Range:

Stimulus Type: Male and Female, no spaces

Single Sample 20.96 seconds Duration:

Activity Level: 100%




Figure 4-4 Spectral Characteristic of full P.50





Figure 4-5Temporal Characteristic of full P.50

FCC ID: ZNFQ710CS	PCTEST INCHES ASSESSED IN NO.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 9 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 9 01 74



ABM2 Measurement Block Diagram:



Figure 4-6 Magnetic Measurement Processing Steps

IV. Test Procedure

- 1. Ambient Noise Check per C63.19 §7.3.1
 - Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
 - b. "A-weighting" and Half-Band Integration was applied to the measurements.
 - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation(See Figure 4-1)
 - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
 - ABM1 Validation
 The magnetic field at the center of the Helmholtz coil is

The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where H_c = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.13m0.08m; R=10.193 Ω 10.2 Ω and using V=29mV18mV:

$$H_c = \frac{20 \cdot (\frac{0.029}{10.193})}{0.13 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$


$$H_c = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 10 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 10 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of $-10 \, dB(A/m)$ in the center of the Helmholtz coil which was used to validate the probe measurement at $-10 \, dB(A/m)$. This was verified to be within $\pm 0.5 \, dB$ of the $-10 \, dB(A/m)$ value (see Page 34).

c. Frequency Response Validation The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:




d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFQ710CS	PCTEST INCIDENCE LABORATORA, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 11 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 11 of 74







Figure 4-8 **ABM2 Frequency Response Validation**

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and Aweighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2 **ABM2 Power Sum Validation**

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 12 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 12 01 74

© 2018 PCTEST Engineering Laboratory, Inc.






Figure 4-10
ABM2 Power Sum Validation

3. Measurement Test Setup

- a. Fine scan above the WD (TEM)
 - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):



Measurement Distance



- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-15 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
 - i. C63.19 Table 7-1 states audio reference input levels for various technologies:

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 13 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 13 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN™	TDMA (22 and 11 Hz)	-18

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- iii. See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.
- c. Real-Time Analyzer (RTA)
 - i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.
- d. WD Radio Configuration Selection
 - i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 8 for more information regarding worst-case configurations for UMTS. LTE configuration information can be found in Section 5. WIFI configuration information can be found in Section 6 and 7.):




Figure 4-13
Vocoder Analysis for ABM Noise for GSM

- 4. Signal Quality Data Analysis
 - a. Narrow-band Magnetic Intensity
 - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.
 - b. Frequency Response
 - i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.

FCC ID: ZNFQ710CS	PCTEST INCHES ASSESSED IN NO.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 14 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 14 01 74

- ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
- iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.

c. Signal Quality Index

- i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
- ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
- iii. This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

V. Test Setup




Figure 4-14
Audio Magnetic Field Test Setup

VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to inaccessibility of RF ports with battery installed.

VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

VIII. Wireless Device Channels and Frequencies

1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes since circuit-switched voice modes were worst-case.

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 15 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 15 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

Table 4-3
Center Channels and Frequencies

Test frequencies & associated channels				
Channel	Frequency (MHz)			
Cellular 850				
190 (GSM)	836.60			
4183 (UMTS)	836.60			
AWS 1750				
1412 (UMTS)	1730.40			
PCS 1900				
661 (GSM) 1880				
9400 (UMTS)	1880			

2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. The middle channel and supported bandwidths from the worst-case band according to Table 7-5 was additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-4 to 9-9 and Table 9-16 for LTE bandwidths and channels.

3. WIFI

The middle channel for each 802.11 standard was tested for each probe orientation. The 2.4GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. The 5GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested on higher U-NII bands as well as applicable low and high channels. See Tables 9-10 to 9-13 and Tables 9-17 to 9-20 for WIFI standards and channels.

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 16 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 10 01 74

IX. **Test Flow**

The flow diagram below was followed (From C63.19):




Figure 4-15 C63.19 T-Coil Signal Test Process

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 17 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 17 of 74

© 2018 PCTEST Engineering Laboratory, Inc.

VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION 5.

I. Test System Setup for VoLTE over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1 Test Setup for VoLTE over IMS T-Coil Measurements

2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

* http://c63.org/documents/misc/posting/new_interpretations.htm

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 18 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		rage 10 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

II. **DUT Configuration for VoLTE over IMS T-coil Testing**

1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. 16QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

> Table 5-1 Vol.TE over IMS SNNR by Radio Configuration

VOLTE OVER INIO CHARLES Y RAGIO COMINGUIALION										
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]		
1880.0	18900	20	QPSK	1	0	5.83	-44.22	50.05		
1880.0	18900	20	QPSK	1	50	5.94	-44.90	50.84		
1880.0	18900	20	QPSK	1	99	5.82	-44.47	50.29		
1880.0	18900	20	QPSK	50	0	5.86	-45.04	50.90		
1880.0	18900	20	QPSK	50	25	5.54	-46.21	51.75		
1880.0	18900	20	QPSK	50	50	5.81	-45.18	50.99		
1880.0	18900	20	QPSK	100	0	5.90	-46.17	52.07		
1880.0	18900	20	16QAM	1	0	5.66	-40.73	46.39		
1880.0	18900	20	16QAM	1	50	6.10	-41.49	47.59		
1880.0	18900	20	16QAM	1	99	6.04	-41.44	47.48		
1880.0	18900	20	16QAM	50	0	6.22	-44.67	50.89		
1880.0	18900	20	16QAM	50	25	6.17	-45.28	51.45		
1880.0	18900	20	16QAM	50	50	6.20	-44.45	50.65		
1880.0	18900	20	16QAM	100	0	6.14	-45.60	51.74		


2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 5-2 AMR Codec Investigation - VolTE over IMS

	, ,,,,		roonganon		• • • • • • • • • • • • • • • • • • • •		
Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	-0.64	-1.71	6.23	5.76			
ABM2 (dBA/m)	-39.50	-39.73	-39.75	-39.90	Axial	LTE Band 2 20MHz	18900
Frequency Response	Pass	Pass	Pass	Pass			
S+N/N (dB)	38.86	38.02	45.98	45.66			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"



Audio Band Magnetic Curve Measurement Block Diagram

	v		•	
FCC ID: ZNFQ710CS	INCIRCLASCE TON INC	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 19 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 19 01 74

6. VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoWIFI over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1
Test Setup for VoWIFI over IMS T-Coil Measurements

2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level². The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

² FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

1 00 Office of Engineer	ing and recimology RDB, 20	COUTE BOZ T CON TESTING TO CIVILE II	voo, ooptember 10, 2	2017
FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	(L) LG	Approved by: Quality Manager
				Quality Manager
Filename:	Test Dates:	DUT Type:		Page 20 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 20 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

DUT Configuration for VoWIFI over IMS T-coil Testing II.

1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each 802.11 standard:

> Table 6-1 802.11b SNNR by Radio Configuration

COZITIS CITIENTS TRACTO COMINGUIGATION								
Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]		
802.11b	6	DSSS	1	-6.13	-42.64	36.51		
802.11b	6	DSSS	2	-6.38	-40.61	34.23		
802.11b	6	CCK	5.5	-6.44	-40.52	34.08		
802.11b	6	CCK	11	-6.66	-41.07	34.41		

Table 6-2 802.11g/a SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11g	6	BPSK	6	-6.32	-45.25	38.93
802.11g	6	BPSK	9	-6.31	-45.17	38.86
802.11g	6	QPSK	12	-6.19	-41.43	35.24
802.11g	6	QPSK	18	-6.43	-44.71	38.28
802.11g	6	16-QAM	24	-6.46	-46.16	39.70
802.11g	6	16-QAM	36	-6.25	-44.13	37.88
802.11g	6	64-QAM	48	-6.39	-43.86	37.47
802.11g	6	64-QAM	54	-6.59	-44.15	37.56

Table 6-3 802 11n/ac 20MHz BW SNNR by Radio Configuration

802.1111/ac 20MHZ BW SNNK by Radio Configuration									
Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]		
802.11n	20	40	BPSK	6.5	-6.88	-36.26	29.38		
802.11n	20	40	QPSK	13	-6.85	-40.64	33.79		
802.11n	20	40	QPSK	19.5	-6.30	-39.30	33.00		
802.11n	20	40	16-QAM	26	-6.31	-37.43	31.12		
802.11n	20	40	16-QAM	39	-6.90	-40.09	33.19		
802.11n	20	40	64-QAM	52	-6.43	-38.73	32.30		
802.11n	20	40	64-QAM	58.5	-6.47	-38.59	32.12		
802.11n	20	40	64-QAM	65	-6.15	-41.52	35.37		
802.11ac	20	40	256-QAM	78	-6.46	-37.91	31.45		

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 24 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 21 of 74

Table 6-4 802.11n/ac 40MHz BW SNNR by Radio Configuration

	002.111/40 40/m1/2 BW Civity by Itaaio Configuration									
Mode	Bandwidth [MHz]	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]			
802.11n	40	38	BPSK	13.5	- 6.90	-36.59	29.69			
802.11n	40	38	QPSK	27	-6.88	-39.43	32.55			
802.11n	40	38	QPSK	40.5	-7.63	-39.72	32.09			
802.11n	40	38	16-QAM	54	- 7.69	-38.90	31.21			
802.11n	40	38	16-QAM	81	-6.25	-37.28	31.03			
802.11n	40	38	64-QAM	108	-6.29	-42.36	36.07			
802.11n	40	38	64-QAM	121.5	-6.68	-39.54	32.86			
802.11n	40	38	64-QAM	135	-6.84	-41.62	34.78			
802.11ac	40	38	256-QAM	162	-6.86	-36.89	30.03			
802.11ac	40	38	256-QAM	180	-6.32	-38.58	32.26			

2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.6kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 6-5 AMR Codec Investigation - VoWIFI over IMS

Awin Codec investigation - vovvii i over iwis									
Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel	
ABM1 (dBA/m)	-5.36	-6.04	-3.67	-2.67		Axial 2.4GHz	IEEE 802.11b	6	
ABM2 (dBA/m)	-42.24	-42.52	-43.26	-43.30	Avial				
Frequency Response	Pass	Pass	Pass	Pass	Axiai				
S+N/N (dB)	36.88	36.48	39.59	40.63					

Mute on; Backlight off; Max Volume; Max Contrast




Figure 6-2 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 22 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 22 of 74

OTT VOIP TEST SYSTEM AND DUT CONFIGURATION 7.

Test System Setup for OTT VoIP T-Coil Testing I.

1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 64kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation³. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

II. **DUT Configuration for OTT VolP T-Coil Testing**

1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 6kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

> Table 7-1 Codec Investigation - OTT VoIP (EDGE)

	mvoongan	,,, <u> </u>	<u> </u>	
Codec Setting:	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	9.45	9.17		
ABM2 (dBA/m)	-34.39	-33.90	Axial	204
Frequency Response	Pass	Pass	Axiai	661
S+N/N (dB)	43.84	43.07		

³ FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

1 00 Office of Engineer	ing and recimology RDD, 20	BOOTO BOZ T COM TESTING FOR CIVILE II	voo, ooptember 10, 2	2017
FCC ID: ZNFQ710CS	PCTEST INCHESTORS INC	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 23 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		1 age 23 01 74

Table 7-2 Codec Investigation - OTT VoIP (HSPA)

	mroongan		VII (1.101 / 1)	
Codec Setting:	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	8.89	9.65		
ABM2 (dBA/m)	-49.62	-48.45	Axial	9400
Frequency Response	Pass	Pass	Axiai	
S+N/N (dB)	58.51	58.10		

Table 7-3 Codec Investigation - OTT VolP (LTE)

Oddec investigation – OTT voil (ETE)											
Codec Setting:	64kbps	6kbps	Orientation	Band / BW	Channel						
ABM1 (dBA/m)	8.47	8.99			23095						
ABM2 (dBA/m)	-42.66	-39.91	Axial	LTE B12							
Frequency Response	Pass	Pass	Axiai	10MHz							
S+N/N (dB)	51.13	48.90									

Table 7-4 Codec Investigation - OTT VoIP (WIFI)

Codec Setting:	64kbps	6kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	9.04	8.72			IEEE 802.11b	6
ABM2 (dBA/m)	-41.22	-37.54	Avial	2.4.015		
Frequency Response	Pass	Pass	Axial	2.4 GHz		
S+N/N (dB)	50.26	46.26				

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.F




Figure 7-1 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 24 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 24 01 74

2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE band to be used for OTT VoIP testing. LTE Band 12 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE bands:

Table 7-5
OTT VoIP (LTE) SNNR by LTE Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2	1880.0	18900	20	16QAM	1	0	9.23	-39.46	48.69
4	1732.5	20175	20	16QAM	1	0	9.05	-39.59	48.64
5	836.5	20525	10	16QAM	1	0	8.97	-40.47	49.44
12	707.5	23095	10	16QAM	1	0	8.70	-39.08	47.78
14	793.0	23330	10	16QAM	1	0	8.96	-39.51	48.47
30	2310.0	27710	10	16QAM	1	0	8.75	-40.92	49.67

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 25 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 25 of 74

FCC 3G MEASUREMENTS 8.

I. **UMTS Test Configurations**

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:



Figure 8-1 **UMTS Audio Band Magnetic Noise**

Table 8-1 **Codec Investigation - UMTS**

		cc investigatio			
Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel
ABM1 (dBA/m)	-8.44	-7.88	-7.29		9538
ABM2 (dBA/m)	-48.98	-48.61	-48.28	Axial	
Frequency Response	Pass	Pass	Pass	Axidi	
S+N/N (dB)	40.54	40.73	40.99		

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC="All 1s"




Figure 8-2 Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 26 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 20 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

T-COIL TEST SUMMARY 9.

Table 9-1 **Consolidated Tabled Results**

			esponse rgin	Mag	netic / Verdict	FCC S	SNNR dict	Margin from FCC Limit	C63.19-2011
C63 19) Section	8.3.2		8.3	3.1	8.3.4		(dB)	Rating
		Axial	Radial	Axial	Radial	Axial	Radial		
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-3.56	Т3
	PCS	PASS	NA	PASS	PASS	PASS	PASS	0.00	10
EDGE	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-10.89	Т4
(OTT VoIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS	-10.03	1.7
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
UMTS	AWS	PASS	NA	PASS	PASS	PASS	PASS	-12.41	T4
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
HSPA (OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS	-27.33	T4
, ,	PCS	PASS	NA	PASS	PASS	PASS	PASS		
	B12	PASS	NA	PASS	PASS	PASS	PASS		
	B14	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD	B5	PASS	NA	PASS	PASS	PASS	PASS	-11.74	Т4
LIEFDD	B4	PASS	NA	PASS	PASS	PASS	PASS	-11.74	17
	B2	PASS	NA	PASS	PASS	PASS	PASS		
	B30	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD (OTT VoIP)	B12	PASS	NA	PASS	PASS	PASS	PASS	-21.27	T4
	802.11b	PASS	NA	PASS	PASS	PASS	PASS		
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-9.75	Т3
	802.11n	PASS	NA	PASS	PASS	PASS	PASS		
	802.11b	PASS	NA	PASS	PASS	PASS	PASS		
WLAN (OTT VoIP)	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-22.28	T4
,	802.11n	PASS	NA	PASS	PASS	PASS	PASS		
	802.11a	PASS	NA	PASS	PASS	PASS	PASS		
U-NII	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-13.24	T4
	802.11ac	PASS	NA	PASS	PASS	PASS	PASS		
U-NII	802.11a	PASS	NA	PASS	PASS	PASS	PASS	-22.17	T4
(OTT VoIP)	802.11n	PASS	NA	PASS	PASS	PASS	PASS	-22.17	14

FCC ID: ZNFQ710CS	PETEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 27 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 27 of 74

I. **Raw Handset Data**

Table 9-2 **Raw Data Results for GSM**

Mode	Orientation	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		128	02185	3.71	-21.04		1.43	24.75	20.00	-4.75	T3	
	Axial	190	02185	3.68	-20.70	-63.43	1.42	24.38	20.00	-4.38	T3	1.6, 3.4
GSM850		251	02185	3.73	-20.24		1.42	23.97	20.00	-3.97	T3	
GSW630		128	02185	-0.83	-24.84			24.01	20.00	-4.01	T3	
	Radial	190	02185	-0.73	-24.36	-63.11	N/A	23.63	20.00	-3.63	T3	2.2, 4.4
		251	02185	-0.82	-24.38			23.56	20.00	-3.56	T3	
		512	02185	3.67	-24.55		1.40	28.22	20.00	-8.22	Т3	
	Axial	661	02185	3.68	-24.80	-63.43	1.41	28.48	20.00	-8.48	Т3	1.6, 3.4
GSM1900		810	02185	3.66	-25.00		1.41	28.66	20.00	-8.66	T3	
GSWI1900		512	02185	-0.88	-28.17			27.29	20.00	-7.29	T3	
	Radial	661	02185	-0.87	-28.65	-63.11	N/A	27.78	20.00	-7.78	T3	2.2, 4.4
		810	02185	-0.78	-28.65			27.87	20.00	-7.87	T3	

Table 9-3 **Raw Data Results for UMTS**

Mode	Orientation	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		4132	02185	-9.94	-50.10		2.00	40.16	20.00	-20.16	T4	
	Axial	4183	02185	-9.79	-50.60	-63.43	2.00	40.81	20.00	-20.81	T4	1.6, 3.4
UMTS V		4233	02185	-10.61	-50.07		2.00	39.46	20.00	-19.46	T4	
OWITS		4132	02185	-17.59	-51.15			33.56	20.00	-13.56	T4	
	Radial	4183	02185	-17.84	-52.61	-63.11	N/A	34.77	20.00	-14.77	T4	2.2, 4.4
		4233	02185	-17.36	-53.57			36.21	20.00	-16.21	T4	
		1312	02185	-9.40	-49.61		2.00	40.21	20.00	-20.21	T4	
	Axial	1412	02185	-9.35	-49.59	-63.43	2.00	40.24	20.00	-20.24	T4	1.6, 3.4
LIMTO IV		1513	02185	-8.74	-49.46	1	2.00	40.72	20.00	-20.72	T4	
UMTS IV		1312	02185	-17.71	-52.84			35.13	20.00	-15.13	T4	
	Radial	1412	02185	-17.69	-52.68	-63.11	N/A	34.99	20.00	-14.99	T4	2.2, 4.4
		1513	02185	-17.27	-52.96			35.69	20.00	-15.69	T4	
		9262	02185	-9.43	-49.91		2.00	40.48	20.00	-20.48	T4	
	Axial	9400	02185	-9.69	-49.95	-63.43	2.00	40.26	20.00	-20.26	T4	1.6, 3.4
LIMTO		9538	02185	-9.08	-48.79		2.00	39.71	20.00	-19.71	T4	
UMTS II		9262	02185	-17.91	-50.32			32.41	20.00	-12.41	T4	
	Radial	9400	02185	-17.65	-50.24	-63.11	N/A	32.59	20.00	-12.59	T4	2.2, 4.4
		9538	02185	-17.67	-50.69			33.02	20.00	-13.02	T4	

Table 9-4 **Raw Data Results for LTE B12**

Mode	Orientation	Bandwidth	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		10MHz	23095	02185	-1.93	-39.73		1.66	37.80	20.00	-17.80	T4	
	Axial	5MHz	23095	02185	-1.68	-39.37	-63.43	1.52	37.69	20.00	-17.69	T4	1.6. 3.4
	Axidi	3MHz	23095	02185	-1.66	-39.14	-03.43	1.51	37.48	20.00	-17.48	T4	1.0, 3.4
LTE Band		1.4MHz	23095	02185	-2.17	-40.06		1.55	37.89	20.00	-17.89	T4	
12		10MHz	23095	02185	-11.44	-44.97			33.53	20.00	-13.53	T4	
	Radial	5MHz	23095	02185	-11.49	-46.34	-63.11	N/A	34.85	20.00	-14.85	T4	2.2. 4.4
	Naulai	3MHz	23095	02185	-11.85	-45.82	-03.11	IN/A	33.97	20.00	-13.97	T4	2.2, 4.4
		1.4MHz	23095	02185	-11.90	-46.15			34.25	20.00	-14.25	T4	

Table 9-5 Raw Data Results for LTE B14

					att Date								
Mode	Orientation	Bandwidth	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	10MHz	23330	02185	-2.00	-41.47	-63.43	1.54	39.47	20.00	-19.47	T4	1.6. 3.4
LTE Band	Axiai	5MHz	23330	02185	-1.94	-43.20	-03.43	1.56	41.26	20.00	-21.26	T4	1.0, 3.4
14	Radial	10MHz	23330	02185	-11.68	-43.72	-63.11	N/A	32.04	20.00	-12.04	T4	2.2, 4.4
	radial	5MHz	23330	02185	-11.27	-44.58	-03.11	IN/A	33.31	20.00	-13.31	T4	2.2, 4.4

FCC ID: ZNFQ710CS	PCTEST INCIDENCE LABORATORA, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 28 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 20 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

Table 9-6 Raw Data Results for LTE B5

					~ ~ ~								
Mode	Orientation	Bandwidth	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		10MHz	20525	02185	-1.76	-42.63		1.61	40.87	20.00	-20.87	T4	
	Axial	5MHz	20525	02185	-2.07	-41.68	-63.43	1.64	39.61	20.00	-19.61	T4	1.6, 3.4
	Axidi	3MHz	20525	02185	-1.72	-40.20	-03.43	1.63	38.48	20.00	-18.48	T4	1.0, 3.4
		1.4MHz	20525	02185	-2.10	-40.54		1.67	38.44	20.00	-18.44	T4	
LTE Band 5		10MHz	20525	02185	-11.75	-45.06			33.31	20.00	-13.31	T4	
LIE Ballu 5		5MHz	20625	02185	-11.47	-46.36			34.89	20.00	-14.89	T4	
	Radial	5MHz	20525	02185	-11.81	-43.82	-63.11	N/A	32.01	20.00	-12.01	T4	2.2. 4.4
	ixaulai	5MHz	20425	02185	-11.57	-46.88	-03.11	IN/PA	35.31	20.00	-15.31	T4	2.2, 4.4
		3MHz	20525	02185	-11.48	-43.81			32.33	20.00	-12.33	T4	
		1.4MHz	20525	02185	-11.87	-44.14			32.27	20.00	-12.27	T4]

Table 9-7 Raw Data Results for LTE B4

	Frequency Margin from														
Mode	Orientation	Bandwidth	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
		20MHz	20175	02185	-1.64	-40.29		1.60	38.65	20.00	-18.65	T4			
		15MHz	20175	02185	-1.83	-39.13		1.61	37.30	20.00	-17.30	T4			
		10MHz	20175	02185	-1.84	-38.84		1.62	37.00	20.00	-17.00	T4			
	Axial	5MHz	20175	02185	-2.27	-39.21	-63.43	1.53	36.94	20.00	-16.94	T4	1.6, 3.4		
	Axidi	3MHz	20385	02185	-1.74	-40.86	-03.43	1.60	39.12	20.00	-19.12	T4	1.0, 3.4		
		3MHz	20175	02185	-1.92	-38.73		1.54	36.81	20.00	-16.81	T4			
LTE Band 4		3MHz	19965	02185	-1.74	-40.16		1.64	38.42	20.00	-18.42	T4			
LIE Ballu 4		1.4MHz	20175	02185	-1.77	-39.09		1.59	37.32	20.00	-17.32	T4			
		20MHz	20175	02185	-11.49	-43.63			32.14	20.00	-12.14	T4			
		15MHz	20175	02185	-11.88	-42.67			30.79	20.00	-10.79	T4			
	Radial	10MHz	20175	02185	-11.77	-42.03	-63.11	N/A	30.26	20.00	-10.26	T4	2.2.4.4		
	radiai	5MHz	20175	02185	-11.73	-42.07	-03.11	IN/A	30.34	20.00	-10.34	T4	2.2, 4.4		
		3MHz	20175	02185	-11.39	-41.54			30.15	20.00	-10.15	T4			
		1.4MHz	20175	02185	-11.24	-42.72			31.48	20.00	-11.48	T4			

Table 9-8 Raw Data Results for LTE B2

	NAW DATA RESUITS IOI LIL DZ													
Mode	Orientation	Bandwidth	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		20MHz	18900	02185	-1.66	-39.26		1.59	37.60	20.00	-17.60	T4		
		15MHz	18900	02185	-2.11	-39.69		1.61	37.58	20.00	-17.58	T4		
	Axial	10MHz	18900	02185	-1.95	-39.38	-63.43	1.54	37.43	20.00	-17.43	T4	1.6, 3.4	
	Axidi	5MHz	18900	02185	-2.13	-40.62	-03.43	1.61	38.49	20.00	-18.49	T4	1.0, 3.4	
		3MHz	18900	02185	-1.86	-40.91		1.61	39.05	20.00	-19.05	T4		
LTE Band 2		1.4MHz	18900	02185	-2.06	-41.37		1.53	39.31	20.00	-19.31	T4		
LIE Ballu Z		20MHz	18900	02185	-11.54	-43.49			31.95	20.00	-11.95	T4		
		15MHz	18900	02185	-11.52	-43.26			31.74	20.00	-11.74	T4		
	Radial	10MHz	18900	02185	-11.69	-43.81	-63.11	N/A	32.12	20.00	-12.12	T4	2.2, 4.4	
	radial	5MHz	18900	02185	-11.82	-44.48	-03.11	IN/A	32.66	20.00	-12.66	T4	2.2, 4.4	
		3MHz	18900	02185	-11.68	-44.23			32.55	20.00	-12.55	T4		
		1.4MHz	18900	02185	-11.69	-43.91			32.22	20.00	-12.22	T4		

Table 9-9 Raw Data Results for LTE B30

ı	Mode	Orientation	Bandwidth	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	LTE Band Axial	Avial	10MHz	27710	02185	-2.22	-41.07	-63.43	1.72	38.85	20.00	-18.85	T4	1.6, 3.4
LT		5MHz	27710	02185	-1.84	-42.33	-03.43	1.56	40.49	20.00	-20.49	T4	1.0, 3.4	
	30	Radial	10MHz	27710	02185	-11.13	-43.99	-63.11	N/A	32.86	20.00	-12.86	T4	2.2, 4.4
		Naulai	5MHz	27710	02185	-11.57	-45.42	-03.11	IN/A	33.85	20.00	-13.85	T4	2.2, 4.4

FCC ID: ZNFQ710CS	X INCIRCTANG LABORATORS, INC.		LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 29 of 74

Table 9-10 Raw Data Results for 2.4GHz WIFI

	Train Buta Noodito for Elifotti VIII I													
Mode	Orientation	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
WLAN	Axial	6	02235	-6.31	-40.95	-63.18	1.66	34.64	20.00	-14.64	T4	1.6, 3.4		
802.11b	Radial	6	02235	-14.69	-47.09	-63.00	N/A	32.40	20.00	-12.40	T4	2.2, 4.4		
WLAN	Axial	6	02235	-6.83	-44.11	-63.18	1.71	37.28	20.00	-17.28	T4	1.6, 3.4		
802.11g	Radial	6	02235	-14.81	-50.49	-63.00	N/A	35.68	20.00	-15.68	T4	2.2, 4.4		
		1	02235	-7.12	-40.35		1.73	33.23	20.00	-13.23	T4			
	Axial	6	02235	-7.10	-40.22	-63.18	1.61	33.12	20.00	-13.12	T4	1.6, 3.4		
WLAN		11	02235	-6.49	-41.32	Ī	1.75	34.83	20.00	-14.83	T4			
802.11n		1	02235	-15.14	-48.65			33.51	20.00	-13.51	T4			
	Radial	6	02235	-14.80	-44.55	-63.00	N/A	29.75	20.00	-9.75	T3	2.2, 4.4		
		11	02235	-15.54	-47.22			31.68	20.00	-11.68	T4			

Table 9-11 Raw Data Results for 5GHz WIFI 802.11a

Transport Marcin from														
Mode	Orientation	Bandwidth	U-NII	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	1	36	02235	-7.16	-44.75		1.74	37.59	20.00	-17.59	T4	
		20MHz	1	40	02235	-6.59	-43.51		1.63	36.92	20.00	-16.92	T4	
	Axial	20MHz	1	48	02235	-6.95	-45.59	-63.18	1.54	38.64	20.00	-18.64	T4	1.6, 3.4
	Axiai	20MHz	2A	56	02235	-7.01	-44.27	-03.10	1.56	37.26	20.00	-17.26	T4	1.0, 3.4
		20MHz	2C	120	02235	-6.54	-43.94		1.60	37.40	20.00	-17.40	T4	
		20MHz	3	157	02235	-7.13	-44.40		1.78	37.27	20.00	-17.27	T4	
802.11a														
		20MHz	1	40	02235	-14.69	-49.44			34.75	20.00	-14.75	T4	
		20MHz	2A	56	02235	-15.30	-49.33			34.03	20.00	-14.03	T4	
	Radial	20MHz	2C	100	02235	-15.11	-48.76	-63.00	N/A	33.65	20.00	-13.65	T4	2.2, 4.4
	radiai	20MHz	2C	120	02235	-15.27	-48.51	-03.00	IWA	33.24	20.00	-13.24	T4	2.2, 4.4
		20MHz	2C	140	02235	-14.88	-49.69			34.81	20.00	-14.81	T4	
		20MHz	3	157	02235	-15.56	-48.90			33.34	20.00	-13.34	T4	

Table 9-12 Raw Data Results for 5GHz WIFI 802.11n

Me	ode	Orientation	Bandwidth	U-NII	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		Axial	40MHz	1	38	02235	-7.16	-44.93	-63.18	1.78	37.77	20.00	-17.77	T4	1.6, 3.4
			20MHz	1	40	02235	-6.49	-45.28	-03.10	1.57	38.79	20.00	-18.79	T4	1.0, 5.4
802	802.11n														
		Radial	40MHz	1	38	02235	-15.44	-50.25	-63.00	N/A	34.81	20.00	-14.81	T4	2.2.4.4
			20MHz	1	40	02235	-15.38	-50.43	-03.00	IN/A	35.05	20.00	-15.05	T4	2.2, 4.4

Table 9-13 Raw Data Results for 5GHz WIFI 802.11ac

	Mode	Orientation	Bandwidth	U-NII	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
I		Axial	40MHz	1	38	02235	-6.51	-43.70	-63.18	1.66	37.19	20.00	-17.19	T4	1.6, 3.4
			20MHz	1	40	02235	-7.05	-44.60	-03.10	1.65	37.55	20.00	-17.55	T4	1.0, 3.4
	802.11ac														
ı		Padial	40MHz	1	38	02235	-15.05	-52.48	-63.00	N/A	37.43	20.00	-17.43	T4	2.2.4.4
		Radial	20MHz	1	40	02235	-15.47	-50.71	-63.00	INA	35.24	20.00	-15.24	T4	2.2, 4.4

Table 9-14 Raw Data Results for EDGE (OTT VoIP)

Mode	Orientation	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
EDGE85	Axial	190	02185	8.97	-35.36	-63.43	1.72	44.33	20.00	-24.33	T4	1.6, 3.4
EDGE85	Radial	190	02185	-0.84	-31.73	-63.11	N/A	30.89	20.00	-10.89	T4	2.2, 4.4
EDGE190	Axial	661	02185	9.07	-33.88	-63.43	1.72	42.95	20.00	-22.95	T4	1.6, 3.4
EDGE190	Radial	661	02185	-0.57	-33.30	-63.11	N/A	32.73	20.00	-12.73	T4	2.2, 4.4

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 74
1M1803280056-10-R1.ZNF 04/30/2018 - 05/09/2018		Portable Handset		Page 30 of 74

Table 9-15 Raw Data Results for HSPA (OTT VoIP)

						• • • • • •	. , , ₍	, , , , , , , , , , , , , , , , , , ,				
Mode	Orientation	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
HSPA V	Axial	4183	02185	9.17	-48.71	-63.43	1.67	57.88	20.00	-37.88	T4	1.6, 3.4
погач	Radial	4183	02185	-0.67	-48.00	-63.11	N/A	47.33	20.00	-27.33	T4	2.2, 4.4
HSPA IV	Axial	1412	02185	9.67	-46.99	-63.43	1.69	56.66	20.00	-36.66	T4	1.6, 3.4
порату	Radial	1412	02185	-0.42	-49.88	-63.11	N/A	49.46	20.00	-29.46	T4	2.2, 4.4
HSPA II	Axial	9400	02185	9.34	-45.81	-63.43	1.70	55.15	20.00	-35.15	T4	1.6, 3.4
пораш	Radial	9400	02185	-0.62	-49.81	-63.11	N/A	49.19	20.00	-29.19	T4	2.2, 4.4

Table 9-16 Raw Data Results for LTE B12 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	Battery Cover	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		10MHz	23095	02185	9.58	-39.36		1.81	48.94	20.00	-28.94	T4	
		5MHz	23155	02185	9.56	-41.64		1.76	51.20	20.00	-31.20	T4	
	Avial	5MHz	23095	02185	9.27	-38.85	-63.43	1.81 48.94 20 1.76 51.20 20 1.66 48.12 20 1.64 50.65 20 1.68 48.58 20 1.68 48.58 20 41.50 20 44.57 20	20.00	-28.12	T4	1.6, 3.4	
		5MHz	23035	02185	9.08	-41.57	-03.43	1.64	50.65	20.00	-30.65	T4	1.0, 3.4
		3MHz	23095	02185	9.18	-39.47		1.51	48.65	20.00	-28.65	T4	
LTE Band		1.4MHz	23095	02185	9.14	-39.44		1.68	48.58	20.00	-28.58	T4	
12		10MHz	23095	02185	-0.95	-42.45			41.50	20.00	-21.50	T4	
		5MHz	23155	02185	-0.43	-45.00			44.57	20.00	-24.57	T4	
	Radial	5MHz	23095	02185	-0.67	-41.94	-63.11	N/A	41.27	20.00	-21.27	T4	2.2. 4.4
	Radiai	5MHz	23035	02185	-0.60	-45.51	-03.11	N/A	44.91	20.00	-24.91	T4	2.2, 4.4
		3MHz	23095	02185	-0.57	-42.12			41.55	20.00	-21.55	T4	
		1.4MHz	23095	02185	-0.67	-42.92			42.25	20.00	-22.25	T4	

Table 9-17 Raw Data Results for 2.4GHz WIFI (OTT VoIP)

Mode	Orientation	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	02235	8.72	-37.53		1.64	46.25	20.00	-26.25	T4	
	Axial	6	02235	8.92	-37.84	-63.18	1.79	46.76	20.00	-26.76	T4	1.6, 3.4
WLAN		11	02235	9.04	-41.23	İ	1.69	50.27	20.00	-30.27	T4	
802.11b		1	02235	-0.03	-43.59			43.56	20.00	-23.56	T4	
	Radial	6	02235	-0.55	-44.00	-63.00	N/A	43.45	20.00	-23.45	T4	2.2, 4.4
	Radiai	11	02235	-0.09	-43.33	Ī		43.24	20.00	-23.24	T4	
WLAN	Axial	6	02235	9.03	-42.60	-63.18	1.69	51.63	20.00	-31.63	T4	1.6, 3.4
802.11g	Radial	6	02235	0.14	-46.32	-63.00	N/A	46.46	20.00	-26.46	T4	2.2, 4.4
WLAN	Axial	6	02235	8.37	-40.55	-63.18	1.50	48.92	20.00	-28.92	T4	1.6, 3.4
802.11n	Radial	6	02235	-0.18	-47.60	-63.00	N/A	47.42	20.00	-27.42	T4	2.2, 4.4

Table 9-18 Raw Data Results for 5GHz WIFI 802.11a (OTT VoIP)

			1.70	att Dutt	i i voodi	1010	OIIZ II	111 1 002	. ı ıu ₁ 0	11 1011				
Mode	Orientation	Bandwidth	U-NII	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	20MHz	1	40	02235	8.33	-37.33	-63.18	1.80	45.66	20.00	-25.66	T4	1.6, 3.4
802.11a														
	Radial	20MHz	1	40	02235	0.25	-46.77	-63.00	N/A	47.02	20.00	-27.02	T4	2.2, 4.4

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 24 of 74
1M1803280056-10-R1.ZNF	1M1803280056-10-R1.ZNF 04/30/2018 - 05/09/2018			Page 31 of 74

Table 9-19 Raw Data Results for 5GHz WIFI 802.11n (OTT VoIP)

Mode	Orientation	Bandwidth	U-NII	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		40MHz	1	38	02235	8.36	-37.49		1.71	45.85	20.00	-25.85	T4	
		20MHz	1	36	02235	7.74	-35.30		1.82	43.04	20.00	-23.04	T4	
		20MHz	1	40	02235	8.05	-35.94		1.81	43.99	20.00	-23.99	T4	
		20MHz	1	48	02235	8.19	-39.29		1.86	47.48	20.00	-27.48	T4	
	Axial	40MHz	2A	54	02235	8.92	-35.33	-63.18	1.63	44.25	20.00	-24.25	T4	1.6, 3.4
	Axiai	20MHz	2A	56	02235	7.68	-37.68	-03.10	1.65	45.36	20.00	-25.36	T4	1.0, 3.4
		40MHz	2C	110	02235	8.32	-38.97		1.72	47.29	20.00	-27.29	T4	
		20MHz	2C	116	02235	8.23	-37.90		1.36	46.13	20.00	-26.13	T4	
		40MHz	3	151	02235	7.99	-37.46		1.95	45.45	20.00	-25.45	T4	
		20MHz	3	157	02235	8.26	-37.34		1.46	45.60	20.00	-25.60	T4	
802.11n														
		40MHz	1	38	02235	-0.70	-46.88			46.18	20.00	-26.18	T4	
		20MHz	1	36	02235	-0.81	-46.11			45.30	20.00	-25.30	T4	
		20MHz	1	40	02235	-0.28	-42.45			42.17	20.00	-22.17	T4	
		20MHz	1	48	02235	-0.72	-46.01			45.29	20.00	-25.29	T4	
	Dedict	40MHz	2A	54	02235	-0.54	-46.05	62.00	NIA	45.51	20.00	-25.51	T4	20.44
	Radial	20MHz	2A	56	02235	-0.43	-47.59	-63.00	N/A	47.16	20.00	-27.16	T4	2.2, 4.4
		40MHz	2C	110	02235	-0.58	-46.45			45.87	20.00	-25.87	T4	
		20MHz	2C	116	02235	-0.33	-46.67			46.34	20.00	-26.34	T4	1
	-	40MHz	3	151	02235	-0.25	-45.97			45.72	20.00	-25.72	T4	
		20MHz	3	157	02235	-0.31	-50.06			49.75	20.00	-29.75	T4	

Table 9-20 Raw Data Results for 5GHz WIFI 802.11ac (OTT VoIP)

						• . • · •	· · · · · ·				• ,			
Mode	Orientation	Bandwidth	U-NII	Channel	Device SN	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	40MHz	1	38	02235	8.09	-41.26	-63.18	1.38	49.35	20.00	-29.35	T4	1.6, 3.4
		20MHz	1	40	02235	7.88	-37.66	-03.10	1.43	45.54	20.00	-25.54	T4	1.0, 5.4
802.11ac														
	Padial	40MHz	1	38	02235	-0.18	-49.71	-63.00	N/A	49.53	20.00	-29.53	T4	2.2, 4.4
Radial	20MHz	1	40	02235	-0.17	-44.22	-03.00	IVA	44.05	20.00	-24.05	T4	2.2, 4.4	

II. Test Notes

A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- Hearing Aid Mode (Phone→Call Settings→Additional Settings→Hearing aids) as well as Noise Suppression Mode (Phone→Call Settings→Additional Settings→Noise Suppression) was set to ON for Frequency Response compliance.
- 4. Speech Signal: ITU-T P.50 Artificial Voice
- 5. Bluetooth and WIFI were disabled for 2G/3G/4G modes while testing.
- 6. Licensed data modes and Bluetooth were disabled for WIFI modes while testing.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

B. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

C. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 32 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 32 01 74

D. LTE FDD

- Power Configuration: TPC = "Max Power"
- Radio Configuration: 16QAM, 1RB, 0RB offset
- 3. Vocoder Configuration: WB AMR 6.60kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 4 at 3MHz is the worst-case for the Axial probe orientation. LTE Band 5 at 5MHz bandwidth is the worst-case for the Radial probe orientation.

E. WIFI


- 1. Radio Configuration
 - a. 802.11b: CCK, 5.5Mbps
 - b. 802.11g/a: QPSK, 12Mbps
 - 802.11n/ac 20MHz: BPSK, 6.5Mbps
 - 802.11n/ac 40MHz: BPSK, 13.5Mbps
- 2. Vocoder Configuration: WB AMR 6.6kbps
- 3. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11n is the worst-case for both Axial and radial probe orientations.
- The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11a (U-NII 1) is the worst-case for the Axial probe orientation. 802.11a (U-NII 2C) is the worst-case for the Radial probe orientation.

F. OTT VolP


- 1. Vocoder Configuration: 6kbps
- 2. EvDO Configuration
 - a. Revision: A
- 3. EDGE Configuration
 - a. MCS Index: 7
 - b. Number of TX slots: 2
- 4. HSPA Configuration:
 - a. Release: 6
 - 3GPP 34.121 Subtest 1
- LTE FDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 0RB offset
 - c. LTE Band 12 was the worst-case band from Table 7-5 and was used to test both Axial and Radial probe orientations.
 - The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 12 at 5MHz is the worst-case for both Axial and Radial probe orientations.
- 6. WIFI Configuration:
 - Radio Configuration
 - i. 802.11b: CCK, 5.5Mbps
 - ii. 802.11g/a: QPSK, 12Mbps
 - iii. 802.11n/ac 20MHz: BPSK, 6.5Mbps
 - iv. 802.11n/ac 40MHz: BPSK, 13.5Mbps
 - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both Axial and radial probe orientations.
 - The worst-case standard for 5GHz WIFI in each probe orientation is additionally tested on higher U-NII bands as well as applicable low and high channels. 802.11n 20MHz BW (U-NII 1) is the worst-case for both Axial and radial probe orientations.

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Dog 22 of 74	
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 33 of 74	

III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

IV. T-Coil Validation Test Results

Table 9-21 Helmholtz Coil Validation Table of Results - 4/30/2018

Item	Target	Result	Verdict		
Axial					
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.170	PASS		
Environmental Noise	< -58 dBA/m	-63.43	PASS		
Frequency Response, from limits	> 0 dB	0.80	PASS		
Radial					
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.169	PASS		
Environmental Noise	< -58 dBA/m	-63.11	PASS		
Frequency Response, from limits	> 0 dB	0.80	PASS		

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Dog 24 of 74	
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 34 of 74	

Table 9-22
Helmholtz Coil Validation Table of Results - 5/8/2018

Item	Target	Result	Verdict	
Axial				
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.169	PASS	
Environmental Noise	< -58 dBA/m	-63.18	PASS	
Frequency Response, from limits	> 0 dB	0.80	PASS	
Radial				
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.283	PASS	
Environmental Noise	< -58 dBA/m	-63.00	PASS	
Frequency Response, from limits	> 0 dB	0.80	PASS	

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Dog 25 of 74	
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 35 of 74	

ABM1 Magnetic Field Distribution Scan Overlays ٧.




Figure 9-1
T-Coil Scan Overlay Magnetic Field Distributions

Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFQ710CS	PCTEST:	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 36 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 30 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

MEASUREMENT UNCERTAINTY 10.

Table 10-1 Uncertainty Estimation Table

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1)						17.7%	0.71
Expanded uncertainty (k=2), 95% confidence level						35.3%	1.31

Notes:

- 1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFQ710CS	PCTEST INCIDENCE LABORATORA, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 37 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 37 01 74

11. EQUIPMENT LIST

Table 11-1 Equipment List

		Equipment List				
Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/11/2017	Biennial	4/11/2019	7BFNM32
Listen	SoundConnect	Microphone Power Supply	N/A		N/A	0899-PS150
Listen	SoundConnect	Microphone Power Supply	12/2/2016	Biennial	12/2/2018	PS2612
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/11/2017	Biennial	4/11/2019	23528889
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/19/2018	Annual	1/19/2019	162125
Rohde & Schwarz	CMW500	Radio Communication tester	7/14/2017	Annual	7/14/2018	140144
Seekonk	NC-100	Torque Wrench (8" lb)	9/1/2016	Biennial	9/1/2018	21053
TEM	C63.19	Helmholtz Coil	12/7/2016	Biennial	12/7/2018	925
TEM	Radial T-Coil Probe	Radial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1130
TEM	Axial T-Coil Probe	Axial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1124
TEM		HAC System Controller with Software	N/A		N/A	N/A
TEM		HAC Positioner	N/A		N/A	N/A

FCC ID: ZNFQ710CS	HAC (T-COIL) TEST REPORT		LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 38 of 74

12. TEST DATA

FCC ID: ZNFQ710CS	HAC (T-COIL) TEST REPORT		1 LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 39 of 74



Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011

Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum -50.0 -55.0 -60,0 E -65.0 9 -75.0 -80.0 -85.0 -90,0 100 1k 10k [Hz] Frequency Response 3,0 2.0 [dB re 1 A/m/V] 1.0 0.0 -1.0 -2.0 -3.0-300 3k 1k [Hz] Results -9.5/-10,5 Verification 1kHz Intensity -10.17 dB Max/Min Verification ABM2 -58.0 -63.43 dB Maximum Frequency Response Margin Tolerance curves Aligned Data 700m dB

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 40 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 40 01 74



Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011

Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum -50.0 -55.0 -60,0 -70.0 号 -75.0 -80,0 -85.0 --90,0 10k 100 1k [Hz] Frequency Response 3.0 -2.0 1.0 [dB re 1 A/m] 0.0 -2.0--3.0-1k 3k [Hz] Results Verification 1kHz Intensity -10.169 dB Max/Min -9.5/-10.5 Verification ABM2 -63.18 dB Maximum -58.0 Frequency Response Margin 800m dB Tolerance curves Aligned Data

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 41 01 74



Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011

Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum -50.0 --55.0 --60,0 E -65,0 -号 -75.0 -80.0 -85.0 -90.0 100 10k 1k [Hz] Frequency Response 3.0 2.0 1.0 0.0 豐 -1.0 -2.0 -3,0-300 14 3k [Hz] Results -9.5/-10.5 Verification 1kHz Intensity -10.261 dB Max/Min -58.0 Verification ABM2 -63.11 dB Maximum Aligned Data Frequency Response Margin 700m dB Tolerance curves

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 42 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 42 01 74



Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011

Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum -50.0 -55.0 -60.0 -70.0 ₩ -75.0 -80.0 -85.0 10k 100 1k [Hz] Frequency Response 3.0 0.0 e1 A/m] ₩ -1.0 -2.0 -3.0-1k [Hz] Results Verification 1kHz Intensity -10.283 dB Max/Min -9.5/-10.5 Verification ABM2 -58.0 -63 dB Maximum Aligned Data Frequency Response Margin Tolerance curves. 800m dB

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 43 01 74



Type: Portable Handset Serial: 02185


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- Mode: GSM 850
- Channel: 251
- · Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 44 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 44 01 74



Type: Portable Handset Serial: 02185

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM 1900

Channel: 512

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 45 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		raye 43 01 74



Type: Portable Handset Serial: 02185

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

. Mode: UMTS Band V

Channel: 4233

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST TOGRESSION (NC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 46 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 40 01 74



Type: Portable Handset Serial: 02185

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

. Mode: UMTS Band IV

Channel: 1312

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 47 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 47 01 74



Type: Portable Handset Serial: 02185

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

. Mode: UMTS Band II

Channel: 9538

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 48 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 46 01 74



Type: Portable Handset Serial: 02185

Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016


Test Configuration:

Mode: LTE FDD Band 4

Bandwidth: 3MHz

Channel: 20175

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 40 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 49 of 74



Type: Portable Handset Serial: 02235

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: 2.4GHz WIFIStandard: IEEE 802.11n

Channel: 6

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 50 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 50 01 74



Type: Portable Handset Serial: 02235


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe - SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- Mode: 5GHz WIFI
- Standard: IEEE 802.11a (U-NII 1)
- Bandwidth: 20MHz BW
- · Channel: 40
- · Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST TOGRESSION (NC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 51 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		rage 51 01 74



Type: Portable Handset Serial: 02185


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- VolP Application: Google Duo
- Mode: EDGE 1900
- · Channel: 661
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFQ710CS	PCTEST TOGRESSION (NC	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 50 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 52 of 74



Type: Portable Handset Serial: 02185


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM 850Channel: 251



FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	1 LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo F2 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 53 of 74



Type: Portable Handset Serial: 02185


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM 1900Channel: 512



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 54 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 54 of 74



Type: Portable Handset Serial: 02185


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS Band VChannel: 4132



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg FF of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 55 of 74



Type: Portable Handset Serial: 02185


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS Band IVChannel: 1412



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 56 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 30 01 74



Type: Portable Handset Serial: 02185


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS Band II
Channel: 9262



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 57 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 37 01 74



Type: Portable Handset Serial: 02185

Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE Band 5Bandwidth: 5MHzChannel: 20525



FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 50 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 58 of 74



Type: Portable Handset Serial: 02235


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

- Mode: 2.4GHz WIFI
- Standard: IEEE 802.11n
- Channel: 6



FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 59 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 59 01 74



Type: Portable Handset Serial: 02235

Measurement Standard: ANSI C63,19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016


Test Configuration:

Mode: 5GHz WIFI

Standard: IEEE 802.11a (U-NII 2C)

Bandwidth: 20MHz BW

Channel: 120



FCC ID: ZNFQ710CS	PCTEST INCIDENCE LABORATORA, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 60 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 60 01 74



Type: Portable Handset Serial: 02235

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

VolP Application: Google Duo


Mode: EDGE 850Channel: 190



FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 61 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 01 01 74

13. CALIBRATION CERTIFICATES

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	1 LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 60 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 62 of 74



FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 63 of 74
1M1803280056-10-R1 7NF	04/30/2018 - 05/09/2018	Portable Handset		Fage 03 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

HCATEMC_TEM 1124_Dec-07-2016




ISO/IEC 17025: 2005 Calibration Las. Cert. # 1533.01

1575 State Route 96, Victor NY 14564


REPORT OF CALIBRATION

TEM Consulting LP Axial T Coil Probe Model No.: Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab. I. D. No: 80578



Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC Calibration Laboratories Inc. procedure :

Calibration was performed by Wast Calewell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of (SO10012-1, IEC Guige 25, ANSI/NCSL Z540 1, (MIL STD 45662A) and ISO 9001 2008, ISO 17025

Cat. Date: 7-Dac-2016 Calibrated on WCCL system type 9700 Felix Christopher

Rev. 7.0 Jan. 24, 2014 Day # 1038 HCATEMG This designant shall not be reproduced, except in full, without the written approval from West Calebrail Cal. Lake the

Page 1 of 2

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	LG LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 64 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 64 of 74

HCATEMC_TEM 1124_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Raute 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Axial T Coil Probe

Model No.: Axial T Coil Probe

Serial No.: TEM 1124

Company: PCTEST Engineering Lab.

Test	Function	Tolerance		Measured values		
1			Before	Ous	Remarks	
0	Prose Senelsivisy es	1000 H ₊ .	aBV/A/m	-60.23		-
			øB			
2.0	Proba Loval Linearity		6	6.03		
		R. (0 aB)	0 -6	0.00		
			-6	-6.03		
			-12	-12.05		
	12 1 At 1 307		Ha			
3.0	Probe Frequency Response		100	-19.8		
			126	-18.0		
			158	-16.0		
			200	-13.9		
			251	-12.0		
			316	-9,9		
			398	-8.0		
			501	-6.0		
			631	-4.0		
		D (0 D)	794	-2.0		
		R+r. (0 uB)	1000	0,0		
			1259 1585	4.0		
			1995			
			2512	6.0 7.9		
			3162	9.9		
			3981	11.9		
			A. 20-20			
			5012 6310 7943 10000	13.9 15.9 18.0 20.2		

struments used for calleration:			Date or Cal	Teecastity No.	Due Dete	
HP	34401A	S/N	36064102	1-Out-2018	,287708	1-Oor-2017
HP	34401A	S/N	36102471	1-Oct-2015	.287708	1-Oct-2017
HP	33120A	S/N	36043716	1 Oct 2015	.287708	1 Oct 2017
B&K	2133	S/N	1583254	1-0 2016	683/284413-14	1-Oot-2017

Cat: Date: 7-Dec-2016

Tested by: Felle Christopher

Calibrated on WCCL system type 9700

Tala mandangan anan nan na baangan ang ang ang ang buit, wang un top winning ang nang born. Wass Catagoni Car Laber In-


Ray 7.0 Jan 24, 2014 Day #1038 HCATEMC

Page 2 of 2

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 03 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M



FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 66 of 74
1M1803280056-10-R1 7NF	04/30/2018 - 05/09/2018	Portable Handset		Fage 00 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

HCRTEMC TEM-1130 Dec-07-2016






1575 State Route 96, Victor NY 14564

REPORT OF CALIBRATION

TEM Consulting LP Radial T Coil Probe Model No.: Radial T Coil Probe Serial No.: TEM-1130

Company: PCTEST Engineering Lab.


I. D. No: 80579



683/284413-14

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC Calibration Laboratories Inc. procedure :

Calibration was performed by Wast Calewell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of (SO10012-1, IEC Guige 25, ANSI/NCSL Z540 1, (MIL STD 45662A) and ISO 9001 2008, ISO 17025

Cat. Date: 7-Dac-2016 Calibrated on WCCL system type 9700 Felix Christopher

Rev. 7.0 Jan. 24, 2014 Day # 1038 HORTEMO This designant shall not be reproduced, except in full, without the written approval from West Calebrail Cal. Lake the

Page 1 of 2

FCC ID: ZNFQ710CS	PCTEST	HAC (T-COIL) TEST REPORT	1 LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 67 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Page 67 of 74

© 2018 PCTEST Engineering Laboratory, Inc.

HCRTEMC_TEM-1130_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Raute 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Radial T Coil Probe

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

Company: PCTEST Engineering Lab.

est	Function	Tolera	Measured values			
				Batora	Out	Remerke
1.0.	Prone Senelsivisy es	1000 H ₊ .	a BV/A/m	-60.27		
			øΒ	I Janes II		
2.0	O Proba Laval Linearity	al com	6	6.03		
		R. (0 a B)	0	0.00		
			-6	-6.03		
			-12	-12.06		
			Ha	1		
3.0	Probe Frequency Response		100	-19.9		
			126	-18.0		
			158	-16.0		
			200	-13.9		
			251	-12.0		
			316	-10.0		
			398	-8.0		
			501	-6.0		
			631	-4.0		
			794	-2.0		
		R+r. (0 aB)	1000	0.0		
			1259	2.0		
			1585	4.0		
			1995	6.0		
		2512	7.9			
		3162	9.9			
			3981	11.9		
			5012	13.9		
			6310	15.9		
			7943	18.0		
			10000	20.2		

ratruments used for cellbretien.			Dete or Cal	Trecashility No.	Due Dete	
HP	34401A	S/N	36064102	1-O=1-2018	,287708	1-Ooz-2017
HP	34401A	S/N	36102471	1-Oct-2016	.287708	1-Oct-2017
HP	33120A	5/N	36043716	1 Oct 2015	.287708	1 Oct 2017
B&K	2133	S/N	1583254	1-0 2016	683/284413-14	1-Oot-2017

Cal: Date: 7-Dec-2016 Calibrated on WCCL system type 9700

Tested by: Felle Christopher

Ray 7.0 Jan 24. 2014 Day # 1038 HCRTEMC

Page 2 of 2

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 68 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 00 01 74

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 69 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 09 01 74

15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017 2.
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017 3.
- FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 5 FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 6.
- Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, "IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, " U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- 12. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1013, July 1981,
- EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
- EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- 15. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
- 17. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 70 of 74
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset		Fage 70 01 74

- 22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- 24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 25. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- 26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- 28. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January
- 29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFQ710CS	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 71 of 74	
1M1803280056-10-R1.ZNF	04/30/2018 - 05/09/2018	Portable Handset			