

MPE / SAR exemption letter according Interim procedure KDB 447498 D04

Customer	Product	Model	Type	HW Status	SW status	FCC ID
Brose Fahrzeugteile SE & Co. Kommanditgesellschaft, Bamberg Berliner Ring 1 96052, Bamberg Germany	Kick Sensor (HfA)	AWRL 1422	G69634- 100	G69634- 100	B013	2AHV8- G69634

This device is not portable meaning it's not in human hand or near to body. When device is used and e.g. feet is near to Tx short time period it does not make the device to be portable. That's why separation distance for RF exposure evaluation can be set to 20 cm. this is distance which is maintained to the Tx "all the time".

The customer thus declares that the device is not body-worn.

RF Exposure Test Exemptions for Single Source

MPE-based Exemption

According 1.1307(b)(3)(i)(C) Option C – ERP at frequencies above 300 kHz but at distances $R > \lambda/2\pi$ can be exempted as follows:

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source Frequency			Minimum Distance			Threshold ERP
f_L MHz		f_H MHz	$\lambda_L / 2\pi$		$\lambda_H / 2\pi$	W
0.3	–	1.34	159 m	–	35.6 m	$1,920 R^2$
1.34	–	30	35.6 m	–	1.6 m	$3,450 R^2/f^2$
30	–	300	1.6 m	–	159 mm	$3.83 R^2$
300	–	1,500	159 mm	–	31.8 mm	$0.0128 R^2 f$
1,500	–	100,000	31.8 mm	–	0.5 mm	$19.2 R^2$
Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.						

MPE / SAR exemption letter 23-1-0144001T009_TR1-R01

SAR-based Exemption

According 1.1307(b)(3)(i)(B) Option B – Available maximum time-averaged power or effective radiated power (ERP) at frequencies above 300 kHz and below 6 GHz, but with distances from 0.5 cm to 40 cm may be exempted as follows:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

11/29/2021

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

ERP calculation based on external document "Cetecom_advanced_Antenna_Pattern_23-1-0144002T001_TR1-R01"

MPE / SAR exemption letter 23-1-0144001T009_TR1-R01

Radar

MPE-based Exemption

Exemption acc. TABLE 1 TO § 1.1307(b)(3)(i)(C) — SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION													
Band	Technology	Frequency	$\lambda/2\pi$	R	$R \geq \lambda/2\pi$ fulfilled	Total Radiated Power	Maximum Antenna Gain	Duty Cycle	EIRP	ERP	ERP	Threshold ERP	MPE Exemption fulfilled
		(MHz)	(m)	(m)		(dBm)	(dBi)	(%)	(dBm)	(dBm)	(W)	(W)	
77 - 79 GHz	Radar	78000.0	0.001	0.200	yes	4.3	9.6	100.0	13.9	11.8	0.015	0.768	yes

Simultaneous Transmission

The customer declares that the device is not able to transmit simultaneously.

Conclusion

MPE-/ SAR Based Exemption fulfilled

Dipl.-Ing. (FH) Andreas Luckenbill M.Sc.

B.Eng. Martin Nunier

Version	Applied changes	Date of release
R01	Initial release	2024-Oct-17