

ELEMENT WASHINGTON DC LLC

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.element.com

TEST REPORT CBSD-SAS Interoperability

Applicant Name:

Samsung Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si Gyeonggi-do, 16677, Korea Date of Testing:

2/7/2023 – 2/9/2023

Test Site/Location:

Element Lab. Columbia, MD, USA

Test Report Serial No.: 1M2302100007-01.A3L

FCC ID: A3LSOG2201

APPLICANT: Samsung Electronics Co., Ltd.

Application Type:CertificationModel:SOG2201-G30

EUT Type: Smallcell

Frequency Range: 3550 – 3700 MHz

FCC Classification: Citizens Band Category A and B Devices (CBD)

FCC Rule Part(s): Part 96

Test Procedure(s): KDB 940660 D01 v03, WINNF-TS-0122-V1.0.2, ONGO-TS-9001 V.1.0.0

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in the test procedures listed above. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President







FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 1 of 72



TABLE OF CONTENTS

1.0	INTRODUCTION3	
1.1	Scope	
1.2	Element Test Location	
	Test Facility / Accreditations	
2.0	PRODUCT INFORMATION4	
	Equipment Description	
	Device Capabilities	
	Test Configuration4	
	Modifications4	
3.0	TEST EQUIPMENT CALIBRATION DATA	
4.0	ENVIRONMENTAL CONDITIONS	
5.0	EVALUATION PROCEDURE	
6.0	TEST Summary	
	Summary	
	·	
7.0	CONCLUSION	
	NDIX A – TEST RESULT AND DATA	
A1	[WINNF.FT.C.REG.1] MULTI-STEP REGISTRATION	11
A2 A3	[WINNF.FT.C.REG.10] PENDING REGISTRATION (RESPONSECODE 200)	13
A3 A4	[WINNF.FT.C.REG.12] INVALID PARAMETER (RESPONSECODE 103)	14 15
A4 A5	[WINNF.FT.C.REG.14] BLACKLISTED CBSD (RESPONSECODE 101)	15 16
	[WINNF.FT.C.REG.16] UNSUPPORTED SAS PROTOCOL VERSION (RESPONSECODE 100)	17
A7	[WINNF.FT.C.REG.18] GROUP ERROR (RESPONSECODE 201)	
	[WINNF.FT.C.GRA.1] UNSUCCESSFUL GRANT RESPONSECODE=400 (INTERFERENCE)	
	[WINNF.FT.C.GRA.2] UNSUCCESSFUL GRANT RESPONSECODE=401 (GRANT_CONFLICT)	
A10	[WINNF.FT.C.HBT.1] HEARTBEAT SUCCESS CASE (FIRST HEARTBEAT RESPONSE)	21
	[WINNF.FT.C.HBT.3] HEARTBEAT RESPONSECODE=105 (DEREGISTER)	
	[WINNF.FT.C.HBT.4] HEARTBEAT RESPONSECODE=500 (TERMINATED_GRANT)	
	[WINNF.FT.C.HBT.5] HEARTBEAT RESPONSECODE=501 (SUSPENDED_GRANT) IN FIRST HEARTBEAT RESPONSE [WINNF.FT.C.HBT.6] HEARTBEAT RESPONSECODE=501 (SUSPENDED_GRANT) IN SUBSEQUENT HEARTBEAT	. 28
	[WINNEFT.C.RBT.0] REARTBEAT RESPONSECODE=SUT (SUSPENDED_GRANT) IN SUBSEQUENT REARTBEAT	20
	[WINNF.FT.C.HBT.7] HEARTBEAT RESPONSECODE=502 (UNSYNC_OP_PARAM)	
	[WINNF.FT.C.HBT.9] HEARTBEAT RESPONSE ABSENT (FIRST HEARTBEAT)	
A17	[WINNF.FT.C.HBT.10] HEARTBEAT RESPONSE ABSENT (SUBSEQUENT HEARTBEAT)	36
A18	[WINNF.FT.C.MES.1] REGISTRATION RESPONSE CONTAINS MEASREPORTCONFIG	38
A19	WINNF.FT.C.RLQ.1] SUCCESSFUL RELINQUISHMENT	41
A20	WINNF.FT.C.DRG.1] SUCCESSFUL DEREGISTRATION	43
A21	[WINNF.FT.C.SCS.1] SUCCESSFUL TLS CONNECTION BETWEEN UUT AND SAS TEST HARNESS	45
A22	[WINNF.FT.C.SCS.2] TLS FAILURE DUE TO REVOKED CERTIFICATE	47
	[WINNF.FT.C.SCS.3] TLS FAILURE DUE TO EXPIRED SERVER CERTIFICATE	
A24	[WINNF.FT.C.SCS.4] TLS FAILURE WHEN SAS TEST HARNESS CERTIFICATE IS ISSUED BY AN UNKNOWN CA	50
A25	[WINNF.FT.C.SCS.5] TLS FAILURE WHEN CERTIFICATE AT THE SAS TEST HARNESS IS CORRUPTED	51
A26	WINNF.PT.C.HBT.1 UUT RF TRANSMIT POWER MEASUREMENT	52
APPE	NDIX B – TEST LOGS66	

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 2 of 72



1.0 INTRODUCTION

1.1 Scope

Measurement and determination of compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element is a CBRS Alliance (OnGo) Approved Test Lab
- Element is a WInnForum Approved Test Lab
- Element is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for CBRS Alliance Certification Test Plan and WInnForum Conformance and Performance Test Technical Standard.
- Element is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreement.

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 3 of 72



2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Electronics Co.**, **Ltd.**, **Smallcell FCC ID: A3LSOG2201.** The test data contained in this report pertains only to CBSD-SAS interoperability. The EUT is a Category B CBSD.

Test Device Serial Number(s): 12-Samsung_Networks

Test Device Hardware Version: PCS01 **Test Device Software Version:** 23A

2.2 Device Capabilities

This device contains the following capabilities:

NR n48

This device supports the following conditional features:

	Conditional Test Case Definitions	Supported
C1	Mandatory for UUT which supports multi-step registration message	\boxtimes
C2	Mandatory for UUT which supports single-step registration with no CPI-signed data in the registration message. By definition, this is a subset of Category A devices which determine all registration information, including location, without CPI intervention.	
С3	Mandatory for UUT which supports single-step registration containing CPI-signed data in the registration message.	
C4	Mandatory for UUT which supports RECEIVED_POWER_WITHOUT_GRANT measurement report type.	\boxtimes
C5	Mandatory for UUT which supports RECEIVED_POWER_WITH_GRANT measurement report type.	
C6	Mandatory for UUT which supports parameter change being made at the UUT and prior to sending a deregistration	

Table 2-1. Conditional Features

2.3 Test Configuration

The EUT was connected to the SAS Test Harness developed by WINNF WG4-CBSD. The SAS Test Harness (V1.0.0.2) provided by CBRS Alliance was used. The SAS Test Harness is synchronized to UTC time.

2.4 Modifications

No modifications were made to EUT during testing.

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 4 of 72



3.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9020A	MXA Signal Analyzer	3/4/2022	Annual	3/4/2023	US46470561
Dell	Latitude 5580	Test Harness Laptop	N/A	N/A	N/A	N/A

Table 3-1 Annual Test Equipment Calibration Schedule

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 5 of 72



4.0 ENVIRONMENTAL CONDITIONS

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 6 of 72



5.0 EVALUATION PROCEDURE

The measurement procedure described in KDB940660 D01 V03 and WINNF-TS-0122V1.0.2 were used in the measurement of the EUT.

Deviation from measurement procedure......None

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 7 of 72



6.0 TEST SUMMARY

6.1 Summary

Company Name: <u>Samsung Electronics Co., Ltd.</u>

FCC ID: <u>A3LSOG2201</u>

Table 6-1. Summary of Test Results

FCC Part Section(s)	KDB940660 D01 Section 3.3 a)	Test Case Description	WinnForum Test Case	Test Result
96.39 (c)	1	Confirm that the device will only transmit after it receives authorization from a SAS	WINNF.FT.C.REG.1 WINNF.FT.C.REG.8 WINNF.FT.C.REG.10 WINNF.FT.C.REG.12 WINNF.FT.C.REG.14 WINNF.FT.C.REG.16 WINNF.FT.C.REG.18 WINNF.FT.C.GRA.1 WINNF.FT.C.GRA.2 WINNF.FT.C.HBT.5	Pass
96.39 (c)	2	Check the device registration and authorization with the SAS – determine if the device behaves appropriately for successful and unsuccessful registrations. The device should not be transmitting without authorization from the SAS.	WINNF.FT.C.REG.1 WINNF.FT.C.REG.8 WINNF.FT.C.REG.10 WINNF.FT.C.REG.12 WINNF.FT.C.REG.14 WINNF.FT.C.REG.16 WINNF.FT.C.REG.18	Pass
96.39(c)(1)	3	Confirm that the device changes its operating power and/or channel in response to a command from the SAS.	WINNF.FT.C.HBT.1	Pass
96.39	4	Confirm that the device correctly configures based on the different license classes	N/A	Pass
96.39(c)(1)	5	Confirm that the device transmits at a power level less than or equal to the maximum power level approved by the SAS.	WINNF.PT.C.HBT.1	Pass
96.39(b)(c)	6	Confirm that the device transmits with a bandwidth less than or equal to the SAS specified bandwidth.	WINNF.FT.C.HBT.1	Pass
96.39(c)(2)	7	Confirm that the device transmits on the SAS specified frequency.	WINNF.FT.C.HBT.1	Pass
96.39(c)(2)	8	Confirm that the device stops transmission in response to a command from the SAS, within a period as required by Part 96.	WINNF.FT.C.HBT.3 WINNF.FT.C.HBT.4 WINNF.FT.C.HBT.6 WINNF.FT.D.HBT.7 WINNF.FT.C.HBT.10 WINNF.FT.C.RLQ.1 WINNF.FT.C.DRG.1	Pass

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 8 of 72



Table 6-2. Summary of Test Results (continued)

		Table 0-2. Sulfillary of Test Nesults (Collillar	c u <i>)</i>	
96.39 (c)	9	Confirm that the device sends measurements data in response to the command from the SAS.	WINNF.FT.C.MES.1	Pass
96.39(a)	10	For devices with geo-location, confirm that it notifies the SAS of a new location when it is beyond the required distance parameter (±50 m) within the required time frame.	N/A	N/A
96.39 (c)	11	Confirm that the device is capable of reporting the signal level (measurement data) and frequency to SAS.	WINNF.FT.C.MES.1	Pass
	12	For a device that operates as a Category A CBSD and then desires to operate as a Category B CBSD (or vice versa), confirm that it re-registers with the SAS for the updated authorization status.	N/A	Pass
96 E	13	When CBSDs communicate through a management system, confirm compliance with all requirements.	N/A	Pass
96.39	14	When communication between the CBSD and SAS is lost: i) Describe how the CBSD would react if the communications between the device and the SAS is lost. Confirm that the CBSD stops transmission once it loses the link to the SAS. ii) Describe the process for re-establishment of the communications and confirm that the CBSD acts accordingly. iii) Confirm power-on restart process for registration (reregistration) occurs as expected. iv) Confirm the process for de-registration occurs as expected.	WINNF.FT.C.HBT.9 WINNF.FT.C.HBT.10	Pass
96.39(f)	KDB940660 D01 Section 4	SAS and Device Security Requirements	WINNF.FT.C.SCS.1 WINNF.FT.C.SCS.2 WINNF.FT.C.SCS.3 WINNF.FT.C.SCS.4 WINNF.FT.C.SCS.5	Pass

Notes:

- Test cases denoted as "N/A" in the table above are not applicable to the EUT and are either Optional or Conditional per Section 6 of WINNF-TS-0122.
- Please see Appendices for test data.

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 9 of 72

© 2023 ELEMENT



7.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Electronics Co., Ltd., Cat B NR Router FCC ID: A3LSOG2201** has been tested to show compliance with Part 96 and WINNF-TS-0122.

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 10 of 72



APPENDIX A - TEST RESULT AND DATA


A1 [WINNF.FT.C.REG.1] Multi-Step registration

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has successfully completed SAS Discovery and Authentication with the SAS Test Harness UUT is in the Unregistered state CBSD sends correct Registration request information, as specified in [n.5], to the SAS Test Harness: 	-	
2	 The required userId, fccId and cbsdSerialNumber registration parameters shall be sent from the CBSD and conform to proper format and acceptable ranges. Any REG-conditional or optional registration parameters that may be included in the message shall be verified that they conform to proper format and are within acceptable ranges. Note: It is outside the scope of this document to test the Registration information that is supplied via another means. 	×	
3	SAS Test Harness sends a CBSD Registration Response as follows: cbsdld = Ci measReportConfig shall not be included responseCode = 0	1	
4	After completion of step 3, SAS Test Harness will not provide any positive response (responseCode=0) to further request messages from the UUT.		
5	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is complete. This is the end of the test. Verify: • UUT shall not transmit RF	X	

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 11 of 72

© 2023 ELEMENT





Plot 1. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.REG.1) - NR


FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 12 of 72



A2 [WINNF.FT.C.REG.8] Missing Required parameters (responseCode 102)

	Test Execution Steps	PASS	FAIL
	Ensure the following conditions are met for test entry:		
1	UUT has successfully completed SAS Discovery and Authentication with SAS Test		
	Harness		
	UUT is in the Unregistered state		
2	CBSD sends a Registration request to SAS Test Harness.	1	
	SAS Test Harness rejects the request by sending a CBSD Registration Response as		
3	follows:		
3	- SAS response does not include cbsdld		
	- responseCode = R		
4	After completion of step 3, SAS Test Harness will not provide any positive response		
4	(responseCode=0) to further request messages from the UUT.		
	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is		
5	complete. This is the end of the test. Verify:	\boxtimes	
	UUT shall not transmit RF		

Test Plots:



Plot 2. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.REG.8) – NR


FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 13 of 72



A3 [WINNF.FT.C.REG.10] Pending registration (responseCode 200)

	Test Execution Steps	PASS	FAIL
	Ensure the following conditions are met for test entry:		
1	UUT has successfully completed SAS Discovery and Authentication with SAS Test		
1	Harness		
	UUT is in the Unregistered state		
2	CBSD sends a Registration request to SAS Test Harness.	1	
	SAS Test Harness rejects the request by sending a CBSD Registration Response as		
3	follows:		
3	- SAS response does not include cbsdld		
	- responseCode = R		
4	After completion of step 3, SAS Test Harness will not provide any positive response		
4	(responseCode=0) to further request messages from the UUT.		
	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is		
5	complete. This is the end of the test. Verify:	\boxtimes	
	UUT shall not transmit RF		

Test Plots:



Plot 3. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.REG.10) – NR


FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 14 of 72



A4 [WINNF.FT.C.REG.12] Invalid parameter (responseCode 103)

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has successfully completed SAS Discovery and Authentication with SAS Test Harness UUT is in the Unregistered state 	1	
2	CBSD sends a Registration request to SAS Test Harness.		
3	SAS Test Harness rejects the request by sending a CBSD Registration Response as follows: - SAS response does not include cbsdld - responseCode = R	1	
4	After completion of step 3, SAS Test Harness will not provide any positive response (responseCode=0) to further request messages from the UUT.	1	
5	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is complete. This is the end of the test. Verify: • UUT shall not transmit RF	\boxtimes	

Test Plots:



Plot 4. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.REG.12) – NR


FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 15 of 72



A5 [WINNF.FT.C.REG.14] Blacklisted CBSD (responseCode 101)

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has successfully completed SAS Discovery and Authentication with SAS Test Harness UUT is in the Unregistered state 	1	
2	CBSD sends a Registration request to SAS Test Harness.		
3	SAS Test Harness rejects the request by sending a CBSD Registration Response as follows: - SAS response does not include cbsdld - responseCode = R		
4	After completion of step 3, SAS Test Harness will not provide any positive response (responseCode=0) to further request messages from the UUT.	1	
5	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is complete. This is the end of the test. Verify: • UUT shall not transmit RF	\boxtimes	

Test Plots:



Plot 5. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.REG.14) – NR


FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 16 of 72



A6 [WINNF.FT.C.REG.16] Unsupported SAS protocol version (responseCode 100)

	Test Execution Steps	PASS	FAIL
	Ensure the following conditions are met for test entry:		
1	UUT has successfully completed SAS Discovery and Authentication with SAS Test		
1	Harness		
	UUT is in the Unregistered state		
2	CBSD sends a Registration request to SAS Test Harness.		
	SAS Test Harness rejects the request by sending a CBSD Registration Response as		
3	follows:		
3	- SAS response does not include cbsdld		
	- responseCode = R		
4	After completion of step 3, SAS Test Harness will not provide any positive response		
4	(responseCode=0) to further request messages from the UUT.		
	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is		
5	complete. This is the end of the test. Verify:	\boxtimes	
	UUT shall not transmit RF		

Test Plots:



Plot 6. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.REG.16) – NR


FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 17 of 72



A7 [WINNF.FT.C.REG.18] Group Error (responseCode 201)

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has successfully completed SAS Discovery and Authentication with SAS Test Harness UUT is in the Unregistered state 		
2	CBSD sends a Registration request to SAS Test Harness.		
3	SAS Test Harness rejects the request by sending a CBSD Registration Response as follows: - SAS response does not include cbsdld - responseCode = R		
4	After completion of step 3, SAS Test Harness will not provide any positive response (responseCode=0) to further request messages from the UUT.		
5	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is complete. This is the end of the test. Verify: • UUT shall not transmit RF	\boxtimes	

Test Plots:



Plot 7. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.REG.18) – NR


FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 18 of 72



A8 [WINNF.FT.C.GRA.1] Unsuccessful Grant responseCode=400 (INTERFERENCE)

	Test Execution Steps	PASS	FAIL
1	Ensure the following conditions are met for test entry:		
	UUT has registered successfully with SAS Test Harness, with cbsdld = C		
2	UUT sends valid Grant Request.	-	
	SAS Test Harness sends a Grant Response message, including		
3	• cbsdId=C		
	• responseCode = R		
4	After completion of step 3, SAS Test Harness will not provide any positive response		
4	(responseCode=0) to further request messages from the UUT.		
	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is		
5	complete. This is the end of the test. Verify:	\boxtimes	
	UUT shall not transmit RF		

Test Plots:



Plot 8. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.GRA.1) – NR


FCC ID: A3LSOG2201		2201 MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 19 of 72



A9 [WINNF.FT.C.GRA.2] Unsuccessful Grant responseCode=401 (GRANT_CONFLICT)

	Test Execution Steps	PASS	FAIL
1	Ensure the following conditions are met for test entry:		
	• UUT has registered successfully with SAS Test Harness, with cbsdId = C	-	
2	UUT sends valid Grant Request.		
	SAS Test Harness sends a Grant Response message, including		
3	• cbsdld=C		
	• responseCode = R		
4	After completion of step 3, SAS Test Harness will not provide any positive response		
4	(responseCode=0) to further request messages from the UUT.	-	
	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is		
5	complete. This is the end of the test. Verify:	\boxtimes	
	UUT shall not transmit RF		

Test Plots:



Plot 9. Conducted Measurement – No RF transmission in entire band for 60s of elapsed time (WINNF.FT.C.GRA.2) – NR

FCC ID: A3LSOG2201		A3LSOG2201 MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 20 of 72




A10 [WINNF.FT.C.HBT.1] Heartbeat Success Case (first Heartbeat Response)

1 e	est Execution Steps	PASS	FAIL
	sure the following conditions are met for test entry:		
• (JUT has registered successfully with SAS Test Harness, with cbsdId = C		
	JT sends a message:		
	f message is type Spectrum Inquiry Request, go to step 3, or		
	f message is type Grant Request, go to step 5		
	JT sends Spectrum Inquiry Request. Validate:		
	cbsdId = C	\boxtimes	
• L	ist of frequencyRange objects sent by UUT are within the CBRS frequency range		
	S Test Harness sends a Spectrum Inquiry Response message, including the following		
	rameters:		
	cbsdId = C		
	availableChannel is an array of availableChannel objects		
 	responseCode = 0		
	JT sends Grant Request message. Validate:		
5 1	cbsdId = C	\boxtimes	
• r	maxEIRP is at or below the limit appropriate for CBSD category as defined by Part 96		
-	operationFrequencyRange, F, sent by UUT is a valid range within the CBRS band		
	S Test Harness sends a Grant Response message, including the parameters:		
	cbsdId = C		
_	grantId = G = a valid grant ID		
• 8	grantExpireTime = UTC time greater than duration of the test		
• r	responseCode = 0		
	JT sends a first Heartbeat Request message.		
Ve	rify Heartbeat Request message is formatted correctly, including:		
7 • 0	cbsdld = C	\boxtimes	
• 8	grantId = G		
• (pperationState = "GRANTED"		
	S Test Harness sends a Heartbeat Response message, with the following parameters:		
• 0	cbsdId = C		
8 • 8	grantId = G		
• t	ransmitExpireTime = current UTC time + 200 seconds		
• r	responseCode = 0		
Fo	r further Heartbeat Request messages sent from UUT after completion of step 8,		
	lidate message is sent within latest specified heartbeatInterval, and:		
• 0	cbsdId = C		
• 8	grantId = G		
• 0	pperationState = "AUTHORIZED"		
9 an	d SAS Test Harness responds with a Heartbeat Response message including the	\boxtimes	
	llowing parameters:		
• 0	cbsdld = C		
• 8	grantId = G		
• t	ransmitExpireTime = current UTC time + 200 seconds		
• r	responseCode = 0		

FCC ID: A3LSOG2201 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 21 of 72



10	Monitor the RF output of the UUT from start of test until UUT transmission commences. Verify: • UUT does not transmit at any time prior to completion of the first heartbeat response • UUT transmits after step 8 is complete, and its transmission is limited to within the bandwidth range F	X		
----	---	---	--	--



Plot 10. Conducted Measurement - RF transmission after SAS heartbeat response (WINNF.FT.C.HBT.1) - NR

FCC ID: A3LSOG2201 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 22 of 72

© 2023 ELEMENT





Plot 11.Conducted Measurement Occupied Bandwidth for 20MHz (WINNF.FT.C.HBT.1) - NR

FCC ID: A3LSOG2201	OG2201 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 23 of 72



A11 [WINNF.FT.C.HBT.3] Heartbeat responseCode=105 (DEREGISTER)

	Test Execution Steps	PASS	FAIL
	Ensure the following conditions are met for test entry:		
	UUT has registered successfully with SAS Test Harness		
	UUT has a valid single grant as follows:		
	o valid cbsdld = C		
1	o valid grantId = G		
	o grant is for frequency range F, power P		
	o grantExpireTime = UTC time greater than duration of the test		
	• UUT is in AUTHORIZED state and is transmitting within the grant bandwidth F on RF		
	interface		
	UUT sends a Heartbeat Request message.		
	Ensure Heartbeat Request message is sent within Heartbeat Interval specified in the		
2	latest Heartbeat Response, and formatted correctly, including:	\boxtimes	
	• cbsdId = C		Ш
	• grantId = G		
	• operationState = "AUTHORIZED"		
	SAS Test Harness sends a Heartbeat Response message, including the following		
	parameters:		
3	• cbsdId = C		
	• grantId = G		
	• transmitExpireTime = T = Current UTC time		
	• responseCode = 105 (DEREGISTER)		
4	After completion of step 3, SAS Test Harness shall not allow any further grants to the		
-	UUT.		
5	Monitor the RF output of the UUT. Verify:	\boxtimes	
ر	• UUT shall stop transmission within (T + 60 seconds) of completion of step 3		Ш

FCC ID: A3LSOG2201 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 24 of 72

© 2023 ELEMENT





Plot 12.Conducted Measurement - RF transmission stops within 60s of SAS message indicated by Marker 1 (WINNF.FT.C.HBT.3) – NR

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 25 of 72



A12 [WINNF.FT.C.HBT.4] Heartbeat responseCode=500 (TERMINATED_GRANT)

	Test Execution Steps	PASS	FAIL
	Ensure the following conditions are met for test entry:		
	UUT has registered successfully with SAS Test Harness		
	UUT has a valid single grant as follows:		
	o valid cbsdld = C		
1	o valid grantId = G		
	o grant is for frequency range F, power P		
	o grantExpireTime = UTC time greater than duration of the test		
	• UUT is in AUTHORIZED state and is transmitting within the grant bandwidth F on		
	RF interface		
	UUT sends a Heartbeat Request message.		
	Ensure Heartbeat Request message is sent within Heartbeat Interval specified in		
2	the latest Heartbeat Response, and formatted correctly, including:	\boxtimes	
_	• cbsdld = C		
	• grantId = G		
	• operationState = "AUTHORIZED"		
	SAS Test Harness sends a Heartbeat Response message, including the following		
	parameters:		
3	• cbsdld = C		
3	• grantId = G		
	• transmitExpireTime = T = Current UTC time		
	• responseCode = 500 (TERMINATED_GRANT)		
4	After completion of step 3, SAS Test Harness shall not allow any further grants to		
_	the UUT.		
5	Monitor the RF output of the UUT. Verify:	\boxtimes	
	• UUT shall stop transmission within (T + 60 seconds) of completion of step 3		

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 26 of 72





Plot 13. Conducted Measurement - RF transmission stops within 60s of SAS message indicated by Marker 1 (X) (WINNF.FT.C.HBT.4) – NR

FCC ID: A3LSOG2201 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 27 of 72




A13 [WINNF.FT.C.HBT.5] Heartbeat responseCode=501 (SUSPENDED_GRANT) in First Heartbeat Response

	Test Execution Steps	PASS	FAIL
	Ensure the following conditions are met for test entry:		
	UUT has registered successfully with SAS Test Harness		
	UUT has a valid single grant as follows:		
	o valid cbsdld = C		
1	o valid grantid = G		
	o grant is for frequency range F, power P		
	o grantExpireTime = UTC time greater than duration of the test		
	• UUT is in AUTHORIZED state and is transmitting within the grant bandwidth F on		
	RF interface		
	UUT sends a Heartbeat Request message.		
	Ensure Heartbeat Request message is sent within Heartbeat Interval specified in		
2	the latest Heartbeat Response, and formatted correctly, including:		
2	• cbsdld = C	\boxtimes	
	• grantid = G		
	• operationState = "GRANTED"		
	SAS Test Harness sends a Heartbeat Response message, including the following		
	parameters:		
2	• cbsdld = C		
3	• grantid = G		
	• transmitExpireTime = T = Current UTC time		
	• responseCode = 501 (SUSPENDED_GRANT)		
4	After completion of step 3, SAS Test Harness shall not allow any further grants to		
4	the UUT.		
	Monitor the SAS-CBSD interface. Verify either A OR B occurs:		
	A. UUT sends a Heartbeat Request message. Ensure message is sent within latest		
	specified heartbeatInterval, and is correctly formatted with parameters:		
	• cbsdId = C		
	• grantId = G		
5	• operationState = "GRANTED"	\boxtimes	П
)	B. UUT sends a Relinquishment request message. Ensure message is correctly		
	formatted with parameters:		
	• cbdsId = C		
	• grantId = G		
	Monitor the RF output of the UUT. Verify:		
	UUT does not transmit at any time		

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 28 of 72





Plot 14. Conducted Measurement - No RF transmission in entire band (WINNF.FT.C.HBT.5) - NR

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 29 of 72



A14 [WINNF.FT.C.HBT.6] Heartbeat responseCode=501 (SUSPENDED_GRANT) in Subsequent Heartbeat Response

	Test Execution Steps	PASS	FAIL
1	Ensure the following conditions are met for test entry: • UUT has registered successfully with SAS Test Harness • UUT has a valid single grant as follows: o valid cbsdld = C o valid grantld = G o grant is for frequency range F, power P o grantExpireTime = UTC time greater than duration of the test • UUT is in AUTHORIZED state and is transmitting within the grant bandwidth F on RF		
2	 interface UUT sends a Heartbeat Request message. Ensure Heartbeat Request message is sent within Heartbeat Interval specified in the latest Heartbeat Response, and formatted correctly, including: cbsdld = C grantId = G operationState = "AUTHORIZED" 	×	
3	SAS Test Harness sends a Heartbeat Response message, including the following parameters: • cbsdld = C • grantld = G • transmitExpireTime = T = Current UTC time • responseCode = 501 (SUSPENDED_GRANT)		
4	After completion of step 3, SAS Test Harness shall not allow any further grants to the UUT.		
5	Monitor the SAS-CBSD interface. Verify either A OR B occurs: A. UUT sends a Heartbeat Request message. Ensure message is sent within latest specified heartbeatInterval, and is correctly formatted with parameters: • cbsdId = C • grantId = G • operationState = "GRANTED" B. UUT sends a Relinquishment request message. Ensure message is correctly formatted with parameters: • cbdsId = C • grantId = G Monitor the RF output of the UUT. Verify: • UUT shall stop transmission within (T + 60 seconds) of completion of step 3		

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 30 of 72





Plot 15. Conducted Measurement - RF transmission stops within 60s of SAS message indicated by Marker 1 (X) (WINNF.FT.C.HBT.6) – NR

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 31 of 72



A15 [WINNF.FT.C.HBT.7] Heartbeat responseCode=502 (UNSYNC_OP_PARAM)

	Test Execution Steps	PASS	FAIL
	Ensure the following conditions are met for test entry:		
	UUT has registered successfully with SAS Test Harness		
	UUT has a valid single grant as follows:		
	o valid cbsdld = C		
1	o valid grantId = G		
	o grant is for frequency range F, power P		
	o grantExpireTime = UTC time greater than duration of the test		
	• UUT is in AUTHORIZED state and is transmitting within the grant bandwidth F on RF		
	interface		
	UUT sends a Heartbeat Request message.		
2 3	Ensure Heartbeat Request message is sent within Heartbeat Interval specified in the		
	latest Heartbeat Response, and formatted correctly, including:	\boxtimes	
	• cbsdld = C		
	• grantId = G		
	• operationState = "AUTHORIZED"		
	SAS Test Harness sends a Heartbeat Response message, including the following		
	parameters:		
3	• cbsdld = C		
	• grantId = G		
3	• transmitExpireTime = T = Current UTC time		
	• responseCode = 502 (UNSYNC_OP_PARAM)		
4	After completion of step 3, SAS Test Harness shall not allow any further grants to the		
	UUT.		
	Monitor the SAS-CBSD interface. Verify:		
	UUT sends a Grant Relinquishment Request message. Verify message is correctly		
	formatted with parameters:		
5	o cbdsId = C	\boxtimes	
	o grantId = G		
	Monitor the RF output of the UUT. Verify:		
	• UUT shall stop transmission within (T+60) seconds of completion of step 3.		

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 32 of 72





Plot 16. Conducted Measurement - RF transmission stops within 60s of SAS message indicated by Marker 1 (X) (WINNF.FT.C.HBT.7) – NR

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 33 of 72




A16 [WINNF.FT.C.HBT.9] Heartbeat Response Absent (First Heartbeat)

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has registered successfully with SAS Test Harness UUT has a valid single grant as follows: valid cbsdld = C valid grantId = G o grant is for frequency range F, power P o grantExpireTime = UTC time greater than duration of the test UUT is in GRANTED, but not AUTHORIZED state (i.e. has not performed its first Heartbeat Request) 		
2	UUT sends a Heartbeat Request message. Ensure Heartbeat Request message is sent within latest specified heartbeatInterval, and is formatted correctly, including: • cbsdld = C • grantld = G • operationState = "GRANTED"	X	
3	After completion of Step 2, SAS Test Harness does not respond to any further messages from UUT to simulate loss of network connection		
4	Monitor the RF output of the UUT from start of test to 60 seconds after step 3. Verify: • At any time during the test, UUT shall not transmit on RF interface	×	

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 34 of 72

© 2023 ELEMENT





Plot 17. Conducted Measurement - No RF transmission in entire band at anytime (WINNF.FT.C.HBT.9) - NR

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 35 of 72



A17 [WINNF.FT.C.HBT.10] Heartbeat Response Absent (Subsequent Heartbeat)

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has registered successfully with SAS Test Harness UUT has a valid single grant as follows: valid cbsdld = C valid grantId = G o grant is for frequency range F, power P o grantExpireTime = UTC time greater than duration of the test UUT is in AUTHORIZED state and is transmitting within the grant bandwidth F on RF interface 		
2	UUT sends a Heartbeat Request message. Verify Heartbeat Request message issent within the latest specified heartbeatInterval, and is formatted correctly, including: • cbsdld = C • grantld = G • operationState = "AUTHORIZED"	×	
3	SAS Test Harness sends a Heartbeat Response message, including the following parameters: • cbsdld = C • grantld = G • transmitExpireTime = current UTC time + 200 seconds • responseCode = 0		
4	After completion of Step 3, SAS Test Harness does not respond to any further messages from UUT		
5	Monitor the RF output of the UUT. Verify: • UUT shall stop all transmission on RF interface within (transmitExpireTime + 60 seconds), using the transmitExpireTime sent in Step 3.	×	

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 36 of 72



Test Plots:



Plot 18. Conducted Measurement - RF transmission stops within transmitExpireTime + 60s. The last SAS heartbeat message is indicated by Marker 1 (X) (WINNF.FT.C.HBT.10) – NR

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 37 of 72



A18 [WINNF.FT.C.MES.1] Registration Response contains measReportConfig

	Test Execution Steps	PASS	FAIL
1	Ensure the following conditions are met for test entry:		
1	 UUT has successfully completed SAS Discovery and Authentication with SAS Test Harness 		
	UUT sends a Registration Request message.		
	Validate the Registration Request message is formatted correctly, including:		
2	userId is present and correct	×	П
2	fccld is present and correct		
	cbsdSerialNumber is present and correct		
	measCapability = "RECEIVED_POWER_WITHOUT_GRANT"		
	SAS Test Harness sends a Registration Response message, with the following		
	parameters:		
3	• cbsdld = C = valid cbsdld for this UUT		
	measReportConfig= "RECEIVED_POWER_WITHOUT_GRANT"		
	• responseCode = 0		
	UUT sends a message:		
4	• If message is type Spectrum Inquiry Request, go to step 5, or		
	• If message is type Grant Request, go to step 7		
	UUT sends message type Spectrum Inquiry Request. Verify message contains all		
5	required parameters properly formatted, and specifically:	\boxtimes	
	• cbsdld = C		
	• measReport is present, and is a properly formatted rcvdPowerMeasReport.		
	SAS Test Harness sends a Spectrum Inquiry Response, with the following		
	parameters:		
6	• cbsdld = C		
	 availableChannel is an array of availableChannel objects 		
	• responseCode = 0		
	UUT sends message type Grant Request message. Verify message contains all		
7	required parameters properly formatted, and specifically:	\boxtimes	П
,	• cbsdld = C		
	• measReport is present, and is a properly formatted rcvdPowerMeasReport.		

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 38 of 72



```
"rcvdPowerMeasReports": [
   {
        "measBandwidth": 10000000,
        "measFrequency": 3550000000,
        "measRcvdPower": -100
   },
        "measBandwidth": 10000000,
        "measFrequency": 3560000000,
        "measRcvdPower": -100
   },
        "measBandwidth": 10000000,
        "measFrequency": 3570000000,
        "measRcvdPower": -100
   },
        "measBandwidth": 10000000,
        "measFrequency": 3580000000,
        "measRcvdPower": -100
   },
        "measBandwidth": 10000000,
        "measFrequency": 3590000000,
        "measRcvdPower": -100
   },
        "measBandwidth": 10000000,
        "measFrequency": 3600000000,
        "measRcvdPower": -100
   },
        "measBandwidth": 10000000,
        "measFrequency": 3610000000,
        "measRcvdPower": -100
   },
        "measBandwidth": 10000000,
        "measFrequency": 3620000000,
        "measRcvdPower": -100
   },
```

Plot 19. Measurement Report in Registration Response (WINNF.FT.C.MES.1)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 39 of 72



```
{
    "measBandwidth": 10000000,
    "measFrequency": 3630000000,
    "measRcvdPower": -100
},
    "measBandwidth": 10000000,
    "measFrequency": 3640000000,
    "measRcvdPower": -100
},
    "measBandwidth": 10000000,
    "measFrequency": 3650000000,
    "measRcvdPower": -100
},
    "measBandwidth": 10000000,
    "measFrequency": 3660000000,
    "measRcvdPower": -100
},
    "measBandwidth": 10000000,
    "measFrequency": 3670000000,
    "measRcvdPower": -100
},
    "measBandwidth": 10000000,
    "measFrequency": 3680000000,
    "measRcvdPower": -100
},
    "measBandwidth": 10000000,
    "measFrequency": 3690000000,
    "measRcvdPower": -100
```

Plot 20. Measurement Report in Registration Response Cont. (WINNF.FT.C.MES.1)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 40 of 72



A19 [WINNF.FT.C.RLQ.1] Successful Relinquishment

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has successfully completed SAS Discovery and Authentication with SAS Test Harness UUT has successfully registered with SAS Test Harness, with cbsdld=C UUT has received a valid grant with grantId = G UUT is in Grant State AUTHORIZED and is actively transmitting within the bounds of its grant. Invoke trigger to relinquish UUT Grant from the SAS Test Harness 		
2	UUT sends a Relinquishment Request message. Verify message contains all required parameters properly formatted, and specifically: • cbsdld = C • grantld = G	×	
3	SAS Test Harness shall approve the request with a Relinquishment Response message with parameters: • cbsdld = C • grantld = G • responseCode = 0	1-	
4	After completion of step 3, SAS Test Harness will not provide any additional positive response (responseCode=0) to further request messages from the UUT.		
5	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is complete. This is the end of the test. Verify: • UUT shall stop RF transmission at any time between triggering the relinquishment and UUT sending the relinquishment request	×	

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 41 of 72



Test Plots:



Plot 21. Conducted Measurement - RF transmission stops (WINNF.FT.C.RLQ.1) - NR

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 42 of 72



A20 [WINNF.FT.C.DRG.1] Successful Deregistration

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has successfully completed SAS Discovery and Authentication with SAS Test Harness UUT has successfully registered with SAS Test Harness, with cbsdld=C UUT has received a valid grant with grantId = G UUT is in Grant State AUTHORIZED and is actively transmitting within the bounds of its grant. Invoke trigger to deregister UUT from the SAS Test Harness 		
2	UUT sends a Relinquishment request and receives Relinquishment response with responseCode=0		
3	UUT sends Deregistration Request to SAS Test Harness with cbsdld = C.	\boxtimes	
4	SAS Test Harness shall approve the request with a Deregistration Response message with parameters: • cbsdld = C • responseCode = 0		
5	After completion of step 3, SAS Test Harness will not provide any additional positive response (responseCode=0) to further request messages from the UUT		
6	Monitor the RF output of the UUT from start of test until 60 seconds after Step 4 is complete. This is the end of the test. Verify: • UUT stopped RF transmission at any time between triggering the deregistration and either A OR B occurs: A. UUT sending a Registration Request message, as this is not mandatory B. UUT sending a Deregistration Request message	×	

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 43 of 72

© 2023 ELEMENT



Test Plots:



Plot 22.Conducted Measurement - RF transmission stops within 60s. The SAS message is indicated by Marker 1 (X) (WINNF.FT.C.DRG.1) – NR

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 44 of 72



[WINNF.FT.C.SCS.1] Successful TLS connection between UUT and SAS Test **Harness**


	Test Execution Steps	PASS	FAIL
1	 UUT shall start CBSD-SAS communication with the security procedure The UUT shall establish a TLS handshake with the SAS Test Harness using configured certificate. Configure the SAS Test Harness to accept the security procedure and establish the connection 	X	
2	 Make sure that Mutual authentication happens between UUT and the SAS Test Harness. Make sure that UUT uses TLS v1.2 Make sure that cipher suites from one of the following is selected, TLS_RSA_WITH_AES_128_GCM_SHA256 TLS_RSA_WITH_AES_256_GCM_SHA384 TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384 TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 		
3	A successful registration is accomplished using one of the test cases described in section 6.1.4.1, depending on CBSD capability. • UUT sends a registration request to the SAS Test Harness and the SAS Test Harness sends a Registration Response with responseCode = 0 and cbsdld.	×	
4	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is complete. This is the end of the test. Verify: • UUT shall not transmit RF	×	

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:		
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 45 of 72	

© 2023 ELEMENT



Test Plots:



Plot 23. Conducted Measurement - No RF transmission in entire band at anytime (WINNF.FT.C.SCS.1) - NR

	.addr==172.108.154.18					Expression
No.	Time	Source	Destination	Protocol	Length Info	
	82 2023-02-07 17:46:10.109618	172.108.154.18	173.59.230.213	TCP	74 1733 + 443 [SYN] Seq=0 Win=29200 Len=0 MSS=1460 SACK_PERM=1 TSval=3776190790 TSecr=0 WS=256	
	83 2023-02-07 17:46:10.109874	173.59.230.213	172.108.154.18	TCP	66 443 + 1733 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM=1	
	84 2023-02-07 17:46:10.152725	172.108.154.18	173.59.230.213	TCP	60 1733 + 443 [ACK] Seq=1 Ack=1 Win=29440 Len=0	
	85 2023-02-07 17:46:10.152844	172.108.154.18	173.59.230.213	TLSv1.2	294 Client Hello	
	86 2023-02-07 17:46:10.153876	173.59.230.213	172.108.154.18	TLSv1.2	3101 Server Hello, Certificate, Certificate Request, Server Hello Done	
	88 2023-02-07 17:46:10.201341	172.108.154.18	173.59.230.213	TCP	60 1733 → 443 [ACK] Seq=241 Ack=3048 Win=35328 Len=0	
	89 2023-02-07 17:46:10.203230	172.108.154.18	173.59.230.213	TCP	1514 1733 → 443 [ACK] Seq=241 Ack=3048 Win=35328 Len=1460 [TCP segment of a reassembled PDU]	
	90 2023-02-07 17:46:10.203231	172.108.154.18	173.59.230.213	TCP	1514 1733 + 443 [ACK] Seq=1701 Ack=3048 Win=35328 Len=1460 [TCP segment of a reassembled PDU]	
	91 2023-02-07 17:46:10.203232	172.108.154.18	173.59.230.213	TLSv1.2	252 Certificate, Client Key Exchange	
	92 2023-02-07 17:46:10.203321	173.59.230.213	172.108.154.18	TCP	54 443 → 1733 [ACK] Seq=3048 Ack=3359 Win=262656 Len=0	
	93 2023-02-07 17:46:10.206560	172.108.154.18	173.59.230.213	TLSv1.2	323 Certificate Verify	
	94 2023-02-07 17:46:10.206561	172.108.154.18	173.59.230.213	TLSv1.2	60 Change Cipher Spec	
	95 2023-02-07 17:46:10.206562	172.108.154.18	173.59.230.213	TLSv1.2	99 Encrypted Handshake Message	
	96 2023-02-07 17:46:10.206624	173.59.230.213	172.108.154.18	TCP	54 443 + 1733 [ACK] Seq=3048 Ack=3679 Win=262400 Len=0	
	97 2023-02-07 17:46:10.226471	173.59.230.213	172.108.154.18	TLSv1.2	105 Change Cipher Spec, Encrypted Handshake Message	
	98 2023-02-07 17:46:10.270511	172.108.154.18	173.59.230.213	TCP	1514 1733 + 443 [ACK] Seq=3679 Ack=3099 Win=35328 Len=1460 [TCP segment of a reassembled PDU]	
	99 2023-02-07 17:46:10.270511	172.108.154.18	173.59.230.213	TLSv1.2	1074 Application Data	
	100 2023-02-07 17:46:10.270565	173.59.230.213	172.108.154.18	TCP	54 443 → 1733 [ACK] Seq=3099 Ack=6159 Win=262656 Len=0	
	101 2023-02-07 17:46:10.298655	173.59.230.213	172.108.154.18	TLSv1.2	100 Application Data	
	102 2023-02-07 17:46:10.387995	172.108.154.18	173.59.230.213	TCP	60 1733 → 443 [ACK] Seq=6159 Ack=3145 Win=35328 Len=0	
	103 2023-02-07 17:46:10.388056	173.59.230.213	172.108.154.18	TLSv1.2	548 Application Data, Application Data, Application Data, Application Data, Application Data, Application Data	
	104 2023-02-07 17:46:10.437569	172.108.154.18	173.59.230.213	TCP	60 1733 + 443 [ACK] Seq=6159 Ack=3639 Win=38400 Len=0	

Plot 24. WireShark Screenshot - Successful Handshake (WINNF.FT.C.SCS.1) - NR


FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 46 of 72



A22 [WINNF.FT.C.SCS.2] TLS failure due to revoked certificate

	Test Execution Steps	PASS	FAIL
1	UUT shall start CBSD-SAS communication with the security procedure	\boxtimes	
2	 Make sure that UUT uses TLS v1.2 for security establishment. Make sure UUT selects the correct cipher suite. UUT shall use CRL or OCSP to verify the validity of the server certificate. Make sure that Mutual authentication does not happen between UUT and the SAS Test Harness 	×	
3	UUT may retry for the security procedure which shall fail	\boxtimes	
4	SAS Test-Harness shall not receive any Registration request or any application data.		
5	UUT may retry for the security procedure which shall fail		


Test Plots:



Plot 25. Conducted Measurement - No RF transmission in entire band at anytime (WINNF.FT.C.SCS.2) - NR

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:		
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 47 of 72	





Plot 26. WireShark Screenshot - Failed Handshake (WINNF.FT.C.SCS.2) - NR


FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:		
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 48 of 72	



A23 [WINNF.FT.C.SCS.3] TLS failure due to expired server certificate

	Test Execution Steps	PASS	FAIL
1	UUT shall start CBSD-SAS communication with the security procedure	\boxtimes	
2	 Make sure that UUT uses TLS v1.2 for security establishment. Make sure UUT selects the correct cipher suite. UUT shall use CRL or OCSP to verify the validity of the server certificate. Make sure that Mutual authentication does not happen between UUT and the SAS 	\boxtimes	
3	Test Harness.		
4	SAS Test-Harness shall not receive any Registration request or any application data.		
5	UUT may retry for the security procedure which shall fail		

Test Plots:



Plot 27. Conducted Measurement - No RF transmission in entire band at anytime (WINNF.FT.C.SCS.3) - NR

ip.a	addr == 172, 108, 154, 18						
Vo.	Time S	Source	Destination	Protocol	Length	Info	
	168 2023-02-07 17:51:02.652127 1	172.108.154.18	173.59.230.213	TCP		74 15799 → 443 [SYN] Seq=0 Win=29200 Len=0 MSS=1460 SACK_PERM=1 TSval=3776483325 TSecr=0 WS=256	
	169 2023-02-07 17:51:02.652397 1	173.59.230.213	172.108.154.18	TCP		66 443 → 15799 [SYN, ACK] Seq-0 Ack-1 Win-65535 Len-0 MSS-1460 WS-256 SACK_PERM-1	
	170 2023-02-07 17:51:02.704128 1	172.108.154.18	173.59.230.213	TCP		60 15799 → 443 [ACK] Seq=1 Ack=1 Win=29440 Len=0	
		172.108.154.18	173.59.230.213	TLSv1.2		294 Client Hello	
		173.59.230.213	172.108.154.18	TLSv1.2		119 Server Hello, Certificate, Certificate Request, Server Hello Done	
	173 2023-02-07 17:51:02.752757 1	172.108.154.18	173.59.230.213	TCP		60 15799 → 443 [ACK] Seq=241 Ack=3066 Win=35584 Len=0	
	174 2023-02-07 17:51:02.757406 1	172.108.154.18	173.59.230.213	TLSv1.2		61 Alert (Level: Fatal, Description: Certificate Unknown)	
		172.108.154.18	173.59.230.213	TCP		60 15799 → 443 [FIN, ACK] Seq=248 Ack=3066 Win=35584 Len=0	
		173.59.230.213	172.108.154.18	TCP		54 443 → 15799 [ACK] Seq=3066 Ack=249 Win=262400 Len=0	
		173.59.230.213	172.108.154.18	TCP		54 443 → 15799 [FIN, ACK] Seq=3066 Ack=249 Win=262400 Len=0	
_	178 2023-02-07 17:51:02.801546 1	172.108.154.18	173.59.230.213	TCP		60 15799 → 443 [ACK] Seq=249 Ack=3067 Win=35584 Len=0	
_						MEASUREMENT REPORT	Approved by:
FC	CC ID: A3LSOG2201						
. 00 15: 71020002201						(CERTIFICATION)	Technical Manager
Te	est Report S/N:	Test Da	ites:	E	ЈТ Ту	pe:	
	12302100007- .A3L«Rule_Parts_2G3G	2/7/2023	3 – 2/9/2023	Sn	nallce	II	Page 49 of 72

© 2023 ELEMENT



Plot 28. WireShark Screenshot - Failed Handshake (WINNF.FT.C.SCS.3) - NR


FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:		
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 50 of 72	



A24 [WINNF.FT.C.SCS.4] TLS failure when SAS Test Harness certificate is issued by an unknown CA

	Test Execution Steps	PASS	FAIL
1	UUT shall start CBSD-SAS communication with the security procedure	\boxtimes	
	Make sure that UUT uses TLS v1.2 for security establishment.		
	Make sure UUT selects the correct cipher suite.		
2	UUT shall use CRL or OCSP to verify the validity of the server certificate.	\boxtimes	
	Make sure that Mutual authentication does not happen between UUT and the SAS		
	Test Harness.		
3	UUT may retry for the security procedure which shall fail	\boxtimes	
4	SAS Test-Harness shall not receive any Registration request or any application data.		
	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is		
5	complete. This is the end of the test. Verify:	\boxtimes	
	UUT shall not transmit RF		

Test Plots:



Plot 29. Conducted Measurement - No RF transmission in entire band at anytime (WINNF.FT.C.SCS.4) - NR

FCC ID: A3LSOG2201		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:		
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 51 of 72	



	addr==172.108.154.18					[2]	Expression	+
No.	Time	Source	Destination	Protocol	Lengt	Length Info		
	74 2023-02-07 17:52:27.018545	172.108.154.18	173.59.230.213	TCP		74 12560 → 443 [SYN] Seq=0 Win=29200 Len=0 MSS=1460 SACK_PERM=1 TSval=3776567692 TSecr=0 WS=256		
	75 2023-02-07 17:52:27.018777	173.59.230.213	172.108.154.18	TCP		66 443 → 12560 [SYN, ACK] Seq-0 Ack-1 Win-65535 Len-0 MSS-1460 WS-256 SACK PERM-1		
	76 2023-02-07 17:52:27.063080	172.108.154.18	173.59.230.213	TCP		60 12560 → 443 [ACK] Seq-1 Ack-1 Win-29440 Len-0		
	77 2023-02-07 17:52:27.063354	172.108.154.18	173.59.230.213	TLSv1.2		294 Client Hello		
	78 2023-02-07 17:52:27.064354	173.59.230.213	172.108.154.18	TLSv1.2		3121 Server Hello, Certificate, Certificate Request, Server Hello Done		
	79 2023-02-07 17:52:27.113032	172.108.154.18	173.59.230.213	TCP		60 12560 + 443 [ACK] Seq=241 Ack=1461 Win=32256 Len=0		
	80 2023-02-07 17:52:27.113033	172.108.154.18	173.59.230.213	TCP		60 12560 + 443 [ACK] Seq=241 Ack=3068 Win=35584 Len=0		
	81 2023-02-07 17:52:27.117949	172.108.154.18	173.59.230.213	TLSv1.2		61 Alert (Level: Fatal, Description: Certificate Unknown)		
	82 2023-02-07 17:52:27.117949	172.108.154.18	173.59.230.213	TCP		60 12560 + 443 [FIN, ACK] Seq=248 Ack=3068 Win=35584 Len=0		
	83 2023-02-07 17:52:27.118052	173.59.230.213	172.108.154.18	TCP		54 443 → 12560 [ACK] Seq=3068 Ack=249 Win=262400 Len=0		
	84 2023-02-07 17:52:27.118346	173.59.230.213	172.108.154.18	TCP		54 443 → 12560 [FIN, ACK] Seq=3068 Ack=249 Win=262400 Len=0		
L	85 2023-02-07 17:52:27.162680	172,108,154,18	173,59,230,213	TCP		60 12560 + 443 [ACK] Seg=249 Ack=3069 Win=35584 Len=0		

Plot 30.WireShark Screenshot – Failed Handshake (WINNF.FT.C.SCS.4) – NR


FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 52 of 72



A25 [WINNF.FT.C.SCS.5] TLS failure when certificate at the SAS Test Harness is corrupted

	Test Execution Steps	PASS	FAIL
1	UUT shall start CBSD-SAS communication with the security procedure	\boxtimes	
2	 Make sure that UUT uses TLS v1.2 for security establishment. Make sure UUT selects the correct cipher suite. UUT shall use CRL or OCSP to verify the validity of the server certificate. 	×	
	• Make sure that Mutual authentication does not happen between UUT and the SAS Test Harness.		
3	UUT may retry for the security procedure which shall fail	\boxtimes	
4	SAS Test-Harness shall not receive any Registration request or any application data.		
5	Monitor the RF output of the UUT from start of test until 60 seconds after Step 3 is complete. This is the end of the test. Verify: • UUT shall not transmit RF	X	

Test Plots:



Plot 31. Conducted Measurement - No RF transmission in entire band at anytime (WINNF.FT.C.SCS.5) - NR

					Expression
No. Time	Source	Destination	Protocol	Length Info	
17 2023-02-07 17:53:59.084338	172.108.154.18	173.59.230.213	TCP	74 18390 + 443 [SYN] Seq=0 Win=29200 Len=0 MSS=1460 SACK_PERM=1 TSval=3776659757 TSecr=0 WS=256	
18 2023-02-07 17:53:59.084572	173.59.230.213	172.108.154.18	TCP	66 443 + 18390 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM=1	
19 2023-02-07 17:53:59.133956	172.108.154.18	173.59.230.213	TCP	60 18390 → 443 [ACK] Seq=1 Ack=1 Win=29440 Len=0	
20 2023-02-07 17:53:59.133957	172.108.154.18	173.59.230.213	TLSv1.2	294 Client Hello	
21 2023-02-07 17:53:59.135231	173.59.230.213	172.108.154.18	TLSv1.2	3101 Server Hello, Certificate, Certificate Request, Server Hello Done	
22 2023-02-07 17:53:59.183735	172.108.154.18	173.59.230.213	TCP	60 18390 → 443 [ACK] Seq=241 Ack=3048 Win=35328 Len=0	
23 2023-02-07 17:53:59.186848	172.108.154.18	173.59.230.213	TLSv1.2	61 Alert (Level: Fatal, Description: Certificate Unknown)	
24 2023-02-07 17:53:59.186849	172.108.154.18	173.59.230.213	TCP	60 18390 → 443 [FIN, ACK] Seq=248 Ack=3048 Win=35328 Len=0	
25 2023-02-07 17:53:59.186977	173.59.230.213	172.108.154.18	TCP	54 443 → 18390 [ACK] Seq=3048 Ack=249 Win=262400 Len=0	
26 2023-02-07 17:53:59.187390	173.59.230.213	172.108.154.18	TCP	54 443 + 18390 [FIN, ACK] Seq=3048 Ack=249 Win=262400 Len=0	
27 2023-02-07 17:53:59.232850	172.108.154.18	173.59.230.213	TCP	60 18390 + 443 [ACK] Seq=249 Ack=3049 Win=35328 Len=0	
FCC ID: A3LSOG2201				MEASUREMENT REPORT	Approved by:
FCC ID: A3LSUG2201				(CERTIFICATION)	Technical Manager
Test Report S/N:	Test Dat	es:	EU	T Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023	- 2/9/2023	Sm	allcell	Page 53 of 72



Plot 32. WireShark Screenshot - Failed Handshake (WINNF.FT.C.SCS.5) - NR

FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 54 of 72



A26 [WINNF.PT.C.HBT.1] UUT RF Transmit Power Measurement

	Test Execution Steps	PASS	FAIL
1	 Ensure the following conditions are met for test entry: UUT has successfully completed SAS Discovery and Authentication with the SAS Test Harness UUT has registered with the SAS, with CBSD ID = C UUT has a single valid grant G with parameters {lowFrequency = FL, highFrequency = FH, maxEirp = Pi}, with grant in AUTHORIZED state, and grantExpireTime set to a value far past the duration of this test case Note: in order for the UUT to request a grant with the parameters {lowFrequency, highFrequency, maxEirp}, the SAS Test Harness may need to provide appropriate guidance in the availableChannel object of the spectrumInquiry response message, and the operationParam object of the grant response message. Alternately, the UUT vendor may provide the ability to set those parameters on the UUT so that the UUT will request a grant with those parameters. 		
2	 UUT and SAS Test Harness perform a series of Heartbeat Request/Response cycles, which continues until the other test steps are complete. Messaging for each cycle is as follows: UUT sends Heartbeat Request, including:		
3	Tester performs power measurement on RF interface(s) of UUT, and verifies it complies with the maxEirp setting, Pi. The RF measurement method is out of scope of this document, but may include additional configuration of the UUT, as required, to fulfil the requirements of the power measurement method. Note: it may be required for the vendor to provide a method or configuration to bring the UUT to a mode which is required by the measurement methodology. Any such mode is vendor-specific and depends upon UUT behavior and the measurement methodology.	×	

FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 55 of 72

© 2023 ELEMENT



RF Power Measurements:

Testing is performed per KDB 971168 D01 and across the transmit dynamic range of 29dBm/MHz to 17dBm/MHz for 20MHz Bandwidth. Per the manufacturer, when all 8 antennas are operating, the maximum antenna gain is 8dBi. 8dbi is used for maximum directional gain per KDB 662911 because the device operates in 4 sectors, each with a pair of cross-polarized antennas. The PSD of each transmitter was measured and summed in linear terms and then the directional antenna gain was added to yield the max EIRP.

Granted EIRP [dBm/MHz]	Tx1 Conducted PSD [dBm/MHz]	Tx2 Conducted PSD [dBm/MHz]	Tx3 Conducted PSD [dBm/MHz]	Tx4 Conducted PSD [dBm/MHz]	Tx5 Conducted PSD [dBm/MHz]	Tx6 Conducted PSD [dBm/MHz]	Tx7 Conducted PSD [dBm/MHz]	Tx8 Conducted PSD [dBm/MHz]	Summed PSD [dBm/MHz]	Max Directional Ant Gain [dBi]	EIRP [dBm/MHz]	Margin [dB]
29.00	11.40	11.32	11.98	11.14	11.79	11.26	11.51	11.72	20.55	8.00	28.55	-0.45
23.00	5.73	5.39	5.63	5.14	5.40	5.48	5.63	5.38	14.51	8.00	22.51	-0.49
17.00	-0.52	-0.64	-0.70	-0.49	-0.49	-0.32	-0.58	-0.58	8.49	8.00	16.49	-0.51

Table 7-1 RF Output Power Measurements (WINNF.PT.C.HBT.1 – NR)

Example Summed PSD calculation:

11.40 dBm + 11.32 dBm + 11.98 dBm + 11.14 dBm + 11.79 dBm + 11.26 dBm + 11.51 dBm + 11.72 dBm = 11.40 dBm

13.804 mW + 13.552 mW + 15.776 mW + 13.002 mW + 15.101 mW + 13.336 mW + 14.158 mW + 14.859 mW = 113.618 mW = 20.55 dBm

Example EIRP calculation


Total Conducted PSD + Directional Antenna Gain = EIRP/MHz

20.55 dBm/MHz + 8.00 dBi = 28.55 dBm/MHz

FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 56 of 72



Test Plots:




Conducted PSD, 3.56GHz, 20MHz BW - ANT1, SAS Granted maxEIRP 29dBm/MHz (NR) Plot 33.



FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 57 of 72



Plot 34. Conducted PSD, 3.56GHz, 20MHz BW – ANT2, SAS Granted maxEIRP 29dBm/MHz (NR)




Plot 35. Conducted PSD, 3.56GHz, 20MHz BW - ANT3, SAS Granted maxEIRP 29dBm/MHz (NR)



Plot 36. Conducted PSD, 3.56GHz, 20MHz BW – ANT4, SAS Granted maxEIRP 29dBm/MHz (NR)

FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 58 of 72






Plot 37. Conducted PSD, 3.56GHz, 20MHz BW – ANT5, SAS Granted maxEIRP 29dBm/MHz (NR)



FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 59 of 72



Plot 38. Conducted PSD, 3.56GHz, 20MHz BW – ANT6, SAS Granted maxEIRP 29dBm/MHz (NR)




Plot 39. Conducted PSD, 3.56GHz, 20MHz BW – ANT7, SAS Granted maxEIRP 29dBm/MHz (NR)

FCC ID: A3LSOG2201		Approved by: Technical Manager	
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 60 of 72






Plot 40. Conducted PSD, 3.56GHz, 20MHz BW – ANT8, SAS Granted maxEIRP 29dBm/MHz (NR)



Plot 41. Conducted PSD, 3.56GHz, 20MHz BW – ANT1, SAS Granted maxEIRP 23dBm/MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 61 of 72






Plot 42. Conducted PSD, 3.56GHz, 20MHz BW – ANT2, SAS Granted maxEIRP 23dBm /MHz (NR)



Plot 43. Conducted PSD, 3.56GHz, 20MHz BW – ANT3, SAS Granted maxEIRP 23dBm /MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 62 of 72






Plot 44. Conducted PSD, 3.56GHz, 20MHz BW – ANT4, SAS Granted maxEIRP 23dBm /MHz (NR)



Plot 45. Conducted PSD, 3.56GHz, 20MHz BW – ANT5, SAS Granted maxEIRP 23dBm /MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 63 of 72






Plot 46. Conducted PSD, 3.56GHz, 20MHz BW – ANT6, SAS Granted maxEIRP 23dBm /MHz (NR)



Plot 47. Conducted PSD, 3.56GHz, 20MHz BW – ANT7, SAS Granted maxEIRP 23dBm /MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 64 of 72





Plot 48. Conducted PSD, 3.56GHz, 20MHz BW – ANT8, SAS Granted maxEIRP 23dBm /MHz (NR)




Plot 49. Conducted PSD, 3.56GHz, 20MHz BW – ANT1, SAS Granted maxEIRP 17dBm/MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 65 of 72






Plot 50. Conducted PSD, 3.56GHz, 20MHz BW - ANT2, SAS Granted maxEIRP 17dBm /MHz (NR)




Plot 51. Conducted PSD, 3.56GHz, 20MHz BW – ANT3, SAS Granted maxEIRP 17dBm /MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 66 of 72






Plot 52. Conducted PSD, 3.56GHz, 20MHz BW – ANT4, SAS Granted maxEIRP 17dBm /MHz (NR)




Plot 53. Conducted PSD, 3.56GHz, 20MHz BW – ANT5, SAS Granted maxEIRP 17dBm /MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 67 of 72






Plot 54. Conducted PSD, 3.56GHz, 20MHz BW - ANT6, SAS Granted maxEIRP 17dBm /MHz (NR)



Plot 55. Conducted PSD, 3.56GHz, 20MHz BW – ANT7, SAS Granted maxEIRP 17dBm /MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 68 of 72





Plot 56. Conducted PSD, 3.56GHz, 20MHz BW – ANT8, SAS Granted maxEIRP 17dBm /MHz (NR)

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L «Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 69 of 72



APPENDIX B - TEST LOGS

Logs are available upon request

PowerMeasTest_2023-02-09T20.53.29Z	2/9/2023 4:51 PM	Text Document
PowerMeasTest_2023-02-09T21.56.49Z	2/9/2023 5:06 PM	Text Document
PowerMeasTest_2023-02-09T22.07.06Z	2/13/2023 4:06 PM	Text Document
5 SCS.1	2/7/2023 12:47 PM	Wireshark capture
5 SCS.2 SCS.2	2/7/2023 12:50 PM	Wireshark capture
5 SCS.3	2/7/2023 12:51 PM	Wireshark capture
5 SCS.4 €	2/7/2023 12:52 PM	Wireshark capture
5 SCS.5 €	2/7/2023 12:54 PM	Wireshark capture
WINNF.FT.C.DRG.1_2023-02-08T19.36.27Z	2/8/2023 2:39 PM	Text Document
WINNF.FT.C.GRA.1_2023-02-07T17.59.40Z	2/7/2023 1:02 PM	Text Document
WINNF.FT.C.GRA.2_2023-02-07T18.04.51Z	2/7/2023 1:05 PM	Text Document
WINNF.FT.C.HBT.1_2023-02-07T18.06.48Z	2/7/2023 1:17 PM	Text Document
WINNF.FT.C.HBT.3_2023-02-07T22.49.30Z	2/7/2023 5:53 PM	Text Document
WINNF.FT.C.HBT.4_2023-02-07T23.07.37Z	2/7/2023 6:12 PM	Text Document
WINNF.FT.C.HBT.5_2023-02-07T23.16.02Z	2/7/2023 6:17 PM	Text Document
WINNF.FT.C.HBT.6_2023-02-07T23.25.06Z	2/7/2023 6:30 PM	Text Document
WINNF.FT.C.HBT.7_2023-02-08T00.04.41Z	2/7/2023 7:07 PM	Text Document
WINNF.FT.C.HBT.9_2023-02-07T22.25.58Z	2/7/2023 5:30 PM	Text Document
WINNF.FT.C.HBT.10_2023-02-08T19.04.53Z	2/8/2023 2:11 PM	Text Document
WINNF.FT.C.MES.1_2023-02-07T22.24.37Z	2/7/2023 5:25 PM	Text Document
WINNF.FT.C.REG.1_2023-02-07T17.45.43Z	2/7/2023 12:46 PM	Text Document
WINNF.FT.C.REG.8_2023-02-07T17.55.09Z	2/7/2023 12:55 PM	Text Document
WINNF.FT.C.REG.10_2023-02-07T17.56.12Z	2/7/2023 12:56 PM	Text Document
WINNF.FT.C.REG.12_2023-02-07T17.56.54Z	2/7/2023 12:57 PM	Text Document
WINNF.FT.C.REG.14_2023-02-07T17.57.31Z	2/7/2023 12:57 PM	Text Document
WINNF.FT.C.REG.16_2023-02-07T17.58.11Z	2/7/2023 12:58 PM	Text Document
WINNF.FT.C.REG.18_2023-02-07T17.58.53Z	2/7/2023 12:59 PM	Text Document
WINNF.FT.C.RLQ.1_2023-02-08T19.30.36Z	2/8/2023 2:33 PM	Text Document

FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G	2/7/2023 – 2/9/2023	Smallcell	Page 70 of 72



FCC ID: A3LSOG2201	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N:	Test Dates:	EUT Type:	
1M2302100007- 01.A3L«Rule_Parts_2G3G »	2/7/2023 – 2/9/2023	Smallcell	Page 71 of 72