

RF EXPOSURE **EVALUATION REPORT**

APPLICANT

Bragi GMBH

PRODUCT NAME

The Dash Left

MODEL NAME

B1000L

TRADE NAME

Bragi

BRAND NAME

Bragi

FCC ID

2AF5TB1000L

47CFR 2.1093

STANDARD(S)

KDB 447498 D01 General RF Exposure

Guidance v06

ISSUE DATE

2016-3-9

COMMUNICATIONS TECHNOLOGY Co., Ltd. SHENZHEN MORL

NOTE: This document is issued by MORLAB, the test results apply only to the particular same oduced except in full without prior written permission of the the specific tests carried out which is available on request for validation and information confirmed at our website.

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Tel: 86-755-36698555 Fax: 86-755-36698525 Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Http://www.morlab.com E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	3
1. TECHNICAL INFORMATION	4
1.1. IDENTIFICATION OF APPLICANT 1.2. IDENTIFICATION OF MANUFACTURER	4
1.2. IDENTIFICATION OF MANUFACTURER	4
1.3. EQUIPMENT UNDER TEST (EUT)	4
1.3.1. PHOTOGRAPHS OF THE EUT ······	5
1.3.2. IDENTIFICATION OF ALL USED EUT	6
1.4. APPLIED REFERENCE DOCUMENTS	6
2.DEVICE CATEGORY AND RF EXPOSURE LIMIT	·······7
all glab more mo.	ELAB MORL MO. AE IN
3.MEASUREMENT OF CONDUCTED PEAK OUTPUT I	POWER8
E REAL HOPE WO IE ELAB	HOPE MO SEASON
4. RF EXPOSURE EVALUATION	9
ANNEX A GENERAL INFORMATION	10

	Change History				
Issue Date Reason for change					
1.0	2016-3-9 First edition				
MORE	MIN	B SLAL MORE ME AB SRIAL MORE			



TEST REPORT DECLARATION

Applicant	Bragi GMBH
Applicant Address	Sendlinger Str. 7/ Angerblock 2.OG, 80331 München, Germany
Manufacturer	Bragi GMBH
Manufacturer Address	Sendlinger Str. 7/ Angerblock 2.OG, 80331 München, Germany
Product Name	The Dash Left
Model Name	B1000L
Brand Name	Bragi
HW Version	B1.2 for Beta3
SW Version	B3_RC2
Test Standards	47CFR 2.1093; KDB 447498 D01 General RF Exposure Guidance v06
Issue Date	2016-3-9
SAR Evaluation	Not Required

Tested by	: <u>p</u>	:LIN Jum		
		Liu Jun		
Reviewed by	e:	zhu zhan	de Contraction de la contracti	
		Zhu Zhan		
Approved by	: <u> </u>	Leng Dewn		
		Zena Dexin		



1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant

Company Name:	Bragi GMBH
Address:	Sendlinger Str. 7/ Angerblock 2.OG, 80331 München, Germany

1.2. Identification of Manufacturer

Company Name:	Bragi GMBH
Address:	Sendlinger Str. 7/ Angerblock 2.OG, 80331 München, Germany

1.3. Equipment Under Test (EUT)

Model Name:	B1000L
Trade Name:	Bragi
Brand Name:	Bragi
Hardware Version:	B1.2 for Beta3
Software Version:	B3_RC2
Frequency Bands:	Bluetooth 2.1+EDR/ Bluetooth 4.0:2402-2480MHz;
Modulation Mode:	Bluetooth 2.1+EDR: GFSK/π/4-DQPSK/8-DPSK
OF THE TLAS	Bluetooth 4.0: GFSK;
Antenna type:	Fixed Internal Antenna
Development Stage:	Identical prototype



1.3.1. Photographs of the EUT

EUT front view



2. EUT view





1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	B1.2 for Beta3	B3_RC2

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1 OPLAS	47 CFR§2.1093	Radiofrequency Radiation Exposure Evaluation: portable devices
2	KDB 447498 D01v06	General RF Exposure Guidance



2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, this device is a Bluetooth Headset. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices:

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.





3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

1. Bluetooth Average output power

Band	Channel	Frequency	Output Power(dBm)		
Dallu	Chaine	(MHz)	GFSK	π/4-DQPSK	8-DPSK
N. SLAE	0	2402	7.77	7.60	7.75
BT2.1+EDR	39	2441	9.41	9.39	9.36
LAE ORL	78	2480	9.34	9.31	9.27

		Frequency	Output Power(dBm)
Band		(MHz)	GFSK
RLAL	.o° 0	2402	6.12
BT4.0	19	2440	7.36
MORL	39	2480	7.12



4. RF EXPOSURE EVALUATION

The device only incorporates a Bluetooth transmitter, so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

Standalone transmission SAR evaluation

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] ≤ 3.0

The maximum tune-up limit power is 8.91mW @ 2.441GHz

When Bluetooth Headset is worn on the head, BT antenna spacing 0mm from body, so use **5mm** as the most conservative minimum test separation distance,

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] =2.76 \leq 3.0

So SAR evaluation is not required for this device.





ANNEX A GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

