

1. This device is a programmable Bluetooth low energy beacon.
2. The equipment is powered by CR2032 battery.
3. The equipment includes 2 monochrome LEDs (red/green) and a touch switch for developers to use.
4. The initial software version, after power-on, the device will broadcast at an interval of 300ms.
5. The broadcast name is: Puck. js.   xxxx (XXXX is 2 bytes after the MAC address).
6. Bluetooth UUID Sever: 6E400001-B5A3-F393-E0A9-E50E24DCCA9E  
    Notify UUID: 6E400003-B5A3-F393-E0A9-E50E24DCCA9E  
    Write UUID: 6E400002-B5A3-F393-E0A9-E50E24DCCA9E

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that

interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Warning: changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment