TEST REPORT

DT&C Co., Ltd. **Dt&C** 42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042 Tel: 031-321-2664, Fax: 031-321-1664 1. Report No: DRTFCC1904-0092 2. Customer Name : LG Electronics USA, Inc. Address : 1000 Sylvan Ave. Englewood Cliffs, New Jersey, United States 07632 3. Use of Report : FCC Original Grant 4. Product Name / Model Name : Mobile Phone / LM-G810EAW FCC ID : ZNFG810EAW 5. Test Method Used : ANSI C63.10-2013 Test Specification : FCC Part 15.225 6. Date of Test : 2019.03.15 ~ 2019.03.28 7. Testing Environment : Refer to appended test report. 8. Test Result : Refer to the attached test result. Tested by Reviewed by Affirmation Name: GeunKi Son Name: SunGeun Lee

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DT&C Co., Ltd.

2019.01.15.

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description
DRTFCC1904-0092	Apr. 15, 2019	Initial issue

CONTENTS

1. General Information4
1.1. Testing Laboratory4
1.2. Testing Environment4
1.3. Measurement Uncertainty4
1.4. Details of Applicant5
1.5. Description of EUT5
1.6. EUT CAPABILITIES5
2. Information about test items 6
2.1 Test mode6
2.2 Tested frequency6
2.3 EMI Suppression Device(s)/Modifications6
3. Antenna requirements6
4. Test report7
4.1 Summary of tests7
4.2 Transmitter requirements8
4.2.1 20dB bandwidth 8
4.2.2 In-band emissions9
4.2.3 Out-of-band emissions11
4.2.4 Frequency Stability13
4.2.5 AC Line Conducted Emissions 14
APPENDIX

1. General Information

1.1. Testing Laboratory

DT&C Co., Ltd.

The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042. The test site complies with the requirements of § 2.948 according to ANSI C63.4-2014.

- FCC MRA Accredited Test Firm No. : KR0034

www.dtnc.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.2. Testing Environment

Ambient Condition			
 Temperature 	+20 °C ~ +23 °C		
 Relative Humidity 	35 % ~ 45 %		

1.3. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C 63.4-2014. All measurement uncertainty values are shown with a coverage factor of k = 2 to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty	
AC conducted emission	2.4 dB (The confidence level is about 95 %, $k = 2$)	
Radiated Disturbance (Below 1 GHz)	5.1 dB (The confidence level is about 95 %, $k = 2$)	



1.4. Details of Applicant

Applicant	:	LG Electronics USA, Inc.
Address	:	1000 Sylvan Ave. Englewood Cliffs, New Jersey, United States 07632
Contact person	:	Kyung-Su Han

1.5. Description of EUT

FCC Equipment Class	Low Power Communications Device Transmitter(DXX)		
EUT	Mobile Phone		
Model Name	LM-G810EAW		
Add Model Name	LMG810EAW, G810EAW, LM-G810EA, LMG810EA, G810EA, LM-G810RA, LMG810RA, G810RA		
Serial Number	Identical prototype		
Power Supply	DC 4.0 V		
Frequency Band	13.56 MHz		
Modulation Type	ASK		
Channel(s)	1		
Antenna type	Loop Antenna		

1.6. EUT CAPABILITIES

This EUT contains the following capabilities:

850/1900 GSM/EDGE, 850/1900 WCDMA/HSUPA, Multi-band LTE, 802.11b/g/n/ac WLAN(2.4GHz), 802.11a/n/ac WLAN(5GHz), Bluetooth(BDR, EDR, LE), NFC, WPC, 60G Wireless transmission.

2. Information about test items

2.1 Test mode

Test mode1	est mode1 Continuous transmitting mode	
Test mode2	Continuous transmitting mode(With Wireless charging pad)	

Note 1: This device supports wireless charging capability.

So per KDB 648474 D03 v01r04, the radiated test items were performed both normal and charging conditions. For wireless charging condition, the handset is placed on the representative charging pad under normal conditions and in a simulated call configuration.

Note 2: The worst case data rate was determined according to the fundamental emission level. And data rate was tested at the worst case(106 kbps).

2.2 Tested frequency

Channel	TX Frequency(MHz)	
Lowest	13.56	
Middle	-	
Highest	-	

2.3 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing \rightarrow None

3. Antenna requirements

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

The antenna is attached on the device by means of unique coupling method (Spring Tension). Therefore this E.U.T Complies with the requirement of §15.203

4. Test report

4.1 Summary of tests

FCC part section(s)	RSS section(s)	Parameter	Limit	Test condition	Status Note 1
2.1049	-	20 dB Bandwidth	-		С
-	RSS-Gen [6.7]	Occupied Bandwidth	-		NA
15.225 (a)	RSS-210 [B6(a)]	In-Band Emissions	15,848 µV/m @ 30 m 13.553 – 13.567 MHz		C Note 3
15.225 (b)	RSS-210 [B6(b)]	In-Band Emissions	334 μV/m @ 30 m 13.410 – 13.553 MHz 13.567 – 13.710 MHz	Radiated	C Note 3
15.225 (c)	RSS-210 [B6(c)]	In-Band Emissions	106 μV/m @ 30 m 13.110 – 13.410 MHz 13.710 – 14.010 MHz		C Note 3
15.225 (d) 15.209	RSS-210 [B6(d)] RSS-GEN [8.9]	Out-of Band Emissions	Emissions outside of the specified band (13.110-14.010 MHz) must meet the radiated limits detailed in 15.209		C Note 3
15.225 (e)	RSS-210 [B6]	Frequency Stability	±0.01 % of operating frequency	Temp & Humid Test Chamber	С
15.207	RSS-Gen [8.8]	AC Conducted Emissions	FCC Part 15.207	AC Line Conducted	С
15.203	-	Antenna Requirements	FCC Part 15.203	-	С

Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable

Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS.

Note 3: This test items were performed both normal and charging conditions.

4.2 Transmitter requirements

4.2.1 20dB bandwidth

- Procedure:

The 20 dB Bandwidth is measured with a spectrum analyzer connected via a receive antenna placed near the EUT while the EUT is operating in transmission mode.

And spectrum analyzer setting use following test procedure of ANCSI C63.10-2013 – Section 6.9.2.

- 1. Center frequency = EUT channel center frequency
- 2. Span = 2 ~ 5 times the OBW
- 3. RBW = 1 % ~ 5 % OBW
- 4. VBW \ge 3 x RBW
- 5. Detector = Peak
- 6. Trace = Max hold
- 7. The trace was allowed to stabilize
- 8. Determine the reference value = Set the spectrum analyzer marker to the highest level of the displayed trace
- Using the marker-delta function of the instrument, determine the "-xx dB down amplitude" using [(reference value) xx].
- 10. Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

- Measurement Data: Comply



Note: The 20dB bandwidth was measured at all data rate and the worst case data was reported

- Minimum Standard: NA



4.2.2 In-band emissions

- Test Configuration



- Procedure: The radiated emission was tested according to the section 6.4 of the ANSI C63.10-2013.

The EUT was placed on a 0.8 m high non-conductive table and it was placed at 3m distance from the antenna. Measurements were performed for each of the three antenna orientations. (ie. parallel, perpendicular, and ground-parallel)

Also, measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

RBW = As specified in below table, $VBW \ge 3 \times RBW$, Sweep = Auto, Detector = PeakTrace mode = Max Hold until the trace stabilizes.

Frequency	RBW	
9-150 kHz	200-300 Hz	
0.15-30 MHz	9-10 kHz	
30-1000 MHz	100-120 kHz	
> 1000 MHz	1 MHz	

- Minimum Standard: Part 15.225(a), (b), (c) & RSS-210 [B6(a), (b), (c)]

Frequency Band [MHz]	Limit at 30 m measurement distance		
	[uV/m]	[dBuV/m]	
13.553-13.567	15,848	84.00	
13.410-13.553 13.567-13.710	334	50.47	
13.110-13.410 13.710-14.010	106	40.51	

- Measurement Data: Test mode 1

Tested Frequency	:	13.56 MHz
Measurement Distance	:	3 Meters

Test Frequency Band [MHz]	Freq. [MHz]	EUT Axis.	ANT (Note 1)	Reading Level [dBuV]	T.F [dB/m]	Field Strength @3 m [dBuV/m]	Field Strength @30 m [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13.110 ~ 13.410	13.346	Y	Р	15.50	19.22	34.72	-5.28	40.51	45.79
13.410 ~ 13.553	13.553	Y	Р	20.30	19.22	39.52	-0.48	50.47	50.95
13.553 ~ 13.567	13.559	Y	Р	28.00	19.22	47.22	7.22	84.00	76.78
13.567 ~ 13.710	13.665	Y	Р	18.00	19.22	37.22	-2.78	50.47	53.25
13.710 ~ 14.010	13.772	Y	Р	14.70	19.22	33.92	-6.08	40.51	46.59

- Measurement Data: Test mode 2

Tested Frequency:13.56 MHzMeasurement Distance:3 Meters

Test Frequency Band [MHz]	Freq. [MHz]	EUT Axis.	ANT (Note 1)	Reading Level [dBuV]	T.F [dB/m]	Field Strength @3 m [dBuV/m]	Field Strength @30 m [dBuV/m]	Limit [dBuV/m]	Margin [dB]
13.110 ~ 13.410	13.347	Х	Р	14.03	19.22	33.25	-6.75	40.51	47.26
13.410 ~ 13.553	13.553	Х	Р	21.63	19.22	40.85	0.85	50.47	49.62
13.553 ~ 13.567	13.559	Х	Р	29.63	19.22	48.85	8.85	84.00	75.15
13.567 ~ 13.710	13.665	Х	Р	15.83	19.22	35.05	-4.95	50.47	55.42
13.710 ~ 14.010	13.771	Х	Р	13.62	19.22	32.84	-7.16	40.51	47.67

Note 1. Loop antenna orientation

"P": Parallel, "V": perpendicular, "G": ground-parallel

Note 2. This test item was performed at 3 m and the data were extrapolated to the specified measurement distance of 30 m using the square of an inverse linear distance extrapolation factor (40 dB/decade) as specified in §15.31(f)2.

• Extrapolation Factor = $20 \log_{10}(30/3)^2 = 40 \text{ dB}$

Note 3. All data were recorded using a spectrum analyzer employing a peak detector.

If PK results were meet Quasi-peak limit, Quasi-peak measurements were omitted.

Note 4. Sample Calculation.

- Margin = Limit Field Strength @ 30 m
- / Field Strength @ 30 m = Field Strength @ 3 m 40 dB
- Field Strength @ 3 m = Reading + T.F
- / T.F = AF + CL

Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss

4.2.3 Out-of-band emissions

- Test configuration



- Procedure: The radiated emission was tested according to the section 6.4, 6.5 of the ANSI C63.10-2013.

The EUT was tested from 9 kHz up to the 1 GHz excluding the band 13.110-14.010 MHz.

The EUT was placed on a 0.8 m high non-conductive table and it was placed at 3m distance from the antenna. For measurements below 30MHz were performed for each of the three antenna orientations.

(ie. parallel, perpendicular, and ground-parallel) For measurements above 30MHz were performed for each of the both horizontal and vertical polarizations.

Also, measurements were performed with the EUT oriented in 3 orthogonal axis and rotated 360 degrees to determine worst-case orientation for maximum emissions.

RBW = As specified in below table, VBW \ge 3 x RBW, Sweep = Auto, Detector = Peak Trace mode = Max Hold until the trace stabilizes.

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

- Minimum Standard: Part 15.209, 225(d) & RSS-210[B6(d)], RSS-GEN[8.9] • FCC Part 15.209(a):

Frequency [MHz]	Field Strength [uV/m]	Measurement Distance [Meters]
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	200	3

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

• FCC Part 15.209(b):

In the emission table above, the tighter limit applies at the band edges.

Dt&C

- Measurement Data: Test mode 1

Tested Frequency	:	13.56 MHz
Measurement Distance	:	<u>3 Meters</u>

Frequency [MHz]	EUT Axis.	ANT (Note 1)	Reading [dBuV]	T.F [dB/m]	Distance factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
0.099	Y	Р	56.8	18.68	80	-4.52	27.7	32.22
1.581	Y	Р	14.5	18.87	40	-6.63	23.6	30.23
20.680	Y	Р	12	19.72	40	-8.28	29.5	37.78
27.120	Y	Р	10.4	20.2	40	-9.4	29.5	38.9
40.549	Y	Н	27.6	-10.46	0	17.14	40	22.86
40.549	Y	V	28	-10.46	0	17.54	40	22.46
67.951	Y	V	27.4	-12.25	0	15.15	40	24.85
102.870	Y	Н	31.7	-12.26	0	19.44	43.5	24.06
419.808	Y	Н	26.2	-4.17	0	22.03	46	23.97
592.726	Y	V	25.9	0.06	0	25.96	46	20.04
882.456	Y	Н	26.5	4.18	0	30.68	46	15.32

- Measurement Data: Test mode 2

Tested Frequency	:	13.56 MHz
Measurement Distance	:	3 Meters

Frequency [MHz]	EUT Axis.	ANT (Note 1)	Reading [dBuV]	T.F [dB/m]	Distance factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
0.125	Х	Р	61.61	18.67	80	0.28	25.7	25.42
0.722	Х	Р	26.7	18.69	40	5.39	30.4	25.01
25.100	Х	Р	12.29	20.06	40	-7.65	29.5	37.15
27.140	Х	Р	11.72	20.38	40	-7.9	29.5	37.4
40.549	Х	Н	37.1	-10.46	0	26.64	40	13.36
40.549	Х	V	45.5	-10.46	0	35.04	40	4.96
67.709	Х	V	45.6	-12.21	0	33.39	40	6.61
149.065	Х	Н	35.9	-8.79	0	27.11	43.5	16.39
241.091	Х	Н	39.2	-9.63	0	29.57	46	16.43
747.839	Х	V	25.9	2.73	0	28.63	46	17.37
787.845	Х	V	26.2	4.07	0	30.27	46	15.73

Note 1. Loop antenna orientation (30 MHz Below)

"P"= Parallel, "V"= perpendicular, "G"= ground-parallel

Bilog antenna polarization (30 MHz above)

"H"= Horizontal, "V"= Vertical

Note 2. All data were recorded using a spectrum analyzer employing a peak detector.

If PK results were meet Quasi-peak limit, Quasi-peak measurements were omitted.

Note 3. No other spurious and harmonic emissions were reported greater than listed emissions above table.

Note 4. Sample calculation

 $\begin{array}{l} Margin = Limit - Field \ Strength \\ Field \ Strength = Reading + T.F - Distance \ factor \\ T.F = AF + CL - AG \\ Distance \ factor = 20 log(Measurement \ distance \ / \ The \ measured \ distance)^2 \\ Where, \ T.F = \ Total \ Factor, \quad AF = \ Antenna \ Factor, \quad CL = \ Cable \ Loss, \quad AG = \ Amplifier \ Gain \$

4.2.4 Frequency Stability

- Procedure:

Part 15.225 requires that devices operating in the 13.553 - 13.567 MHz shall maintain the carrier frequency within 0.01 % of the operating frequency over the temperature variation of -20 degrees to + 50 degrees C at normal supply voltage.

- Measurement Data: Comply

Operating Frequency : 13,560,000 Hz

VOLTAGE (%)	POWER (V _{DC})	TEMP (℃)	Frequency (Hz)	Freq. Dev. (Hz)	Deviation (%)
100%		+20(ref)	13,560,030	30	0.000220
100%		-20	13,559,944	-56	0.000413
100%		-10	13,559,980	-20	0.000147
100%		0	13,560,004	4	0.000029
100%	4.0	+10	13,560,028	28	0.000206
100%		+20	13,560,030	30	0.000220
100%		+30	13,560,049	49	0.000361
100%		+40	13,560,183	183	0.001350
100%		+50	13,560,207	207	0.001527
110%	4.4	+20	13,560,082	82	0.000605
BATT.ENDPOINT	3.0	+20	13,560,005	5	0.000037

Note. At the request of the applicant, the voltage of highest level is tested at 110%.

- Minimum Standard: Part 15. 225(e) & RSS-210 [B6]

The frequency tolerance of the carrier signal shall be maintained within ±0.01 % of the operating frequency.



4.2.5 AC Line Conducted Emissions

- Test Requirements and limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 µH/50 ohms line impedance stabilization network (LISN).

Frequency Range	Conducted Limit (dBuV)			
(MHz)	Quasi-Peak	Average		
0.15 ~ 0.5	66 to 56 *	56 to 46 *		
0.5 ~ 5	56	46		
5 ~ 30	60	50		

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

- Test Configuration

See test photographs for the actual connections between EUT and support equipment.

- Test Procedure

- 1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
- 2. The EUT is connected via LISN to a test power supply.
- 3. The measurement results are obtained as described below:
- 4. Detectors Quasi Peak and Average Detector.
- Measurement Data: Comply (refer to the next page)

Measurement Data

Results of Conducted Emission





Measurement Data

DTNC

Results of Conducted Emission

Date 2019-03-15

Order No. Model No. LM-G810EAW Serial No. Test Condition NFC			Referrence Power Sup Temp/Hun Operator	e No. oply ni.	120 V, 60 Hz 23 'C / 45 % Lee Sun Geun				
Mem	0								
LIMIT	FCC P15 FCC P15	.207 QF .207 AV	r r						
NO	FREQ	REA QP [dBuV]	DING CAV][dBuV	C.FACTOR] [dB]	RESULT QP CAV [dBuV] [dBu	LI QP [V] [dBuV	MIT CAV [dBuV]	MARGIN QP CAV] [dBuV][dBuV	PHASE
1	0.16815	18.38	3.51	9.99	28.37 13.50	65.05	55.05	36.68 41.55	N
2	0.24328	14.69	3.72	9.98	24.67 13.70	61.98	51.98	37.31 38.28	N
3	0.41709	10.51	2.29	9.99	20.50 12.28	57.51	47.51	37.01 35.23	N
4	0.60374	0.72	-2.95	10.01	10.73 7.00	5 56.00	46.00	45.27 38.94	N
5	1.14640	-0.44	-3.60	10.01	9.57 6.41	56.00	46.00	46.4339.59	N
6	2.14280	0.94	-3.67	10.07	11.01 6.40	56.00	46.00	44.9939.60	N
7	4.70540	5.36	0.36	10.18	15.54 10.54	56.00	46.00	40.4635.46	N
8	6.97660	8.51	2.90	10.26	18.77 13.10	5 60.00	50.00	41.2336.84	N
9	16.74240	2.37	-2.98	10.51	12.88 7.53	60.00	50.00	47.12 42.47	N
10	0.15536	17.80	4.40	9.96	27.7614.30	5 65.71	55.71	37.95 41.35	L1
11	0.21756	13.13	4.35	9.96	23.09 14.31	62.91	52.91	39.82 38.60	L1
12	0.43626	13.10	8.98	9.96	23.0618.94	57.13	47.13	34.0728.19	L1
13	0.85666	3.39	0.38	9.98	13.37 10.30	5 56.00	46.00	42.6335.64	L1
14	2.10040	4.20	-0.83	10.03	14.23 9.20	56.00	46.00	41.7736.80	L1
15	3.64800	3.64	-1.06	10.10	13.74 9.04	56.00	46.00	42.2636.96	L1
16	6.33540	12.92	4.62	10.20	23.12 14.82	2 60.00	50.00	36.88 35.18	Ll
17	6.63300	10.08	2.24	10.20	20.28 12.44	60.00	50.00	39.72 37.56	Ll
18	13.22980	1.62	-3.99	10.40	12.02 6.41	60.00	50.00	47.98 43.59	Ll
19	19.66040	-0.18	-5.01	10.50	10.32 5.49	60.00	50.00	49.6844.51	L1

APPENDIX TEST EQUIPMENT FOR TESTS



Туре	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	18/12/19	19/12/19	MY50410357
Multimeter	FLUKE	17B	18/12/18	19/12/18	26030065WS
Signal Generator	Rohde Schwarz	SMBV100A	18/12/19	19/12/19	255571
Thermohygrometer	BODYCOM	BJ5478	18/12/27	19/12/27	120612-1
Thermohygrometer	SATO	PC-5000TRH-II	18/07/18	19/07/18	N/A
HYGROMETER	TESTO	608-H1	19/01/31	20/01/31	34862883
Temp & Humi Test Chamber	SJ Science	SJ-TH-S50	18/07/06	19/07/06	U5542113
Loop Antenna	Schwarzbeck	FMZB1513	18/01/30	20/01/30	1513-128
BILOG ANTENNA	Schwarzbeck	VULB 9160	18/07/13	20/07/13	3359
PreAmplifier	tsj	MLA-10K01-B01-27	18/10/31	19/10/31	2005354
EMI Receiver	ROHDE&SCHWARZ	ESW44	18/08/06	19/08/06	101645
EMI Test Receiver	Rohde Schwarz	ESCI7	19/01/30	20/01/30	100910
PULSE LIMITER	Rohde Schwarz	ESH3-Z2	18/09/27	19/09/27	101333
			18/03/20	19/03/20	- 06183
LISN	SCHWARZBECK	NNLK 8121	19/03/19	20/03/19	
Cable	HUBER+SUHNER	SUCOFLEX	18/12/21	19/12/21	C-1
Cable	HUBER+SUHNER	SUCOFLEX	18/12/21	19/12/21	C-2
Cable	HUBER+SUHNER	SUCOFLEX	18/12/21	19/12/21	C-3
Cable	HUBER+SUHNER	SUCOFLEX	18/12/21	19/12/21	C-4
Cable	DT&C	CABLE	18/07/05	19/07/05	RF-82

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017 Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.