

TP-LINK®

Antenna Specification



Product Number:

Product Name: Antenna

TP-LINK®

COPYRIGHT & TRADEMARKS

Specifications are subject to change without notice. **TP-LINK®** is a registered trademark of TP-LINK TECHNOLOGIES CO., LTD. Other brands and product names are trademarks or registered trademarks of their respective holders.

No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK TECHNOLOGIES CO., LTD. Copyright © 2011 TP-LINK TECHNOLOGIES CO., LTD. All rights reserved.

<http://www.tp-link.com>

Product Number:

Product Name: Antenna

TP-LINK®

Specification For Approval

Product Number:

Product Name: Antenna

TP-LINK®

Date: _____

File No. : _____

Version: 1.0

Customer: _____ / _____

Customer P/N : _____ / _____

TP-LINK P/N: _____

Description: Tapo T100(US)1.0 antenna

TP-LINK Checked By:
Customer Approved By:

TP-LINK®

TP-LINK TECHNOLOGIES CO., LTD.

South Buiding, No.5 Keyuan Road,
Central Zone, Science&Technology Park,
Nanshan, Shenzhen, P.R.China

TEL: + 86 755 26612350

+ 86 755 26504400

[http:// www.tp-link.com](http://www.tp-link.com)

Index

Specification	2
I. Characteristics and Reliability Test.....	2
II. Antenna – S Parameter Test Data.....	5
III. Antenna – Radiation Pattern Test Data	6
Packing Drawing	7

Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency	912~932 MHz
Impedance	50 Ohm
S.W.R.	≤ 3.0
Antenna Gain	-6.0dBi
Max Input Power	≤ 2 W
Polarization	Linear
Radiation pattern	Omni-Directional
B. Material & Mechanical Characteristics	
Material of Radiator	Copper
Material of Plastic	/
Cable Type	/
Connector Type	/
Connector Pull Test	/
C. Environmental	
Operation Temperature	In accordance with PCB
Storage Temperature	In accordance with PCB

I. Characteristics and Reliability Test

Test Items		Test Condition and Procedure	Requirements
C1	S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification
C2	Antenna Gain	Set DUT on Antenna Chamber;	Directive DUT specification

Product Number:

Product Name: Antenna

TP-LINK®

		make individual calibration to test	
M1	Vibration	MIL-STD-202G, 201 A Amplitude: 0.03 inch (0.76mm); Freq: 10 to 55 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol. <=5%
M2	Random Drop	Height: 1.5 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol. <=5%
M3	Drop Test	Combine DUT with router; Height: 0.6 Meter; 1 direction; 3 times for the direction	1. No parts separated 2. Frequency Tol. <=5%
M4	Terminal- Pull Test	MIL-STD-202G, 211A, cond. A Holding with individual specification; force applied to axis of terminal	1. Directive DUT specification 2. Frequency Tol. <=5%
M5	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	SE-GS-90T Temp: 35°C; RH: 93%±3%; NaCl solution proportion: 1.026 ~ 1.041; Time: 12 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. <=5%
E2	Thermal Shock	1 Cycle: -20°C (30 minutes) to +70°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. <=5%
E3	Life (HighTemp.)	MIL-STD-202G, 108A, cond. A Temp: 70°C; Time: 8 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol. <=5%

Product Number:

Product Name: Antenna


TP-LINK®

Product Number:

Product Name: Antenna

TP-LINK®

II. Antenna – S Parameter Test Data



Product Number:

Product Name: Antenna

TP-LINK®

III. Antenna – Radiation Pattern Test Data

Testing Equipment Specification	
Microwave Chamber	ETS AMS-8923
Testing Equipment	Agilent E5071C

III.1 Ant 1

Ant 1											
Freq. (MHz)	912	914	916	918	920	922	924	926	928	930	932
Gain (dBi)	-7.41	-6.70	-6.55	-6.36	-6.40	-6.00	-6.00	-6.15	-6.64	-6.39	-6.53
Effi. (%)	7.967	9.863	12.23	13.50	13.20	11.98	10.77	10.33	10.61	11.03	10.6

Product Number:

Product Name: Antenna

TP-LINK®

Packing Drawing

