



TEST REPORT

Report No. : AF026279-001 Date : 2005 November 16

Application No. : LF219586(9)

Client : Mattel Asia Pacific Sourcing Limited
13/F., South Tower, World Finance Centre,
Harbour City, Tsimshatsui, Kowloon, Hong Kong.

Sample Description : One(1) submitted sample(s) stated to be 1: 32 GT Racer
of Model No. H9283
Rating : 2 x 1.5V AA size batteries
No. of submitted sample : Three (3) piece(s)

Date Received : 2005 November 03

Test Period : 2005 November 03 – 2005 November 14

Test Requested : FCC Part 15 Certification.

Test Method : FCC Rules and Regulations Part 15 – July 2004
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15
Subpart C.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____

Danny Chui
EMC Engineer - EL. Division

FCC ID: PIYH9283-05A2T

Page 1 of 11



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	10
5.1	Bandwidth	10
5.2	Duty cycle	10
5.3	Transmission time	10
6	Appendices	11



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for 1: 32 GT Racer operating at 27.145MHz which is controlled by a crystal. The EUT is powered by 2 x 1.5V AA size battery. It has two trigger button keys in the centre of EUT. When the trigger key is pressed once, it will transmit a radio signal to receiver go forward or spin moving.

The brief circuit description is listed as follows :

- X1 and associated circuit act as oscillator.
- U1 and associated circuit act as encoder.
- T1, L3 and associated circuit act as filter.



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	2GB05000535-0001
Loop Antenna	EMCO	6502	00056620	49906



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
27.145	V	51.4	16.4	-6.1	61.7	80.0	-18.3
54.289	V	17.4	8.1	-	25.5	40.0	-14.5
81.434	V	15.8	7.2	-	23.0	40.0	-17.0
*108.586	V	12.1	11.0	-	23.1	43.5	-20.4
*135.728	V	10.1	12.4	-	22.5	43.5	-21.0
*162.883	H	11.2	10.4	-	21.6	43.5	-21.9
190.020	V	12.6	9.2	-	21.8	43.5	-21.7
217.165	H	13.3	9.7	-	23.0	46.0	-23.0
*244.420	H	20.9	9.7	-	30.6	46.0	-15.4
*271.450	H	13.2	13.9	-	27.1	46.0	-18.9



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

Test Result :

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 Duty cycle

The duty cycle is simply the on-time divided by the period :

$$\begin{aligned}\text{The duration of one cycle} &= 31\text{ms} \\ \text{Effective period of the cycle} &= (0.92 \times 8)\text{ms} + (0.44 \times 18)\text{ms} \\ &= 15.28\text{ms} \\ \text{Duty Cycle} &= 15.28 / 31.0 \\ &= 0.493\end{aligned}$$

Therefore, the average factor is found by $20 \log_{10} 0.493 = -6.1\text{dB}$

5.3 Transmission time

NA



TEST REPORT

Report No. : AF026279-001

Date : 2005 November 16

6 Appendices

A1	Photos of the set-up of Radiated Emissions	1	Page
A2	Photos of External Configurations	1	Page
A3	Photos of Internal Configurations	1	Page
A4	ID Label/Location	1	Page
A5	Bandwidth Plot	1	Page
A6	Average Factor	2	Pages
A7	Block Diagram	1	Page
A8	Schematics	1	Page
A9	User Manual	4	Pages
A10	Operation Description	1	Page

***** End of Report *****