

# TEST REPORT

**Applicant:** Shanghai Mobiletek Communication Ltd.  
**Address:** Part 6H3 Factory No.17 No.33 Xiya Rd.  
China(Shanghai) Pilot Free Trade Zone  
**Equipment Type:** LTE Module  
**Model Name:** L511-2  
**Brand Name:** LYNQ  
**FCC ID:** 2AK9DL511-2  
**Test Standard:** 47 CFR Part 2.1091  
KDB 447498 D04 v01  
**Test Date:** Dec. 30, 2024 - Jan. 02, 2025  
**Date of Issue:** Jan. 14, 2025

**ISSUED BY:**

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Xiong Lining

**Checked by:** Xu Rui

**Approved by:** Tolan Tu  
(Testing Director)

*Xiong Li Ning*

*Xu Rui*

*Tolan Tu*

**Revision History**

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Jan. 14, 2025</u>	<u>Initial Issue</u>

**TABLE OF CONTENTS**

<b>1</b>	<b>GENERAL INFORMATION</b>	<b>3</b>
1.1	Test Laboratory	3
1.2	Test Location	3
<b>2</b>	<b>PRODUCT INFORMATION</b>	<b>4</b>
2.1	Applicant Information	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Technical Information	4
<b>3</b>	<b>SUMMARY OF TEST RESULT</b>	<b>5</b>
3.1	Test Standards	5
3.2	Limit Standards	5
<b>4</b>	<b>DEVICE CATEGORY AND LEVELS LIMITS</b>	<b>6</b>
<b>5</b>	<b>ASSESSMENT RESULT</b>	<b>8</b>
5.1	Output Power	8
5.2	Tune-up power	8
5.3	RF Exposure Evaluation Result	8
5.4	Conclusion	8

# 1 GENERAL INFORMATION

## 1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

## 1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input checked="" type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	Shanghai Mobiletek Communication Ltd.
Address	Part 6H3 Factory No.17 No.33 Xiya Rd. China(Shanghai) Pilot Free Trade Zone

### 2.2 Manufacturer Information

Manufacturer	Shanghai Mobiletek Communication Ltd.
Address	Part 6H3 Factory No.17 No.33 Xiya Rd. China(Shanghai) Pilot Free Trade Zone

### 2.3 General Description for Equipment under Test (EUT)

EUT Name	LTE Module
Model Name Under Test	L511-2
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

### 2.4 Technical Information

Network and Wireless connectivity	4G Network LTE FDD Band 1/2/3/4/5/7/8/28/66 LTE TDD Band 40 GPS, BDS, GLONASS
-----------------------------------	-------------------------------------------------------------------------------------

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	LTE		
Frequency Range	LTE B2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE B4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE B5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE B7	TX: 2500 ~ 2570 MHz	RX: 2620 ~ 2690 MHz
	LTE B66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2200 MHz
Antenna Type	WWAN	PIFA Antenna	
Exposure Category	General Population/Uncontrolled Exposure		
Product Type	Mobile Device		

### 3 SUMMARY OF TEST RESULT

#### 3.1 Test Standards

No.	Identity	Document Title
1	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

#### 3.2 Limit Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices

## 4 DEVICE CATEGORY AND LEVELS LIMITS

### Mobile Devices:

CFR Title 47 §2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

### FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1).  
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
300		39	65	88	110	129	148	166	184	201	217
450		22	44	67	89	112	135	158	180	203	226
835		9	25	44	66	90	116	145	175	207	240
1900		3	12	26	44	66	92	122	157	195	236
2450		3	10	22	38	59	83	111	143	179	219
3600		2	8	18	32	49	71	96	125	158	195
5800		1	6	14	25	40	58	80	106	136	169

## 5 ASSESSMENT RESULT

### 5.1 Output Power

LTE					
Mode	Band 2	Band 4	Band 5	Band 7	Band 66
Conducted Power (dBm)	22.85	24.28	22.02	22.22	22.87
Antenna Gain (dBi)	2.30	2.30	2.30	2.30	2.30
EIRP/ERP (dBm)	25.15	26.58	22.17	24.52	25.17
Note: This report listed the worst case conducted power value, please refer to RF test report No. BL-SH24C1024-501 for more details.					

### 5.2 Tune-up power

Mode		Conducted Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)
LTE	Band 2	【22.00,24.00】	【24.30,26.30】	【22.15,24.15】
	Band 4	【23.50,25.50】	【25.80,27.80】	【23.65,25.65】
	Band 5	【21.00,23.00】	/	【21.15,23.15】
	Band 7	【21.00,23.00】	【23.30,25.30】	【21.15,23.15】
	Band 66	【22.00,24.00】	【24.30,26.30】	【22.15,24.15】
Note1: ERP= EIRP -2.15dB.				
Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.				

### 5.3 RF Exposure Evaluation Result

Evolution mode	Frequency(MHz)	Distance (cm)	Maximum power (dBm)	Maximum power (mw)	Threshold Power (mW)	Verdict
LTE Band 2	1850	20	24.15	260.02	3060.00	Pass
LTE Band 4	1710	20	25.65	367.28	3060.00	Pass
LTE Band 5	824	20	23.15	206.54	1680.96	Pass
LTE Band 7	2500	20	23.15	206.54	3060.00	Pass
LTE Band 66	1710	20	24.15	260.02	3060.00	Pass

### 5.4 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.



## Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--