



# ELEMENT MATERIALS TECHNOLOGY

(formerly know PCTEST)  
 18855 Adams Ct, Morgan Hill, CA 95307 USA  
 Tel. +1.410.290.6652 / Fax +1.410.290.6654  
<http://www.element.com>



## SAR EVALUATION REPORT

**Applicant Name:**

Apple, Inc.  
 One Apple Park Way  
 Cupertino, CA 95014 USA

**Date of Testing:**

08/07/2022 – 08/16/2022

**Test Site/Location:**

Element, Morgan Hill, CA, USA

**Document Serial No.:**

1C2205090043-22.BCG

**FCC ID:**

**BCG-A2684**

**APPLICANT:**

**APPLE, INC.**

**DUT Type:**

Watch

**Application Type:**

Certification

**FCC Rule Part(s):**

CFR §2.1093

**Model(s):**

A2684, A2859

**Reference FCC ID:**

BCG-A2622

Equipment Class	Band & Mode	Tx Frequency	SAR	
			1g Head (W/kg)	10g Extremity (W/kg)
PCT	UMTS 850	826.40 - 846.60 MHz	< 0.1	0.31
PCT	UMTS 1750	1712.4 - 1752.6 MHz	0.17	< 0.1
PCT	UMTS 1900	1852.4 - 1907.6 MHz	0.74	< 0.1
PCT	LTE Band 26 (Cell)	814.7 - 848.3 MHz	< 0.1	0.38
PCT	LTE Band 5 (Cell)	824.7 - 848.3 MHz	< 0.1	0.34
PCT	LTE Band 66 (AWS)	1710.7 - 1779.3 MHz	0.13	< 0.1
PCT	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	N/A	N/A
PCT	LTE Band 25 (PCS)	1850.7 - 1914.3 MHz	0.93	< 0.1
PCT	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	N/A	N/A
PCT	LTE Band 7	2502.5 - 2567.5 MHz	0.65	0.18
PCT	LTE Band 41	2498.5 - 2687.5 MHz	0.48	0.17
DTS	2.4 GHz WLAN	2412 - 2472 MHz	0.33	0.12
NII	U-NII-1	5180 - 5240 MHz	N/A	N/A
NII	U-NII-2A	5260 - 5320 MHz	< 0.1	< 0.1
NII	U-NII-2C	5500 - 5720 MHz	< 0.1	< 0.1
NII	U-NII-3	5745 - 5825 MHz	< 0.1	< 0.1
DSS/DTS	Bluetooth	2402 - 2480 MHz	< 0.1	< 0.1
Simultaneous SAR per KDB 690783 D01v01r03:			1.26	0.55

This table above includes test data from RF exposure technical report S/N: 1C2205090042-22.BCG per FCC TCB workshop for data referencing of closely related product FCC ID: BCG-A2622.

This watch has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.9 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

RJ Ortanez  
 Executive Vice President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: [sartick@mwfai.info](mailto:sartick@mwfai.info).

<b>FCC ID:</b> BCG-A2684	<b>SAR EVALUATION REPORT</b>	<b>Approved by:</b> Technical Manager
<b>Document S/N:</b> 1C2205090043-22.BCG	<b>DUT Type:</b> Watch	Page 1 of 32

# TABLE OF CONTENTS

1	DEVICE UNDER TEST .....	3
2	LTE INFORMATION .....	10
3	INTRODUCTION .....	11
4	DOSIMETRIC ASSESSMENT .....	12
5	TEST CONFIGURATION POSITIONS.....	13
6	RF EXPOSURE LIMITS .....	14
7	FCC MEASUREMENT PROCEDURES.....	15
8	SYSTEM VERIFICATION.....	20
9	SAR DATA SUMMARY .....	24
10	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	27
11	EQUIPMENT LIST .....	28
12	MEASUREMENT UNCERTAINTIES.....	29
13	CONCLUSION.....	30
14	REFERENCES .....	31
APPENDIX A: SAR TISSUE SPECIFICATIONS		
APPENDIX B: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 2 of 32

# 1 DEVICE UNDER TEST

## 1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 26 (Cell)	Voice/Data	814.7 - 848.3 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 66 (AWS)	Voice/Data	1710.7 - 1779.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 25 (PCS)	Voice/Data	1850.7 - 1914.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
LTE Band 7	Voice/Data	2502.5 - 2567.5 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
UWB	Data	6489.6 - 7987.2 MHz

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 3 of 32

## 1.2 Data Referencing

Mode	Reference Model BCG-A2622	Variant Model BCG-A2684
UMTS 850	Fully Evaluated	Referenced
UMTS 1750	Fully Evaluated	Referenced
UMTS 1900	Fully Evaluated	Referenced
LTE Band 12	Fully Evaluated	Not Referenced
LTE Band 17	Fully Evaluated	Not Referenced
LTE Band 13	Fully Evaluated	Not Referenced
LTE Band 14	Fully Evaluated	Not Referenced
LTE Band 26 (Cell)	Fully Evaluated	Referenced
LTE Band 5 (Cell)	Fully Evaluated	Referenced
LTE Band 66 (AWS)	Fully Evaluated	Referenced
LTE Band 4 (AWS)	Fully Evaluated	Referenced
LTE Band 25 (PCS)	Fully Evaluated	Referenced
LTE Band 2 (PCS)	Fully Evaluated	Referenced
LTE Band 7	Fully Evaluated	Referenced
LTE Band 41	Fully Evaluated	Referenced
2.4 GHz WLAN	Fully Evaluated	Referenced
U-NII-1	Fully Evaluated	Referenced
U-NII-2A	Fully Evaluated	Referenced
U-NII-2C	Fully Evaluated	Referenced
U-NII-3	Fully Evaluated	Referenced
Bluetooth	Fully Evaluated	Referenced

Per manufacturer declaration, there are two watch devices FCC ID: BCG-A2622 and FCC ID: BCG-A2684, with high degree of similarity, reference model FCC ID: BCG-A2622 and variant model FCC ID: BCG-A2684. The reference model supports LTE B12, B13, B17 and B14 operations, however the variant model does not. Both models share the same material, form factor, circuit design, and components, including antennas and their locations. The reference and variant models use the same material, form factor, circuit design, and components, including antennas and their locations. The reference and variant models use the same power tables and have same tune-up tolerances.

Per FCC Approved Data Referencing Test Plan, testing was done fully on the reference model FCC ID: BCG-A2622, while spot-check verification has been performed on variant model FCC ID: BCG-A2684. The reference and variant model comparison data summary is included in section 9. Please see RF exposure technical report S/N: 1C2205090042-22.BCG for complete compliance evaluation for the reference model.

## 1.3 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 4 of 32

## 1.4 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

### 1.4.1 Maximum Output Power – UMTS Mode

Mode/Band		Modulated Average Output Power (in dBm)		
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6
UMTS Band 5 (850 MHz)	Max allowed power	25.00	25.00	24.00
	Nominal	24.00	24.00	23.00
UMTS Band 4 (1750 MHz)	Max allowed power	24.00	24.00	24.00
	Nominal	23.00	23.00	23.00
UMTS Band 2 (1900 MHz)	Max allowed power	24.00	24.00	24.00
	Nominal	23.00	23.00	23.00

### 1.4.2 Maximum Output Power – LTE Mode

Mode / Band		Modulated Average Output Power (in dBm)
LTE FDD Band 26	Max allowed power	25.50
	Nominal	24.50
LTE FDD Band 5	Max allowed power	25.50
	Nominal	24.50
LTE FDD Band 4	Max allowed power	24.50
	Nominal	23.50
LTE FDD Band 66	Max allowed power	24.50
	Nominal	23.50
LTE FDD Band 2	Max allowed power	24.50
	Nominal	23.50
LTE FDD Band 25	Max allowed power	24.50
	Nominal	23.50
LTE FDD Band 7	Max allowed power	23.50
	Nominal	22.50
LTE TDD Band 41 (PC3)	Max allowed power	23.50
	Nominal	22.50

FCC ID: BCG-A2684	SAR EVALUATION REPORT		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch		Page 5 of 32

### 1.4.3

### Maximum Output Power – WiFi Mode

Mode/ Band			IEEE 802.11b (2.4 GHz)		IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm)	20 MHz Bandwidth	1	19.00	18.00	17.00	16.00	17.00	16.00
		2	19.00	18.00	18.00	17.00	18.00	17.00
		3	19.00	18.00	18.50	17.50	18.50	17.50
		4	19.00	18.00	18.50	17.50	18.50	17.50
		5	19.00	18.00	18.50	17.50	18.50	17.50
		6	19.00	18.00	18.50	17.50	18.50	17.50
		7	19.00	18.00	18.50	17.50	18.50	17.50
		8	19.00	18.00	18.50	17.50	18.50	17.50
		9	19.00	18.00	18.00	17.00	18.00	17.00
		10	19.00	18.00	17.00	16.00	17.00	16.00
		11	19.00	18.00	14.00	13.00	14.00	13.00
		12	18.00	17.00	13.00	12.00	13.00	12.00
		13	16.00	15.00	2.00	1.00	2.00	1.00

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm)	20 MHz Bandwidth	36	17.00	16.00	17.00	16.00
		40	17.00	16.00	17.00	16.00
		44	17.00	16.00	17.00	16.00
		48	17.00	16.00	17.00	16.00
		52	17.00	16.00	17.00	16.00
		56	17.00	16.00	17.00	16.00
		60	17.00	16.00	17.00	16.00
		64	17.00	16.00	17.00	16.00
		100	17.00	16.00	17.00	16.00
		104	17.00	16.00	17.00	16.00
		108	17.00	16.00	17.00	16.00
		112	17.00	16.00	17.00	16.00
		116	17.00	16.00	17.00	16.00
		120	17.00	16.00	17.00	16.00
		124	17.00	16.00	17.00	16.00
		128	17.00	16.00	17.00	16.00
		132	17.00	16.00	17.00	16.00
		136	16.00	15.00	16.00	15.00
		140	14.50	13.50	14.50	13.50
		144	17.00	16.00	17.00	16.00
		149	17.00	16.00	17.00	16.00
		153	17.00	16.00	17.00	16.00
		157	17.00	16.00	17.00	16.00
		161	17.00	16.00	17.00	16.00
		165	17.00	16.00	17.00	16.00

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>		Approved by:
Document S/N: 1C2205090043-22.BCG			Technical Manager
DUT Type: Watch			Page 6 of 32

#### 1.4.4

#### Maximum Output Power – Bluetooth Mode

Mode / Band		Modulated Average - Single Tx Chain (dBm)
Bluetooth BDR/LE	Maximum	<b>13.00</b>
	Nominal	<b>12.00</b>
Bluetooth EDR	Maximum	<b>13.00</b>
	Nominal	<b>12.00</b>
Bluetooth HDR	Maximum	<b>13.00</b>
	Nominal	<b>12.00</b>

### 1.5 DUT Antenna Locations

A diagram showing the location of the device antennas can be found in Appendix B.

### 1.6 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna. A diagram showing the location of the NFC antenna can be found in Appendix B.

### 1.7 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 7 of 32

**Table 1-1  
Simultaneous Transmission Scenarios**

No.	Capable Transmit Configuration	Head	Extremity
1	UMTS + 2.4 GHz WI-FI	Yes	Yes
2	UMTS + 5 GHz WI-FI	Yes	Yes
3	UMTS + 2.4 GHz Bluetooth	Yes	Yes
4	UMTS + 2.4 GHz Bluetooth + 5 GHz WI-FI	Yes	Yes
5	LTE + 2.4 GHz WI-FI	Yes	Yes
6	LTE + 5 GHz WI-FI	Yes	Yes
7	LTE + 2.4 GHz Bluetooth	Yes	Yes
8	LTE + 2.4 GHz Bluetooth + 5 GHz WI-FI	Yes	Yes
9	2.4 GHz Bluetooth + 5 GHz WI-FI	Yes	Yes

1. 2.4 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
2. 2.4 GHz WLAN, and 5 GHz WLAN share the same antenna path and cannot transmit simultaneously.
3. Licensed modes cannot transmit simultaneously.
4. When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN scenario.
5. This device supports VOLTE.
6. This device supports VOWIFI.

## 1.8 Miscellaneous SAR Test Considerations

### (A) WIFI/BT

This device supports channel 1-13 for 2.4 GHz WLAN. However, because channel 12/13 targets are not higher than that of channels 1-11, channels 1, 6, and 11 were considered for SAR testing per FCC KDB 248227 D01V02r02.

Since U-NII-1 and U-NII-2A bands have the same maximum output power and the highest reported SAR for U-NII-2A is less than 1.2 W/kg, SAR is not required for U-NII-1 band according to FCC KDB Publication 248227 D01v02r02.

### (B) Licensed Transmitter(s)

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r04.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 8 of 32



This device supports LTE capabilities with overlapping transmission frequency ranges. When the supported frequency range of an LTE Band falls completely within an LTE band with a larger transmission frequency range, both LTE bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both LTE bands share the same transmission path and signal characteristics, SAR was only assessed for the band with the larger transmission frequency range.

This device is limited to 27 RB on the uplink for 16QAM modulation. Additional measurements were evaluated to support SAR test exclusion for 16 QAM as described in Section 7.5.4.

## 1.9 Guidance Applied

- FCC KDB Publication 941225 D01v03r01, D05v02r04 (3G/4G)
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance, Wrist-worn Device Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- IEEE 1528-2013

## 1.10 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 9.

## 1.11 Bibliography

Report Type	Report Serial Number
BCG-A2622 FCC SAR Report	1C2205090042-22.BCG

## 1.12 Device Housing Types and Wrist Band Types

This device has one housing type that was evaluated independently for SAR: Titanium. The device can also be used with different wristband accessories. The non-metallic wrist accessory, sport and fabric band, were evaluated for all exposure conditions.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 9 of 32

## 2 LTE INFORMATION

LTE Information					
Form Factor	Watch				
	LTE Band 26 (Cell) (814.7 - 848.3 MHz)				
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)				
	LTE Band 66 (AWS) (1710.7 - 1779.3 MHz)				
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)				
	LTE Band 25 (PCS) (1850.7 - 1914.3 MHz)				
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)				
	LTE Band 7 (2502.5 - 2567.5 MHz)				
	LTE Band 41 (2498.5 - 2687.5 MHz)				
	LTE Band 26 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz				
	LTE Band 66 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 25 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 7: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
	LTE Band 41: 5 MHz, 10 MHz, 15 MHz, 20 MHz				
Channel Numbers and Frequencies (MHz)	Low	Low-Mid	Mid	Mid-High	High
LTE Band 26 (Cell): 1.4 MHz		814.7 (26697)	831.5 (26865)	848.3 (27033)	
LTE Band 26 (Cell): 3 MHz		815.5 (26705)	831.5 (26865)	847.5 (27025)	
LTE Band 26 (Cell): 5 MHz		816.5 (26715)	831.5 (26865)	846.5 (27015)	
LTE Band 26 (Cell): 10 MHz		819 (26740)	831.5 (26865)	844 (26990)	
LTE Band 5 (Cell): 1.4 MHz		824.7 (20407)	836.5 (20525)	848.3 (20643)	
LTE Band 5 (Cell): 3 MHz		825.5 (20415)	836.5 (20525)	847.5 (20635)	
LTE Band 5 (Cell): 5 MHz		826.5 (20425)	836.5 (20525)	846.5 (20625)	
LTE Band 5 (Cell): 10 MHz		829 (20450)	836.5 (20525)	844 (20600)	
LTE Band 66 (AWS): 1.4 MHz		1710.7 (131979)	1745 (132322)	1779.3 (132665)	
LTE Band 66 (AWS): 3 MHz		1711.5 (131987)	1745 (132322)	1778.5 (132657)	
LTE Band 66 (AWS): 5 MHz		1712.5 (131997)	1745 (132322)	1777.5 (132647)	
LTE Band 66 (AWS): 10 MHz		1715 (132022)	1745 (132322)	1775 (132622)	
LTE Band 66 (AWS): 15 MHz		1717.5 (132047)	1745 (132322)	1772.5 (132597)	
LTE Band 66 (AWS): 20 MHz		1720 (132072)	1745 (132322)	1770 (132572)	
LTE Band 4 (AWS): 1.4 MHz		1710.7 (19957)	1732.5 (20175)	1754.3 (20393)	
LTE Band 4 (AWS): 3 MHz		1711.5 (19965)	1732.5 (20175)	1753.5 (20385)	
LTE Band 4 (AWS): 5 MHz		1712.5 (19975)	1732.5 (20175)	1752.5 (20375)	
LTE Band 4 (AWS): 10 MHz		1715 (20000)	1732.5 (20175)	1750 (20350)	
LTE Band 4 (AWS): 15 MHz		1717.5 (20025)	1732.5 (20175)	1747.5 (20325)	
LTE Band 4 (AWS): 20 MHz		1720 (20050)	1732.5 (20175)	1745 (20300)	
LTE Band 25 (PCS): 1.4 MHz		1850.7 (26047)	1882.5 (26365)	1914.3 (26683)	
LTE Band 25 (PCS): 3 MHz		1851.5 (26055)	1882.5 (26365)	1913.5 (26675)	
LTE Band 25 (PCS): 5 MHz		1852.5 (26065)	1882.5 (26365)	1912.5 (26665)	
LTE Band 25 (PCS): 10 MHz		1855 (26090)	1882.5 (26365)	1910 (26640)	
LTE Band 25 (PCS): 15 MHz		1857.5 (26115)	1882.5 (26365)	1907.5 (26615)	
LTE Band 25 (PCS): 20 MHz		1860 (26140)	1882.5 (26365)	1905 (26590)	
LTE Band 2 (PCS): 1.4 MHz		1850.7 (18607)	1880 (18900)	1909.3 (19193)	
LTE Band 2 (PCS): 3 MHz		1851.5 (18615)	1880 (18900)	1908.5 (19185)	
LTE Band 2 (PCS): 5 MHz		1852.5 (18625)	1880 (18900)	1907.5 (19175)	
LTE Band 2 (PCS): 10 MHz		1855 (18650)	1880 (18900)	1905 (19150)	
LTE Band 2 (PCS): 15 MHz		1857.5 (18675)	1880 (18900)	1902.5 (19125)	
LTE Band 2 (PCS): 20 MHz		1860 (18700)	1880 (18900)	1900 (19100)	
LTE Band 7: 5 MHz		2502.5 (20775)	2535 (21100)	2567.5 (21425)	
LTE Band 7: 10 MHz		2505 (20800)	2535 (21100)	2565 (21400)	
LTE Band 7: 15 MHz		2507.5 (20825)	2535 (21100)	2562.5 (21375)	
LTE Band 7: 20 MHz		2510 (20850)	2535 (21100)	2560 (21350)	
LTE Band 41: 5 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 10 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 15 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
LTE Band 41: 20 MHz	2506 (39750)	2549.5 (40185)	2593 (40620)	2636.5 (41055)	2680 (41490)
UE Category	1				
Modulations Supported in UL	QPSK, 16QAM				
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3-6.2.5? (manufacturer attestation to be provided)	YES				
A-MPR (Additional MPR) disabled for SAR Testing?	YES				
LTE Additional Information	This device does not support full CA features on 3GPP Release 12. All uplink communications are identical to the Release 8 Specifications. The following LTE Release 12 Features are not supported: Carrier Aggregation, Relay, HetNet, Enhanced MIMO, eICIC, WiFi Offloading, eMBMS, Cross-Carrier Scheduling, Enhanced SC-FDMA.				

FCC ID: BCG-A2684	SAR EVALUATION REPORT		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 10 of 32	

## 3 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

### 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1**  
**SAR Mathematical Equation**

$$SAR = \frac{d}{dt} \left( \frac{dU}{dm} \right) = \frac{d}{dt} \left( \frac{dU}{\rho dv} \right)$$

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- $\sigma$  = conductivity of the tissue-simulating material (S/m)
- $\rho$  = mass density of the tissue-simulating material (kg/m<sup>3</sup>)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 11 of 32

## 4 DOSIMETRIC ASSESSMENT

### 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 4-1).
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 4-1). On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
  - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
  - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.



**Figure 4-1**  
**Sample SAR Area**  
**Scan**

**Table 4-1**  
**Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04\***

Frequency	Maximum Area Scan Resolution (mm) ( $\Delta x_{\text{area}}, \Delta y_{\text{area}}$ )	Maximum Zoom Scan Resolution (mm) ( $\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$ )	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

\*Also compliant to IEE 1528-2013 Table 6

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch		Page 12 of 32

## 5 TEST CONFIGURATION POSITIONS

### 5.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . Additionally, a manufacturer provided low-loss foam was used to position the device for head SAR evaluations.

### 5.2 Positioning for Head

Devices that are designed to be worn on the wrist may operate in speaker mode for voice communication, with the device worn on the wrist and positioned next to the mouth. When next-to-mouth SAR evaluation is required, the device is positioned at 10 mm from a flat phantom filled with head tissue-equivalent medium. The device is evaluated with wrist bands strapped together to represent normal use conditions.

### 5.3 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. When extremity SAR evaluation is required, the device is evaluated with the back of the device touching the flat phantom. The phantom was filled with head tissue equivalent medium. The device was evaluated with Sport wristband unstrapped and touching the phantom. For the Fabric wristband, the device was evaluated with wristbands strapped and the distance between wristbands and the phantom was minimized to represent the spacing created by actual use conditions.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 13 of 32

## 6 RF EXPOSURE LIMITS

### 6.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 6.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 6-1**  
**SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
<b>Peak Spatial Average SAR</b> Head	1.6	8.0
<b>Whole Body SAR</b>	0.08	0.4
<b>Peak Spatial Average SAR</b> Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 14 of 32

## 7 FCC MEASUREMENT PROCEDURES

Power measurements for licensed transmitters are performed using a base station simulator under digital average power.

### 7.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

### 7.2 3G SAR Test Reduction Procedure

In FCC KDB Publication 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is  $\leq 0.25$  dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is  $\leq 1.2$  W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

### 7.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01v03r01 “3G SAR Measurement Procedures.”

The device is placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test are evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device is tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviates by more than 5%, the SAR test and drift measurements are repeated.

### 7.4 SAR Measurement Conditions for UMTS

#### 7.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 15 of 32

## 7.4.2 Head SAR Measurements

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

## 7.4.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH<sub>n</sub> configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using an applicable RMC configuration with the corresponding spreading code or DPDCH<sub>n</sub>, for the highest reported SAR configuration in 12.2 kbps RMC.

## 7.4.4 SAR Measurements with Rel 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

## 7.4.5 SAR Measurements with Rel 6 HSUPA

The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

## 7.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r04 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 7.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 7.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch		Page 16 of 32



### 7.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

### 7.5.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r04:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
  - i. The required channel and offset combination with the highest maximum output power is required for SAR.
  - ii. When the reported SAR is  $\leq 0.8$  W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
  - iii. When the reported SAR for a required test channel is  $> 1.45$  W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is  $< 0.8$  W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to  $\frac{1}{2}$  dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is  $< 1.45$  W/kg.
- e. This device can only operate with 16QAM on the uplink with less than or equal to 27 RB. For 16QAM configurations with 10 MHz, 15 MHz and 20 MHz bandwidths, LTE powers for RB size of 15 ("50% RB") and 27 ("100% RB") with offsets to upper edge, middle, and lower edge of the channel are additionally measured for both QPSK and 16QAM modulations to support comparison and SAR test exclusion per Section 5.2.4 and 5.3.

### 7.5.5 TDD

LTE TDD testing is performed using the SAR test guidance provided in FCC KDB 941225 D05v02r04. TDD is tested at the highest duty factor using UL-DL configuration 0 with special subframe configuration 6 and applying the FDD LTE procedures in KDB 941225 D05v02r04. SAR testing is performed using the extended cyclic prefix listed in 3GPP TS 36.211 Section 4.

## 7.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 17 of 32

### 7.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

### 7.6.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is  $> 1.2$  W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is  $> 1.2$  W/kg. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

### 7.6.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

### 7.6.4 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is  $\leq 0.8$  W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is  $> 0.8$  W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is  $> 1.2$  W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is  $> 1.2$  W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch		Page 18 of 32

### 7.6.5 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, and 802.11n or 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n or 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

### 7.6.6 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is  $\leq 0.8$  W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is  $\leq 1.2$  W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 7.6.5). When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

### 7.6.7 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is  $\leq 1.2$  W/kg, no additional SAR tests for the subsequent test configurations are required. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 19 of 32

## 8 SYSTEM VERIFICATION

### 8.1 Tissue Verification

**Table 8-1**  
**Measured Head Tissue Properties**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon$	TARGET Conductivity, $\sigma$ (S/m)	TARGET Dielectric Constant, $\epsilon$	% dev $\sigma$	% dev $\epsilon$
08/10/2022	835 Head	22.5	815	0.925	39.873	0.898	41.594	3.01%	-4.14%
			820	0.927	39.863	0.899	41.578	3.11%	-4.12%
			835	0.932	39.821	0.900	41.500	3.56%	-4.05%
			850	0.936	39.776	0.916	41.500	2.18%	-4.15%
08/09/2022	1900 Head	24.8	1850	1.336	40.411	1.400	40.000	-4.57%	1.03%
			1860	1.347	40.365	1.400	40.000	-3.79%	0.91%
			1880	1.367	40.288	1.400	40.000	-2.36%	0.72%
			1900	1.387	40.204	1.400	40.000	-0.93%	0.51%
			1905	1.392	40.184	1.400	40.000	-0.57%	0.46%
08/14/2022	2450 Head	21.4	1910	1.397	40.158	1.400	40.000	-0.21%	0.40%
			2300	1.749	38.931	1.670	39.500	4.73%	-1.44%
			2310	1.756	38.915	1.679	39.480	4.59%	-1.43%
			2320	1.763	38.895	1.687	39.460	4.51%	-1.43%
			2400	1.825	38.783	1.756	39.289	3.93%	-1.29%
			2450	1.865	38.683	1.800	39.200	3.61%	-1.32%
			2480	1.887	38.643	1.833	39.162	2.95%	-1.33%
			2500	1.901	38.604	1.855	39.136	2.48%	-1.36%
			2510	1.910	38.584	1.866	39.123	2.36%	-1.38%
			2535	1.931	38.543	1.893	39.092	2.01%	-1.40%
			2550	1.943	38.523	1.909	39.073	1.78%	-1.41%
			2560	1.951	38.510	1.920	39.060	1.61%	-1.41%
			2600	1.984	38.436	1.964	39.009	1.02%	-1.47%
			2650	2.024	38.341	2.018	38.945	0.30%	-1.55%
08/16/2022	2450 Head	22.7	2680	2.049	38.286	2.051	38.907	-0.10%	-1.60%
			2700	2.065	38.253	2.073	38.882	-0.39%	-1.62%
			2300	1.741	38.122	1.670	39.500	4.25%	-3.49%
			2310	1.748	38.106	1.679	39.480	4.11%	-3.48%
			2320	1.755	38.086	1.687	39.460	4.03%	-3.48%
			2400	1.815	37.965	1.756	39.289	3.36%	-3.37%
			2450	1.853	37.851	1.800	39.200	2.94%	-3.44%
			2480	1.875	37.802	1.833	39.162	2.29%	-3.47%
			2500	1.889	37.775	1.855	39.136	1.83%	-3.48%
			2510	1.896	37.760	1.866	39.123	1.61%	-3.48%
			2535	1.916	37.724	1.893	39.092	1.22%	-3.50%
			2550	1.927	37.691	1.909	39.073	0.94%	-3.54%
			2560	1.935	37.672	1.920	39.060	0.78%	-3.55%
			2600	1.966	37.604	1.964	39.009	0.10%	-3.60%
			2650	2.007	37.499	2.018	38.945	-0.55%	-3.71%
			2680	2.031	37.456	2.051	38.907	-0.98%	-3.73%
			2700	2.046	37.427	2.073	38.882	-1.30%	-3.74%

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 20 of 32	

**Table 8-2**  
**Measured Head Tissue Properties (Cont.)**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon$	TARGET Conductivity, $\sigma$ (S/m)	TARGET Dielectric Constant, $\epsilon$	% dev $\sigma$	% dev $\epsilon$
08/07/2022	5200-5800 Head	20.3	5180	4.516	35.213	4.635	36.009	-2.57%	-2.21%
			5190	4.527	35.187	4.645	35.998	-2.54%	-2.25%
			5200	4.539	35.159	4.655	35.986	-2.49%	-2.30%
			5210	4.552	35.138	4.666	35.975	-2.44%	-2.33%
			5220	4.564	35.125	4.676	35.963	-2.40%	-2.33%
			5240	4.588	35.094	4.696	35.940	-2.30%	-2.35%
			5250	4.600	35.078	4.706	35.929	-2.25%	-2.37%
			5260	4.610	35.045	4.717	35.917	-2.27%	-2.43%
			5270	4.619	35.025	4.727	35.906	-2.28%	-2.45%
			5280	4.628	35.010	4.737	35.894	-2.30%	-2.46%
			5290	4.642	34.999	4.748	35.883	-2.23%	-2.46%
			5300	4.654	34.975	4.758	35.871	-2.19%	-2.50%
			5310	4.666	34.943	4.768	35.860	-2.14%	-2.56%
			5320	4.676	34.923	4.778	35.849	-2.13%	-2.58%
			5500	4.881	34.621	4.963	35.643	-1.65%	-2.87%
			5510	4.893	34.605	4.973	35.632	-1.61%	-2.88%
			5520	4.905	34.589	4.983	35.620	-1.57%	-2.89%
			5530	4.917	34.573	4.994	35.609	-1.54%	-2.91%
			5540	4.927	34.555	5.004	35.597	-1.54%	-2.93%
			5550	4.939	34.538	5.014	35.586	-1.50%	-2.94%
			5560	4.951	34.523	5.024	35.574	-1.45%	-2.95%
			5580	4.974	34.488	5.045	35.551	-1.41%	-2.99%
			5600	4.996	34.442	5.065	35.529	-1.36%	-3.06%
			5610	5.008	34.421	5.076	35.518	-1.34%	-3.09%
			5620	5.022	34.410	5.086	35.506	-1.26%	-3.09%
			5640	5.042	34.389	5.106	35.483	-1.25%	-3.08%
			5660	5.059	34.348	5.127	35.460	-1.33%	-3.14%
			5670	5.069	34.327	5.137	35.449	-1.32%	-3.17%
			5680	5.081	34.302	5.147	35.437	-1.28%	-3.20%
			5690	5.094	34.280	5.158	35.426	-1.24%	-3.23%
			5700	5.107	34.262	5.168	35.414	-1.18%	-3.25%
			5710	5.118	34.243	5.178	35.403	-1.16%	-3.28%
			5720	5.128	34.233	5.188	35.391	-1.16%	-3.27%
			5745	5.160	34.182	5.214	35.363	-1.04%	-3.34%
			5750	5.165	34.167	5.219	35.357	-1.03%	-3.37%
			5755	5.171	34.151	5.224	35.351	-1.01%	-3.39%
			5765	5.180	34.130	5.234	35.340	-1.03%	-3.42%
			5775	5.191	34.115	5.245	35.329	-1.03%	-3.44%
			5785	5.203	34.098	5.255	35.317	-0.99%	-3.45%
			5795	5.213	34.083	5.265	35.305	-0.99%	-3.46%
			5800	5.219	34.072	5.270	35.300	-0.97%	-3.48%
			5800	5.219	34.072	5.270	35.300	-0.97%	-3.48%
			5805	5.224	34.058	5.275	35.294	-0.97%	-3.50%
			5825	5.249	34.024	5.296	35.271	-0.89%	-3.54%
			5835	5.260	34.012	5.305	35.230	-0.85%	-3.46%
			5845	5.271	33.998	5.315	35.210	-0.83%	-3.44%
			5855	5.284	33.977	5.325	35.197	-0.77%	-3.47%
			5865	5.295	33.963	5.336	35.190	-0.77%	-3.49%
			5865	5.295	33.963	5.336	35.190	-0.77%	-3.49%
			5865	5.295	33.963	5.336	35.190	-0.77%	-3.49%
			5875	5.306	33.945	5.347	35.183	-0.77%	-3.52%
			5885	5.317	33.924	5.357	35.177	-0.75%	-3.56%

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch		Page 21 of 32

**Table 8-3**  
**Measured Head Tissue Properties (Cont.)**

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, $\sigma$ (S/m)	Measured Dielectric Constant, $\epsilon$	TARGET Conductivity, $\sigma$ (S/m)	TARGET Dielectric Constant, $\epsilon$	% dev $\sigma$	% dev $\epsilon$
08/15/2022	5200-5800 Head	20.9	5905	5.343	33.884	5.379	35.163	-0.67%	-3.64%
			5180	4.518	35.564	4.635	36.009	-2.52%	-1.24%
			5190	4.530	35.535	4.645	35.998	-2.48%	-1.29%
			5200	4.543	35.509	4.655	35.986	-2.41%	-1.33%
			5210	4.557	35.487	4.666	35.975	-2.34%	-1.36%
			5220	4.569	35.468	4.676	35.963	-2.29%	-1.38%
			5240	4.590	35.438	4.696	35.940	-2.26%	-1.40%
			5250	4.598	35.422	4.706	35.929	-2.29%	-1.41%
			5260	4.608	35.398	4.717	35.917	-2.31%	-1.44%
			5270	4.617	35.366	4.727	35.906	-2.33%	-1.50%
			5280	4.628	35.330	4.737	35.894	-2.30%	-1.57%
			5290	4.640	35.302	4.748	35.883	-2.27%	-1.62%
			5300	4.652	35.283	4.758	35.871	-2.23%	-1.64%
			5310	4.665	35.263	4.768	35.860	-2.16%	-1.66%
			5320	4.677	35.241	4.778	35.849	-2.11%	-1.70%
			5500	4.884	34.945	4.963	35.643	-1.59%	-1.96%
			5510	4.897	34.936	4.973	35.632	-1.53%	-1.95%
			5520	4.910	34.933	4.983	35.620	-1.46%	-1.93%
			5530	4.923	34.925	4.994	35.609	-1.42%	-1.92%
			5540	4.934	34.918	5.004	35.597	-1.40%	-1.91%
			5550	4.947	34.904	5.014	35.586	-1.34%	-1.92%
			5560	4.958	34.885	5.024	35.574	-1.31%	-1.94%
			5580	4.979	34.848	5.045	35.551	-1.31%	-1.98%
			5600	5.002	34.798	5.065	35.529	-1.24%	-2.06%
			5610	5.016	34.777	5.076	35.518	-1.18%	-2.09%
			5620	5.030	34.772	5.086	35.506	-1.10%	-2.07%
			5640	5.052	34.755	5.106	35.483	-1.06%	-2.05%
			5660	5.068	34.718	5.127	35.460	-1.15%	-2.09%
			5670	5.074	34.695	5.137	35.449	-1.23%	-2.13%
			5680	5.083	34.672	5.147	35.437	-1.24%	-2.16%
			5690	5.095	34.642	5.158	35.426	-1.22%	-2.21%
			5700	5.107	34.620	5.168	35.414	-1.18%	-2.24%
			5710	5.118	34.598	5.178	35.403	-1.16%	-2.27%
			5720	5.128	34.585	5.188	35.391	-1.16%	-2.28%
			5745	5.156	34.526	5.214	35.363	-1.11%	-2.37%
			5750	5.162	34.513	5.219	35.357	-1.09%	-2.39%
			5755	5.167	34.503	5.224	35.351	-1.09%	-2.40%
			5765	5.177	34.487	5.234	35.340	-1.09%	-2.41%
			5775	5.189	34.464	5.245	35.329	-1.07%	-2.45%
			5785	5.201	34.438	5.255	35.317	-1.03%	-2.49%
			5795	5.213	34.419	5.265	35.305	-0.99%	-2.51%
			5805	5.225	34.393	5.275	35.294	-0.95%	-2.55%
			5825	5.246	34.354	5.296	35.271	-0.94%	-2.60%
			5835	5.256	34.341	5.305	35.230	-0.92%	-2.52%
			5845	5.266	34.331	5.315	35.210	-0.92%	-2.50%
			5855	5.278	34.308	5.325	35.197	-0.88%	-2.53%
			5875	5.303	34.241	5.347	35.183	-0.82%	-2.68%
			5885	5.314	34.211	5.357	35.177	-0.80%	-2.75%
			5905	5.344	34.171	5.379	35.163	-0.65%	-2.82%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 22 of 32

## 8.2 Tissue Verification


Prior to SAR assessment, the system is verified to  $\pm 10\%$  of the SAR measurement on the reference dipole at the time of calibration by the calibration facility.

**Table 8-4**  
**System Verification Results – 1g**

System Verification TARGET & MEASURED												
SAR System	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp. (C)	Liquid Temp. (C)	Input Power (W)	Source SN	Probe SN	Measured SAR1g (W/kg)	1W Target SAR1g (W/kg)	1W Normalized SAR 1g (W/kg)	Deviation1g (%)
AM10	1900	HEAD	08/09/2022	24.0	22.9	0.10	5d181	7308	4.080	40.10	40.800	1.75%
AM4	2450	HEAD	08/16/2022	24.7	22.6	0.10	750	3837	5.490	52.60	54.900	4.37%
AM8	5250	HEAD	08/15/2022	20.0	20.8	0.05	1123	7546	3.960	80.50	79.200	-1.61%
AM8	5600	HEAD	08/15/2022	20.0	20.8	0.05	1123	7546	3.910	83.70	78.200	-6.57%
AM8	5750	HEAD	08/15/2022	20.0	20.8	0.05	1123	7546	3.880	80.50	77.600	-3.60%

**Table 8-5**  
**System Verification Results – 10g**

System Verification TARGET & MEASURED												
SAR System	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp. (C)	Liquid Temp. (C)	Input Power (W)	Source SN	Probe SN	Measured SAR10g (W/kg)	1W Target SAR10g (W/kg)	1W Normalized SAR10g (W/kg)	Deviation10g (%)
AM12	835	HEAD	08/10/2022	24.2	21.2	0.20	4d040	7499	1.340	6.38	6.700	5.02%
AM4	2450	HEAD	08/14/2022	21.9	21.0	0.10	921	3837	2.520	25.50	25.200	-1.18%
AM4	2450	HEAD	08/16/2022	24.7	22.6	0.10	750	3837	2.540	24.50	25.400	3.67%
AM8	5250	HEAD	08/07/2022	20.0	19.5	0.05	1123	7546	1.070	22.90	21.400	-6.55%
AM8	5600	HEAD	08/07/2022	20.0	19.5	0.05	1123	7546	1.140	23.70	22.800	-3.80%
AM8	5750	HEAD	08/07/2022	20.0	19.5	0.05	1123	7546	1.150	22.70	23.000	1.32%



**Figure 8-1**  
**System Verification Setup Diagram**



**Figure 8-2**  
**System Verification Setup Photo**

FCC ID: BCG-A2684	SAR EVALUATION REPORT		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch		Page 23 of 32

## 9 SAR DATA SUMMARY

## 9.1 Standalone Head SAR Data

**Table 9-1**  
**PCB Head Spot-check Verification for Data Referencing**

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Wrist Band Type	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Housing Type	Device Serial Number	Modulation	RB Size	RB Offset	Side	Spacing	Duty Cycle	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Reported SAR for Reference Model	
MHz	Ch.																(W/kg)	(W/kg)	(W/kg)			
1905.00	26590	High	LTE Band 25	20	Fabric	24.50	22.85	0.04	0	Titanium	DG67D2G5N4	QPSK	1	50	Front	10 mm	1:1	0.624	1.462	1.000	0.912	0.926
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak										Head 1.6 W/kg (mW/g) averaged over 1 gram												
Uncontrolled Exposure/General Population																						

**Table 9-2**  
**DSS/DTS Head Spot-check Verification for Data Referencing**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Test Position	Housing Type	Wristband Type	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Reported SAR for Reference Model (1g)
MHz	Ch.														(W/kg)				
2437	6	802.11b	DSSS	22	19.00	18.78	-0.13	10 mm	Front	Titanium	Fabric	DG67D2GSW4	1	99.7%	0.278	1.052	1.003	0.293	0.334
2480	78	Bluetooth	FHSS	N/A	13.00	12.56	0.10	10 mm	Front	Titanium	Sport	DQFM2LW21M	1	100.0%	0.076	1.107	1.000	0.084	0.076
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

**Table 9-3**  
**NII Head Spot-check Verification for Data Referencing**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Test Position	Housing Type	Wristband Type	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Reported SAR for Reference Model (1g)
MHz	Ch.														(W/kg)			(W/kg)	(W/kg)
5745	149	802.11a	OFDM	20	17.00	16.00	-0.11	10 mm	Front	Titanium	Sport	LTLQ4H4127	6	97.6%	0.055	1.259	1.025	0.071	0.083
ANSI / IEEE C95.1 1992 - SAFETY LIMIT										Head									
Spatial Peak										1.6 W/kg (mW/g)									
Uncontrolled Exposure/General Population										averaged over 1 gram									

## 9.2 Standalone Extremity SAR Data

**Table 9-4**  
**PCB Extremity Spot-check Verification for Data Referencing**

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Bandwidth [MHz]	Wristband Type	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Housing Type	Device Serial Number	Modulation	RB Size	RB Offset	Side	Spacing	Duty Cycle	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (10g)	Reported SAR for Reference Model	
MHz	Ch.																(W/kg)	(W/kg)	(W/kg)			
819.00	26740	Low	LTE Band 26	10	Sport	25.50	24.52	0.01	0	Titanium	LTLO4H41127	QPSK	1	25	Back	0 mm	1:1	0.249	1.253	1.000	0.312	0.382
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak																		Extremity 4.0 W/kg (mW/g) averaged over 10 grams				
Uncontrolled Exposure/General Population																						

**Table 9-5**  
**DSS/DTS Extremity Spot-check Verification for Data Referencing**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Test Position	Housing Type	Wristband Type	Device Serial Number	Data Rate [Mbps]	Duty Cycle (%)	SAR (10g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	Reported SAR for Reference Model (1g)
MHz	Ch.														(W/kg)				
2437	6	802.11b	DSSS	22	19.00	18.78	0.13	0 mm	Back	Titanium	Sport	DQFM2LW21M	1	99.7%	0.104	1.052	1.003	0.110	0.118
2480	78	Bluetooth	FHSS	N/A	13.00	12.56	0.20	0 mm	Back	Titanium	Fabric	DG67D2GSW4	1	100.0%	0.014	1.107	1.000	0.015	0.013
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Extremity 4.0 W/kg (mW/g) averaged over 10 grams									

<b>FCC ID:</b> BCG-A2684	<b>SAR EVALUATION REPORT</b>	<b>Approved by:</b> Technical Manager
<b>Document S/N:</b> 1C2205090043-22 BCG	<b>DUT Type:</b> Watch	Page 24 of 32



**Table 9-6**  
**NII Extremity Spot-check Verification for Data Referencing**

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Test Position	Housing Type	Wristband Type	Device Serial Number	Data Rate (Mbps)	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g) (W/kg)	Reported SAR for Reference Model (1g) (W/kg)
MHz	Ch.														(W/kg)				
5260	52	802.11a	OFDM	20	17.00	15.76	-0.13	0 mm	Back	Titanium	Fabric	DQFM2LW21M	6	97.6%	0.003	1.330	1.025	0.004	0.008
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Extremity 4.0 W/kg (mW/g) averaged over 10 grams									

### 9.3 SAR Test Notes

#### General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in FCC KDB Publication 447498 D01v06.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
6. Per FCC KDB Publication 865664 D01v01r04, variability SAR tests were not required since measured SAR results for all frequency bands were less than 0.8 W/kg and 2.0 W/kg for 10g SAR.
7. This device has one housing type: Titanium. The non-metallic wrist accessory, sport and fabric band, were evaluated for all exposure conditions.
8. This device is a portable wrist-worn device and does not support any other use conditions. Therefore, the procedures in FCC KDB Publication 447498 D01v06 Section 6.2 have been applied for extremity and next to mouth (head) conditions.
9. Unless otherwise noted, when 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds below.

#### UMTS Notes:

1. UMTS mode was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v03r01. AMR and HSPA SAR was not required per the 3G Test Reduction Procedure in KDB Publication 941225 D01v03r01.
2. Per FCC KDB Publication 447498 D01v06, if the reported (scaled) SAR measured at the highest output power channel for each test configuration is  $\leq 0.8$  W/kg for 1g evaluations and  $\leq 2.0$  W/kg for 10g SAR then testing at the other channels is not required for such test configuration(s).

#### LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r04. The general test procedures used for testing can be found in Section 7.5.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 and MCC=001 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).
4. Per FCC KDB Publication 447498 D01v06, when the reported LTE Band 41 SAR measured at the highest output power channel in a given a test configuration was  $> 0.6$  W/kg for 1g evaluations and  $> 1.5$  W/kg for 10g SAR, testing at the other channels was required for such test configurations.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 25 of 32

5. TDD LTE was tested per the guidance provided in FCC KDB Publication 941225 D05v02r04. Testing was performed using UL-DL configuration 0 with 6 UL subframes and 2 S subframes using extended cyclic prefix only and special subframe configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Section 4, the duty factor for special subframe configuration 6 using extended cyclic prefix is 0.633.
6. This device can only operate with 16 QAM on the uplink with less than or equal to 27 RB. QPSK and 16QAM LTE powers for RB size of 15 ("50% RB") and 27 ("100% RB") were additionally measured to support comparison and SAR test exclusion per KDB 941225 D05v02r04 Section 5.2.4 and 5.3.

#### WLAN Notes:

1. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 7.6.4 for more information.
2. Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 7.6.5 for more information.
3. When the maximum reported 1g averaged SAR is  $\leq 0.8$  W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was  $\leq 1.20$  W/kg for 1g evaluations or all test channels were measured. When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance.

#### Bluetooth Notes

1. To determine compliance, Bluetooth SAR was measured with the maximum power condition. Bluetooth was evaluated with a test mode with 100% transmission duty factor.

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 26 of 32

## 10 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

### 10.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

### 10.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is  $\leq 1.6$  W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

Please see complete compliance evaluation of reference FCC ID BCG-A2622 in RF Exposure Technical Report S/N: 1C2205090042-22.BCG for standalone reported SAR for models and bands not evaluated for variant models.

### 10.3 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 .

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 27 of 32

# 11 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E4438C	ESG Vector Signal Generator	12/14/2020	Biennial	12/14/2022	MY42082385
Agilent	E4438C	ESG Vector Signal Generator	5/10/2022	Annual	5/10/2023	MY42082659
Agilent	N5182A	MXG Vector Signal Generator	11/17/2021	Annual	11/17/2022	US46240505
Agilent	N5182A	MXG Vector Signal Generator	7/20/2022	Annual	7/20/2023	MY47420800
Agilent	8753ES	S-Parameter Vector Network Analyzer	2/11/2022	Annual	2/11/2023	MY40003841
Agilent	8753ES	S-Parameter Vector Network Analyzer	6/14/2022	Annual	6/14/2023	US39170118
Agilent	N4010A	Wireless Connectivity Test Set	2/4/2022	Annual	2/4/2023	GB43193563
Agilent	E5515C	Wireless Connectivity Test Set	5/12/2022	Annual	5/12/2023	GB43304278
Agilent	N9020A	MXA Signal Analyzer	5/6/2022	Annual	5/6/2023	MY51240479
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	353317
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	353468
Anritsu	ML2495A	Power Meter	3/29/2022	Annual	3/29/2023	1306009
Anritsu	ML2496A	Power Meter	12/6/2021	Annual	12/6/2022	1351001
Anritsu	MA2411B	Pulse Power Sensor	3/2/2022	Annual	3/2/2023	1126066
Anritsu	MA2411B	Pulse Power Sensor	4/29/2022	Annual	4/29/2023	1207470
Anritsu	MT8821C	Radio Communication Analyzer	5/2/2022	Annual	5/2/2023	6200901190
Anritsu	MT8821C	Radio Communication Analyzer	5/24/2022	Annual	5/24/2023	6201144418
Anritsu	MT8821C	Radio Communication Analyzer	3/31/2022	Annual	3/31/2023	6201664756
Anritsu	MT8821C	Radio Communication Analyzer	6/27/2022	Annual	6/27/2023	6261895213
Anritsu	MA24106A	USB Power Sensor	4/12/2022	Annual	4/12/2023	1244524
Anritsu	MA24106A	USB Power Sensor	10/20/2021	Annual	10/20/2022	1344545
Control Company	4353	Long Stem Thermometer	1/24/2022	Biennial	1/24/2024	200043588
Control Company	4353	Long Stem Thermometer	1/24/2022	Biennial	1/24/2024	200043634
Control Company	4352	Long Stem Thermometer	1/24/2022	Biennial	1/24/2024	200043644
Control Company	4352	Long Stem Thermometer	1/24/2022	Biennial	1/24/2024	200043647
Control Company	4040	Therm./ Clock/ Humidity Monitor	2/17/2022	Biennial	2/17/2024	200113269
Control Company	4040	Therm./ Clock/ Humidity Monitor	2/17/2022	Biennial	2/17/2024	200113274
Control Company	4040	Therm./ Clock/ Humidity Monitor	3/6/2022	Biennial	3/6/2024	200170289
Control Company	4040	Therm./ Clock/ Humidity Monitor	3/6/2022	Biennial	3/6/2024	200170296
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	ZHDC-16-63-S+	50-6000MHz Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE5011-1	Torque Wrench	12/21/2021	Biennial	12/21/2023	82475
Insize	1108-150	Digital Caliper	4/5/2022	Biennial	4/5/2024	409193536
SPEAG	MAIA	Modulation and Audio Interference Analyzer	N/A	N/A	N/A	1324
SPEAG	MAIA	Modulation and Audio Interference Analyzer	N/A	N/A	N/A	1260
SPEAG	DAKS-3.5	Portable DAK	10/7/2021	Annual	10/7/2022	1045
SPEAG	D835V2	835 MHz SAR Dipole	5/16/2022	Annual	5/16/2023	4040
SPEAG	D1900V2	1900 MHz SAR Dipole	9/10/2022	Biennial	9/10/2022	5d181
SPEAG	D2450V2	2450 MHz SAR Dipole	5/11/2022	Annual	5/11/2023	750
SPEAG	D2450V2	2450 MHz SAR Dipole	11/9/2021	Annual	11/9/2022	921
SPEAG	D5GHzV2	5 GHz SAR Dipole	3/22/2022	Annual	3/22/2023	1123
SPEAG	EX3DV4	SAR Probe	4/19/2023	Annual	4/19/2023	7499
SPEAG	EX3DV4	SAR Probe	2/21/2022	Annual	2/21/2023	7308
SPEAG	EX3DV4	SAR Probe	1/19/2022	Annual	1/19/2023	3837
SPEAG	EX3DV4	SAR Probe	4/22/2022	Annual	4/22/2023	7546
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/13/2022	Annual	4/13/2023	1465
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/24/2022	Annual	2/24/2023	467
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/13/2022	Annual	1/13/2023	793
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/14/2022	Annual	4/14/2023	1402

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements. Each equipment item was used solely within its respective calibration period.

FCC ID: BCG-A2684	SAR EVALUATION REPORT		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 28 of 32	

## 12 MEASUREMENT UNCERTAINTIES

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c <sub>i</sub> 1gm	c <sub>i</sub> 10 gms	1gm u <sub>i</sub> (± %)	10gms u <sub>i</sub> (± %)	v <sub>i</sub>
<b>Measurement System</b>									
Probe Calibration	E2.1	7	N	1	1	1	7.0	7.0	∞
Axial Isotropy	E2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E2.2	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	E2.3	2	R	1.732	1	1	1.2	1.2	∞
Linearity	E2.4	0.3	N	1	1	1	0.3	0.3	∞
System Detection Limits	E2.4	0.25	R	1.732	1	1	0.1	0.1	∞
Modulation Response	E2.5	4.8	R	1.732	1	1	2.8	2.8	∞
Readout Electronics	E2.6	0.3	N	1	1	1	0.3	0.3	∞
Response Time	E2.7	0.8	R	1.732	1	1	0.5	0.5	∞
Integration Time	E2.8	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Conditions - Noise	E6.1	3	R	1.732	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E6.1	3	R	1.732	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	0.8	R	1.732	1	1	0.5	0.5	∞
Probe Positioning w/ respect to Phantom	E6.3	6.7	R	1.732	1	1	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E5	4	R	1.732	1	1	2.3	2.3	∞
<b>Test Sample Related</b>									
Test Sample Positioning	E4.2	3.12	N	1	1	1	3.1	3.1	35
Device Holder Uncertainty	E4.1	1.67	N	1	1	1	1.7	1.7	5
Output Power Variation - SAR drift measurement	E2.9	5	R	1.732	1	1	2.9	2.9	∞
SAR Scaling	E6.5	0	R	1.732	1	1	0.0	0.0	∞
<b>Phantom &amp; Tissue Parameters</b>									
Phantom Uncertainty (Shape & Thickness tolerances)	E3.1	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	E3.3	4.3	N	1	0.78	0.71	3.3	3.0	76
Liquid Permittivity - measurement uncertainty	E3.3	4.2	N	1	0.23	0.26	1.0	1.1	75
Liquid Conductivity - Temperature Uncertainty	E3.4	3.4	R	1.732	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	E3.4	0.6	R	1.732	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	E3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	E3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
<b>Combined Standard Uncertainty (k=1)</b>							RSS	12.2	12.0
<b>Expanded Uncertainty</b> (95% CONFIDENCE LEVEL)							k=2	24.4	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2013

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>		Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch		Page 29 of 32

## 13 CONCLUSION

### 13.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: BCG-A2684	<b>SAR EVALUATION REPORT</b>	Approved by: Technical Manager
Document S/N: 1C2205090043-22.BCG	DUT Type: Watch	Page 30 of 32

## 14 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

<b>FCC ID:</b> BCG-A2684	<b>SAR EVALUATION REPORT</b>	<b>Approved by:</b> Technical Manager
<b>Document S/N:</b> 1C2205090043-22.BCG	<b>DUT Type:</b> Watch	Page 31 of 32

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

<b>FCC ID:</b> BCG-A2684	<b>SAR EVALUATION REPORT</b>	<b>Approved by:</b> Technical Manager
<b>Document S/N:</b> 1C2205090043-22.BCG	<b>DUT Type:</b> Watch	Page 32 of 32