



FCC CFR47 PART 22H and 24E

TEST REPORT

FOR

SMARTPHONE

MODEL: ST10B

FCC ID: NM8VIVIDA

REPORT NUMBER: 04T2860-1

ISSUE DATE: AUGUST 5, 2004

Prepared for HIGH TECH COMPUTER CORP. 1F, 6-3, BAU-CHIAN RD., HSIN TIEN TAIPAI, TAIWAN, 231

Prepared by COMPLIANCE CERTIFICATION SERVICES 561F MONTEREY ROAD, ROUTE 2 MORGAN HILL, CA 95037, USA TEL: (408) 463-0885 FAX: (408) 463-0888



TABLE OF CONTENT

1.	TEST RESULT CERTIFICATION	3
2.	EUT DESCRIPTION	4
3.	TEST METHODOLOGY	5
4.	TEST FACILITY	5
5	ACCREDITATION AND LISTING	5
6	MEASURING INSTRUMENT CALIERATION	5
0. -		
7.	TEST SETUP, PROCEDURE AND RESULT	6
7	1.1. RADIATED EMISSION	6
7	2. POWERLINE CONDUCTED EMISSION	12

Page 2 of 15

1. TEST RESULT CERTIFICATION

COMPANY NAME:	HIGH TECH COMPUTER CORP. 1F, 6-3, BAU-CHIAN RD., HSIN TIEN TAIPAI, TAIWAN, 231
EUT DESCRIPTION:	SMARTPHONE
MODEM NAME:	ST10B

DATE TESTED: JULY 30, 2004

TYPE OF EQUIPMENT	INTENTIONAL RADIATOR
EQUIPMENT TYPE	LICENSED TX MODULE IN MOBILE APPLICATION
MEASUREMENT PROCEDURE	ANSI 63.4 / 2001, TIA/EIA 603
PROCEDURE	CERTICFICATION
FCC RULE	CFR 47 PART 22 Subpart H and 24 Subpart E

Compliance Certification Services, Inc. tested the above equipment for compliance with the requirement set forth in CFR 47, PART 22 Subpart H-Cellular Radiotelephone Service and 24 Subpart E-Broadband PCS. The equipment in the configuration described in this report, shows the measured emission levels emanating from the equipment do not exceed the specified limit.

Note: This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document.

Tested By:

Chin Pany

CHIN PANG EMC TECHNICIAN COMPLIANCE CERTIFICATION SERVICES

Released For CCS By:

121

THU CHAN EMC SUPERVISOR COMPLIANCE CERTIFICATION SERVICES

Page 3 of 15

2. EUT DESCRIPTION

The PDA Phone is designed for the bands transmitting of frequency range $824 \sim 849$ MHz and $1850 \sim 1910$ MHz. The EUT filed under this application has removed the camera component.

Page 4 of 15

3. TEST METHODOLOGY

Both conducted and radiated testing were performed according to the procedures documented on chapter 13 of ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057.

4. TEST FACILITY

The open area test sites and conducted measurement facilities used to collect the radiated data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5. ACCREDITATION AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200065-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT (1300B3) and 31040/SIT (1300F2))

6. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Page 5 of 15

7. TEST SETUP, PROCEDURE AND RESULT

7.1. RADIATED EMISSION

Detector Setting of Spectrum Analyzer

Frequency Range (MHz) Detector Function		Resolution Bandwidth	Video Bandwidth
30 to 1000	⊠ Peak	⊠ 100 KHz	⊠ 100 KHz
	⊠ Quasi Peak	⊠ 1 MHz	⊠ 1 MHz

TEST PERIPHERAL

TEST PERIPHERALS								
Device Type Manufacturer Model Number Serial Number FC								
AC adapter	Phihong	PSC11A-050	N/A	N/A				
USB MOUSE	LOGITECH	M-UA34	N/A	DZL211087				
MODEM	ACEEX	1414	9013537	IFAXDM1414				
PRINTER	HP	2225C	2541841679	BS46XU2225C				
Laptop	HP	Ze4205	CN25110353	DoC				
AC adapter	HP	ADP-75HB	MVT0243196915	DoC				

TEST EQUIPMENT

TEST EQUIPMENT LIST									
Name of Equipment Manufacturer Model No. Serial No. Due Da									
HP	8542E	3942A00286	11/20/2004						
HP	85420E	3705A00256	11/20/2004						
Sunol Sciences	JB1 Antenna	A121003	12/22/2004						
R & S	ESHS 20	827129/006	7/17/2005						
FCC	LISN-50/250-25-2	2023	10/13/2004						
Lindgren	LMF-3489	497	CNR						
	TEST EQUIPME Manufacturer HP HP Sunol Sciences R & S FCC Lindgren	TEST EQUIPMENT LISTManufacturerModel No.HP8542EHP85420ESunol SciencesJB1 AntennaR & SESHS 20FCCLISN-50/250-25-2LindgrenLMF-3489	TEST EQUIPMENT LISTManufacturerModel No.Serial No.HP8542E3942A00286HP85420E3705A00256Sunol SciencesJB1 AntennaA121003R & SESHS 20827129/006FCCLISN-50/250-25-22023LindgrenLMF-3489497						

Page 6 of 15

I/O CABLE

	TEST I / O CABLES									
Cable	I/O	# of I/O	Connector	Type of	Cable	Data				
No	Port	Port	Туре	Cable	Length	Traffic	Bundled	Remark		
1	AC	1	US 115V	Un-shielded	2m	No	No	N/A		
2	DC	1	DC	Un-shielded	1m	No	No	N/A		
3	Serial	1	DB9	Shielded	1m	Yes	No	N/A		
4	USB	1	Mouse	Un-shielded	2m	Yes	No	N/A		
5	Parallel	1	DB25	Shielded	2m	Yes	Yes	N/A		
6	USB	1	USB	Un-shielded	2m	Yes	No	Connect EUT to Laptop		

TEST SETUP





1. The EUT was placed on the turn table 0.8 meter above ground inside 3 meter Anechoic Chamber.

2. Set the resolution bandwidth to 120KHz in the test receiver and select Peak function to scan the frequency below 1 GHz.

3. Shift the interference-receiving antenna located in antenna tower upwards and downwards between 1 and 4 meters above ground and find out the local peak emission on frequency domain.

4. Locate the interference-receiving antenna at the position where the local peak reach the maximum emission.

5. Rotate the turn table and stop at the angle where the measurement device has maximum reading

6. Shift the interference-receiving antenna again to detect the maximum emission of the local peak

7. If the reading of the local peak under Peak function is lower than limit by 6dB, then Quasi Peak detection is not needed and this reading should be recorded. And if it is higher than Peak limit, then the test is fail. Others, switch the receiver to Quasi Peak function, set the resolution bandwidth to 100kHz and repeat the procedures (3)~(6). If the reading is lower than limit, this reading should be recorded, otherwise, the test is fail.

MEASUREMENT RESULT

No non-compliance noted, as shown below.

Page 8 of 15

Horizontal:



Page 9 of 15

Vertical:



Page 10 of 15

Radiated Emission photos

Front View:



Back View:



Page 11 of 15

7.2. POWERLINE CONDUCTED EMISSION

Detector Function Setting of Test Receiver

Frequency Range (MHz)	(MHz) Detector Function		Video Bandwidth
150 KHz to 30 MHz	⊠ Peak □ CISPR Quasi Peak	9 KHz	9 KHz

Power Line Conducted Emission photos

Front View:



Page 12 of 15

Side View:



Page 13 of 15

TEST PROCEDURE

1. The EUT was placed on a wooden table 40 cm from a vertical ground plane and approximately 80 cm above the horizontal ground plane on the floor. The EUT was set to transmit in a continuous mode.

2. Line conducted data was recorded for both NEUTRAL and HOT lines.

MEASUREMENT RESULT

No non-compliance noted, as shown below.

Freq.	Reading			Reading	Closs	Limit	EN_B	Mar	gin	Remark
(MHz)	PK (dBuV)	QP (dBuV)	AV (dBuV)	(dB)	QP	AV	QP (dB)	AV (dB)	L1 / L2	
0.78	34.38			0.00	56.00	46.00	-21.62	-11.62	L1	
8.73	37.48			0.00	60.00	50.00	-22.52	-12.52	L1	
14.99	35.46			0.00	60.00	50.00	-24.54	-14.54	L1	
0.40	31.50			0.00	58.91	48.91	-27.41	-17.41	L2	
0.90	33.82			0.00	56.00	46.00	-22.18	-12.18	L2	
10.96	34.48			0.00	60.00	50.00	-25.52	-15.52	L2	
6 Worst I	Data									

Page 14 of 15

LINE 1&2 RESULTS



END OF REPORT

Page 15 of 15