Commsignia, Inc. FCC ID: 2AOZ5-CM-OB4

4 FCC §2.1091– RF Exposure

4.1 Applicable Standard

According to FCC §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

4.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

4.3 MPE Results

Single Chain MPE Evaluation

Chain 0

Maximum declared output power at antenna input terminal (dBm):

Maximum declared output power at antenna input terminal (mW):

Prediction distance (cm):

Prediction frequency (MHz):

Maximum Antenna Gain, typical (dBi):

Maximum Antenna Gain (numeric):

Power density of prediction frequency at 20 cm (mW/cm²):

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):

100

20

Prediction distance (cm):

Maximum Antenna Gain, typical (dBi):

13.00

0.397

^{* =} Plane-wave equivalent power density

Commsignia, Inc. FCC ID: 2AOZ5-CM-OB4

Chain 1

 Maximum declared output power at antenna input terminal (dBm):
 20

 Maximum declared output power at antenna input terminal (mW):
 100

 Prediction distance (cm):
 20

 Prediction frequency (MHz):
 5860

Maximum Antenna Gain, typical (dBi): 13.00

Maximum Antenna Gain (numeric): 19.95

Power density of prediction frequency at 20 cm (mW/cm²): 0.397

MPE limit for uncontrolled exposure at prediction frequency (mW/cm²): 1

Multiple Chains MPE Evaluation

Chain 0+Chain 1=0.397/1+0.397/1=0.794\le 1.0

Conclusion

The device compliances with FCC MPE limit at 20 cm distance.

Report Number: R1711205-95 Page 13 of 35 FCC Part 95 Test Report