

RF Exposure evaluation

FCC ID	2BMKC-ZX-R08S
Product Name	WiFi repeater
Model/Type reference	ZX-R08S
Listed Model(s)	ZX-R01S, ZX-R02S, ZX-R03S, ZX-R04S, ZX-R05S, ZX-R06S, ZX-R07S, ZX-R09S, ZX-R10S, ZX-R11S, ZX-R12S, ZX-R13S, ZX-R14S, ZX-R15S, ZX-R16S, ZX-R17S, ZX-R18S, ZX-R19S, ZX-R20S
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

1. Reference

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radio frequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radio frequency radiation exposure evaluation: mobile devices

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500–100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

FLW8189FSA7-A WiFi module can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
2.4GWIFI	External Antenna	1.88dBi	2412-2462MHz
5GWIFI	External Antenna	1.34dBi	5745-5825MHz

5. Manufacturing Tolerance

2.4GWIFI:

ANT0:

IEEE 802.11b:14-16

IEEE 802.11g:14-16

IEEE 802.11n_20:14-16

IEEE 802.11n_20:14-16

ANT1:

IEEE 802.11b:14-16

IEEE 802.11g:14-16

IEEE 802.11n_20:14-16

IEEE 802.11n_20:14-16

5.8GWIFI

ANT0

IEEE 802.11a:13-15

IEEE 802.11n_20:14-16

IEEE 802.11n_40:13-15

IEEE 802.11ac_20:13-15

IEEE 802.11ac_40:13-15

IEEE 802.11ac_80:13-15

ANT1

IEEE 802.11a:14-16
 IEEE 802.11n_20:13-16
 IEEE 802.11n_40:13-15
 IEEE 802.11ac_20:14-16
 IEEE 802.11ac_40:13-15
 IEEE 802.11ac_80:13-15

6. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna is 2.54dBi, the RF power density can be obtained.

Mode	Output power		Antenna Gain (dBi)	Antenna Gain(linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
2.4GWIFI	16	39.81	1.88	1.54	0.01221	1.0000
5.8GWIFI	16	39.81	1.34	1.36	0.01078	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7. Simultaneous Transmission MPE Evaluation

The EUT equipped with two 2.4GWIFI antennas and two 5.8GWIFI antennas. So, need consider simultaneous transmission;

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$$\sum \sum \text{of MPE ratios} \leq 1.0$$

2.4GWIFI MAX MPE ratios	2.4GWIFI MAX MPE ratios	5.8GWIFI MAX MPE ratios	5.8GWIFI MAX MPE ratios	$\sum$ MPE ratios	Limit	Results
0.01221	0.01221	0.01078	0.01078	0.04598	1.0	Pass

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----End of the report-----