

FCC ID : 2BEA6TPC121

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic	Power	Average			
Range(MHz)	Strength(V/m)	Field	Density(mW/cm ²)	Time			
		Strength(A/m)					
(A) Limits for Occupational/Control Exposures							
300-1500			F/300	6			
1500-	-		5	6			
100000							
(B) Limits for General Population/Uncontrol Exposures							
300-1500			F/1500	6			
1500-			1	30			
100000							

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm Pd the limit of MPE, 1mW/cm², If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn

EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn



11.2 Measurement Result

Below BT and WIFI mode can transmit simultaneously.

Mode	Max Conducted Power (dBm)	Antenna gain (dBi)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
BLE	11.91	5	3.16	0.01147	1
BT	13.04	5	3.16	0.01488	1
2.4G WIFI	29.00	5.5	3.55	0.58712	1
5G WIFI	24.88	5.7	3.72	0.22737	1

Max RF Exposure evaluation.

BT	2.4G WIFI	Summation of Evaluation result	Power density Limits
(mW/cm2)	(mW/cm2)	(mW/cm2)	(mW/cm2)
0.01488	0.58712	0.602	1

Note: All the modes are tested, only the worst data are described in the table.

----- The End -----