

# FCC RF Test Report

**APPLICANT** : Verifone, Inc.  
**EQUIPMENT** : Point of Sales Terminal  
**BRAND NAME** : Verifone  
**MODEL NAME** : C680 3G  
**FCC ID** : B32C6803G  
**STANDARD** : FCC Part 15 Subpart C §15.225  
**CLASSIFICATION** : (DXX) Low Power Communication Device Transmitter


The testing was completed on Apr. 11, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Supervisor



---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.**



## Table of Contents

<b>SUMMARY OF THE TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL INFORMATION.....</b>	<b>5</b>
1.1 Applicant .....	5
1.2 Manufacturer.....	5
1.3 Product Details.....	5
1.4 Modification of EUT.....	6
1.5 Testing Location .....	6
1.6 Applicable Standards .....	6
1.7 Test Modes.....	7
1.8 Test Configurations.....	8
1.9 Table for Supporting Units .....	9
<b>2. CONDUCTED EMISSION TEST.....</b>	<b>10</b>
2.1 Measuring Instruments .....	10
2.2 Test setup .....	10
2.3 Test Result of Conducted Emission Test.....	10
2.4 AC Power Line Conducted Emissions Measurement .....	11
<b>3. CONDUCTED TEST ITEMS .....</b>	<b>12</b>
3.1 Measuring Instruments .....	12
3.2 Test Setup .....	12
3.3 Test Result of Conducted Test Items.....	12
3.4 20dB and 99% OBW Spectrum Bandwidth Measurement.....	13
3.5 Frequency Stability Measurement .....	13
<b>4. RADIATED TEST ITEMS.....</b>	<b>14</b>
4.1 Measuring Instruments .....	14
4.2 Test Setup .....	14
4.3 Test Result of Radiated Test Items .....	14
4.4 Field Strength of Fundamental Emissions and Mask Measurement .....	15
4.5 Radiated Emissions Measurement .....	16
<b>5. LIST OF MEASURING EQUIPMENT .....</b>	<b>18</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	
<b>APPENDIX B. TEST RESULTS OF CONDUCTED EMISSION TEST</b>	
<b>APPENDIX C. TEST RESULTS OF CONDUCTED TEST ITEMS</b>	
C.1. Test Result of 20dB Spectrum Bandwidth	
C.2 Test Result of Frequency Stability	
<b>APPENDIX D. TEST RESULTS OF RADIATED TEST ITEMS</b>	
D.1 Test Result of Field Strength of Fundamental Emissions	
D.2 Results of Radiated Emissions (9 kHz~30MHz)	
D.3 Results of Radiated Emissions (30MHz~1GHz)	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR631831	Rev. 01	Initial issue of report	Apr. 21, 2016
FR631831	Rev. 02	Revising applicant address	May 03, 2016

## SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	FCC Rule	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	3.10 dB at 27.118 MHz
3.2	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	41.59 dB at 13.560 MHz
3.3	2.1049	20dB Spectrum Bandwidth	Complies	-
3.3	-	99% OBW Spectrum Bandwidth	Complies	-
3.4	15.225(d) 15.209	Radiated Emissions	Complies	25.44 dB at 0.52755 MHz for Quasi-Peak
3.5	15.225(e)	Frequency Stability	Complies	-
3.6	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.26dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±4.80dB	Confidence levels of 95%



## 1. GENERAL INFORMATION

### 1.1 Applicant

**Verifone, Inc.**

1400 West Stanford Ranch Road, Suite 100, 150 & 200, Rocklin CA 95765 USA

### 1.2 Manufacturer

**Inventec Appliances (Pudong) Corporation**

Building 1 - 3, No.789 Pu Xing Road, Caohejing Export Processing Zone, Shanghai, P.R.C.

### 1.3 Product Details

Items	Description
<b>Tx/Rx Frequency Range</b>	13.553 ~ 13.567MHz
<b>Channel Number</b>	1
<b>20dBW</b>	2.64 KHz
<b>99%OBW</b>	2.24 KHz
<b>Antenna Type</b>	Bobbin Antenna
<b>Type of Modulation</b>	ASK

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Specification of Accessory		
<b>AC Adapter</b>	<b>Brand Name</b>	Verifone, Inc.
	<b>Model Name</b>	A111-3050223U
	<b>Power Rating</b>	Input : 100-240Vac, 50/60Hz, 0.5A Output: 5.0V DC 2.2A
	<b>Power Cord</b>	1.8 meter, non-shielded cable, without ferrite core
<b>Battery 1</b>	<b>Brand Name</b>	Verifone, Inc.
	<b>Manufacturer</b>	Palladium Energy Inc.
	<b>Model Name</b>	BPK260-001
<b>Battery 2</b>	<b>Brand Name</b>	Verifone, Inc.
	<b>Manufacturer</b>	Panasonic Corporation
	<b>Model Name</b>	BPK260-001

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		
	TH03-HY	CO05-HY	03CH07-HY
Test Engineer	Tommy Lee	Kai-Chun Chu	James Chiu
Temperature	21~24	23~24	21~23
Relative Humidity	50~55	48~49	55~58

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2013




## 1.7 Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.


Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz
<b>Note:</b> 1. The EUT was programmed to be in continuously transmitting mode. 2. The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.	

## 1.8 Test Configurations

### <AC Conducted Emissions>



### < For Fundamental Emissions and Mask and Radiated Emissions Measurement >





**1.9 Table for Supporting Units**


Support Unit	Manufacturer	Model	FCC ID
Base Station	Anritsu	MT8820C	N/A
Exchange	Sun Moon Star	SMS-4 PLUS	95180108
USB Dongle	Transcend	TS8GJF300	FCC DoC
SD Card	SanDisk	MicroSD HC	FCC DoC
Smart Card	N/A	N/A	N/A

## 2. CONDUCTED EMISSION TEST

### 2.1 Measuring Instruments

See list of measuring instruments of this test report.

### 2.2 Test setup



### 2.3 Test Result of Conducted Emission Test

Please refer to Appendix B.

## 2.4 AC Power Line Conducted Emissions Measurement

### 2.4.1 Limit

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 2.4.2 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3. CONDUCTED TEST ITEMS

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup

##### 3.2.1 20dB and 99% OBW Spectrum Bandwidth



##### 3.2.2 Frequency Stability



#### 3.3 Test Result of Conducted Test Items

Please refer to Appendix C.



### **3.4 20dB and 99% OBW Spectrum Bandwidth Measurement**

#### **3.4.1 Limit**

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

#### **3.4.2 Test Procedures**

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

### **3.5 Frequency Stability Measurement**

#### **3.5.1 Limit**

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

#### **3.5.2 Test Procedures**

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The  $f_c$  is declaring of channel frequency. Then the frequency error formula is  $(f_c - f)/f_c \times 10^6$  ppm and the limit is less than  $\pm 100$ ppm.
6. Extreme temperature rule is -20°C~50°C.


## 4. RADIATED TEST ITEMS

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated emissions below 30MHz



#### 4.2.2 For radiated emissions above 30MHz



### 4.3 Test Result of Radiated Test Items

Please refer to Appendix D.

## 4.4 Field Strength of Fundamental Emissions and Mask Measurement

### 4.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
	IC RSS-210 A2.6			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength ( $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 30m	Field Strength (dB $\mu$ V/m) at 10m	Field Strength (dB $\mu$ V/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

### 4.4.2 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.

Note: Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).

## 4.5 Radiated Emissions Measurement

### 4.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength ( $\mu$ V/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.



#### **4.5.3 Test Procedures**

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
1. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
2. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
3. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
4. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

#### **4.5.4 Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

#### **4.5.5 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.




## 5. LIST OF MEASURING EQUIPMENT

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F104070011	50Hz~60Hz	Dec. 02, 2015	Mar. 30, 2016 ~ Mar. 31, 2016	Dec. 01, 2016	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 24, 2015	Mar. 30, 2016 ~ Mar. 31, 2016	Jun. 23, 2016	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Nov. 20, 2015	Mar. 30, 2016 ~ Mar. 31, 2016	Nov. 19, 2016	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 07, 2016 ~ Apr. 11, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Apr. 07, 2016 ~ Apr. 11, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Apr. 07, 2016 ~ Apr. 11, 2016	Dec. 01, 2016	Conduction (CO05-HY)
Bilog Antenna	TESEQ	CBL 6111D	35419	30MHz to 1GHz	Jan. 13, 2016	Apr. 07, 2016	Jan. 12, 2017	Radiation (03CH07-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	20Hz ~ 8.4GHz	Nov. 04, 2015	Apr. 07, 2016	Nov. 03, 2016	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Apr. 07, 2016	Sep. 01, 2016	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Feb. 27, 2016	Apr. 07, 2016	Feb. 26, 2017	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Apr. 07, 2016	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208368	Control Ant Mast	N/A	Apr. 07, 2016	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Apr. 07, 2016	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Apr. 07, 2016	N/A	Radiation (03CH07-HY)
Amplifier	Sonoma-Instrument	310 N	187282	10MHz~1GHz	Dec. 31, 2015	Apr. 07, 2016	Dec. 30, 2016	Radiation (03CH07-HY)

## **Appendix A. Setup Photographs**

**<Conducted Emission>**

**<Original Test Result>**




**<Terminal Test Result>**




**<Radiated Emission>**

From 9kHz~30MHz




From 30MHz~1GHz



## Appendix B. Test Results of Conducted Emission Test

### <Original Test Result>

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	GSM1900 Idle + Smart Card Reader + Magnetic Card Reader + RFID Tx + Battery 1 + Adapter + RS-232/4-Pin Cable (Load) + RS-232/RJ11 Cable (Load) + Printer + SAM Card + Micro SD Card + Primary Micro-USB Port (Cable Load) + Secondary Micro-USB Port (Data Link with USB Storage Device)		




### Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.494000	44.1	Off	L1	19.6	12.0	56.1
0.534000	43.4	Off	L1	19.6	12.6	56.0
0.566000	39.5	Off	L1	19.6	16.5	56.0
1.030000	36.0	Off	L1	19.6	20.0	56.0
1.518000	35.4	Off	L1	19.6	20.6	56.0
2.006000	34.8	Off	L1	19.6	21.2	56.0
2.926000	33.1	Off	L1	19.6	22.9	56.0
13.558000	80.3	Off	L1	19.8	-20.3	60.0
20.190000	34.0	Off	L1	19.8	26.0	60.0
27.118000	54.4	Off	L1	19.9	5.6	60.0




<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	GSM1900 Idle + Smart Card Reader + Magnetic Card Reader + RFID Tx + Battery 1 + Adapter + RS-232/4-Pin Cable (Load) + RS-232/RJ11 Cable (Load) + Printer + SAM Card + Micro SD Card + Primary Micro-USB Port (Cable Load) + Secondary Micro-USB Port (Data Link with USB Storage Device)		


**Final Result : Average**


Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.494000	38.8	Off	L1	19.6	7.3	46.1
0.534000	38.4	Off	L1	19.6	7.6	46.0
0.566000	32.7	Off	L1	19.6	13.3	46.0
1.030000	25.7	Off	L1	19.6	20.3	46.0
1.518000	25.9	Off	L1	19.6	20.1	46.0
2.006000	24.3	Off	L1	19.6	21.7	46.0
2.926000	22.4	Off	L1	19.6	23.6	46.0
13.558000	79.5	Off	L1	19.8	-29.5	50.0
20.190000	26.9	Off	L1	19.8	23.1	50.0
27.118000	46.9	Off	L1	19.9	3.1	50.0

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	GSM1900 Idle + Smart Card Reader + Magnetic Card Reader + RFID Off + Battery 1 + Adapter + RS-232/4-Pin Cable (Load) + RS-232/RJ11 Cable (Load) + Printer + SAM Card + Micro SD Card + Primary Micro-USB Port (Cable Load) + Secondary Micro-USB Port (Data Link with USB Storage Device)		


**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.494000	42.6	Off	N	19.6	13.5	56.1
0.526000	42.7	Off	N	19.6	13.3	56.0
1.022000	37.7	Off	N	19.6	18.3	56.0
1.478000	38.0	Off	N	19.6	18.0	56.0
1.718000	37.0	Off	N	19.6	19.0	56.0
2.174000	37.9	Off	N	19.5	18.1	56.0
2.878000	36.3	Off	N	19.6	19.7	56.0
3.646000	38.0	Off	N	19.6	18.0	56.0
4.310000	37.1	Off	N	19.6	18.9	56.0
13.558000	79.3	Off	N	19.8	-19.3	60.0
20.038000	34.2	Off	N	19.9	25.8	60.0
27.118000	55.6	Off	N	20.1	4.4	60.0

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	GSM1900 Idle + Smart Card Reader + Magnetic Card Reader + RFID Off + Battery 1 + Adapter + RS-232/4-Pin Cable (Load) + RS-232/RJ11 Cable (Load) + Printer + SAM Card + Micro SD Card + Primary Micro-USB Port (Cable Load) + Secondary Micro-USB Port (Data Link with USB Storage Device)		


**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.494000	36.8	Off	N	19.6	9.3	46.1
0.526000	36.3	Off	N	19.6	9.7	46.0
1.022000	28.8	Off	N	19.6	17.2	46.0
1.478000	28.5	Off	N	19.6	17.5	46.0
1.718000	27.3	Off	N	19.6	18.7	46.0
2.174000	27.3	Off	N	19.5	18.7	46.0
2.878000	25.4	Off	N	19.6	20.6	46.0
3.646000	27.0	Off	N	19.6	19.0	46.0
4.310000	26.9	Off	N	19.6	19.1	46.0
13.558000	78.0	Off	N	19.8	-28.0	50.0
20.038000	26.1	Off	N	19.9	23.9	50.0
27.118000	44.6	Off	N	20.1	5.4	50.0

(1) with antenna

Remark: 13.558MHz is the NFC RF fundamental signal.


(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.



**<Terminal Test Result>**

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	GSM1900 Idle + Smart Card Reader + Magnetic Card Reader + RFID Tx + Battery 1 + Adapter + RS-232/4-Pin Cable (Load) + RS-232/RJ11 Cable (Load) + Printer + SAM Card + Micro SD Card + Primary Micro-USB Port (Cable Load) + Secondary Micro-USB Port (Data Link with USB Storage Device)		



**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	25.3	Off	L1	19.8	34.7	60.0

**Final Result : Average**

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
13.558000	19.6	Off	L1	19.8	30.4	50.0

<b>Test Mode :</b>	NFC Tx	<b>Test Voltage :</b>	120Vac / 60Hz
<b>Function Type :</b>	GSM1900 Idle + Smart Card Reader + Magnetic Card Reader + RFID Off + Battery 1 + Adapter + RS-232/4-Pin Cable (Load) + RS-232/RJ11 Cable (Load) + Printer + SAM Card + Micro SD Card + Primary Micro-USB Port (Cable Load) + Secondary Micro-USB Port (Data Link with USB Storage Device)		


**Final Result : Quasi-Peak**

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
13.558000	25.0	Off	N	19.8	35.0	60.0



**Final Result : Average**

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
13.558000	19.5	Off	N	19.8	30.5	50.0



## Appendix C. Test Results of Conducted Test Items

### C.1 Test Result of 20dB Spectrum Bandwidth


Test mode	NFC Tx	Test Frequency (MHz)	13.56
 <p>Ref 20 dBm Att 50 dB RBW 1 kHz VBW 3 kHz SWT 20 ms Marker 1 [T1] 4.72 dBm 13.559920000 MHz</p> <p>ndB [T1] 20.00 dB BW 2.64000000 kHz Temp 1 [T1 dBm] -15.00 dBm 13.558560000 MHz Temp 2 [T1 dBm] -15.67 dBm 13.561220000 MHz</p> <p>Center 13.56 MHz 1 kHz/ Span 10 kHz</p> <p>Date: 30.MAR.2016 14:51:11</p>		 <p>Ref 20 dBm Att 50 dB RBW 1 kHz VBW 3 kHz SWT 20 ms Marker 1 [T1] 5.27 dBm 13.559920000 MHz</p> <p>OSW 2.24000000 kHz Temp 1 [T1 OSW] -9.26 dBm 13.558780000 MHz Temp 2 [T1 OSW] -9.26 dBm 13.561020000 MHz</p> <p>Center 13.56 MHz 1 kHz/ Span 10 kHz</p> <p>Date: 30.MAR.2016 15:12:49</p>	
20dB Bandwidth (kHz)	2.640	99% OccupiedBW(kHz)	2.240
Frequency range (MHz)	$f_L > 13.553$	13.55858	Test Result
	$f_H < 13.567$	13.56122	Complies


**C.2 Test Result of Frequency Stability**

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
120	13.559890	-20	13.559940
102	13.559880	-10	13.559940
138	13.559900	0	13.559920
		10	13.559920
		20	13.559900
		30	13.559890
		40	13.559880
		50	13.559880
Max.Deviation (MHz)	-0.000120	Max.Deviation (MHz)	-0.000120
Max.Deviation (ppm)	-8.8496	Max.Deviation (ppm)	-8.8496
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS

## Appendix D. Test Results of Radiated Test Items

### D.1 Test Result of Field Strength of Fundamental Emissions





**Note:** All NFC's spurious emissions are below 20dB of limits.

**D.2 Results of Radiated Emissions (9 kHz~30MHz)**

Test Mode :		NFC Tx		Polarization :		Horizontal			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.0368	50.08	-66.21	116.29	29.31	20.09	0.68	-	-	Average
0.06465	55.9	-55.49	111.39	35.18	20.04	0.68	-	-	Average
0.1094	39.63	-67.19	106.82	18.96	19.99	0.68	-	-	QP
0.12932	39.89	-65.48	105.37	19.24	19.97	0.68	-	-	Average
0.15102	32.43	-71.59	104.02	11.8	19.95	0.68	-	-	Average
0.52755	47.72	-25.44	73.16	27.14	19.9	0.68	100	0	QP
11.504	36.7	-32.8	69.5	15.97	20.05	0.68	-	-	QP
13.56	82.18	-	-	61.45	20.05	0.68	-	-	QP
24.712	37.69	-31.81	69.5	16.04	20.58	1.07	-	-	QP
29.71	37.7	-31.8	69.5	16.28	20.35	1.07	-	-	QP

Test Mode :		NFC Tx		Polarization :		Vertical			
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
0.037	54.6	-61.64	116.24	33.83	20.09	0.68	-	-	Average
0.06465	47.51	-63.88	111.39	26.79	20.04	0.68	-	-	Average
0.10806	38.56	-68.37	106.93	17.89	19.99	0.68	-	-	QP
0.12932	34.66	-70.71	105.37	14.01	19.97	0.68	-	-	Average
0.15068	31.57	-72.47	104.04	10.94	19.95	0.68	-	-	Average
0.49	44.19	-29.61	73.8	23.61	19.9	0.68	100	0	QP
13.216	37.21	-32.29	69.5	16.48	20.05	0.68	-	-	QP
13.56	78.61	-	-	57.88	20.05	0.68	-	-	QP
19.402	38.05	-31.45	69.5	17.01	20.36	0.68	-	-	QP
28.1	37.28	-32.22	69.5	15.61	20.6	1.07	-	-	QP

**Note:**

1. 13.56 MHz is fundamental signal which can be ignored.
2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
4. Limit line = specific limits (dBμV) + distance extrapolation factor.

**D.3 Results of Radiated Emissions (30MHz~1GHz)**

<b>Test Mode :</b>		NFC Tx				<b>Polarization :</b>		Horizontal		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
30.27	28.23	-11.77	40	32.51	26	1.07	31.35	-	-	Peak
113.97	25.64	-17.86	43.5	38.03	17.57	1.55	31.51	-	-	Peak
209.28	34.13	-9.37	43.5	47.45	16.27	1.87	31.46	100	0	Peak
328.7	23.5	-22.5	46	31.72	20.61	2.41	31.24	-	-	Peak
626.2	28.83	-17.17	46	30.39	25.66	3.57	30.79	-	-	Peak
946.8	34.36	-11.64	46	30.69	30.13	4.07	30.53	-	-	Peak

<b>Test Mode :</b>		NFC Tx				<b>Polarization :</b>		Vertical		
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
40.8	36.11	-3.89	40	46.69	19.84	1.07	31.49	100	0	Peak
67.8	25.21	-14.79	40	42.94	12.56	1.28	31.57	-	-	Peak
209.82	23.7	-19.8	43.5	37.02	16.27	1.87	31.46	-	-	Peak
441.4	25.28	-20.72	46	30.52	22.98	2.89	31.11	-	-	Peak
569.5	27.68	-18.32	46	30.41	24.91	3.24	30.88	-	-	Peak
818.7	30.71	-15.29	46	29.32	28.07	3.9	30.58	-	-	Peak

**Note:**

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.