



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.com.cn

Maximum Permissible Exposure Evaluation

FCC ID: 2APPZ-X7A

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

Product Name:	IP phone
Trade Mark:	Fanvil
Model/Type reference:	X7A
Listed Model(s):	N/A
Frequency band (Operating)	☒ BT: 2.402GHz ~ 2.480GHz ☒ BLE: 2.402GHz ~ 2.480GHz ☒ WLAN: 2.412GHz ~ 2.462GHz ☒ RLAN: 5.180GHz ~ 5.240GHz ☒ RLAN: 5.745GHz ~ 5.825GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☒ fixed (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure (S=5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	2.2dBi for 2.4GHz 2.3dBi for 5GHz WIFI
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

BLE							
Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
GFSK	2402	5.87	5±1	6	2.2	0.00131	1
	2440	4.78	4±1	5	2.2	0.00104	1
	2480	3.89	3±1	4	2.2	0.00083	1

BR/ EDR							
Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
8-DPSK	2402	8.25	8±1	9	2.2	0.00262	1
	2441	7.55	7±1	8	2.2	0.00208	1
	2480	6.51	6±1	7	2.2	0.00165	1

2.4G WIFI							
Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
802.11 b	2412	17.19	17±1	18	2.2	0.02083	1
	2437	17.28	17±1	18	2.2	0.02083	1
	2462	17.32	17±1	18	2.2	0.02083	1



5G WIFI U-NII-1							
Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11a	5180	15.83	15±1	16	2.3	0.01345	1
	5200	15.59	15±1	16	2.3	0.01345	1
	5240	15.01	15±1	16	2.3	0.01345	1
802.11 n40	5190	14.33	14±1	15	2.3	0.01068	1
	5230	14.87	14±1	15	2.3	0.01068	1
802.11 ac80	5210	10.66	10±1	11	2.3	0.00425	1

5G WIFI U-NII-3							
Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11a	5745	11.28	11±1	12	2.3	0.00535	1
	5785	10.22	10±1	11	2.3	0.00425	1
	5825	9.88	9±1	10	2.3	0.00338	1
802.11 n40	5755	8.98	8±1	9	2.3	0.00268	1
	5795	8.27	8±1	9	2.3	0.00268	1
802.11 ac80	5775	6.56	6±1	7	2.3	0.00169	1

The WLAN or Bluetooth can transmit simultaneously

WLAN Power density at 20cm (mW/cm ²)	BT Power density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
0.02083	0.00262	0.02345	1

Note

For a more detailed features description, please refer to the RF Test Report.

*****THE END*****