

FCC Test Report

Client Name : SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.

Address : Building 2, Yingfeng Industrial Zone, Tantou Community,
Songgang Street, Bao'an, Shenzhen, China

Product Name : Android Tablet

Date : May 28 2020



Shenzhen Anbotek Compliance Laboratory Limited

Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	5
1.4. Description of Test Modes.....	5
1.5. List of channels.....	6
1.6. Description Of Test Setup.....	7
1.7. Test Equipment List.....	8
1.8. Measurement Uncertainty.....	9
1.9. Description of Test Facility.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	11
4. Radiation Spurious Emission and Band Edge.....	16
4.1. Test Standard and Limit.....	16
4.2. Test Setup.....	16
4.3. Test Procedure.....	17
4.4. Test Data.....	18
5. Maximum Peak Output Power Test.....	34
5.1. Test Standard and Limit.....	34
5.2. Test Setup.....	34
5.3. Test Procedure.....	34
5.4. Test Data.....	34
6. Occupy Bandwidth Test.....	36
6.1. Test Standard.....	36
6.2. Test Setup.....	36
6.3. Test Procedure.....	36
6.4. Test Data.....	36
7. Power Spectral Density Test.....	52
7.1. Test Standard and Limit.....	52
7.2. Test Setup.....	52
7.3. Test Procedure.....	52
7.4. Test Data.....	52
8. Antenna Requirement.....	61
8.1. Test Standard and Requirement.....	61
8.2. Antenna Connected Construction.....	62
9. Frequency Stability.....	63
APPENDIX I -- PHOTOGRAPH.....	64



TEST REPORT

Applicant : SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.

Manufacturer : SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.

Product Name : Android Tablet

Model No. : WH1332T, WH1012T, WH1342T, WH1013T, WH1512T, WH1513T, WB1901A, WB1902A, WB2101A, WB2102A, WB2401A, WB2402A, WB2801A, WB2802A, WB3701A, WB3702A, WB4801A, WB4802A, WM19, WM18

Trade Mark : N.A.

Rating(s) : Input: 12V $\overline{=}$ 2.0A (via adapter input: AC 100~240V, 50/60Hz, 0.6A Max; output: 12V $\overline{=}$ 2.0A, 24.0W)

Test Standard(s) : FCC Part15 Subpart E 2019, Paragraph 15.407

Test Method(s) : ANSI C63.10: 2013,
KDB 789033 D02 General UNII Test Procedures New Rules v02r01

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart E requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.


Date of Receipt

Apr. 28, 2020

Date of Test


Apr. 28~May 20, 2020

Prepared By



(Engineer / Dolly Mo)

Reviewer



(Supervisor / Bibo Zhang)

Approved & Authorized Signer



(Manager / Tom Chen)

1. General Information

1.1. Client Information

Applicant	:	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	:	Building 2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China
Manufacturer	:	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	:	Building 2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China
Factory	:	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	:	Building 2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China

1.2. Description of Device (EUT)

Product Name	:	Android Tablet
Model No.	:	WH1332T, WH1012T, WH1342T, WH1013T, WH1512T, WH1513T, WB1901A, WB1902A, WB2101A, WB2102A, WB2401A, WB2402A, WB2801A, WB2802A, WB3701A, WB3702A, WB4801A, WB4802A, WM19, WM18 (Note: All samples are the same except the model name, so we prepare "WH1332T" for test only.)
Trade Mark	:	N.A.
Test Power Supply	:	AC 120V, 60Hz for adapter / AC 240V, 60Hz for adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Product Description	Operation Frequency:	WiFi 2.4G: 802.11b/ g/ n(HT20) 2412-2462MHz 802.11n(HT40) 2422-2452MHz BLE: 2402-2480MHz WiFi 5.1G: 5180MHz~5240MHz WiFi 5.8G: 5745MHz~5825MHz
	Number of Channel:	WiFi 2.4G: 11 Channels for 802.11b/ g/ n(HT20) 7 Channels for 802.11n(HT40) BLE: 40 Channels WiFi 5.1G: 4 Channels for 802.11a 4 Channels for 802.11n(HT20) 4 Channels for 802.11ac(HT20) 2 Channels for 802.11n(HT40) 2 Channels for 802.11ac(HT40) 1 Channels for 802.11ac(HT80)

		WiFi 5.8G: 5 Channels for 802.11a 5 Channels for 802.11n(HT20) 5 Channels for 802.11ac(HT20) 2 Channels for 802.11n(HT40) 2 Channels for 802.11ac(HT40) 1 Channels for 802.11ac(HT80)
	Modulation Type:	WiFi 2.4G: 802.11b CCK; 802.11g/n OFDM BLE: GFSK WiFi 5.1G: OFDM with BPSK/QPSK/16QAM/64QAM/256QAM WiFi 5.8G: OFDM with BPSK/QPSK/16QAM/64QAM/256QAM
	Antenna Type:	PIFA Antenna
	Antenna Gain(Peak):	WiFi 2.4G&BLE: 1.5 dBi WiFi 5.1G&WiFi 5.8G: 1.23dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2) This report is for Wifi 5.8G module.		

1.3. Auxiliary Equipment Used During Test

Adapter	:	M/N: FJ-SW1202000N Input: 100-240V~ 50/60Hz, 0.6A Max Output: 12.0V --- 2.0A, 24.0W
---------	---	---

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Mode	Test channel	Frequency (MHz)
OFDM(802.11a/n20/ac20)	CH 149	5745MHz
	CH 157	5785MHz
	CH 165	5825MHz
OFDM(802.11n40/ac40)	CH 151	5755MHz
	CH 159	5795MHz
OFDM(802.11ac80)	CH 155	5775MHz

Note:

1. The measurements are performed at the highest, middle, lowest available channels.
2. The EUT has been tested as an independent unit. And Continual Transmitting in maximum power.
3. For the relevant Conducted Measurement, the temporary antenna connector is used during the measurement. Antenna Connector Impedance: 50Ω, Cable Loss: 1.0 dB
4. The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is more than 98%

1.5. List of channels**802.11a/n20/ac20**

Channel	Freq. (MHz)	Channel	Freq. (MHz)
149	5745	153	5765
157	5785	161	5805
165	5825		



802.11n40/ac40

Channel	Freq. (MHz)	Channel	Freq. (MHz)
151	5755	159	5795

802.11ac80

Channel	Freq. (MHz)
155	5775

1.6. Description Of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 04, 2019	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 04, 2019	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 04, 2019	1 Year
4.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
5.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	Nov. 04, 2019	1 Year
6.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 01, 2019	1 Year
7.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 01, 2019	1 Year
8.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 01, 2019	1 Year
9.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Nov. 01, 2019	1 Year
10.	Pre-amplifier	SONOMA	310N	186860	Nov. 04, 2019	1 Year
11.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
12.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 04, 2019	1 Year
13.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 04, 2019	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 04, 2019	1 Year
15.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
16.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 04, 2019	1 Year
17.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 04, 2019	1 Year
18.	DC Power Supply	LW	TPR-6420D	374470	Nov. 04, 2019	1 Year
19.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Nov. 04, 2019	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 27, 2019.

ISED-Registration No.: 8058A

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, March 07, 2019.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results


Standard	Test Type	Result
15.207 & 15.407	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.407(b)	Band Edge	PASS
15.407(a)(5)&15.407(e)	Occupy Bandwidth	PASS
15.407(a)(3)	Maximum Conducted Output Power	PASS
15.407(a)(3)	Peak Power Spectral Density	PASS
15.203	Antenna Requirement	PASS
15.407(g)	Frequency Stability	PASS

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207&15.407		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, and found the 802.11a CH 149 which is the worst case, only the worst case is recorded in the report.

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: 802.11a CH 149
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 24.4°C Hum.: 57%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.4140	14.90	19.94	34.84	47.57	-12.73	AVG	
2	3.7460	25.79	20.17	45.96	56.00	-10.04	QP	
3	3.8620	25.63	20.18	45.81	56.00	-10.19	QP	
4	4.3420	27.77	20.19	47.96	56.00	-8.04	QP	
5	4.9340	29.63	20.20	49.83	56.00	-6.17	QP	
6	5.0500	30.19	20.21	50.40	60.00	-9.60	QP	
7	5.0500	19.04	20.21	39.25	50.00	-10.75	AVG	
8	5.2340	28.31	20.21	48.52	60.00	-11.48	QP	
9	6.5380	16.63	20.25	36.88	50.00	-13.12	AVG	
10	9.8060	16.14	20.33	36.47	50.00	-13.53	AVG	
11	11.9460	16.73	20.31	37.04	50.00	-12.96	AVG	
12	23.1299	13.60	20.30	33.90	50.00	-16.10	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: 802.11a CH 149
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 24.4°C Hum.: 57%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.4180	24.23	19.94	44.17	57.49	-13.32	QP	
2	0.4180	14.11	19.94	34.05	47.49	-13.44	AVG	
3	4.3380	26.91	20.19	47.10	56.00	-8.90	QP	
4	4.3380	15.88	20.19	36.07	46.00	-9.93	AVG	
5	4.3980	17.24	20.19	37.43	46.00	-8.57	AVG	
6	4.9940	29.42	20.21	49.63	56.00	-6.37	QP	
7	4.9940	18.78	20.21	38.99	46.00	-7.01	AVG	
8	6.8940	26.54	20.26	46.80	60.00	-13.20	QP	
9	9.1540	26.52	20.32	46.84	60.00	-13.16	QP	
10	9.3900	16.59	20.32	36.91	50.00	-13.09	AVG	
11	11.8860	16.63	20.31	36.94	50.00	-13.06	AVG	
12	12.1820	27.58	20.31	47.89	60.00	-12.11	QP	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: 802.11a CH 149
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 24.4°C Hum.: 57%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1700	39.65	19.90	59.55	64.96	-5.41	QP	
2	0.2700	29.61	19.89	49.50	61.12	-11.62	QP	
3	0.3140	28.13	19.90	48.03	59.86	-11.83	QP	
4	0.3540	29.12	19.91	49.03	58.87	-9.84	QP	
5	0.4380	14.47	19.95	34.42	47.10	-12.68	AVG	
6	4.4580	28.70	20.19	48.89	56.00	-7.11	QP	
7	4.4580	18.81	20.19	39.00	46.00	-7.00	AVG	
8	5.7660	17.06	20.23	37.29	50.00	-12.71	AVG	
9	6.3620	28.87	20.24	49.11	60.00	-10.89	QP	
10	7.1340	15.74	20.26	36.00	50.00	-14.00	AVG	
11	9.2700	14.43	20.32	34.75	50.00	-15.25	AVG	
12	12.6020	15.89	20.30	36.19	50.00	-13.81	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 802.11a CH 149
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 24.4°C Hum.: 57%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1660	42.57	19.90	62.47	65.15	-2.68	QP	
2	0.2020	38.13	19.90	58.03	63.52	-5.49	QP	
3	0.2180	36.39	19.90	56.29	62.89	-6.60	QP	
4	0.2260	36.49	19.89	56.38	62.59	-6.21	QP	
5	0.2940	32.40	19.89	52.29	60.41	-8.12	QP	
6	0.4340	13.80	19.95	33.75	47.18	-13.43	AVG	
7	3.0900	25.97	20.16	46.13	56.00	-9.87	QP	
8	3.0900	10.96	20.16	31.12	46.00	-14.88	AVG	
9	4.9940	11.78	20.21	31.99	46.00	-14.01	AVG	
10	7.3100	13.81	20.27	34.08	50.00	-15.92	AVG	
11	9.2140	15.15	20.32	35.47	50.00	-14.53	AVG	
12	12.6580	16.35	20.30	36.65	50.00	-13.35	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209, 15.205 and 15.407				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	68.2	Peak	3

Remark:

- (1)The lower limit shall apply at the transition frequency.
- (2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.
- (3)Above 1GHz limit: $E[dBuV/m] = EIRP[dBm] + 95.2 = 68.2 \text{ dBuV/m}$, for $EIPR[dBm] = -27\text{dBm}$.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Shenzhen Anbotech Compliance Laboratory Limited

Code:AB-RF-05-a

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

Tel:(86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotech.com



Hotline

400-003-0500

www.anbotech.com

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, and found the 802.11a CH 149 which is the worst case, only the worst case is recorded in the report.

Report No.: 18220WC00043804

FCC ID: 2ABC5-E0004

Page 19 of 64

Test Results (30~1000MHz)

Job No.: 18220WC00043804


Temp.(°C)/Hum.(%RH): 24.5°C/57%RH

Standard: FCC PART 15C

Power Source: AC 120V, 60Hz for adapter

Test Mode: 802.11a CH 149

Polarization: Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (°)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	52.5752	28.94	-16.02	12.92	40.00	-27.08	QP	100	0	
2	83.6688	39.76	-19.12	20.64	40.00	-19.36	QP	100	360	
3	303.5437	44.24	-17.03	27.21	46.00	-18.79	QP	100	0	
4	416.1791	47.05	-14.52	32.53	46.00	-13.47	QP	100	360	
5	628.3745	41.63	-11.90	29.73	46.00	-16.27	QP	100	0	
6	876.7829	36.82	-7.90	28.92	46.00	-17.08	QP	100	360	

Report No.: 18220WC00043804

FCC ID: 2ABC5-E0004

Page 20 of 64

Test Results (30~1000MHz)

Job No.: 18220WC00043804


Temp.(°C)/Hum.(%RH): 24.5°C/57%RH

Standard: FCC PART 15C

Power Source: AC 120V, 60Hz for adapter

Test Mode: 802.11a CH 149

Polarization: Vertical



No.	Freq. (MHz)	Reading (dBuV)	Factor (°)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.7991	44.54	-16.81	27.73	40.00	-12.27	QP	100	0	
2	82.2146	42.26	-19.65	22.61	40.00	-17.39	QP	100	360	
3	147.9214	44.20	-20.37	23.83	43.50	-19.67	QP	100	0	
4	268.4852	40.28	-16.76	23.52	46.00	-22.48	QP	100	360	
5	423.5403	37.62	-14.40	23.22	46.00	-22.78	QP	100	0	
6	628.3745	40.52	-11.90	28.62	46.00	-17.38	QP	100	360	



Test Results (Above 1000MHz)

Test mode:	IEEE 802.11a	Test channel:	Low CH
------------	--------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11490.00	41.24	31.98	17.08	33.91	56.39	68.20	-11.81	V
17235.00	39.87	32.65	20.03	34.85	57.70	68.20	-10.50	V
11490.00	41.52	31.98	17.08	33.91	56.67	68.20	-11.53	H
17235.00	39.79	32.65	20.03	34.85	57.62	68.20	-10.58	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11490.00	28.00	31.98	17.08	33.91	43.15	54.00	-10.85	V
17235.00	28.56	32.65	20.03	34.85	46.39	54.00	-7.61	V
11490.00	28.64	31.98	17.08	33.91	43.79	54.00	-10.21	H
17235.00	29.46	32.65	20.03	34.85	47.29	54.00	-6.71	H

Test mode:	IEEE 802.11a	Test channel:	Mid CH
------------	--------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11570.00	40.74	32.44	17.18	33.91	56.45	68.20	-11.75	V
17355.00	40.66	32.78	20.12	34.86	58.70	68.20	-9.50	V
11570.00	41.76	32.44	17.18	33.91	57.47	68.20	-10.73	H
17355.00	40.69	32.78	20.12	34.86	58.73	68.20	-9.47	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11570.00	27.31	32.44	17.18	33.91	43.02	54.00	-10.98	V
17355.00	28.34	32.78	20.12	34.86	46.38	54.00	-7.62	V
11570.00	27.97	32.44	17.18	33.91	43.68	54.00	-10.32	H
17355.00	29.89	32.78	20.12	34.86	47.93	54.00	-6.07	H

Test mode:	IEEE 802.11a	Test channel:	High CH
------------	--------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11650.00	41.35	32.59	18.02	33.92	58.04	68.20	-10.16	V
17475.00	39.16	32.87	20.15	34.88	57.30	68.20	-10.90	V
11650.00	39.18	32.59	18.02	33.92	55.87	68.20	-12.33	H
17475.00	40.47	32.87	20.15	34.88	58.61	68.20	-9.59	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11650.00	28.43	32.59	18.02	33.92	45.12	54.00	-8.88	V
17475.00	28.99	32.87	20.15	34.88	47.13	54.00	-6.87	V
11650.00	27.17	32.59	18.02	33.92	43.86	54.00	-10.14	H
17475.00	28.00	32.87	20.15	34.88	46.14	54.00	-7.86	H

Test mode:	IEEE 802.11n(HT20)	Test channel:	Low CH
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11490.00	40.54	31.98	17.08	33.91	55.69	68.20	-12.51	V
17235.00	41.97	32.65	20.03	34.85	59.80	68.20	-8.40	V
11490.00	40.32	31.98	17.08	33.91	55.47	68.20	-12.73	H
17235.00	39.74	32.65	20.03	34.85	57.57	68.20	-10.63	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11490.00	28.98	31.98	17.08	33.91	44.13	54.00	-9.87	V
17235.00	29.77	32.65	20.03	34.85	47.60	54.00	-6.40	V
11490.00	27.73	31.98	17.08	33.91	42.88	54.00	-11.12	H
17235.00	29.82	32.65	20.03	34.85	47.65	54.00	-6.35	H

Test mode:	IEEE 802.11n(HT20)	Test channel:	Mid CH
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11570.00	40.84	32.44	17.18	33.91	56.55	68.20	-11.65	V
17355.00	39.71	32.78	20.12	34.86	57.75	68.20	-10.45	V
11570.00	39.47	32.44	17.18	33.91	55.18	68.20	-13.02	H
17355.00	40.13	32.78	20.12	34.86	58.17	68.20	-10.03	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11570.00	27.36	32.44	17.18	33.91	43.07	54.00	-10.93	V
17355.00	29.51	32.78	20.12	34.86	47.55	54.00	-6.45	V
11570.00	27.22	32.44	17.18	33.91	42.93	54.00	-11.07	H
17355.00	28.01	32.78	20.12	34.86	46.05	54.00	-7.95	H

Test mode:	IEEE 802.11n(HT20)	Test channel:	High CH
------------	--------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11650.00	39.28	32.59	18.02	33.92	55.97	68.20	-12.23	V
17475.00	39.88	32.87	20.15	34.88	58.02	68.20	-10.18	V
11650.00	39.62	32.59	18.02	33.92	56.31	68.20	-11.89	H
17475.00	39.56	32.87	20.15	34.88	57.70	68.20	-10.50	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11650.00	29.07	32.59	18.02	33.92	45.76	54.00	-8.24	V
17475.00	28.39	32.87	20.15	34.88	46.53	54.00	-7.47	V
11650.00	28.76	32.59	18.02	33.92	45.45	54.00	-8.55	H
17475.00	29.77	32.87	20.15	34.88	47.91	54.00	-6.09	H

Test mode:	IEEE 802.11ac(HT20)	Test channel:	Low CH
------------	---------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11490.00	40.96	31.98	17.08	33.91	56.11	68.20	-12.09	V
17235.00	40.47	32.65	20.03	34.85	58.30	68.20	-9.90	V
11490.00	40.60	31.98	17.08	33.91	55.75	68.20	-12.45	H
17235.00	39.18	32.65	20.03	34.85	57.01	68.20	-11.19	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11490.00	27.43	31.98	17.08	33.91	42.58	54.00	-11.42	V
17235.00	27.21	32.65	20.03	34.85	45.04	54.00	-8.96	V
11490.00	28.14	31.98	17.08	33.91	43.29	54.00	-10.71	H
17235.00	28.48	32.65	20.03	34.85	46.31	54.00	-7.69	H

Test mode:	IEEE 802.11ac(HT20)	Test channel:	Mid CH
------------	---------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11570.00	39.66	32.44	17.18	33.91	55.37	68.20	-12.83	V
17355.00	39.77	32.78	20.12	34.86	57.81	68.20	-10.39	V
11570.00	39.25	32.44	17.18	33.91	54.96	68.20	-13.24	H
17355.00	39.84	32.78	20.12	34.86	57.88	68.20	-10.32	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11570.00	27.89	32.44	17.18	33.91	43.60	54.00	-10.40	V
17355.00	29.01	32.78	20.12	34.86	47.05	54.00	-6.95	V
11570.00	28.17	32.44	17.18	33.91	43.88	54.00	-10.12	H
17355.00	29.05	32.78	20.12	34.86	47.09	54.00	-6.91	H

Test mode:	IEEE 802.11ac(HT20)	Test channel:	High CH
------------	---------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11650.00	40.19	32.59	18.02	33.92	56.88	68.20	-11.32	V
17475.00	40.99	32.87	20.15	34.88	59.13	68.20	-9.07	V
11650.00	39.65	32.59	18.02	33.92	56.34	68.20	-11.86	H
17475.00	41.07	32.87	20.15	34.88	59.21	68.20	-8.99	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11650.00	29.50	32.59	18.02	33.92	46.19	54.00	-7.81	V
17475.00	29.51	32.87	20.15	34.88	47.65	54.00	-6.35	V
11650.00	28.81	32.59	18.02	33.92	45.50	54.00	-8.50	H
17475.00	27.56	32.87	20.15	34.88	45.70	54.00	-8.30	H

Test mode:	IEEE 802.11n(HT40)	Test channel:	Low CH
------------	--------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11510.00	40.01	31.98	17.08	33.91	55.16	68.20	-13.04	V
17265.00	41.09	32.65	20.03	34.85	58.92	68.20	-9.28	V
11510.00	41.36	31.98	17.08	33.91	56.51	68.20	-11.69	H
17265.00	39.63	32.65	20.03	34.85	57.46	68.20	-10.74	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11510.00	28.28	31.98	17.08	33.91	43.43	54.00	-10.57	V
17265.00	27.27	32.65	20.03	34.85	45.10	54.00	-8.90	V
11510.00	28.92	31.98	17.08	33.91	44.07	54.00	-9.93	H
17265.00	27.47	32.65	20.03	34.85	45.30	54.00	-8.70	H

Test mode:	IEEE 802.11n(HT40)	Test channel:	High CH
------------	--------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11590.00	40.90	32.59	18.02	33.92	57.59	68.20	-10.61	V
17385.00	41.59	32.87	20.15	34.88	59.73	68.20	-8.47	V
11590.00	41.80	32.59	18.02	33.92	58.49	68.20	-9.71	H
17385.00	41.77	32.87	20.15	34.88	59.91	68.20	-8.29	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11590.00	28.42	32.59	18.02	33.92	45.11	54.00	-8.89	V
17385.00	29.09	32.87	20.15	34.88	47.23	54.00	-6.77	V
11590.00	28.84	32.59	18.02	33.92	45.53	54.00	-8.47	H
17385.00	28.71	32.78	20.12	34.86	46.75	54.00	-7.25	H

Test mode:	IEEE 802.11ac(HT40)	Test channel:	Low CH
------------	---------------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11510.00	41.31	31.98	17.08	33.91	56.46	68.20	-11.74	V
17265.00	41.39	32.65	20.03	34.85	59.22	68.20	-8.98	V
11510.00	39.27	31.98	17.08	33.91	54.42	68.20	-13.78	H
17265.00	40.99	32.65	20.03	34.85	58.82	68.20	-9.38	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11510.00	29.84	31.98	17.08	33.91	44.99	54.00	-9.01	V
17265.00	29.88	32.65	20.03	34.85	47.71	54.00	-6.29	V
11510.00	27.67	31.98	17.08	33.91	42.82	54.00	-11.18	H
17265.00	28.48	32.65	20.03	34.85	46.31	54.00	-7.69	H

Test mode:	IEEE 802.11ac(HT40)	Test channel:	High CH
------------	---------------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11590.00	39.05	32.59	18.02	33.92	55.74	68.20	-12.46	V
17385.00	40.81	32.87	20.15	34.88	58.95	68.20	-9.25	V
11590.00	41.77	32.59	18.02	33.92	58.46	68.20	-9.74	H
17385.00	40.69	32.87	20.15	34.88	58.83	68.20	-9.37	H

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11590.00	27.46	32.59	18.02	33.92	44.15	54.00	-9.85	V
17385.00	27.90	32.87	20.15	34.88	46.04	54.00	-7.96	V
11590.00	29.98	32.59	18.02	33.92	46.67	54.00	-7.33	H
17385.00	28.29	32.78	20.12	34.86	46.33	54.00	-7.67	H

Test mode:	IEEE 802.11ac(HT80)	Test channel:	
------------	---------------------	---------------	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11550.00	40.47	32.44	17.18	33.91	56.18	68.20	-12.02	V
17325.00	40.37	32.78	20.12	34.86	58.41	68.20	-9.79	V
11550.00	41.32	32.44	17.18	33.91	57.03	68.20	-11.17	H
17325.00	39.71	32.78	20.12	34.86	57.75	68.20	-10.45	H


Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Pol.
11550.00	28.74	32.44	17.18	33.91	44.45	54.00	-9.55	V
17325.00	27.64	32.78	20.12	34.86	45.68	54.00	-8.32	V
11550.00	27.42	32.44	17.18	33.91	43.13	54.00	-10.87	H
17325.00	29.38	32.78	20.12	34.86	47.42	54.00	-6.58	H


Note:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss–Preamplifier Factor


Band Edge test:




802.11a: Band Edge, Left Side




802.11a: Band Edge, Right Side




802.11n(20): Band Edge, Left Side




802.11n(20): Band Edge, Right Side




802.11ac(20): Band Edge, Left Side




802.11ac(20): Band Edge, Right Side




802.11n(40): Band Edge, Left Side




802.11n(40): Band Edge, Right Side



802.11ac(40): Band Edge, Left Side



802.11ac(40): Band Edge, Right Side




802.11ac(80): Band Edge

5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.407 (a) (3)
Test Limit	30dBm

5.2. Test Setup



5.3. Test Procedure

1. The Transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the power value.
3. Repeat above procedures on all channels needed to be tested.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

5.4. Test Data

Test Item	:	Max. peak output power
Test Voltage	:	AC 120V, 60Hz for adapter
Test Result	:	PASS

Test Mode	:	CH Low ~ CH High
Temperature	:	24℃
Humidity	:	55%RH


Mode	Channel Frequency (MHz)	Peak Power output (dBm)	Correctional Limit (dBm)	Results
802.11a	5745	12.06	30	PASS
	5785	11.46	30	PASS
	5825	10.93	30	PASS
802.11n20	5745	11.09	30	PASS
	5785	10.40	30	PASS
	5825	9.83	30	PASS
802.11ac20	5745	11.54	30	PASS
	5785	10.61	30	PASS
	5825	9.83	30	PASS
802.11n40	5755	10.52	30	PASS
	5795	9.43	30	PASS
802.11ac40	5755	10.24	30	PASS
	5795	9.13	30	PASS
802.11ac80	5775	10.42	30	PASS

6. Occupy Bandwidth Test

6.1. Test Standard

Test Standard	FCC Part15 C Section 15.407 (a)(5)&15.407(e)
---------------	--

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

3. Set the spectrum analyzer as:

26 dB & 99% bandwidth

RBW = approximately 1% of the emission bandwidth;

Set the VBW > RBW;

Detector= Peak

Trace mode= Max hold.

Sweep- auto couple.

6 dB bandwidth

RBW = 100kHz;

Set the video bandwidth (VBW) ≥ 3 RBW;

Detector= Peak

Trace mode= Max hold.

Sweep- auto couple.

4. Measure the maximum width of the emission that is 26dB /6dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer.

5. Repeat until all the rest channels are investigated.

6.4. Test Data

Test Item : 6dB &26dB BW

Test Voltage : AC 120V, 60Hz for adapter

Test Result : PASS

Test Mode : CH Low ~ CH High


Temperature : 24℃

Humidity : 55%RH


Mode	Channel Frequency (MHz)	6dB BW(MHz)	Limit	Results
802.11a	5745	16.11	>0.5MHz	PASS
	5785	16.39		PASS
	5825	16.32		PASS
802.11n20	5745	17.33		PASS
	5785	17.40		PASS
	5825	17.40		PASS
802.11ac20	5745	17.32		PASS
	5785	17.32		PASS
	5825	17.60		PASS
802.11n40	5755	35.99		PASS
	5795	35.77		PASS
802.11ac40	5755	36.04		PASS
	5795	35.97		PASS
802.11ac80	5775	75.45		PASS

Mode	Channel Frequency (MHz)	26dB BW(MHz)	99% Bandwidth (MHz)
802.11a	5745	21.31	16.735
	5785	21.41	16.743
	5825	21.30	16.701
802.11n20	5745	21.37	17.856
	5785	21.51	17.855
	5825	21.48	17.868
802.11ac20	5745	21.47	17.859
	5785	21.34	17.852
	5825	21.37	17.860
802.11n40	5755	39.45	36.262
	5795	40.18	36.318
802.11ac40	5755	39.83	36.216
	5795	39.68	36.290
802.11ac80	5775	81.10	75.467


6dB Bandwidth




Test Mode: 802.11a--Low




Test Mode: 802.11a---Middle




Test Mode: 802.11a---High




Test Mode: 802.11n20---Low




Test Mode: 802.11n20---Middle




Test Mode: 802.11n20---High




Test Mode: 802.11ac20--Low




Test Mode: 802.11ac20---Middle




Test Mode: 802.11ac20---High




Test Mode: 802.11n40---Low




Test Mode: 802.11n40---High



Test Mode: 802.11ac40---Low




Test Mode: 802.11ac40---High




Test Mode: 802.11ac80


26dB & 99% Bandwidth




Test Mode: 802.11a--Low



Test Mode: 802.11a---Middle




Test Mode: 802.11a---High




Test Mode: 802.11n20---Low







Test Mode: 802.11n20---Middle




Test Mode: 802.11n20---High




Test Mode: 802.11ac20--Low




Test Mode: 802.11ac20---Middle




Test Mode: 802.11ac20---High




Test Mode: 802.11n40---Low




Test Mode: 802.11n40---High



Test Mode: 802.11ac40---Low



Test Mode: 802.11ac40---High




Test Mode: 802.11ac80

7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.407 (a) (3)
Test Limit	30 dBm/500KHz

7.2. Test Setup



7.3. Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz).


1. The EUT is directly connected to the spectrum analyzer;
2. Set RBW =510KHz;
3. Set VBW $\geq$ 3 RBW=2MHz;
3. Set the span to encompass the entire emissions bandwidth (EBW) of the signal;
5. Detector=RMS;
6. Sweep time= auto couple;
7. Trace mode=max. hold;

7.4. Test Data


Test Item : Power Spectral Density
 Test Voltage : AC 120V, 60Hz for adapter
 Test Result : PASS

Test Mode : CH Low ~ CH High
 Temperature : 24℃
 Humidity : 55%RH

Mode	Channel Frequency (MHz)	Final Power Spectral Density (dBm/500KHz)	Limit	Results
802.11a	5745	-2.278	30	PASS
	5785	-3.315	30	PASS
	5825	-4.265	30	PASS
802.11n20	5745	-3.328	30	PASS
	5785	-3.516	30	PASS
	5825	-4.646	30	PASS
802.11ac20	5745	-5.129	30	PASS
	5785	-3.715	30	PASS
	5825	-4.272	30	PASS
802.11n40	5755	-6.633	30	PASS
	5795	-8.162	30	PASS
802.11ac40	5755	-7.274	30	PASS
	5795	-8.420	30	PASS
802.11ac80	5775	-10.585	30	PASS




Test Mode: 802.11a--Low




Test Mode: 802.11a---Middle




Test Mode: 802.11a---High




Test Mode: 802.11n20---Low




Test Mode: 802.11n20---Middle




Test Mode: 802.11n20---High




Test Mode: 802.11ac20--Low




Test Mode: 802.11ac20---Middle




Test Mode: 802.11ac20---High




Test Mode: 802.11n40---Low




Test Mode: 802.11n40---High



Test Mode: 802.11ac40---Low



Test Mode: 802.11ac40---High



Test Mode: 802.11ac80


8. Antenna Requirement

8.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /15.407
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.407 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

8.2. Antenna Connected Construction

The antenna is a PIFA Antenna which permanently attached, and the best case gain of the antenna is 1.23 dBi. It complies with the standard requirement.



9. Frequency Stability

According to the manufacturer, under any normal operating conditions, the working frequency of the product is in the range of 5725-5850MHz.



APPENDIX I -- PHOTOGRAPH

Reference to the test report 18220WC00043801.

----- End of Report -----

