

---

# FCC Test Report

---

Report No.: AGC05426151101FE04

**FCC ID** : 2ACCL-MAXPLUS55  
**APPLICATION PURPOSE** : Original Equipment  
**PRODUCT DESIGNATION** : MOBILE PHONE  
**BRAND NAME** : IONE  
**MODEL NAME** : MAX PLUS 5.5  
**CLIENT** : IMAXX INTERNATIONAL INC.  
**DATE OF ISSUE** : Dec.23, 2015  
**STANDARD(S)** : FCC Part 15.247  
**TEST PROCEDURE(S)** : KDB 558074 v03r02  
**REPORT VERSION** : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



**CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



### Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Dec.23, 2015	Valid	Original Report

## TABLE OF CONTENTS

<b>1. VERIFICATION OF CONFORMITY .....</b>	<b>5</b>
<b>2. GENERAL INFORMATION .....</b>	<b>6</b>
2.1. PRODUCT DESCRIPTION .....	6
2.2. TABLE OF CARRIER FREQUENCIES.....	6
2.3. IEEE 802.11N MODULATION SCHEME .....	7
2.4. RELATED SUBMITTAL(S) / GRANT (S) .....	7
2.5. TEST METHODOLOGY .....	7
2.6. SPECIAL ACCESSORIES.....	7
2.7. EQUIPMENT MODIFICATIONS .....	8
<b>3. MEASUREMENT UNCERTAINTY.....</b>	<b>9</b>
<b>4. DESCRIPTION OF TEST MODES.....</b>	<b>9</b>
<b>5. SYSTEM TEST CONFIGURATION .....</b>	<b>10</b>
5.1. CONFIGURATION OF EUT SYSTEM.....	10
5.2. EQUIPMENT USED IN EUT SYSTEM.....	10
5.3. SUMMARY OF TEST RESULTS .....	10
<b>6. TEST FACILITY .....</b>	<b>11</b>
<b>7. OUTPUT POWER .....</b>	<b>13</b>
7.1. MEASUREMENT PROCEDURE.....	13
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	14
7.3. LIMITS AND MEASUREMENT RESULT .....	15
<b>8. 6DB BANDWIDTH .....</b>	<b>17</b>
8.1. MEASUREMENT PROCEDURE.....	17
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	17
8.3. LIMITS AND MEASUREMENT RESULTS.....	17
<b>9. CONDUCTED SPURIOUS EMISSION .....</b>	<b>22</b>
9.1. MEASUREMENT PROCEDURE.....	22
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	22
9.3. MEASUREMENT EQUIPMENT USED.....	22
9.4. LIMITS AND MEASUREMENT RESULT .....	22
<b>10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY .....</b>	<b>51</b>
10.1 MEASUREMENT PROCEDURE.....	51
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	51
10.3 MEASUREMENT EQUIPMENT USED.....	51
10.4 LIMITS AND MEASUREMENT RESULT .....	51

**11. RADIATED EMISSION ..... 56**

11.1. MEASUREMENT PROCEDURE ..... 56

11.2. TEST SETUP ..... 57

11.3. LIMITS AND MEASUREMENT RESULT ..... 58

11.4. TEST RESULT ..... 58

**12. BAND EDGE EMISSION ..... 66**

12.1. MEASUREMENT PROCEDURE..... 66

12.2. TEST SET-UP ..... 66

12.3. Radiated Test Result ..... 67

12.4. Conducted Test Result ..... 68

**13. FCC LINE CONDUCTED EMISSION TEST ..... 72**

13.1. LIMITS OF LINE CONDUCTED EMISSION TEST ..... 72

13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST ..... 72

13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST ..... 73

13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST ..... 73

13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST ..... 74

**APPENDIX A: PHOTOGRAPHS OF TEST SETUP ..... 76**

**APPENDIX B: PHOTOGRAPHS OF EUT ..... 78**

## 1. VERIFICATION OF CONFORMITY

<b>Applicant</b>	IMAXX INTERNATIONAL INC.
<b>Address</b>	9024 KENNEDY DR DES PLAINESDES PLAINES, IL 60016United States
<b>Manufacturer</b>	IMAXX INTERNATIONAL INC.
<b>Address</b>	9024 KENNEDY DR DES PLAINESDES PLAINES, IL 60016United States
<b>Product Designation</b>	MOBILE PHONE
<b>Brand Name</b>	IONE
<b>Test Model</b>	MAX PLUS 5.5
<b>Date of test</b>	Dec.08, 2015 to Dec.10, 2015
<b>Deviation</b>	None
<b>Condition of Test Sample</b>	Normal
<b>Report Template</b>	AGCRT-US-BGN/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with requirement of FCC Part 15 Rules requirement.

Tested By

*Matt Zhang*

Matt Zhang(Zhang Liang)

Dec.23, 2015

Reviewed By

*Bart Xie*

Bart Xie(Xie Xiaobin)

Dec.23, 2015

Approved By

*Solger Zhang*

Solger Zhang(Zhang Hongyi)  
Authorized Officer

Dec.23, 2015

## 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

The EUT is designed as “MOBILE PHONE”. It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

<b>Operation Frequency</b>	2.412 GHz~2.462GHz
<b>Output Power</b>	IEEE 802.11b:10.89dBm; IEEE 802.11g:9.34dBm; IEEE 802.11n(20):8.89dBm; IEEE 802.11n(40):7.46dBm
<b>Modulation</b>	DSSS(DBPSK/DQPSK/CCK);OFDM(BPSK/QPSK/16-QAM/64-QAM)
<b>Number of channels</b>	11
<b>Hardware Version</b>	G5 3.0
<b>Software Version</b>	201511V1.0
<b>Antenna Designation</b>	Integrated Antenna
<b>Antenna Gain</b>	0.8dBi
<b>Power Supply</b>	DC3.7V by Built-in Li-ion Battery

### 2.2. TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	1	2412 MHZ
	2	2417 MHZ
	3	2422 MHZ
	4	2427 MHZ
	5	2432 MHZ
	6	2437 MHZ
	7	2442 MHZ
	8	2447 MHZ
	9	2452 MHZ
	10	2457 MHZ
	11	2462 MHZ

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11

For 40MHZ bandwidth system use Channel 3 to Channel 9

### 2.3. IEEE 802.11N MODULATION SCHEME

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Data rate(Mbps)	
									800nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval

### 2.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ACCL-MAXPLUS55** filing to comply with the FCC Part 15 requirements.

### 2.5. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4 (2009).

Radiated testing was performed at an antenna to EUT distance 3 meters.

Others testing (listed at item 5.3) was performed according to the procedures in FCC Part 15.247 rules KDB 558074 D01 DTS Meas Guidance v03r02.

### 2.6. SPECIAL ACCESSORIES

Refer to section 5.2.

## **2.7. EQUIPMENT MODIFICATIONS**

Not available for this EUT intended for grant.



### 3. MEASUREMENT UNCERTAINTY

Conducted measurement: +/- 2.75dB

Radiated measurement: +/- 3.2dB

### 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal operating

Note:  
Transmit by 802.11b with Data rate (1/2/5.5/11)  
Transmit by 802.11g with Data rate (6/9/12/18/24/36/48/54)  
Transmit by 802.11n (20MHz) with Data rate (6.5/13/19.5/26/39/52/58.5/65)  
Transmit by 802.11n (40MHz) with Data rate  
(13.5/27/40.5/54/81/108/121.5/135)


**Note:**

1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency Individually, and the eut is operating at its maximum duty cycle>or equal 98%
2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

## 5. SYSTEM TEST CONFIGURATION

### 5.1. CONFIGURATION OF EUT SYSTEM

Configure:



### 5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Note
1	Mobile Phone	MAX PLUS 5.5	FCC ID: 2ACCL-MAXPLUS55	EUT
2	Adapter	MAX PLUS 5.5	DC5V, 1000mA	Accessory
3	Battery	MAX PLUS 5.5	DC3.7V/2000mAh	Accessory
4	Earphone	MAX PLUS 5.5	N/A	Accessory
5	USB Cable	MAX PLUS 5.5	N/A	Accessory

Note: All the accessories have been used during the test in conduction emission test.

### 5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Output Power	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.247	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Line Conduction Emission	Compliant

**Note:** The EUT received power from DC3.7V lithium battery.

## 6. TEST FACILITY

<b>Site</b>	Dongguan Precise Testing Service Co., Ltd.
<b>Location</b>	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
<b>FCC Registration No.</b>	371540
<b>Description</b>	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

## ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016
Power Probe	R&S	NRP-Z23	100323	July 25,2015	July 24,2016
RF attenuator	N/A	RFA20db	68	N/A	N/A

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016
Power Probe	R&S	NRP-Z23	100323	July 25,2015	July 24,2016
RF attenuator	N/A	RFA20db	68	N/A	N/A

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2015	July 7, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2015	July 3, 2016
Shielded Room	CHENGYU	843	PTS-002	June 6,2015	June 5,2016

## **7. OUTPUT POWER**

### **7.1. MEASUREMENT PROCEDURE**


For max average conducted output power test:

1. Connect EUT RF output port to power probe through an RF attenuator.
2. Connect the power probe to the PC.
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Record the maximum power from the software.

**Note :** The EUT was tested according to KDB 558074v03r02 for compliance to FCC 47CFR 15.247 requirements.

## 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

### AVERAGE POWER SETUP



### 7.3. LIMITS AND MEASUREMENT RESULT

<b>TEST ITEM</b>	OUTPUT POWER
<b>TEST MODE</b>	802.11b with data rate 1

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	10.89	30	Pass
2.437	10.68	30	Pass
2.462	10.63	30	Pass

<b>TEST ITEM</b>	OUTPUT POWER
<b>TEST MODE</b>	802.11g with data rate 6

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	9.34	30	Pass
2.437	9.29	30	Pass
2.462	9.21	30	Pass

<b>TEST ITEM</b>	OUTPUT POWER
<b>TEST MODE</b>	802.11n 20 with data rate 6.5

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	8.89	30	Pass
2.437	8.85	30	Pass
2.462	8.69	30	Pass

<b>TEST ITEM</b>	OUTPUT POWER
<b>TEST MODE</b>	802.11n 40 with data rate 13.5

<b>Frequency (GHz)</b>	<b>Average Power (dBm)</b>	<b>Applicable Limits (dBm)</b>	<b>Pass or Fail</b>
2.422	7.46	30	Pass
2.437	7.32	30	Pass
2.452	7.18	30	Pass




## 8. 6DB BANDWIDTH

### 8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW $\geq 3 \times$  RBW.
4. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.


### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)









### 8.3. LIMITS AND MEASUREMENT RESULTS




Mode	Channel	6dB Bandwidth [MHz]	OBW [MHz]	Verdict
11B	LCH	9.62	12.74	PASS
11B	MCH	9.62	12.91	PASS
11B	HCH	10.09	13.24	PASS
11G	LCH	14.68	16.39	PASS
11G	MCH	13.24	16.47	PASS
11G	HCH	14.11	16.40	PASS
11N20SISO	LCH	16.67	17.57	PASS
11N20SISO	MCH	17.62	17.73	PASS
11N20SISO	HCH	13.94	17.57	PASS
11N40SISO	LCH	35.32	35.75	PASS
11N40SISO	MCH	35.20	35.89	PASS
11N40SISO	HCH	35.16	35.74	PASS

## Test Graph



11G/LCH	 <p>Agilent R T Freq/Channel</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>#Peak Log 10 dB/Offst 0.9 dB</p> <p>Center 2.412 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 16.3855 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 16.969 kHz</p> <p>x dB Bandwidth 14.683 MHz</p> <p>File name error</p>
11G/MCH	 <p>Agilent R T Freq/Channel</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>#Peak Log 10 dB/Offst 0.9 dB</p> <p>Center 2.437 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 16.4721 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 18.836 kHz</p> <p>x dB Bandwidth 13.244 MHz</p> <p>File name error</p>
11G/HCH	 <p>Agilent R L Freq/Channel</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>#Peak Log 10 dB/Offst 0.9 dB</p> <p>Center 2.462 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 16.4044 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 21.201 kHz</p> <p>x dB Bandwidth 14.110 MHz</p> <p>File name error</p>

11N20SISO/LCH	 <p>Agilent R L</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>Log 10 dB/Offst 0.9 dB</p> <p>Center 2.412 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5652 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 11.344 kHz x dB Bandwidth 16.668 MHz</p> <p>File name error</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
11N20SISO/MCH	 <p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>Log 10 dB/Offst 0.9 dB</p> <p>Center 2.437 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.7319 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 23.116 kHz x dB Bandwidth 17.619 MHz</p> <p>File name error</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
11N20SISO/HCH	 <p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>Log 10 dB/Offst 0.9 dB</p> <p>Center 2.462 00 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5705 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 7.002 kHz x dB Bandwidth 13.937 MHz</p> <p>File name error</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

11N40SISO/LCH	 <p><b>Agilent</b> R L</p> <p>Ch Freq 2.422 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>#Peak Log 10 dB/Offst 0.9 dB</p> <p>Center 2.422 00 GHz Span 60 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 5.76 ms (601 pts)</p> <p><b>Occupied Bandwidth</b> 35.7474 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 12.814 kHz</p> <p>x dB Bandwidth 35.323 MHz</p> <p>File name error</p> <p>Freq/Channel</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.39200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 6.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
11N40SISO/MCH	 <p><b>Agilent</b> R L</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>#Peak Log 10 dB/Offst 0.9 dB</p> <p>Center 2.437 00 GHz Span 60 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 5.76 ms (601 pts)</p> <p><b>Occupied Bandwidth</b> 35.8911 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 29.621 kHz</p> <p>x dB Bandwidth 35.202 MHz</p> <p>File name error</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.40700000 GHz</p> <p>Stop Freq 2.46700000 GHz</p> <p>CF Step 6.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
11N40SISO/HCH	 <p><b>Agilent</b> R T</p> <p>Ch Freq 2.452 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 30 dBm #Atten 40 dB</p> <p>#Peak Log 10 dB/Offst 0.9 dB</p> <p>Center 2.452 00 GHz Span 60 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 5.76 ms (601 pts)</p> <p><b>Occupied Bandwidth</b> 35.7410 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -2.419 kHz</p> <p>x dB Bandwidth 35.164 MHz</p> <p>File name error</p> <p>Freq/Channel</p> <p>Center Freq 2.45200000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.48200000 GHz</p> <p>CF Step 6.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

## 9. CONDUCTED SPURIOUS EMISSION

### 9.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW > RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW > RBW) are conform to the requirement.

### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.


### 9.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6.

### 9.4. LIMITS AND MEASUREMENT RESULT



LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS


## Test Graph















































Puw/11G/HCH



















































## 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

### 10.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of AVGPSD in the KDB 558074 item 10.3 was used in this testing.

### 10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 8.2.


### 10.3 MEASUREMENT EQUIPMENT USED


Refer To Section 6.


### 10.4 LIMITS AND MEASUREMENT RESULT

Mode	Channel	Av.PSD [dBm/20kHz]	Limit[dBm/3kHz]	Verdict
11B	LCH	-4.61	8	PASS
11B	MCH	-4.23	8	PASS
11B	HCH	-5.64	8	PASS
11G	LCH	-10.8	8	PASS
11G	MCH	-8.01	8	PASS
11G	HCH	-9.34	8	PASS
11N20SISO	LCH	-9.88	8	PASS
11N20SISO	MCH	-8.68	8	PASS
11N20SISO	HCH	-10.38	8	PASS
11N40SISO	LCH	-17.12	8	PASS
11N40SISO	MCH	-13.52	8	PASS
11N40SISO	HCH	-16.42	8	PASS

## Test Graph









## 11. RADIATED EMISSION


### 11.1. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.




## 11.2. TEST SETUP

### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz



### 11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.


### 11.4. TEST RESULT

#### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

### RADIATED EMISSION BELOW 1GHZ

EUT	MOBILE PHONE	Model Name	MAX PLUS 5.5
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Horizontal



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: MOBILE PHONE

M/N: MAX PLUS 5.5

Mode: Low channel TX

Note:

Polarization: **Horizontal**

Power: AC 230V/50Hz

Distance:


Temperature: 23.9

Humidity: 56.7 %

No.	Mk	Freq. MHz	Reading dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		52.6332	9.64	11.22	20.86	40.00	-19.14	peak			
2	*	156.0997	15.43	15.30	30.73	43.50	-12.77	peak			
3		277.3500	5.13	14.73	19.86	46.00	-26.14	peak			
4		434.1666	6.10	20.11	26.21	46.00	-19.79	peak			
5		867.4333	1.88	27.76	29.64	46.00	-16.36	peak			
6		954.7332	1.28	29.95	31.23	46.00	-14.77	peak			

**RESULT: PASS**

EUT	MOBILE PHONE	Model Name	MAX PLUS 5.5
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Vertical



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: MOBILE PHONE  
M/N: MAX PLUS 5.5  
Mode: Low channel TX  
Note:


Polarization: **Vertical**  
Power: AC 230V/50Hz  
Distance:

Temperature: 23.9  
Humidity: 56.7 %

No.	Mk	Freq. MHz	Reading dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		41.3166	19.49	8.81	28.30	40.00	-11.70	peak			
2	*	151.2500	19.72	15.27	34.99	43.50	-8.51	peak			
3		266.0332	2.94	14.38	17.32	46.00	-28.68	peak			
4		432.5500	1.96	20.06	22.02	46.00	-23.98	peak			
5		634.6331	2.16	23.51	25.67	46.00	-20.33	peak			
6		953.1167	0.98	29.97	30.95	46.00	-15.05	peak			

**RESULT: PASS**

EUT	MOBILE PHONE	Model Name	MAX PLUS 5.5
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2437MHZ	Antenna	Horizontal




Site: site #1 Polarization: **Horizontal** Temperature: 23.9  
Limit: FCC Class B 3M Radiation Power: AC 230V/50Hz Humidity: 56.7 %  
EUT: MOBILE PHONE Distance:  
M/N: MAX PLUS 5.5  
Mode: Middle channel TX  
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		52.6332	7.64	11.22	18.86	40.00	-21.14	peak			
2	*	156.0997	16.93	15.30	32.23	43.50	-11.27	peak			
3		319.3833	2.84	16.70	19.54	46.00	-26.46	peak			
4		434.1666	6.10	20.11	26.21	46.00	-19.79	peak			
5		700.9166	1.74	25.22	26.96	46.00	-19.04	peak			
6		867.4333	0.88	27.76	28.64	46.00	-17.36	peak			

**RESULT: PASS**

EUT	MOBILE PHONE	Model Name	MAX PLUS 5.5
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2437MHZ	Antenna	Vertical



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: MOBILE PHONE  
M/N: MAX PLUS 5.5  
Mode: Middle channel TX  
Note:


Polarization: **Vertical**  
Power: AC 230V/50Hz  
Distance:

Temperature: 23.9  
Humidity: 56.7 %

No.	Mk	Freq. MHz	Reading dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		41.3166	21.99	8.81	30.80	40.00	-9.20	peak			
2	*	151.2500	20.72	15.27	35.99	43.50	-7.51	peak			
3		350.1000	1.76	18.74	20.50	46.00	-25.50	peak			
4		547.3333	1.95	22.41	24.36	46.00	-21.64	peak			
5		668.5833	1.57	24.35	25.92	46.00	-20.08	peak			
6		865.8165	2.42	27.72	30.14	46.00	-15.86	peak			

**RESULT: PASS**

EUT	MOBILE PHONE	Model Name	MAX PLUS 5.5
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Horizontal



Site: site #1 Polarization: **Horizontal** Temperature: 23.9  
Limit: FCC Class B 3M Radiation Power: AC 230V/50Hz Humidity: 56.7 %  
EUT: MOBILE PHONE Distance:  
M/N: MAX PLUS 5.5  
Mode: High channel TX  
Note:

No.	Mk	Freq. MHz	Reading dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		52.6332	8.64	11.22	19.86	40.00	-20.14	peak			
2	*	156.0997	17.93	15.30	33.23	43.50	-10.27	peak			
3		277.3500	4.63	14.73	19.36	46.00	-26.64	peak			
4		434.1666	3.10	20.11	23.21	46.00	-22.79	peak			
5		700.9166	2.24	25.22	27.46	46.00	-18.54	peak			
6		954.7332	-0.22	29.95	29.73	46.00	-16.27	peak			

**RESULT: PASS**

EUT	MOBILE PHONE	Model Name	MAX PLUS 5.5
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Vertical



Site: site #1  
Limit: FCC Class B 3M Radiation  
EUT: MOBILE PHONE  
M/N: MAX PLUS 5.5  
Mode: High channel TX  
Note:

Polarization: **Vertical**  
Power: AC 230V/50Hz  
Distance:

Temperature: 23.9  
Humidity: 56.7 %

No.	Mk	Freq. MHz	Reading dBuV	Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		41.3166	21.99	8.81	30.80	40.00	-9.20	peak			
2	*	151.2500	20.22	15.27	35.49	43.50	-8.01	peak			
3		411.5332	1.10	19.42	20.52	46.00	-25.48	peak			
4		547.3333	0.95	22.41	23.36	46.00	-22.64	peak			
5		620.0833	0.20	23.18	23.38	46.00	-22.62	peak			
6		904.6167	1.32	28.74	30.06	46.00	-15.94	peak			

## RESULT: PASS

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin= Result -Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. 30MHz~1GHz:(Scan with 11b,11g,11n, the worst case is 11b Mode)



### RADIATED EMISSION ABOVE 1GHZ

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
TX 11b 2412MHz							
4824.092	46.81	10.44	57.25	74	-16.75	Pk	Horizontal
4824.092	31.21	10.44	41.65	54	-12.35	AV	Horizontal
7236.127	43.48	10.39	53.87	74	-20.13	pk	Horizontal
7236.127	33.37	10.39	43.76	54	-10.24	AV	Horizontal
4824.098	49.67	10.39	60.06	74	-13.94	Pk	Vertical
4824.082	33.29	10.39	43.68	54	-10.32	AV	Vertical
7236.110	48.46	10.68	59.14	74	-14.86	Pk	Vertical
7236.054	30.81	10.68	41.49	54	-12.51	AV	Vertical
TX 11b 2437MHz							
4874.072	49.32	10.39	59.71	74	-14.29	Pk	Horizontal
4874.108	33.21	10.39	43.6	54	-10.4	AV	Horizontal
7311.092	48.79	12.68	61.47	74	-12.53	Pk	Horizontal
7311.131	30.51	12.68	43.19	54	-10.81	AV	Horizontal
4874.098	49.89	10.39	60.28	74	-13.72	Pk	Vertical
4874.044	33.66	10.39	44.05	54	-9.95	AV	Vertical
7311.145	48.48	12.68	61.16	74	-12.84	Pk	Vertical
7311.104	30.36	12.68	43.04	54	-10.96	AV	Vertical
TX 11b 2462MHz							
4924.128	49.93	10.39	60.32	74	-13.68	pk	Horizontal
4924.083	33.17	10.39	43.56	54	-10.44	AV	Horizontal
7386.071	48.85	12.68	61.53	74	-12.47	pk	Horizontal
7386.134	30.67	12.68	43.35	54	-10.65	AV	Horizontal
4924.042	49.29	10.39	59.68	74	-14.32	pk	Vertical
4924.060	33.48	10.39	43.87	54	-10.13	AV	Vertical
7386.051	48.67	12.68	61.35	74	-12.65	pk	Vertical
7386.054	30.55	12.68	43.23	54	-10.77	AV	Vertical

### RESULT: PASS

**Note:** 1~25GHz scan with 11b. No recording in the test report at least have 20dB margin.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

## 12. BAND EDGE EMISSION

### 12.1. MEASUREMENT PROCEDURE

1) Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

2) Conducted Emissions at the bang edge

a) The transmitter output was connected to the spectrum analyzer


b) Set RBW=100kHz, VBW=300kHz

c) Suitable frequency span including 100kHz bandwidth from band edge

### 12.2. TEST SET-UP

Radiated same as 11.2

Conducted set up



### 12.3. Radiated Test Result

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
TX 11b 2412MHz							
2399.9	78.72	-13	65.72	74	-8.28	peak	Horizontal
2399.9	59.69	-13	46.69	54	-7.31	AVG	Horizontal
2400	79.24	-12.99	66.25	74	-7.75	peak	Horizontal
2400	58.57	-12.99	45.58	54	-8.42	AVG	Horizontal
2399.9	79.53	-12.97	66.56	74	-7.44	peak	Vertical
2399.9	59.49	-12.97	46.52	54	-7.48	AVG	Vertical
2400	79.26	-12.94	66.32	74	-7.68	peak	Vertical
2400	59.24	-12.94	46.3	54	-7.7	AVG	Vertical
TX 11b 2462MHz							
2483.5	78.85	-12.78	66.07	74	-7.93	peak	Horizontal
2483.5	58.61	-12.78	45.83	54	-8.17	AVG	Horizontal
2483.6	78.27	-12.77	65.5	74	-8.5	peak	Horizontal
2483.6	58.84	-12.77	46.07	54	-7.93	AVG	Horizontal
2483.5	79.69	-12.76	66.93	74	-7.07	peak	Vertical
2483.5	57.87	-12.76	45.11	54	-8.89	AVG	Vertical
2483.6	78.23	-12.72	65.51	74	-8.49	peak	Vertical
2483.6	58.37	-12.72	45.65	54	-8.35	AVG	Vertical

### RESULT: PASS

**Note:** Scan with 11b,11g,11n, the worst casw is 11b Mode

Factor=Antenna Factor + Cable loss - Amplifier gain,

Emission Level = Meter Reading + Factor


Margin= Emission Level -Limit.


The “Factor” value can be calculated automatically by software of measurement system.


#### 12.4. Conducted Test Result

Mode	Channel	Carrier Power[dBm]	Max.Spurious Level [dBm]	Limit [dBm]	Verdict
11B	LCH	7.01	-33.79	-12.99	PASS
11B	HCH	6.55	-45.55	-13.45	PASS
11G	LCH	0.58	-34.26	-19.42	PASS
11G	HCH	1.26	-42.16	-18.74	PASS
11N20SISO	LCH	1.46	-29.42	-18.54	PASS
11N20SISO	HCH	2.66	-40.25	-17.34	PASS
11N40SISO	LCH	-2.93	-35.18	-22.93	PASS
11N40SISO	HCH	-3.8	-36.32	-23.8	PASS

## Test Graph







### 13. FCC LINE CONDUCTED EMISSION TEST


#### 13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.( dBuV)	Average( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

#### 13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





### **13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received charging voltage by adapter which received 120V/60Hz power by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

### **13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

### 13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

#### LINE CONDUCTED EMISSION TEST LINE 1-L




Site: Conduction  
Limit: FCC Class B Conduction(QP)  
EUT: MOBILE PHONE  
M/N: MAX PLUS 5.5  
Mode: Normal Operation(WIFI)  
Note:

Phase: **L1**  
Power: AC 120V/60Hz  
Temperature: 23.5  
Humidity: 57.2 %

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2060	28.36		18.94	10.22	38.58		29.16	63.36	53.36	-24.78	-24.20	P	
2	0.4940	25.44		21.17	10.40	35.84		31.57	56.10	46.10	-20.26	-14.53	P	
3	0.7380	25.74		20.26	10.32	36.06		30.58	56.00	46.00	-19.94	-15.42	P	
4	1.3260	22.24		14.58	10.38	32.62		24.96	56.00	46.00	-23.38	-21.04	P	
5	3.5460	29.39		11.90	10.50	39.89		22.40	56.00	46.00	-16.11	-23.60	P	
6	23.1700	5.73		-6.77	10.11	15.84		3.34	60.00	50.00	-44.16	-46.66	P	

# Line Conducted Emission Test Line 2-N



Site: Conduction Phase: **N** Temperature: 23.5  
Limit: FCC Class B Conduction(QP) Power: AC 120V/60Hz Humidity: 57.2 %  
EUT: MOBILE PHONE  
M/N: MAX PLUS 5.5  
Mode: Normal Operation(WIFI)  
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1580	22.04		8.65	10.17	32.21		18.82	65.56	55.56	-33.35	-36.74	P	
2	0.5180	24.82		7.89	10.38	35.20		18.27	56.00	46.00	-20.80	-27.73	P	
3	1.2820	21.03		2.56	10.38	31.41		12.94	56.00	46.00	-24.59	-33.06	P	
4	3.5140	23.57		4.59	10.51	34.08		15.10	56.00	46.00	-21.92	-30.90	P	
5	6.1220	13.95		-0.71	10.28	24.23		9.57	60.00	50.00	-35.77	-40.43	P	
6	29.8340	7.64		-4.40	10.12	17.76		5.72	60.00	50.00	-42.24	-44.28	P	

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP






## APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT





BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT







RIGHT VIEW OF EUT



OPEN VIEW OF EUT-1



OPEN VIEW OF EUT-2




OPEN VIEW OF EUT-3



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----