

RF Exposure Report

Report No.: SABWIN-WTW-P21040653-2

FCC ID: J9C-QCNFA725

Test Model: QCNFA725

Received Date: Apr. 20, 2021

Test Date: May 26 to July 05, 2021

Issued Date: Oct. 08, 2021

Applicant: Qualcomm Technologies, Inc.

Address: 5775 Morehouse Drive, San Diego, CA 92121-1714

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result	7

Release Control Record

Issue No.	Description	Date Issued
SABWIN-WTW-P21040653-2	Original release.	Oct. 08, 2021

1 Certificate of Conformity

Product: Wi-Fi 6E BT 5.2 M.2 1418 Module
Brand: Qualcomm
Test Model: QCNFA725
Sample Status: Engineering sample
Applicant: Qualcomm Technologies, Inc.
Test Date: May 26 to July 05, 2021
Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Phoenix Huang, **Date:** Oct. 08, 2021
Phoenix Huang / Specialist

Approved by : Clark Lin, **Date:** Oct. 08, 2021
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna Set	RF Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length
1	Chain0/1	HONGBO	260-25094	3.53	2.4~2.4835 GHz	0.76	PIFA	i-pex(MHF 4L)	300mm
				3.06	5.15~5.25 GHz	1.16			
				3.07	5.25~5.35 GHz	1.18			
				4.81	5.47~5.725 GHz	1.2			
				4.2	5.725~5.850 GHz	1.27			
2	Chain0/1	HONGBO	260-25083	5.09	5.850~5.895 GHz	1.29	PIFA	i-pex(MHF 4L)	300mm
				5.14	5.925~6.425 GHz	1.32			
				5.09	6.425~6.525 GHz	1.35			
				5.16	6.525~6.875 GHz	1.4			
				5.12	6.875~7.125 GHz	1.45			
3	Chain0/1	HONGBO	260-25084	3.22	2.4~2.4835 GHz	0.5	Monopole	i-pex(MHF 4L)	200mm
				3.35	5.150~5.250 GHz	0.76			
				3.42	5.250~5.350 GHz	0.78			
				4.77	5.470~5.725 GHz	0.81			
				4.72	5.725~5.850 GHz	0.85			
				4.71	5.850~5.895 GHz	0.86			
				4.75	5.925~6.425 GHz	0.87			
				4.29	6.425~6.525 GHz	0.91			
				4.81	6.525~6.875 GHz	0.96			
				4.74	6.875~7.125 GHz	0.98			

Note: The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.5 Calculation Result

Operation Mode	Max. Power (dBm)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN (2.4GHz)	22.50	177.828	6.54	20	0.15949	1
WLAN (5GHz)	22.00	158.489	7.82	20	0.19087	1
WLAN (5.9GHz)	21.5	141.253	8.1	20	0.18144	1
WLAN (6GHz)	19.00	79.433	8.17	20	0.10369	1
Bluetooth	16.00	39.811	3.53	20	0.01785	1

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- 2.4GHz: Directional gain = 3.53dBi + 10log(2) = 6.54dBi
 5GHz:
 U-NII-1: Directional gain = 3.35dBi + 10log(2) = 6.36dBi
 U-NII-2A: Directional gain = 3.42dBi + 10log(2) = 6.43dBi
 U-NII-2C: Directional gain = 4.81dBi + 10log(2) = 7.82dBi
 U-NII-3: Directional gain = 4.72dBi + 10log(2) = 7.73dBi
 U-NII-4: Directional gain = 5.09dBi + 10log(2) = 8.1dBi
 6GHz:
 U-NII-5: Directional gain = 5.14dBi + 10log(2) = 8.15dBi
 U-NII-6: Directional gain = 5.09dBi + 10log(2) = 8.10dBi
 U-NII-7: Directional gain = 5.16dBi + 10log(2) = 8.17dBi
 U-NII-8: Directional gain = 5.12dBi + 10log(2) = 8.13dBi
- This power include tune-up tolerance range that specified in QCNFA725 Tune Up power table.
- WLAN (2.4GHz) and Bluetooth, BT-LE and BT-EDR are can't transmit simultaneously.

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

Simultaneously transmission condition.

Condition	Technology	
1	WLAN(2.4GHz)	WLAN(6GHz)
2	WLAN(2.4GHz)	WLAN(5GHz)
3	WLAN(2.4GHz)	WLAN(5.9GHz)
4	WLAN(6GHz)	Bluetooth
5	WLAN(5GHz)	Bluetooth
6	WLAN(5.9GHz)	Bluetooth

$WLAN\ 2.4GHz + WLAN\ 6GHz = 0.15949 / 1 + 0.10369 / 1 = 0.26318$

$WLAN\ 2.4GHz + WLAN\ 5GHz = 0.15949 / 1 + 0.19087 / 1 = 0.35036$

$WLAN\ 2.4GHz + WLAN\ 5.9GHz = 0.15949 / 1 + 0.18144 / 1 = 0.34093$

$WLAN\ 6GHz + Bluetooth = 0.10369 / 1 + 0.01785 / 1 = 0.12154$

$WLAN\ 5GHz + Bluetooth = 0.19087 / 1 + 0.01785 / 1 = 0.20872$

$WLAN\ 5.9GHz + Bluetooth = 0.18144 / 1 + 0.01785 / 1 = 0.19929$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---