

6	7	8		
REV.	Description	By	Date	ECN No.
△	初版发行	Necole	2016/3/30	

69.85mm+/-0.2

Powered Subwoofer

Model: SB16-ULTRA

SN: SB16UMMY1001E





FCC ID: 2AGJ4SB16 IC: 20885-SB16
CAN ICES-3 (B)/NMB-3(B)


Design and Engineering by SVS, Ohio USA
Made in P.R.C. Exclusively for SVS

25.4mm+/-0.2

Note:

1. Parts shall be approved by Tymphany Engineering prior to mass production.
所有零部件都需超声工程师确定后才可生产。
2. ■ indicates design-critical dimension, and ◆ indicates customer-controlled dimension. Supplier must establish quality control plan for these dimensions. Customer-controlled dimension cannot be changed without prior customer approval.
有■标识的尺寸为重要管控尺寸(IQC必检), 有◆标识的尺寸为客户重要管控尺寸(IQC必检)。
3. Comply with Tymphany QSI057-1031 "Green Product Chemical Substances Specification".
符合QSI057-1031绿色产品化学物质限用规格;
4. Follow customer's specification as required.符合客户要求。
5. Follow Halogen- Free requirement : Br<900 ppm, Cl<900 ppm, Br+Cl< 1500 ppm if required.
有要求时需符合无卤要求 : Br<900 ppm, Cl<900 ppm, Br+Cl< 1500 ppm 。
6. All dimensions and tolerances indicated on the drawing indicate delivered part dimensions;
All dimensions not indicated on the drawing are per 3D model.
来料部件或产品的尺寸及公差需符合图纸标识, 未标识的尺寸请参考3D
7. Material(材质): 铜版纸FASSON-AW5209 Artpaper FASSON-AW5209 Weight(重量 0.8±5%g)
8. Finishing(表面处理): 黑色印刷, Black color Printing

TYMPHANY			This drawing is the property of Tymphany corporation. It contains material that is confidential and/or legally privileged for the sole use of the intended recipient. Any review or distribution by others is strictly prohibited and punishable to the full extent of the law.					Tolerance				Cus. Model No.	
								Angular			±0.25°		SVS SB16-Ultra
Quotation	Version NO.:	Scale : 1:1	Unit : MM	Dimension	F	G	H	J	Tymphany Model No.				
	1	Sheet : 1/1	Size : A4		0-8	±0.05	±0.1	±0.1	±0.2	T02-258013701			
Sample	Drawn By	Checked By	Approved By		>8-25	±0.08	±0.15	±0.15	±0.3	Part No.			
					>25-80	±0.12	±0.2	±0.25	±0.4	T304001834000			
Tooling	Necole.Dang 30Mar2016	Suki.Deng	Janice.Chang		>80-250	±0.25	±0.3	±0.4	±0.6	DWG No.			
					>250-800	±0.5	±0.6	±0.8	±1.0	T304001834000			
Official Issue					>800-2500	±1.0	±1.0	±1.5	±1.7	Part Name.			
					>2500~	±2.0	±2.0	±3.0	±3.0	Serial label			



8.70

unit:cm

14.21



SLEDGE
AMPLIFIER TECHNOLOGY
STA-1500D

[serial number]




This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received, including interference that may cause undesired operation.



ON



OFF



100-240V ~ 50-60Hz 1500W

LINE LEVEL
OUTPUT

LINE LEVEL
INPUT





TRIGGER
INPUT



3V-12V | AC/DC

BALANCED
OUTPUT

RIGHT



LEFT



RIGHT

LEFT

BALANCED
INPUT



“WARNING: TO REDUCE THE RISK OF FIRE OR ELECTRIC SHOCK, DO NOT EXPOSE THIS APPLIANCE TO RAIN OR MOISTURE.”

“AVERTISSEMENT: POUR PRÉVENIR LES RISQUES D'INCENDIE OU DE CHOC ÉLECTRIQUE, ÉVITER D'EXPOSER CET APPAREIL À LA PLUIE OU À L'HUMIDITÉ.”

SVS | 260 Victoria Rd. Youngstown, OH, USA | svsound.com



Label location

Material : Artpaper with Black Color Printing