


Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 125 of 311



Power Spectral Density NVNT_ANT2_802_11n(HT40)_5230



Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5190

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 126 of 311



Power Spectral Density NVNT_ANT2_802_11ac(VHT40)_5190



Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5230


Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 127 of 311



Power Spectral Density NVNT ANT2 802_11ac(VHT40) 5230



Power Spectral Density NVNT ANT1 802_11ax(HE40) 5190


Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 128 of 311



Power Spectral Density NVNT ANT2 802_11ax(HE40) 5190




Power Spectral Density NVNT ANT1 802_11ax(HE40) 5230

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 129 of 311



Power Spectral Density NVNT ANT2 802_11ax(HE40) 5230



Power Spectral Density NVNT ANT1 802_11ac(VHT80) 5210

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 130 of 311



Power Spectral Density NVNT ANT2 802_11ac(VHT80) 5210



Power Spectral Density NVNT ANT1 802_11ax(HE80) 5210

Appendix B

CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 131 of 311



Power Spectral Density NVNT ANT2 802 11ax(HE80) 5210



Appendix B

CN24K76Q 003

Prüfbericht - Produkte

Test Report - Products

Page 132 of 311

3.2 Test Datas Bands U-NII-3

Condition	Antenna	Modulation	Frequency (MHz)	PSD_SA (dBm/RBW)	Duty factor (dB)	RB factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
NVNT	ANT1	802.11a	5745.00	-3.16	0.32	-0	-2.84	30	Pass
NVNT	ANT2	802.11a	5745.00	-5.79	0.32	-0	-5.47	30	Pass
NVNT	ANT1	802.11a	5785.00	-4.58	0.32	-0	-4.26	30	Pass
NVNT	ANT2	802.11a	5785.00	-6.11	0.29	-0	-5.82	30	Pass
NVNT	ANT1	802.11a	5825.00	-4.07	0.32	-0	-3.75	30	Pass
NVNT	ANT2	802.11a	5825.00	-8.03	0.32	-0	-7.71	30	Pass
NVNT	ANT1	802.11n(HT20)	5745.00	-1.73	0.32	-0	-1.41	30	Pass
NVNT	ANT2	802.11n(HT20)	5745.00	-2.71	0.32	-0	-2.39	30	Pass
NVNT	ANT1	802.11n(HT20)	5785.00	-3.31	0.32	-0	-2.99	30	Pass
NVNT	ANT2	802.11n(HT20)	5785.00	-2.19	0.32	-0	-1.87	30	Pass
NVNT	ANT1	802.11n(HT20)	5825.00	-2.84	0.32	-0	-2.52	30	Pass
NVNT	ANT2	802.11n(HT20)	5825.00	-2.96	0.32	-0	-2.64	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5745.00	-2.76	0.00	-0	-2.76	30	Pass
NVNT	ANT2	802.11ac(VHT20)	5745.00	-2.62	0.00	-0	-2.62	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5785.00	-2.02	0.00	-0	-2.02	30	Pass
NVNT	ANT2	802.11ac(VHT20)	5785.00	-2.24	0.00	-0	-2.24	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5825.00	-2.76	0.00	-0	-2.76	30	Pass
NVNT	ANT2	802.11ac(VHT20)	5825.00	-3.10	0.00	-0	-3.10	30	Pass
NVNT	ANT1	802.11ax(HE20)	5745.00	-1.72	0.00	-0	-1.72	30	Pass
NVNT	ANT2	802.11ax(HE20)	5745.00	-2.09	0.00	-0	-2.09	30	Pass
NVNT	ANT1	802.11ax(HE20)	5785.00	-3.29	0.00	-0	-3.29	30	Pass
NVNT	ANT2	802.11ax(HE20)	5785.00	-2.48	0.00	-0	-2.48	30	Pass
NVNT	ANT1	802.11ax(HE20)	5825.00	-2.58	0.00	-0	-2.58	30	Pass
NVNT	ANT2	802.11ax(HE20)	5825.00	-3.61	0.00	-0	-3.61	30	Pass
NVNT	ANT1	802.11n(HT40)	5755.00	-7.51	0.62	-0	-6.89	30	Pass
NVNT	ANT2	802.11n(HT40)	5755.00	-7.50	0.62	-0	-6.88	30	Pass
NVNT	ANT1	802.11n(HT40)	5795.00	-11.51	0.62	-0	-10.89	30	Pass
NVNT	ANT2	802.11n(HT40)	5795.00	-12.88	0.62	-0	-12.26	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5755.00	-4.44	0.00	-0	-4.44	30	Pass
NVNT	ANT2	802.11ac(VHT40)	5755.00	-6.87	0.00	-0	-6.87	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5795.00	-5.48	0.00	-0	-5.48	30	Pass
NVNT	ANT2	802.11ac(VHT40)	5795.00	-7.89	0.00	-0	-7.89	30	Pass
NVNT	ANT1	802.11ax(HE40)	5755.00	-5.03	0.17	-0	-4.86	30	Pass
NVNT	ANT2	802.11ax(HE40)	5755.00	-7.54	0.17	-0	-7.37	30	Pass
NVNT	ANT1	802.11ax(HE40)	5795.00	-6.26	0.17	-0	-6.09	30	Pass
NVNT	ANT2	802.11ax(HE40)	5795.00	-8.83	0.17	-0	-8.66	30	Pass
NVNT	ANT1	802.11ac(VHT80)	5775.00	-8.40	0.00	-0	-8.40	30	Pass
NVNT	ANT2	802.11ac(VHT80)	5775.00	-11.02	0.00	-0	-11.02	30	Pass
NVNT	ANT1	802.11ax(HE80)	5775.00	-10.02	0.31	-0	-9.71	30	Pass
NVNT	ANT2	802.11ax(HE80)	5775.00	-12.55	0.31	-0	-12.24	30	Pass

Condition	Antenna	Mode	Frequency (MHz)	MIMO PSD(dBm/500kHz)	Limit(dBm/500kHz)	Result
NVNT	MIMO_TX	802.11n(HT20)	5745.00	0.45	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	5785.00	-0.04	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	5825.00	-0.35	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5745.00	0.01	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5785.00	0.54	30	Pass
NVNT	MIMO_TX	802.11ac(VHT20)	5825.00	-0.58	30	Pass
NVNT	MIMO_TX	802.11ax(HE20)	5745.00	0.73	30	Pass
NVNT	MIMO_TX	802.11ax(HE20)	5785.00	-0.30	30	Pass
NVNT	MIMO_TX	802.11ax(HE20)	5825.00	-0.68	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	5755.00	-4.88	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	5795.00	-8.89	30	Pass
NVNT	MIMO_TX	802.11ac(VHT40)	5755.00	-3.13	30	Pass
NVNT	MIMO_TX	802.11ac(VHT40)	5795.00	-3.87	30	Pass
NVNT	MIMO_TX	802.11ax(HE40)	5755.00	-3.68	30	Pass
NVNT	MIMO_TX	802.11ax(HE40)	5795.00	-4.50	30	Pass
NVNT	MIMO_TX	802.11ac(VHT80)	5775.00	-6.88	30	Pass
NVNT	MIMO_TX	802.11ax(HE80)	5775.00	-8.33	30	Pass

Note: The cable loss and duty cycle factor are taken into account in results, e.i.r.p.=P_(Peak power)+ G

Appendix B

CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 133 of 311

Power Spectral Density NVNT ANT1 802 11a 5745



Power Spectral Density NVNT ANT2 802 11a 5745



Power Spectral Density NVNT ANT1 802 11a 5785

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 134 of 311



Power_Spectral_Density NVNT_ANT2_802_11a_5785



Power_Spectral_Density NVNT_ANT1_802_11a_5825

Appendix B

CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 135 of 311



Power Spectral Density NVNT_ANT2_802_11a_5825



Power Spectral Density NVNT_ANT1_802_11n(HT20)_5745

Appendix B
CN24K76Q 003
Page 136 of 311

Prüfbericht - Produkte
Test Report - Products



Power Spectral Density NVNT_ANT2_802_11n(HT20)_5745



Power Spectral Density NVNT_ANT1_802_11n(HT20)_5785


Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 137 of 311



Power Spectral Density NVNT_ANT2_802_11n(HT20)_5785



Power Spectral Density NVNT_ANT1_802_11n(HT20)_5825

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 138 of 311



Power Spectral Density NVNT_ANT2_802_11n(HT20)_5825



Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5745

Appendix B
CN24K76Q 003
Page 139 of 311

Prüfbericht - Produkte
Test Report - Products



Power Spectral Density NVNT_ANT2_802_11ac(VHT20)_5745



Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5785

Appendix B

CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 140 of 311



Power Spectral Density NVNT_ANT2_802_11ac(VHT20)_5785



Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5825

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 141 of 311



Power Spectral Density NVNT ANT2_802_11ac(VHT20)_5825




Power Spectral Density NVNT ANT1_802_11ax(HE20)_5745

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 142 of 311



Power Spectral Density NVNT ANT2 802 11ax(HE20) 5745



Power Spectral Density NVNT ANT1 802 11ax(HE20) 5785

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 143 of 311



Power Spectral Density NVNT ANT2 802 11ax(HE20) 5785




Power Spectral Density NVNT ANT1 802 11ax(HE20) 5825

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 144 of 311



Power Spectral Density NVNT ANT2 802 11ax(HE20) 5825



Power Spectral Density NVNT ANT1 802 11n(HT40) 5755

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 145 of 311



Power Spectral Density NVNT_ANT2_802_11n(HT40)_5755




Power Spectral Density NVNT_ANT1_802_11n(HT40)_5795

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 146 of 311



Power Spectral Density NVNT_ANT2_802_11n(HT40)_5795



Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5755

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 147 of 311



Power Spectral Density NVNT_ANT2_802_11ac(VHT40)_5755



Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5795

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 148 of 311



Power Spectral Density NVNT ANT2 802_11ac(VHT40) 5795



Power Spectral Density NVNT ANT1 802_11ax(HE40) 5755

Appendix B

CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 149 of 311



Power Spectral Density NVNT ANT2 802_11ax(HE40) 5755



Power Spectral Density NVNT ANT1 802_11ax(HE40) 5795

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 150 of 311



Power Spectral Density NVNT ANT2 802_11ax(HE40) 5795



Power Spectral Density NVNT ANT1 802_11ac(VHT80) 5775

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 151 of 311



Power Spectral Density NVNT ANT2 802_11ac(VHT80) 5775



Power Spectral Density NVNT ANT1 802_11ax(HE80) 5775

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 152 of 311



Power Spectral Density_NVNT_ANT2_802_11ax(HE80)_5775



4. Transmitter Spurious Emissions

Note:

1. Testing is carried out with frequency rang 9kHz to the tenth harmonics. And it verified that the emssions above 18GHz are just floor-nises, no need to report it.
2. The highest emissions are the fundamental waves, the emissions more than 20dB below the limits not recorded.
3. All modes for required channel tested, only the worst-case reported.

4.1 Transmitter Spurious Emissions, Below 1GHz

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 154 of 311

U-NII-1 Band:



Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: 11a 5180MHz(Ant 1)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeScan TE25 W)

Radiated Emission Measurement

Test Date: 2024/10/31 10:37:48



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	125.0065	15.95	12.89	28.84	43.50	-14.66	QP	200	124	P	
2	148.4410	11.49	14.09	25.58	43.50	-17.92	QP	200	103	P	
3	195.8220	18.71	11.41	30.12	43.50	-13.38	QP	200	157	P	
4	219.0753	28.99	11.87	40.86	46.00	-5.14	QP	200	142	P	
5 *	286.9823	27.43	14.67	42.10	46.00	-3.90	QP	200	201	P	
6	614.2142	14.44	23.12	37.56	46.00	-8.44	QP	200	136	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

File: TX 30-1000M\Data :#2

Page: 1

Engineer Signature:

Appendix B
CN24K76Q 003

Prüfbericht - Produkte
Test Report - Products

Page 155 of 311



Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: 11a 5200MHz(Ant 1)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeScan TE25 W)

Radiated Emission Measurement

Test Date: 2024/10/31 10:41:58



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	125.0065	14.79	12.89	27.68	43.50	-15.82	QP	200	210	P	
2	197.8928	20.67	11.28	31.95	43.50	-11.55	QP	200	145	P	
3	219.0753	26.50	11.87	38.37	46.00	-7.63	QP	200	178	P	
4 *	289.0020	26.86	14.70	41.56	46.00	-4.44	QP	200	154	P	
5	351.7080	18.02	16.36	34.38	46.00	-11.62	QP	200	201	P	
6	584.7894	15.19	22.47	37.66	46.00	-8.34	QP	200	234	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit