

DATA SHEET

WIRELESS COMPONENTS
Ceramic Chip Antenna
ANT5320LL24R2400A

2.4 - 2.5 GHz
5320 Series



FEATURES

- Compact size
- Omni-directional radiation
- Tape & reel automatic mounting
- Reflow process compatible
- RoHS compliant

APPLICATIONS

- 2.4 GHz WiFi device
- Bluetooth gadget
- Zigbee device
- ISM band equipment

ORDERING INFORMATION

All part numbers are identified by the series, packing type, material, size, antenna type, working frequency and packing quantity.

PART NUMBER**ANT 5320 L L24 R 2400A**

(1) (2) (3) (4) (5) (6)

(1) PRODUCT

ANT = Antenna

(2) SIZE

5320= 5.3 × 2.0 mm

(3) ANTENNA TYPE

L,F,A = Chip Antenna

(4) SERIAL NO.

L24

(5) PACKING STYLE

R = Tape and Reel

(6) WORKING FREQUENCY

2400 = 2.4 GHz

PHYCOMP CTC

CAN4311753242452K

I2NC

431175324245

Manufature:Qingdao Thunderobot Technology Co.,Ltd.

Address :No. 1, Haier Road, Laoshan District, Qingdao

SPECIFICATION

Table I

DESCRIPTION	VALUE
Centre Frequency	2.45 GHz
Bandwidth	84 MHz (Typ.)
Polarization	Linear
Azimuth Beamwidth	Omni-directional
Peak Gain	2.78 dBi (Typ.)
Impedance	50 Ω
Operating Temperature	- 40~105 $^{\circ}\text{C}$
Maximum Power	1 W
Termination	Ni / Sn (Environmentally-Friendly Leadless)
Resistance to Soldering Heats	260 $^{\circ}\text{C}$, 10sec.

NOTE

I. The specification is defined on Yageo evaluation board

DIMENSIONS

Table 2 Machinical Dimension

	DIMENSION
L (mm)	5.30 $\pm$ 0.10
W (mm)	2.00 $\pm$ 0.10
T (mm)	1.20 $\pm$ 0.10


OUTLINES

Fig. I Antenna outlines

REFERENCE DESIGN OF EVALUATION BOARD




Fig. 2 Outlook and dimension of evaluation board




Fig. 3 Dimension of footprint




Fig. 4 Details of soldering pad


ELECTRICAL PERFORMANCES

Fig. 5 Return loss




Fig. 6 Radiation pattern