



# TEST REPORT

No.I17N00032-EMC

for

**Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd**

**Smart phone**

**Model Name: Coolpad 3632A**

**FCC ID: R38YL3632A**

with

**Hardware Version: P2**

**Software Version: 7.0.013.00.P0.161201.3632A.tmo**

**Issued Date: 2017-02-15**

**Test Laboratory:**

***FCC 2.948 Listed: No.342690***

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633, Fax:+86(0)10-62304633 Email:cttl@chinattl.com, website:[www.chinattl.com](http://www.chinattl.com)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I17N00032-EMC01	Rev.0	1st edition	2017-02-15

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE .....</b>	<b>4</b>
<b>2. CLIENT INFORMATION .....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION .....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION .....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT .....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE .....</b>	<b>6</b>
<b>3.4. EUT SET-UPS .....</b>	<b>7</b>
<b>4. REFERENCE DOCUMENTS .....</b>	<b>8</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING .....</b>	<b>8</b>
<b>5. LABORATORY ENVIRONMENT .....</b>	<b>9</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>7. TEST FACILITIES UTILIZED .....</b>	<b>11</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>12</b>

## 1. Test Laboratory

### 1.1. Testing Location

Address: TCL International E city No. 1001 Zhongshanyuan Road, Nanshan District, Shenzhen, Guangdong, China  
Postal Code: 518048  
Telephone: +86(755)33322000  
Fax: +86(755)33322001


### 1.2. Testing Environment

Normal Temperature: 15-35℃  
Relative Humidity: 20-75%

### 1.3. Project data

Testing Start Date: 2017-01-12  
Testing End Date: 2017-02-09

### 1.4. Signature



---

Du Zhaoxuan


(Prepared this test report)



---

Zhang Yunzhuan

(Reviewed this test report)



---

Cao Junfei

Director of the laboratory  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd  
Coolpad Information Harbor, High-tech Industrial Park (North),  
Address: Nanshan District, Shenzhen, P.R.C.

### **2.2. Manufacturer Information**

Company Name: Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd  
Coolpad Information Harbor, High-tech Industrial Park (North),  
Address: Nanshan District, Shenzhen, P.R.C.

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	Smart phone
Model Name	Coolpad 3632A
FCC ID	R38YL3632A

The Equipment Under Test (EUT) are a model of Smart phone with integrated antenna.

The EUT supports GPRS service and EGPRS service. It has Bluetooth and WLAN functions.

Remark: The above EUT's information is declared by manufacturer. Please refer to the specifications or user's manual for more detailed information.

#### **3.2. Internal Identification of EUT**

EUT ID*	SN or IMEI
EUT1	862006030009736

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE**

AE ID*	Description	SN
AE1	Battery	/
AE2	Travel charger	/
AE3	USB cable	/
AE1-1		
Model	CPLD-417	
Manufacturer	Tianjin Lishen Battery Joint-Stock Co.,Ltd.	
Capacitance	2450mAh	
Nominal Voltage	3.85V	
IMEI	CPLD41716424000001	
AE1-2		
Model	CPLD-417	
Manufacturer	Zhuhai COSLIGHT Battery CO., Ltd	
Capacitance	2450mAh	
Nominal Voltage	3.85V	
IMEI	CPLD41716424000001	



AE2

Model	CYSN05-050100
Manufacturer	JIANGSU CHENYANG ELECTRON CO.,LTD.
SN	CPSJD1646015841

AE3

Model	SYL-A126A
Manufacturer	Shenzhen Saibao Communication industrial Co.,Ltd

\*AE ID: is used to identify the test sample in the lab internally.

### 3.4. EUT set-ups

EUT set-up No.	Combination of EUT and AE	Remarks
Set.1	EUT1+ AE1-1 + AE2+ AE3	Charging mode
Set.2	EUT1+ AE1-1 + AE3	USB mode

#### 4. Reference Documents

##### 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15, Subpart B	Radio frequency devices	10-1-2015 Edition
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014



## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz-1MHz,>60dB; 1MHz-18000MHz,>90dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3 m distance, from 30 to 1000 MHz

**Shield room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz-1MHz,>60dB; 1MHz-10000MHz,>90dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω

**Fully-anechoic chamber** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	0.014MHz-1MHz,>60dB; 1MHz-18000MHz,>90dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3 m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

## 6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
P	Pass
NA	Not applicable
F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Radiated Emission	15.109(a)	A.1	P
2	Conducted Emission	15.107(a)	A.2	P

**7. Test Facilities Utilized**

NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CALDUE DATE	CAL PERIOD
1.	Test Receiver	ESCI	100701	R&S	2017.08.09	1 year
2.	Test Receiver	ESR7	101675	R&S	2017.07.21	1 year
3.	Spectrum Analyzer	FSP 40	100378	R&S	2017.12.15	1 year
4.	BiLog Antenna	VULB9163	9163 330	Schwarzbeck	2017.04.22	3 years
5.	LISN	ESH2-Z5	100196	R&S	2018.01.05	1 year
6.	Horn Antenna	3117	00066585	ETS-Lindgren	2019.03.05	3 years
7.	Universal Radio Communication Tester	E5515C	GB44051324	Agilent	2017.05.18	1 year
8.	PC	2OET-A00DC D	PF-OIYDAK	Lenovo	/	/
9.	Printer	P1008	VNF6C12491	HP	/	/
10.	Mouse	MO28UOL	44B39412	Lenovo	/	/
11.	Chamber	FACT5-2.0	4166	ETS-Lindgren	2018.05.13	3 years

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 Radiated Emission (§15.109(a))**

#### **Reference**

FCC: CFR Part 15.109(a)

#### **A.1.1 Method of measurement**

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

#### **A.1.2 EUT Operating Mode:**

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo 2OET-A00DCD, and the serial number of the PC is PF-OIYDAK. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

#### **A.1.3 Measurement Limit**

Limit from CFR Part 15.109(a)


Frequency range (MHz)	Field strength limit ( $\mu\text{V/m}$ )		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

\*Note: The original limit is defined at 10m test distance. This limit is calculated according to CISPR requirements.


#### **A.1.4 Test Condition**

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz (IF bandwidth)	5
Above 1000	1MHz/3MHz	15

**A.1.5 Test set-up:  
30MHz-1GHz**



**1GHz-18GHz**



### A.1.6 Measurement Results

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

$G_A$ : Antenna factor of receive antenna

$G_{\text{PL}}$ : Path Loss

$P_{\text{Mea}}$ : Measurement result on receiver.

Note: the result contains vertical part and Horizontal part

**RE Measurement uncertainty:** 30M-1GHz: 5.12dB (k=2);  
1GHz-18GHz: 4.48 dB (k=2)

#### Set.1 Charging mode / Peak detector

Frequency(MHz)	Result(dBuV/m)	Limit (dBμV/m)	Margin(dB)	Polar ity	$A_{\text{Rpl}}$ (dB)	$P_{\text{Mea}}$ (dBμV)
14147.500000	54.52	74.00	19.48	V	11.2	43.32
14586.500000	54.96	74.00	19.04	V	11.9	43.06
15840.000000	55.91	74.00	18.09	V	12.9	43.01
16204.000000	56.37	74.00	17.63	V	13.1	43.27
16805.000000	56.65	74.00	17.35	V	13.9	42.75
17430.000000	56.85	74.00	17.15	V	14.0	42.85

#### Set.1 Charging mode / Average detector

Frequency(MHz)	Result(dBuV/m)	Limit (dBμV/m)	Margin(dB)	Polar ity	$A_{\text{Rpl}}$ (dB)	$P_{\text{Mea}}$ (dBμV)
14523.000000	43.38	54.00	10.62	V	11.8	31.58
15144.500000	43.75	54.00	10.25	V	12.1	31.65
15775.000000	45.11	54.00	8.89	V	12.8	32.31
16222.500000	44.94	54.00	9.06	V	13.1	31.84
16788.000000	45.55	54.00	8.45	V	13.9	31.65
17373.000000	44.94	54.00	9.06	V	14.0	30.94

**Set.2 USB mode / Peak detector**

Frequency(MHz)	Result(dBuV/m)	Limit (dBμV/m)	Margin(dB)	Polar ity	A <sub>Rpl</sub> (dB)	P <sub>Mea</sub> (dBμV)
14129.000000	54.89	74.00	19.11	V	11.2	43.69
15161.500000	55.05	74.00	18.95	V	12.1	42.95
15690.500000	56.16	74.00	17.84	V	12.7	43.46
16322.500000	55.82	74.00	18.18	V	13.4	42.42
16811.000000	56.12	74.00	17.88	V	13.9	42.22
17440.500000	56.23	74.00	17.77	V	14.0	42.23

**Set.2 USB mode / Average detector**

Frequency(MHz)	Result(dBuV/m)	Limit (dBμV/m)	Margin(dB)	Polar ity	A <sub>Rpl</sub> (dB)	P <sub>Mea</sub> (dBμV)
14525.500000	43.06	54.00	10.94	V	11.8	31.26
15091.500000	43.29	54.00	10.71	V	12.1	31.19
15688.500000	44.32	54.00	9.68	V	12.7	31.62
16317.500000	44.15	54.00	9.85	V	13.3	30.85
16811.000000	44.77	54.00	9.23	V	13.9	30.87
17344.500000	44.09	54.00	9.91	V	14.0	30.09

Note: The measurement result of Set.1 and Set.2 showed here are worst cases of combinations of different batteries and USB cables.

Charging mode: Set 1




Figure A.1 Radiated Emission from 30MHz to 1GHz




Figure A.2 Radiated Emission from 1GHz to 18GHz



USB mode: Set 2




Figure A.3 Radiated Emission from 30MHz to 1GHz




Figure A.4 Radiated Emission from 1GHz to 18GHz

**A.2 Conducted Emission (§15.107(a))****Reference**

FCC: CFR Part 15.107(a)

**A.2.1 Method of measurement**

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 - 2014, section 7.3.


**A.2.2 EUT Operating Mode:**

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is Lenovo 2OET-A00DCD, and the serial number of the PC is PF-OIYDAK. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

**A.2.3 Measurement Limit**

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency		

#### A.2.4 Test set-up:



#### A.2.5 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60
240	60

RBW	Sweep Time(s)
9kHz	1

**CE Measurement uncertainty:** 3.06 dB (k=2)

## A.2.6 Measurement Results

Charging mode:Set.1

Voltage:120V




Figure A.5 Conducted Emission

### Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.186000	45.9	GND	N	9.6	18.3	64.2
0.230000	42.4	GND	N	9.6	20.0	62.4
0.278000	38.3	GND	N	9.6	22.6	60.9
0.322000	36.4	GND	N	9.6	23.2	59.7
2.350000	33.7	GND	N	9.6	22.3	56.0
4.814000	28.4	GND	N	9.6	27.6	56.0

### Final Measurement Detector 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.186000	34.0	GND	N	9.6	20.2	54.2
0.230000	31.6	GND	N	9.6	20.8	52.4
0.278000	27.9	GND	N	9.6	22.9	50.9
0.322000	25.2	GND	N	9.6	24.4	49.7
0.506000	22.6	GND	N	9.7	23.4	46.0
2.350000	22.7	GND	N	9.6	23.3	46.0

USB mode:Set.2

Voltage:120V

ESH2-Z5 Scan-FCC




Figure A.6 Conducted Emission

**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	50.2	GND	N	9.6	15.4	65.6
16.834000	41.2	GND	N	9.9	18.8	60.0
19.266000	42.4	GND	N	10.0	17.6	60.0
19.390000	42.7	GND	N	10.0	17.3	60.0
19.510000	43.0	GND	N	10.0	17.0	60.0
19.794000	43.2	GND	N	10.0	16.8	60.0

**Final Measurement Detector 2**

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
19.350000	34.9	GND	N	10.0	15.1	50.0
19.526000	35.8	GND	N	10.0	14.2	50.0
19.618000	35.2	GND	N	10.0	14.8	50.0
19.710000	35.3	GND	N	10.0	14.7	50.0
19.794000	36.1	GND	N	10.0	13.9	50.0
19.886000	35.1	GND	N	10.0	14.9	50.0

Charging mode:Set.1

Voltage:240V

ESH2-Z5 Scan-FCC




Figure A.7 Conducted Emission

**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.186000	42.2	GND	N	9.6	22.0	64.2
2.338000	33.7	GND	N	9.6	22.3	56.0
4.430000	30.0	GND	N	9.6	26.0	56.0
4.542000	32.1	GND	N	9.6	23.9	56.0
4.606000	30.6	GND	N	9.6	25.4	56.0
4.630000	30.3	GND	N	9.6	25.7	56.0


**Final Measurement Detector 2**

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.186000	30.6	GND	N	9.6	23.6	54.2
0.230000	28.7	GND	N	9.6	23.7	52.4
0.414000	22.8	GND	N	9.7	24.7	47.6
0.506000	23.1	GND	N	9.7	22.9	46.0
0.598000	23.0	GND	N	9.6	23.0	46.0
2.322000	24.4	GND	N	9.6	21.6	46.0

USB mode:Set.2

Voltage:240V

ESH2-Z5 Scan-FCC



**Figure A.8 Conducted Emission**

**Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	50.2	GND	N	9.6	15.4	65.6
16.834000	41.2	GND	N	9.9	18.8	60.0
19.266000	42.4	GND	N	10.0	17.6	60.0
19.390000	42.7	GND	N	10.0	17.3	60.0
19.510000	43.0	GND	N	10.0	17.0	60.0
19.794000	43.2	GND	N	10.0	16.8	60.0

**Final Measurement Detector 2**

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
19.350000	34.9	GND	N	10.0	15.1	50.0
19.526000	35.8	GND	N	10.0	14.2	50.0
19.618000	35.2	GND	N	10.0	14.8	50.0
19.710000	35.3	GND	N	10.0	14.7	50.0
19.794000	36.1	GND	N	10.0	13.9	50.0
19.886000	35.1	GND	N	10.0	14.9	50.0

\*\*\*END OF REPORT\*\*\*