

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

11.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


12.Radiated Emission

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/10
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/04/01
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/04/01
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/04/01
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/17
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2024/07/11
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/23
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/23
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2024/07/14
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/23
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/04/01
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/04/01
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/04/01
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/04/01
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/04/01
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/25

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above	1000	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
POE Power Supply	DONGGUAN SHILONG FUHUA ELECTRONIC CO.,LTD.	POE35-54A	INPUT:100-240V~ 50/60Hz OUTPUT:DC 54.0V/0.65A	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT through three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

12.6. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limits and RSS-Gen section 8.9 limits.

Note 1: According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

Note 2: 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is 802.11 ax HE 20 mode)

Note 3: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in 802.11ax HE 20, Tx 2462 MHz mode.

Note 4: For emissions above 1 GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit, only recorded the worst case in this report.

Note5: 2.4G +5G+6G WIFI is the worst simultaneous case and was recorded.

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

TX mode 2.4G WIFI

Power Supply:

AC 120V/60Hz
(Power By Adapter)

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032709-1E\FCC BELOW 1G\20240408-090220_H

Memo:

Sample Number:S24032709-002 Power Setting:16 (Adapter power supply)



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	53.875	33.6	12.46	4.74	-30.67	20.13	40.00	19.87	QP	Horizontal
2	72.579	33.55	9.37	4.80	-30.55	17.17	40.00	22.83	QP	Horizontal
3	119.991	31.47	10.00	5.17	-30.84	15.80	43.50	27.70	QP	Horizontal
4	189.137	38.95	9.18	5.64	-30.63	23.14	43.50	20.36	QP	Horizontal
5	270.067	38.18	12.50	6.02	-30.39	26.31	46.00	19.69	QP	Horizontal
6	354.754	36.57	15.45	6.45	-30.19	28.28	46.00	17.72	QP	Horizontal

Note:

- Result Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

TX mode 2.4G WIFI

Power Supply:

AC 120V/60Hz
(Power By Adapter)

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032709-1E\FCC BELOW 1G\20240408-090304_V

Memo:

Sample Number:S24032709-002 Power Setting:16



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	55.253	42.73	12.60	4.75	-30.66	29.42	40.00	10.58	QP	Vertical
2	63.126	43.97	12.39	4.77	-30.61	30.52	40.00	9.48	QP	Vertical
3	154.878	39.86	9.09	5.36	-30.74	23.57	43.50	19.93	QP	Vertical
4	354.008	37.04	15.30	6.45	-30.19	28.60	46.00	17.40	QP	Vertical
5	479.588	33.67	16.48	6.88	-29.94	27.09	46.00	18.91	QP	Vertical
6	995.802	27.05	22.44	8.68	-28.14	30.03	54.00	23.97	QP	Vertical

Note:

- Result Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-14

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

TX mode 2.4G WIFI

Power Supply:

AC 120V/60Hz
(Power By POE)

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24032709-1E\FCC BELOW 1G\20240614-150244_H

Memo:

Sample Number:S24032709-002 Power Setting:16 (POE power supply)



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.619	3.83	11.30	3.78	0.00	18.91	40.00	21.09	QP	Horizontal
2	59.212	5.07	12.41	3.95	0.00	21.43	40.00	18.57	QP	Horizontal
3	72.433	11.39	9.43	4.04	0.00	24.86	40.00	15.14	QP	Horizontal
4	258.501	11.52	11.59	5.03	0.00	28.14	46.00	17.86	QP	Horizontal
5	513.804	4.12	16.31	6.05	0.00	26.48	46.00	19.52	QP	Horizontal
6	900.195	1.9	21.90	7.20	0.00	31.00	46.00	15.00	QP	Horizontal

Note:


1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-06-14
Tested By: Junchang Du
EUT: Wireless Access Point
Model Number: RG-RAP73Pro
Test Mode: TX mode 2.4G WIFI
Power Supply: AC 120V/60Hz
(Power By POE)
Condition: Temp:23.4°C;Humi:62.3%
Test Site: DDT 3# Chamber
File Path: d:\ts\2024 report data\Q24032709-1E\FCC BELOW 1G\20240614-150333_V
Memo: Sample Number:S24032709-002 Power Setting:16 (POE power supply)



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.907	14.86	10.39	3.77	0.00	29.02	40.00	10.98	QP	Vertical
2	62.299	15.19	12.68	3.97	0.00	31.84	40.00	8.16	QP	Vertical
3	72.179	17.65	9.53	4.04	0.00	31.22	40.00	8.78	QP	Vertical
4	84.955	17.24	9.17	4.12	0.00	30.53	40.00	9.47	QP	Vertical
5	512.007	9.79	16.02	6.04	0.00	31.85	46.00	14.15	QP	Vertical
6	948.786	3.43	22.41	7.33	0.00	33.17	46.00	12.83	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2412MHz

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\9

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2261.400	46.13	27.19	5.95	-37.75	41.52	74.00	32.48	PK	Horizontal
2	3833.900	46.83	30.84	5.81	-40.35	43.13	74.00	30.87	PK	Horizontal
3	4826.700	54.34	33.19	7.52	-40.14	54.91	74.00	19.09	PK	Horizontal
4	7388.600	43.10	36.72	7.64	-41.67	45.79	74.00	28.21	PK	Horizontal
5	11844.300	42.74	38.90	10.40	-39.49	52.55	74.00	21.45	PK	Horizontal
6	15506.100	38.30	38.79	13.64	-39.06	51.67	74.00	22.33	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4824.260	49.79	33.19	7.52	-40.14	50.36	54.0	3.64	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2412MHz

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\10

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2271.600	46.54	27.08	5.95	-37.78	41.79	74.00	32.21	PK	Vertical
2	3900.200	45.98	31.20	5.83	-40.39	42.62	74.00	31.38	PK	Vertical
3	4826.700	57.83	33.19	7.52	-40.14	58.40	74.00	15.60	PK	Vertical
4	7526.300	43.57	36.45	7.65	-42.02	45.65	74.00	28.35	PK	Vertical
5	11342.800	42.35	39.24	9.96	-39.25	52.30	74.00	21.70	PK	Vertical
6	15812.100	38.69	38.28	15.03	-39.25	52.75	74.00	21.25	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4823.710	48.88	33.19	7.52	-40.14	49.45	54.0	4.55	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2437MHz

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\11

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2217.200	45.85	27.63	5.97	-37.62	41.83	74.00	32.17	PK	Horizontal
2	3890.000	46.97	31.14	5.83	-40.38	43.56	74.00	30.44	PK	Horizontal
3	4874.300	50.54	33.41	7.62	-40.13	51.44	74.00	22.56	PK	Horizontal
4	7432.800	43.98	36.63	7.64	-41.78	46.47	74.00	27.53	PK	Horizontal
5	11708.300	42.58	38.99	10.28	-39.42	52.43	74.00	21.57	PK	Horizontal
6	15706.700	38.54	38.49	14.55	-39.18	52.40	74.00	21.60	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4874.300	45.23	33.41	7.62	-40.13	46.13	54.0	7.87	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2437MHz

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\12

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2269.900	46.12	27.10	5.95	-37.77	41.40	74.00	32.60	PK	Vertical
2	3810.100	47.04	30.74	5.81	-40.33	43.26	74.00	30.74	PK	Vertical
3	4877.700	52.19	33.36	7.62	-40.13	53.04	74.00	20.96	PK	Vertical
4	7346.100	43.36	36.81	7.63	-41.57	46.23	74.00	27.77	PK	Vertical
5	11546.800	42.02	39.11	10.14	-39.35	51.92	74.00	22.08	PK	Vertical
6	16056.900	38.33	37.94	15.66	-39.41	52.52	74.00	21.48	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4877.700	47.86	33.36	7.62	-40.13	48.71	54.0	5.29	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2462MHz

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\13

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2266.500	46.11	27.14	5.95	-37.76	41.44	74.00	32.56	PK	Horizontal
2	3745.500	47.71	30.49	5.79	-40.29	43.70	74.00	30.30	PK	Horizontal
3	4925.300	51.31	33.05	7.72	-40.11	51.97	74.00	22.03	PK	Horizontal
4	7307.000	43.10	36.89	7.63	-41.47	46.15	74.00	27.85	PK	Horizontal
5	11711.700	42.10	38.99	10.28	-39.42	51.95	74.00	22.05	PK	Horizontal
6	15468.700	38.84	38.86	13.47	-39.04	52.13	74.00	21.87	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4924.805	45.43	33.05	7.72	-40.11	46.09	54.0	7.91	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2462MHz

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\14

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2222.300	45.98	27.58	5.97	-37.64	41.89	74.00	32.11	PK	Vertical
2	3743.800	46.51	30.49	5.79	-40.29	42.50	74.00	31.50	PK	Vertical
3	4923.600	52.81	33.05	7.72	-40.11	53.47	74.00	20.53	PK	Vertical
4	7385.200	43.34	36.73	7.64	-41.66	46.05	74.00	27.95	PK	Vertical
5	11868.100	42.13	38.90	10.42	-39.50	51.95	74.00	22.05	PK	Vertical
6	15645.500	39.10	38.55	14.27	-39.15	52.77	74.00	21.23	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4923.600	48.36	33.05	7.72	-40.11	49.02	54.0	4.98	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13.Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/23
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2024/07/11
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/23
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/10
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/04/01
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/04/01
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2024/07/14
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/04/01
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/04/01
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/04/01
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/04/01
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/23
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/25
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/04/01
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/17
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/04/01

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2412MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\17

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2385.252	19.56	27.24	3.86	0.00	50.66	74.00	23.34	PK	Horizontal
2	2390.000	16.76	27.26	3.87	0.00	47.89	74.00	26.11	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2412MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\18

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2380.548	20.27	27.22	3.86	0.00	51.35	74.00	22.65	PK	Vertical
2	2390.000	18.81	27.26	3.87	0.00	49.94	74.00	24.06	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2412MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\15

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2381.424	18.87	27.23	3.86	0.00	49.96	74.00	24.04	PK	Horizontal
2	2390.000	16.07	27.26	3.87	0.00	47.20	74.00	26.80	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-03

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2412MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\16

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2389.212	21.75	27.26	3.87	0.00	52.88	74.00	21.12	PK	Vertical
2	2390.000	19.19	27.26	3.87	0.00	50.32	74.00	23.68	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2462MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\47

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	18.59	27.53	3.94	0.00	50.06	74.00	23.94	PK	Horizontal
2	2484.402	20.21	27.54	3.94	0.00	51.69	74.00	22.31	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2462MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\48

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	19.90	27.53	3.94	0.00	51.37	74.00	22.63	PK	Vertical
2	2488.500	21.74	27.55	3.94	0.00	53.23	74.00	20.77	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2462MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\49

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2483.500	17.56	27.53	3.94	0.00	49.03	74.00	24.97	PK	Horizontal
2	2485.266	20.45	27.54	3.94	0.00	51.93	74.00	22.07	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11B TX 2462MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\50

Memo:

Sample Number:S24032709-002 Power Setting:17

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	22.65	27.53	3.94	0.00	54.12	74.00	19.88	PK	Vertical
2	2484.270	23.93	27.54	3.94	0.00	55.41	74.00	18.59	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	15.36	27.53	3.94	0.00	46.83	54.0	7.17	AV	Vertical
2	2484.270	16.42	27.54	3.94	0.00	47.90	54.0	6.10	AV	Vertical

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2412MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\55

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2368.738	19.70	27.17	3.85	0.00	50.72	74.00	23.28	PK	Horizontal
2	2390.000	17.43	27.26	3.87	0.00	48.56	74.00	25.44	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2412MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\56

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2372.813	19.50	27.19	3.85	0.00	50.54	74.00	23.46	PK	Vertical
2	2390.000	17.01	27.26	3.87	0.00	48.14	74.00	25.86	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2412MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\57

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2371.200	19.63	27.18	3.85	0.00	50.66	74.00	23.34	PK	Horizontal
2	2390.000	16.17	27.26	3.87	0.00	47.30	74.00	26.70	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2412MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\58

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2369.275	19.70	27.18	3.85	0.00	50.73	74.00	23.27	PK	Vertical
2	2390.000	19.55	27.26	3.87	0.00	50.68	74.00	23.32	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2462MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\53

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	17.33	27.53	3.94	0.00	48.80	74.00	25.20	PK	Horizontal
2	2483.951	20.10	27.54	3.94	0.00	51.58	74.00	22.42	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2462MHz ANT1

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\54

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	18.32	27.53	3.94	0.00	49.79	74.00	24.21	PK	Vertical
2	2485.178	20.60	27.54	3.94	0.00	52.08	74.00	21.92	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2462MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\51

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	18.17	27.53	3.94	0.00	49.64	74.00	24.36	PK	Horizontal
2	2483.973	23.55	27.54	3.94	0.00	55.03	74.00	18.97	PK	Horizontal

Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.973	16.39	27.54	3.94	0.00	47.87	54.0	6.13	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-08

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11G TX 2462MHz ANT2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\52

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	26.73	27.53	3.94	0.00	58.20	74.00	15.80	PK	Vertical
2	2483.709	30.75	27.53	3.94	0.00	62.22	74.00	11.78	PK	Vertical

Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	19.36	27.53	3.94	0.00	50.83	54.0	3.17	AV	Vertical
2	2483.709	18.64	27.53	3.94	0.00	50.11	54.0	3.89	AV	Vertical

- Note:
- Level = Reading + Cable loss + Antenna Factor + AMP
 - If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 - Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11N20 TX 2412MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\21

Memo:

Sample Number:S24032709-002 Power Setting:15

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2380.750	19.98	27.22	3.86	0.00	51.06	74.00	22.94	PK	Horizontal
2	2390.000	20.71	27.26	3.87	0.00	51.84	74.00	22.16	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11N20 TX 2412MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\22

Memo:

Sample Number:S24032709-002 Power Setting:15

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2389.000	23.09	27.26	3.87	0.00	54.22	74.00	19.78	PK	Vertical
2	2390.000	22.73	27.26	3.87	0.00	53.86	74.00	20.14	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11N20 TX 2462MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\19

Memo:

Sample Number:S24032709-002 Power Setting:15

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	19.22	27.53	3.94	0.00	50.69	74.00	23.31	PK	Horizontal
2	2483.621	23.59	27.53	3.94	0.00	55.06	74.00	18.94	PK	Horizontal

Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.621	14.68	27.53	3.94	0.00	46.15	54.0	7.85	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11N20 TX 2462MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\20

Memo:

Sample Number:S24032709-002 Power Setting:15

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	30.92	27.53	3.94	0.00	62.39	74.00	11.61	PK	Vertical
2	2483.638	31.46	27.53	3.94	0.00	62.93	74.00	11.07	PK	Vertical

Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	18.86	27.53	3.94	0.00	50.33	54.0	3.67	AV	Vertical
2	2483.638	19.03	27.53	3.94	0.00	50.50	54.0	3.50	AV	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AC20 TX 2412MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\25

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2380.000	20.14	27.22	3.86	0.00	51.22	74.00	22.78	PK	Horizontal
2	2390.000	17.39	27.26	3.87	0.00	48.52	74.00	25.48	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AC20 TX 2412MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\26

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2382.675	19.25	27.23	3.86	0.00	50.34	74.00	23.66	PK	Vertical
2	2390.000	20.61	27.26	3.87	0.00	51.74	74.00	22.26	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AC20 TX 2462MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\23

Memo:

Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	19.55	27.53	3.94	0.00	51.02	74.00	22.98	PK	Horizontal
2	2483.715	22.66	27.53	3.94	0.00	54.13	74.00	19.87	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2024-04-07

Tested By:Junchang Du

EUT:Wireless Access Point

Model Number:RG-RAP73Pro

Test Mode:11AC20 TX 2462MHz ANT1+2

Power Supply:AC 120V/60Hz


Condition:Temp:23.4°C;Humi:62.3%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\24

Memo:Sample Number:S24032709-002 Power Setting:14

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	23.73	27.53	3.94	0.00	55.20	74.00	18.80	PK	Vertical
2	2484.584	27.89	27.54	3.94	0.00	59.37	74.00	14.63	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	15.36	27.53	3.94	0.00	46.83	54.0	7.17	AV	Vertical
2	2484.584	16.12	27.54	3.94	0.00	47.60	54.0	6.40	AV	Vertical

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2412MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\29

Memo:

Sample Number:S24032709-002 Power Setting:16

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2388.688	19.45	27.25	3.87	0.00	50.57	74.00	23.43	PK	Horizontal
2	2390.000	17.49	27.26	3.87	0.00	48.62	74.00	25.38	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2412MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\30

Memo:

Sample Number:S24032709-002 Power Setting:16

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.900	25.29	27.26	3.87	0.00	56.42	74.00	17.58	PK	Vertical
2	2390.000	20.82	27.26	3.87	0.00	51.95	74.00	22.05	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.900	15.23	27.26	3.87	0.00	46.36	54.0	7.64	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2462MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\27

Memo:

Sample Number:S24032709-002 Power Setting:16

Test Graph



Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	24.17	27.53	3.94	0.00	55.64	74.00	18.36	PK	Horizontal
2	2484.798	22.60	27.54	3.94	0.00	54.08	74.00	19.92	PK	Horizontal

Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	15.56	27.53	3.94	0.00	47.03	54.0	6.97	AV	Horizontal
2	2484.798	15.20	27.54	3.94	0.00	46.68	54.0	7.32	AV	Horizontal

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-04-07

Tested By:

Junchang Du

EUT:

Wireless Access Point

Model Number:

RG-RAP73Pro

Test Mode:

11AX20 TX 2462MHz ANT1+2

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.4°C;Humi:62.3%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24032709-1E\FCC ABOVE 1G\28

Memo:

Sample Number:S24032709-002 Power Setting:16

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	28.37	27.53	3.94	0.00	59.84	74.00	14.16	PK	Vertical
2	2483.742	30.99	27.53	3.94	0.00	62.46	74.00	11.54	PK	Vertical

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	18.66	27.53	3.94	0.00	50.13	54.0	3.87	AV	Vertical
2	2483.718	19.36	27.53	3.94	0.00	50.83	54.0	3.17	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.