

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM161201046504

Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1612010465CR

Applicant: ACOUSTMAX INTERNATIONAL CO., LTD. **Manufacturer:** ACOUSTMAX INTERNATIONAL CO., LTD.

Factory Arts Electronics Co., Ltd.

Product Name: ROCKIN' ROLLER 3 SPEAKER

Model No.(EUT): ROCKIN ROLLER 3(RR3)

Add Model No.: RR3-1, RR3 PRO, RR3 mini, RR3

Trade Mark: Monster

FCC ID: 2AAINYS1349

Standards: 47 CFR Part 1.1307 (2015)

47 CFR Part 1.1310 (2015)

Date of Receipt: 2016-12-06

Date of Test: 2016-12-12 to 2016-12-24

Date of Issue: 2016-12-28

Test Result : PASS*

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM161201046504

Page: 2 of 8

2 Version

Revision Record					
Version	Chapter	Date	Modifier	Remark	
00		2016-12-28		Original	

Authorized for issue by:		
Tested By	Brir Chen	2016-12-24
	(Bill Chen) /Project Engineer	Date
Checked By	Eric Fu	2016-12-28
	(Eric Fu) /Reviewer	Date



Report No.: SZEM161201046504

Page: 3 of 8

3 Contents

		Pa	ge
1	C	COVER PAGE	1
2	٧	/ERSION	2
3	С	CONTENTS	3
4	G	GENERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2		4
	4.3	TEST LOCATION	5
	4.4	TEST FACILITY	5
	4.5		6
	4.6	ABNORMALITIES FROM STANDARD CONDITIONS	6
	4.7	OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5	R	RF EXPOSURE EVALUATION	7
	5.1	RF Exposure Compliance Requirement	7
		5.1.1 Limits	
	5	5.1.2 Test Procedure	7
	4.1.3	3 EUT RF Exposure Evaluation	8



Report No.: SZEM161201046504

Page: 4 of 8

4 General Information

4.1 Client Information

Applicant:	ACOUSTMAX INTERNATIONAL CO., LTD.		
Address of Applicant:	Unit D 16/F Cheuk Nang Plaza 250 Hennessy Road Wanchai HongKong		
Manufacturer:	ACOUSTMAX INTERNATIONAL CO., LTD.		
Address of Manufacturer:	Unit D 16/F Cheuk Nang Plaza 250 Hennessy Road Wanchai HongKong		
Factory:	Arts Electronics Co., Ltd.		
Address of Factory:	NO. 1, SHANGXING LU, SHANGJIAO COMMUNITY, CHANGAN TOWN, DONGGUAN CITY, GUANGDONG PROVINCE, CHINA		

4.2 General Description of EUT

Product Name:	ROCKIN' ROLLER 3 SPEAKER		
Model No.:	ROCKIN ROLLER 3(RR3)		
Trade Mark:	Monster		
Operation Frequency:	2402MHz~2480MHz		
Bluetooth Version:	V4.2 Classic mode		
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)		
Modulation Type:	GFSK, π/4DQPSK, 8DPSK		
Number of Channel:	79		
Hopping Channel Type:	Adaptive Frequency Hopping systems		
Sample Type:	Fixed production		
Antenna Type:	Integral		
Antenna Gain:	0dBi		
Power Supply	Input: AC 120V 60Hz		
	Internal rechargeable battery: DC 12V 9Ah		
Test Voltage:	AC 120V 60Hz		
Cable:	AUX in cable: 190cm unshielded		
	AC cable: 200cm unshielded		
	Microphone cable: 220cm unshielded		

Remark:

Model No.: ROCKIN ROLLER 3(RR3), RR3-1, RR3 PRO, RR3 mini, RR3

Only the model ROCKIN ROLLER 3(RR3) was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models, only different on model No..



Report No.: SZEM161201046504

Page: 5 of 8

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC

Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Report No.: SZEM161201046504

Page: 6 of 8

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None

4.7 Other Information Requested by the Customer

None.



Report No.: SZEM161201046504

Page: 7 of 8

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposures						
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89/f 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34 1.34–30 30–300 300–1500 1500–100,000	614 824/f 27.5	1.63 2.19/f 0.073	*(100) *(180/f²) 0.2 f/1500 1.0	30 30 30 30 30		

F= Frequency in MHz

Friis Formula

Friis transmission formula: Pd = (Pout*G)/(4*Pi*R2)

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



Report No.: SZEM161201046504

Page: 8 of 8

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency	Max Conducted	Output Power	Power Density	Limit	Result
	(MHz)	Peak Output	to Antenna	at R = 20 cm		
		Power (dBm)	(mW)	(mW/cm²)		
Highest	2480	-2.35	0.58	0.0001	1.0	PASS

Note: Refer to report No. SZEM161201046503 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.