Report on the Incident Power Density Testing of the Primescan 2 Cart



Sirona Dental Systems GmbH Model: Primescan 2 Cart

In accordance with FCC 47 CFR 2.1093 (2023)

Prepared for: Sirona Dental Systems GmbH Fabrikstraße 31 64625 Bensheim Germany

FCC ID: 2AD7W-6800457

COMMERCIAL-IN-CONFIDENCE

Document Number: 75962759-01 Issue:01

SIGNATURE Image: Signature NAME JOB TITLE RESPONSIBLE FOR ISSUE DATE Jon Kenny Technical Director Signatories in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

FCC Accreditation

553713/UK2026 Concorde Park, Fareham Test Laboratory

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR 2.1093 (2023) for the tests detailed in section 1.



DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2025 TÜV SÜD. This report relates only to the actual item/items tested.

ACCREDITATION

Results of tests covered by our Flexible UKAS Accreditation Schedule are marked FS (Flexible Scope) Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited) Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

TÜV SÜD

is a trading name of TUV SUD Ltd Registered in Scotland at East Kilbride, Glasgow G75 0QF, United Kingdom Registered number: SC215164 TUV SUD Ltd is a TÜV SÜD Group Company Phone: +44 (0) 1489 558100 Fax: +44 (0) 1489 558101 www.tuv-sud.co.uk TÜV SÜD Octagon House Concorde Way Fareham Hampshire PO15 5RL United Kingdom







CONTENTS

Section

Page No

1	REPORT SUMMARY	3
1.1 1.2 1.3 1.4 1.5 1.6 1.7	Report Modification Record Introduction Identification of the EUT Brief Summary of Results Test Results Summary Power Tables (Tune Up Values) Conducted Power Measurements	4 5 6 7 8 . 13 . 14
2	TEST DETAILS	. 15
2.1	DASY6 Measurement System	. 16
3	TEST EQUIPMENT USED	. 22
3.1 3.2 3.3 3.4 3.5	Test Equipment Used Test Software Test Verification Test Conditions Measurement Uncertainty	. 23 . 24 . 25 . 26 . 27
4	ACCREDITATION, DISCLAIMERS AND COPYRIGHT	. 30
4.1	Accreditation, Disclaimers and Copyright	. 31
ANNEX ANNEX	 A Probe Calibration Reports B Dipole Calibration Reports C SAR Plots D Photographs of DUT 	A.2 B.2 C.2 D.2



SECTION 1

REPORT SUMMARY

Incident Power Density Testing of the Primescan 2 Cart



1.1 REPORT MODIFICATION RECORD

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	12-Mar-2025



1.2 INTRODUCTION

The information contained in this report is intended to show verification of the incident power density (iPD) testing of the Primescan 2 Cart to the requirements of FCC 47 CFR 2.1093 (2023).

Objective	To determine the Equipment Under Test's (EUT) compliance with the requirements specified within FCC 47 CFR 2.1093 (2023).
Applicant	Sirona Dental Systems GmbH
EUT/Sample Identification	Refer to section 1.3
Test Specification/Issue/Date	FCC 47 CFR 2.1093 (2023)
Start of Test	20-February-2025
Finish of Test	24-February-2025
Related Document(s)	FCC 47 CFR 1.1310
	ICNIRP 2020
	IEC/IEEE 62209-1528-2020
	IEC/IEEE 63195-1:2022
	KDB 447498 - D01 v06
	SPEAG, DASY8 Application Note: SAR, APD & PD at
	6 - 10 GHz (Version 6.0), August 2022
	October 2020 TCBC Workshop Notes
Name of Engineer(s)	Umesh Kabbur



1.3 IDENTIFICATION OF THE EUT

The table below details identification of the EUT(s) that have been used to carry out the testing within this report.

Serial Number Model: Primescan 2 Cart: TES Monitor 100420 Model: Primescan 2 Cart: Champ Vision Monitor 100422



1.4 BRIEF SUMMARY OF RESULTS

The measurements shown in this report were made to the requirements of FCC 47 CFR 2.1093 (2023).

1.4.1 Summary of Maximum Values

The maximum iPD 4cm² found during this Assessment:

Max iPD 4cm ² (W/m ²)	7.02 (Measured)			
The maximum iPD averaged over 4cm ² measured for all the tests performed did not exceed the standalone limits for FC General Population/Uncontrolled Exposure of 10.00 W/m ² in accordance with FCC 47 CFR 1.1310.				



1.5 TEST RESULTS SUMMARY

1.5.1 Results Summary Tables

WLAN 6 GHz - 802.11ax - HE160 - MCS0 - TES Display (SISO) Incident Power Density (iPD) - 6 GHz

Test Position	Channel Number	Frequency (MHz)	Measured iPD 4cm ² (W/m ²)	Exposure Ratio	Scan Figure Number	
Top Side (Antenna A)	15	6025	7.02	0.702	C.1	
Left Side (Antenna B) 15 6025 2.35 0.235 -						
iPD limit for General Population/Uncontrolled Exposure of 10.00 W/m ² in accordance with FCC 47 CFR 1.1310.						

Table 4

WLAN 6 GHz - 802.11ax - HE160 - MCS0 - Champ Vision Display (SISO) Incident Power Density (iPD) - 6 GHz

Test Position	Channel Number	Frequency (MHz)	Measured iPD 4cm ² (W/m ²)	Exposure Ratio	Scan Figure Number	
Top Side (Antenna A)	15	6025	5.56	0.556	C.2	
Left Side (Antenna B) 15 6025 1.94 0.194 -						
iPD limit for General Population/Uncontrolled Exposure of 10.00 W/m ² in accordance with FCC 47 CFR 1.1310.						



1.5.2 Technical Description

The equipment under test (EUT) was the computer and display section of a dental scanner system.

1.5.3 Interim Procedures for FCC Radio Frequency Exposure Evaluations

The interim procedure for FCC Radio Frequency (RF) exposure evaluations of U-NII 6-7 GHz band portable devices have been made available during the TCB workshop in October 2020. The procedure is summarized below:

• Evaluate SAR / APD with DASY Module SAR V16.0 or higher. The configurations to be tested are defined in the relevant Knowledge Database (KDB). The peak spatial averaged SAR (psSAR) and the peak spatial averaged absorbed Power Density (psAPD) are reported.

• For the configuration with the highest SAR / APD, evaluate the PD with DASY Module mmWave V3.0 or higher.



1.5.4 Test Configuration and Modes of Operation

The testing that was carried out was required to complete the certification testing of the device documented in this test report. This testing formed the incident power density measurement part of the requirements of FCC 47 CFR 2.1093.

All the other test requirements that consisted of SAR and APD testing were performed by the primary laboratory that subcontracted the iPD testing to TÜV SÜD.

The primary test laboratory is responsible for and derived the test set up.

The device under test (EUT) incorporates an Intel chipset Wi-Fi solution. The Intel test mode support software does not run natively in the Linux environment which is utilised in the EUT. Due to this limitation the customer advised a test to set up that used a small form factor PC with the same chipset solution as the signal source. This signal source was then delivered to the transmit antennas of the EUT via SMA connections and additional RF cabling routed inside the EUT. No internal functionality of the EUT was utilised.

The test software was then run on the external PC in a windows environment.

Supported technologies are WLAN 6GHz.

For each device the top and left faces were assessed for iPD in the channels advised by the primary test lab.

For each scan, the external PC was configured into a continuous transmission test mode at an operational power output defined by the customer and advised by the primary lab. The channel that was defined by the primary test laboratory was channel 15.

Conducted power measurements were provided by the customer and verified with a power meter.

Included in this report are descriptions of the test method; the equipment used and an analysis of the test uncertainties applicable and diagrams indicating the locations of the maximum iPD for each relevant test positions.



1.5.5 Antenna Location Diagram



Figure 1



1.5.6 Deviations from Standard

None.



1.6 POWER TABLES (TUNE UP VALUES)

Note: All values in dBm

Tune up values were provided by the primary laboratory:

6 GHz WLAN - 160 MHz - SISO Antenna A & B

Channel	Frequency (MHz)	802.11ax HE160 (SISO) (dBm)	
15	6025	12.00	



1.7 CONDUCTED POWER MEASUREMENTS

1.7.1 Method

Conducted Power Measurements were made using a power meter. The output power was varied using the intel chipset support software on the external support PC, until the required 12dBm values were achieved.

1.7.2 Measured Results

WLAN 6 GHz SISO

Technology	Channel	Duty Cycle (%)	Rate	Frequency (MHz)	Measured Power (dBm)
802.11ax HE160 (Antenna A)	15	100	MSC0 (HE0)	6025	11.99
802.11ax HE160 (Antenna B)	15	100	MSC0 (HE0)	6025	12.00



SECTION 2

TEST DETAILS

Incident Power Density Testing of the Primescan 2 CART



2.1 DASY6 MEASUREMENT SYSTEM

2.1.1 System Description

The DASY6 system for performing compliance tests consists of the following items:



Figure 2 - System Description Diagram

A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).

An isotropic field probe optimized and calibrated for the targeted measurement.

Data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.

The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.

The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.

A computer running the DASY6 software to display and interact with the robot and information.

There is a remote control and a teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.

The phantom, the device holder and other accessories according to the targeted measuremen



2.1.2 Data Acquisition Electronics

The data acquisition electronics (DAE4 or DAE3) consist of a highly sensitive electrometergrade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit ADconverter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.

2.2 DASY 6 mmWave PD Module

2.2.1 Measurement System

A DASY 6 Measurement System equipped with the DASY 6 mmWave module was used to carry out the peak spatially averaged power density (psPD) measurements. It consists of a 6-axis industrial robot and controller that provides a highly accurate positioning system, a PC for the system control software, a near field probe (EUmmWVx), a probe alignment sensor and the 5G phantom. The high accuracy positioning system places the near field probe at the key location points of the maximum electromagnetic field.



Figure 3 - Typical measurement setup for PD measurement with DASY 6



2.2.2 EUmmWVx E-Field Probe Details

The EUmmWVx probe utilises two dipole elements that are specifically arranged to allow for the generation of pseudo-vector data.

Frequency Range	750 MHz - 110 GHz
Dynamic Range	<20 V/m - 10'000 V/m with PRE-10 (min <20 V/m - 2000 V/m)
Position Precision	<0.2 mm (DASY6)
Dimensions	Overall length: 320 mm (tip: 20 mm) Tip and body diameter: encapsulation 8 mm (internal sensor <1mm) Distance from probe tip to sensor Y cal point:1.5 mm Distance from probe tip to sensor X cal point:1.5 mm
Applications	E-field measurements of 5G devices and other mm-wave transmitters operating above 10GHz in <2 mm distance from device (free-space) Power density, H-field, and far-field analysis using total field reconstruction.
Compatibility	cDASY6 + 5G-Module SW1.0 and higher



Figure 4 - Diagram of the distance sensor to the EUT surface



2.2.3 Peak Spatially Averaged Power Density Assessment based on E-Field Measurements

Power density was determined for both the electric and magnetic fields within a small distance from the transmitting source. In general, the magnitude and phase of two components of either E-field or H-field are needed on a sufficiently large surface to characterise their total distributions. Despite this being the case, a solution based on the direct measurement of the E and H field can be used to compute power density. The measurement approach to achieve this is given below.

a) The local E-field is measured at a reference point on the measurement surface where the field is well above the system noise floor. This reference point is re-visited at the end of the measurement routine and re-measured to determine and assess the power drift of the EUT.

b) The electric field on the measurement surface was scanned using instructions provided by the test system manufacturer. The spatial resolution of the measurement can depend on the measured field characteristic and measurement methodology used by the test system. The planar scan step size is configured to be $\lambda/4$.

c) DASY6 uses a reconstruction algorithm to calculate the H-field from the measured E-field. As the power density calculation requires amplitude and phase, reconstruction algorithms can also be used to obtain field information from the measured E-field data, for example phase information from the amplitude if only the amplitude is measured. Three measurements per point on two measurement planes separated by $\lambda/4$ are carried out in order for the H-field and phase data to be reconstructed.

d) Using the equation below the total peak spatially averaged power density (psPD) distribution on the evaluation surface can be determined. The applicable regulatory requirements specify the spatial averaging area A. A circular shape is used.

$$psPD = \frac{1}{2A_{av}} \qquad \iint_{A_{av}} ||Re\{E \times H^*\}|| dA$$

e) The final quantity used to determine compliance against the applicable limits is the maximum spatial average on the evaluation.

f) Following the measurement of the power drift as described in step a) the drift was assessed. If the drift deviated by more than 5% then the power density test and drift measurements shall be repeated.



2.2.4 Reconstruction Algorithm

Computation of the PD in general requires knowledge of the electric (E-) and magnetic (H-) field amplitudes and phases in the plane of incidence. Reconstruction of these quantities from pseudo-vector E-field measurements is feasible, as they are constrained by Maxwell's equations.

The test system utilises a reconstruction approach based on the Gerchberg-Saxton algorithm which benefits from the availability of the E-field polarization ellipse information obtained with the EUmmWVx probe. This reconstruction algorithm, together with the ability of the probe to measure extremely close to the source without perturbing the field, permits reconstruction of the E- and H-fields and the PD on measurement planes located as near as $\lambda/2\pi$.

2.2.5 Standalone PD Limit

The following formula provides the reference levels for local exposure to electromagnetic fields from >6 GHz to 300GHz for general public as referenced in ICNIRP 2020:

$$55/f_{\rm G}^{0.177}$$

The FCC Oct 2020 TCB workshop states their own incident power density limit of $1mW/cm^2$ plane-wave equivalent, averaged over 4 cm² as reflected in FCC 47 CFR 1.1310.

2.2.6 Exposure Ratio

The following formulas used to calculate the exposure ratio of SAR, APD and iPD respectively as referenced in ICNIRP 2020:



2.2.7 Total Exposure Ratio (TER)

The total exposure ratio is the sum of local specific absorption rate (SAR), local absorbed power density (APD) and local incident power density (iPD) referenced in ICNIRP 2020:

where, SAR_{*i*} and SAR_{BR} are the local SAR level at frequency *i* and the local SAR basic restriction given in ICNIRP 2020. $S_{ab,4cm,i}$ and $S_{ab,4cm,BR}$ are the $4cm^2$ absorbed power density level at frequency *i* and the $4cm^2$ absorbed power density basic restriction given in ICNIRP 2020. $S_{inc,4cm,i}$ and $S_{inc,4cm,RL,i}$ are the local $4cm^2$ incident power density at frequency *i* and the local $4cm^2$ incident power density reference level at frequency *i* given in ICNIRP 2020.

$$\sum_{i=100 \text{ kHz}}^{6 \text{ GHz}} \frac{\text{SAR}_i}{\text{SAR}_{\text{BR}}}$$

$$+\sum_{i>6~\mathrm{GHz}}^{30~\mathrm{GHz}}\frac{\mathrm{S}_{ab,4\mathrm{cm},i}}{\mathrm{S}_{ab,4\mathrm{cm},\mathrm{BR}}}$$

$$+\sum_{i>6 \text{ GHz}}^{30 \text{ GHz}} \left(\frac{S_{\text{inc},4\text{cm},i}}{S_{\text{inc},4\text{cm},\text{RL},i}} \right) \leq 1$$

TER is applied when simultaneous transmission of the different types of measurement is tested, and basic restriction limits cannot be applied. The TER of the applicable measurements is calculated and summed up to not exceed 1.



SECTION 3

TEST EQUIPMENT USED



3.1 TEST EQUIPMENT USED

The following test equipment was used at TÜV SÜD Product Service:

Instrument Description	Manufacturer	Model Type	TE Number	Cal Period (months)	Calibration Due Date
Directional Coupler	Hewlett Packard	11692D	0452	-	ΤU
Hygrometer	Rotronic	I-1000	2829	12	21-May-2025
Measurement server	SPEAG	DASY 6	5337	-	ΤU
Platform	SPEAG	MP6C	5338	-	ΤU
DASY 6 Robot	SPEAG	TX90 XL	5340	-	ΤU
Isotropic E-field Probe	SPEAG	UmmWV4	6353	12	10-Oct-2025
2m Coaxial Cable Assy	Junkosha	MWX221- 02000AMSAMS/A	6361	12	16-May-2025
1m Coaxial Cable Assy	Junkosha	MWX221- 01000AMSAMS/A	6378	12	16-May-2025
1m Coaxial Cable Assy	Junkosha	MWX221- 01000AMSAMS/A	6380	12	16-May-2025
Data Acquisition Electronics	SPEAG	DAE4ip	6501	12	07-Aug-2025
Diode Power Sensor	Rohde & Schwarz	NRP18S	6533	24	11-Apr-2026
Diode Power Sensor	Rohde & Schwarz	NRP18S	6534	24	17-Apr-2025
Power Meter	Rohde & Schwarz	NRX	6535	-	ΤU
Amplifier	Mini-Circuits	ZVE-3W-183+	6540	-	ΤU
Signal Generator	Rohde & Schwarz	SMR20	6677	12	04-Oct-2025
Verification Source	SPEAG	5G Verification Source 6.5GHz	6704	12	14-Nov-2025
Attenuator	RF-Lambda	RFS5G18B10SMP	6835	12	08-Aug-2025

Table 9

TU - Traceability Unscheduled



3.2 TEST SOFTWARE

The following software was used to control the TÜV SÜD Product Service DASY System.

Instrument	Version Number
DASY System	cDASY6 Module mmWave V3.2.2.2358



3.3 TEST VERIFICATION

3.3.1 System Performance Check Results

Prior to formal testing being performed a system performance check in DASY Module mmWave was performed with the verification source available at 6.5 GHz in accordance with IEC/IEEE 63195-1.

iPD System Check Results

Date	Frequency (MHz)	Medium	Measured psPDtot + (W/m ²)	Target psPDtot + (W/m²)	Percentage Deviation from Target (%)
20/02/2025	6500	Air	152	141	7.80
24/02/2025	6500	Air	145	141	2.84



3.4 TEST CONDITIONS

3.4.1 Test Laboratory Conditions

Ambient temperature: Within +18.00°C to +25.00°C.

The actual temperature during the testing ranged from 21.10°C to 21.30°C.

The actual humidity during the testing ranged from 32.50% to 44.50% RH.



3.5 MEASUREMENT UNCERTAINTY

DASY6 Uncertainty Budget for iPD

Symbol	Error Description	Value dB	Probability distribution	Divisor	Ci	<i>u_i</i> (y) dB	(<i>ui</i> (y))^2	V _i or V _{eff}	ui^4(y)
	Uncertainty term	ns depen	dent on the mea	asurement	sys	tem		-	
CAL	Calibration	0.49	normal 1	1.000	1	0.49	0.240	~	0
COR	Probe correction	0.00	rectangular	1.732	1	0.00	0.000	~	0
FRS	Frequency response (BW \leq 1 GHz)	0.20	rectangular	1.732	1	0.12	0.013	∞	0
SCC	Sensor cross coupling	0.00	rectangular	1.732	1	0.00	0.000	∞	0
ISO	Isotropy	0.50	rectangular	1.732	1	0.29	0.083	8	0
LIN	Linearity	0.20	rectangular	1.732	1	0.12	0.013	8	0
PSC	Probe scattering	0.00	rectangular	1.732	1	0.00	0.000	8	0
PPO	Probe positioning offset	0.30	rectangular	1.732	1	0.17	0.030	8	0
PPR	Probe positioning repeatability	0.04	rectangular	1.732	1	0.02	0.001	8	0
SMO	Sensor mechanical offset	0.00	rectangular	1.732	1	0.00	0.000	8	0
PSR	Probe spatial resolution	0.00	rectangular	1.732	1	0.00	0.000	8	0
FLD	Field impedance dependence	0.00	rectangular	1.732	1	0.00	0.000	8	0
APD	Amplitude and phase drift	0.00	rectangular	1.732	1	0.00	0.000	8	0
APN	Amplitude and phase noise	0.04	rectangular	1.732	1	0.02	0.001	8	0
TR	Measurement area truncation	0.00	rectangular	1.732	1	0.00	0.000	8	0
DAQ	Data acquisition	0.03	normal 1	1.000	1	0.03	0.001	8	0
SMP	Sampling	0.00	rectangular	1.732	1	0.00	0.000	8	0
REC	Field reconstruction	0.60	rectangular	1.732	1	0.35	0.120	8	0
TRA	FTE/MEO	0.70	rectangular	1.732	1	0.40	0.163	8	0
SCA	Power density scaling	0.00	rectangular	1.732	1	0.00	0.000	∞	0
SAV	Spatial averaging	0.10	rectangular	1.732	1	0.06	0.003	8	0
SDL	System detection limit	0.04	rectangular	1.732	1	0.02	0.001	8	0
	Uncertainty terms de	pendent	on the DUT and	environm	enta	I factor	s		
PC	Probe coupling with DUT	0.00	rectangular	1.732	1	0.00	0.000	∞	0
MOD	Modulation response	0.40	rectangular	1.732	1	0.23	0.053	~	0
IT	Integration time	0.00	rectangular	1.732	1	0.00	0.000	~	0
RT	Response time	0.00	rectangular	1.732	1	0.00	0.000	∞	0
DH	Device holder influence	0.10	rectangular	1.732	1	0.06	0.003	~	0
DA	DUT alignment	0.00	rectangular	1.732	1	0.00	0.000	~	0
REF	Reflections in laboratory	0.10	rectangular	1.732	1	0.06	0.003	∞	0
TEM	Laboratory temperature	0.10	rectangular	1.732	1	0.06	0.003	~	0
AC	RF ambient conditions	0.04	rectangular	1.732	1	0.02	0.001	∞	0
AR	Ambient reflections	0.04	rectangular	1.732	1	0.02	0.001	8	0
MSI	Immunity / secondary reception	0.00	rectangular	1.732	1	0.00	0.000	∞	0
DRI	Drift of the DUT	0.00	rectangular	1.732	1	0.00	0.000	∞	0
u _c (F _S)	Combined Standard Uncertainty (w/ FTE/MEO)	-	normal	-	-	0.86	0.734	∞	0
U(F _s)	Expanded Uncertainty (w/ FTE/MEO)	-	normal k =	2.00	-	1.7	-	∞	-



					1		(()) • •	Vi	
Symbol	Error Description	Value dB	Probability distribution	Divisor	C _i	<i>u_i</i> (y) dB	(<i>u_i</i> (y))^2 dB	or V _{eff}	ui^4(y)
Uncertai	nty terms dependent on the measure	ement sy	stem	<u>.</u>				-	
CAL	Calibration Repeatability	0.21	normal 1	1.000	1	0.21	0.044	∞	0
COR	Probe correction	0.00	rectangular	1.732	1	0.00	0.000	∞	0
FRS	Frequency response (BW ≤ 1 GHz)	0.20	rectangular	1.732	0	0.00	0.000	∞	0
SCC	Sensor cross coupling	0.00	rectangular	1.732	1	0.00	0.000	∞	0
ISO	Isotropy	0.30	rectangular	1.732	1	0.17	0.030	∞	0
LIN	Linearity	0.20	rectangular	1.732	1	0.12	0.013	∞	0
PSC	Probe scattering	0.00	rectangular	1.732	1	0.00	0.000	∞	0
PPO	Probe positioning offset	0.11	rectangular	1.732	1	0.06	0.004	∞	0
PPR	Probe positioning repeatability	0.04	rectangular	1.732	1	0.02	0.001	∞	0
SMO	Sensor mechanical offset	0.00	rectangular	1.732	1	0.00	0.000	∞	0
PSR	Probe spatial resolution	0.00	rectangular	1.732	1	0.00	0.000	∞	0
FLD	Field impedance dependence	0.00	rectangular	1.732	1	0.00	0.000	∞	0
APD	Amplitude and phase drift	0.00	rectangular	1.732	1	0.00	0.000	∞	0
APN	Amplitude and phase noise	0.04	rectangular	1.732	0	0.00	0.000	∞	0
TR	Measurement area truncation	0.00	rectangular	1.732	1	0.00	0.000	∞	0
DAQ	Data acquisition	0.03	normal 1	1.000	1	0.03	0.001	∞	0
SMP	Sampling	0.00	rectangular	1.732	1	0.00	0.000	∞	0
REC	Field reconstruction	0.60	rectangular	1.732	0.3	0.10	0.011	∞	0
TRA	Forward transformation	0.00	rectangular	1.732	1	0.00	0.000	∞	0
SCA	Power density scaling	0.00	rectangular	1.732	1	0.00	0.000	∞	0
SAV	Spatial averaging	0.10	rectangular	1.732	0	0.00	0.000	∞	0
SDL	System detection limit	0.04	rectangular	1.732	1	0.02	0.001	∞	0
Uncertai	nty terms dependent on the DUT and	1 environ	mental factors	1	L		I		
PC	Probe coupling with DUT	0.00	rectangular	1.732	1	0.00	0.000	∞	0
MOD	Modulation response	0.40	rectangular	1.732	0	0.00	0.000	∞	0
IT	Integration time	0.00	rectangular	1.732	1	0.00	0.000	∞	0
RT	Response time	0.00	rectangular	1.732	1	0.00	0.000	∞	0
DH	Device holder influence	0.10	rectangular	1.732	0	0.00	0.000	∞	0
REF	Reflections in laboratory	0.10	rectangular	1.732	1	0.06	0.003	∞	0
TEM	Laboratory temperature	0.10	rectangular	1.732	1	0.06	0.003	∞	0
DA	DUT alignment	0.00	rectangular	1.732	1	0.00	0.000	∞	0
AC	RF ambient conditions	0.04	rectangular	1.732	1	0.02	0.001	∞	0
AR	Ambient reflections	0.04	rectangular	1.732	1	0.02	0.001	∞	0
MSI	Immunity / secondary reception	0.00	rectangular	1.732	0	0.00	0.000	∞	0
DRI	Drift of the DUT	0.10	rectangular	1.732	1	0.06	0.003	∞	0
u _c (F _S)	Combined Standard Uncertainty (w/ FTE/MEO)	-	normal	-	-	0.34	0.115	∞	0
U(F _S)	Expanded Uncertainty (w/ FTE/MEO)	-	normal k =	2.00	-	0.7		∞	-

DASY6 mmWave Uncertainty Budget - System Performance Check



3.5.1 Decision Rule

Accuracy Method

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2007, Clause 4.4.3 and 4.5.1. (Procedure 2). The measurement results are directly compared with the test limit to determine conformance with the requirements of the standard.

Risk: The uncertainty of measurement about the measured result is negligible with regard to the final pass/fail decision. The measurement result can be directly compared with the test limit to determine conformance with the requirement (compare IEC Guide 115). The level of risk to falsely accept and falsely reject items is further described in ILAC-G8."



SECTION 4

ACCREDITATION, DISCLAIMERS AND COPYRIGHT



4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care.

The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD.

© 2025 TÜV SÜD.

This report relates only to the actual item/items tested.

Results of tests covered by our Flexible UKAS Accreditation Schedule are marked FS (Flexible Scope).

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.



ANNEX A

PROBE CALIBRATION REPORT



Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S

Schweizerischer Kalibrierdienst Service suisse d'étalonnage Servizio svizzero di taratura

С S Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

CALIBRATION (CERTIFICATE
Object	EUmmWV4 - SN:9641
Calibration procedure(s)	QA CAL-02.v9, QA CAL-25.v8, QA CAL-42.v3 Calibration procedure for E-field probes optimized for close near field evaluations in air

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power sensor NRP33T	SN: 100967	28-Mar-24 (No. 217-04038)	Mar-25
Power sensor NRP110T	SN: 101244	04-Apr-24 (No. 0001A300740056)	Apr-25
Spectrum analyzer FSV40	SN: 101832	25-Jan-24 (No. 4030-315007551)	Jan-25
Harmonic mixer FS-Z75	SN: 101566	11-Apr-24 (No. 0001A300750054)	Apr-25
Harmonic mixer FS-Z110	SN: 101633	05-Apr-24 (No. 0001A300740055)	Apr-25
Ref. Probe EUmmWV3	SN: 9374	28-Aug-24 (No. EUmm-9374 Aug24)	Aug-25
DAE4ip	SN: 1662	08-Nov-23 (No. DAE4ip-1662_Nov23)	Nov-24
Secondary Standards	ID -	Check Date (in house)	Scheduled Chark
Generator APSIN26G	SN: 2023	30-Nov-21 (in house check Jun-24)	In house check: Jun-25
Power sensor NRP40T	SN: 101439	08-Nov-21 (in house check Jun-24)	In house check: Jun-25
Power copper NOD110T	SNI: 101000	AE Marcold (in harman shart) 1 O M	in the second se

	Name	Function	Signature
Calibrated by	Joanna Lleshaj	Laboratory Technician	Apoller
Approved by	Sven Kühn	Technical Manager	.A. A. All
This calibration certifica	tte shall not be reproduced except ir	full without written approval of the lab	Issued: October 11, 2024 poratory.

Certificate No: EUmm-9641_Oct24

Page 1 of 18



Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland



S S S

Schweizerlscher Kallbrierdienst Service suisse d'étalonnage

Servizio svizzero di taratura Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary

NORMx,y	sensitivity in free space
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization <i>ð</i>	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system
Sensor Angles	sensor deviation from the probe axis, used to calculate the field orientation and polarization is the wave propagation direction

Calibration is Performed According to the Following Standards:

 a) IEEE Std 1309-2005, "IEEE Standard for calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 GHz", December 2005

Methods Applied and Interpretation of Parameters:

- NORMx,y: Assessed for E-field polarization ∂ = 0 (f ≤ 900MHz in TEM-cell; f > 1800MHz: R22 waveguide). For frequencies > 6 GHz, the far field in front of waveguide horn antennas is measured for a set of frequencies in various waveguide bands up to 110 GHz.
- DCPx,y: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- Note: As the field is measured with a diode detector sensor, it is warrantied that the probe response is linear (E²) below the documented lowest calibrated value.
- · PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- The frequency sensor model parameters are determined prior to calibration based on a frequency sweep (sensor model involving resistors R, R_p, inductance L and capacitors C, C_p).
 Ax,y; Bx,y; Cx,y; Dx,y; VRx,y: A, B, C, D are numerical linearization parameters assessed based on the data of power
- Ax,y; Bx,y; Cx,y; Dx,y; VHx,y: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle: The angle is assessed using the information gained by determining the NORMx (no uncertainty required).
 Equivalent Sensor Angle: The two probe sensors are mounted in the same plane at different angles. The angles are
- assessed using the information gained by determining the NORMx (no uncertainty required).
- Spherical isotropy (3D deviation from isotropy): in a locally homogeneous field realized using an open waveguide / horn setup.

Certificate No: EUmm-9641_Oct24

Page 2 of 18



October 10, 2024

EUmmWV4 - SN:9641

Parameters of Probe: EUmmWV4 - SN:9641

Basic Calibration Parameters

	Sensor X	Sensor Y	Unc (k = 2)
Norm $(\mu V/(V/m)^2)$	0.01940	0.02206	±10.1%
DCP (mV) ^B	106.0	105.0	±4.7%
Equivalent Sensor Angle	-60.8	35.2	

Calibration Results for Frequency Response (750 MHz - 110 GHz)

Frequency GHz	Frequency E-Field Deviation Sensor X GHz V/m dB		Deviation Sensor Y dB	Unc (k = 2) dB
0.75	77.2	-0.26	-0.34	±0.43
1.8	140.4	-0.06	-0.05	±0.43
2.0	133.0	0.13	0.14	±0.43
2.2	124.8	-0.05	-0.04	±0.43
2.5	123.0	0.11	0.15	±0.43
3.5	256.2	-0.09	-0.07	±0.43
3.7	249.8	0.07	0.06	±0.43
6.6	63.3	-0.41	-0.39	±0.98
8.0	58.3	-0.15	-0.17	±0.98
10.0	57.6	0.04	0.05	±0.98
15.0	45.2	0.26	0.24	±0.98
26.6	115.1	0.17	0.17	±0.98
30.0	125.1	-0.01	-0.01	±0.98
35.0	123.5	-0.14	-0.12	±0.98
40.0	101.8	-0.19	-0.21	±0.98
50.0	60.8	0.09	0.06	+0.98
55.0	73.7	-0.03	-0.04	+0.98
60.0	76.4	-0.02	0.00	+0.98
65.0	72.0	0.09	0.13	±0.98
70.0	68.5	0.11	0.08	±0.98
75.0	67.9	0.00	-0.04	±0.98
75.0	89.9	-0.01	-0.05	±0.98
80.0	88.2	-0.11	-0.09	±0.98
85.0	54.3	-0.02	-0.05	±0.98
90.0	80.6	0.01	0.02	±0.98
92.0	80.8	0.01	-0.00	±0.98
95.0	73.2	-0.03	-0.04	±0.98
97.0	65.9	-0.02	-0.06	±0.98
100.0	63.4	0.05	0.06	±0.98
105.0	63.2	-0.15	-0.10	±0.98
110.0	72.1	0.12	0.06	±0.98

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^B Linearization parameter uncertainty for maximum specified field strength.

Certificate No: EUmm-9641_Oct24

Page 3 of 18



October 10, 2024

Parameters of Probe: EUmmWV4 - SN:9641

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dBõV	С	D dB	VR mV	Max dev.	Max Unc ^E
0	cw	X	0.00	0.00	1.00	0.00	123.3	±3.0%	±4.7%
		Y	0.00	0.00	1.00		100.7	5	
10352	Pulse Waveform (200Hz, 10%)	X	4.30	63.45	16.86	10.00	6.0	±1.5%	±9.6%
		Ŷ	3.40	60.69	15.85		6.0		
10353	Pulse Waveform (200Hz, 20%)	X	3.50	65.24	16.44	6.99	12.0	±0.9%	±9.6%
		Y	2.73	62.44	15.43		12.0		
10354	Pulse Waveform (200Hz, 40%)	X	2.06	64.87	15.12	3.98	23.0	±1.2%	±9.6%
		Y	1.59	62.15	14.17		23.0		
10355	Pulse Waveform (200Hz, 60%)	X	0.82	60.00	12.39	2.22	27.0	±0.9%	±9.6%
		Y	0.78	60.00	12.66		27.0		
10387	QPSK Waveform, 1 MHz	X	1.30	60.00	12.58	1.00	22.0	±1.1%	±9.6%
		Y	1.28	60.00	12.79		22.0		
10388	QPSK Waveform, 10 MHz	X	1.26	60.00	12.15	0.00	22.0	±0.8%	±9.6%
		Y	1.24	60.00	12.39		22.0		
10396	64-QAM Waveform, 100 kHz	X	5.29	70.77	18.04	3.01	17.0	±1.0%	±9.6%
		Y	6.76	73.72	19.00		17.0		
10399	64-QAM Waveform, 40 MHz	X	2.06	60.00	12.59	0.00	19.0	±0.8%	±9.6%
	·	Y	2.02	60.00	12.80		19.0		
10414	WLAN CCDF, 64-QAM, 40 MHz	X	3.23	60.00	12.98	0.00	12.0	±1.0%	±9.6%
		Y	3.14	60.00	13.18		12.0		

Note: For details on UID parameters see Appendix

E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Certificate No: EUmm-9641_Oct24

Page 4 of 18



October 10, 2024

EUmmWV4 - SN:9641

Parameters of Probe: EUmmWV4 - SN:9641

Calibration Results for Linearity Response

Frequency GHz	Target E-Field V/m	Deviation Sensor X dB	Deviation Sensor Y dB	Unc (k = 2) dB
0.9	50.0	0.06	0.05	±0.2
0.9	100.0	-0.09	0.02	±0.2
0.9	500.0	0.01	-0.02	±0.2
0.9	1000.0	0.01	0.02	±0.2
0.9	1500.0	0.01	0.01	±0.2
0.9	2100.0	-0.01	-0.00	±0.2

Sensor Frequency Model Parameters (750 MHz - 55 GHz)

	Sensor X	Sensor Y
R (Ω)	54.73	34.12
R _p (Ω)	76.33	44.87
L (nH)	0.05151	0.02821
C (pF)	0.2983	0.6440
Cp (pF)	0.1208	0.2087

Sensor Frequency Model Parameters (55 GHz - 110 GHz)

	Sensor X	Sensor Y
R (Ω)	17.92	36.30
R _p (Ω)	103.65	198.79
L (nH)	0.05691	0.11222
C (pF)	0.0730	0.0384
C _p (pF)	0.0900	0.0477

Sensor Model Parameters

	C1 fF	C2 fF	α V ⁻¹	T1 msV ⁻²	T2 ms V ⁻¹	T3 ms	T4 V ⁻²	T5 V ⁻¹	T6
X	71.9	519.49	33.53	0.00	10.00	5.03	2.00	2.00	1.01
У	71.3	518.14	33.89	0.00	10.00	5.02	2.00	2.00	1.01

Other Probe Parameters

Sensor Arrangement	Rectangular
Connector Angle	163.8°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	320 mm
Probe Body Diameter	8mm
Tip Length	23 mm
Tip Diameter	8.0 mm
Probe Tip to Sensor X Calibration Point	1.5 mm
Probe Tip to Sensor Y Calibration Point	1.5 mm

Certificate No: EUmm-9641_Oct24

Page 5 of 18



October 10, 2024



60GHz: 3D isotropy, E-field parallel to probe axis



Parallel to the field propagation ($\psi = 0^{\circ} - 90^{\circ}$) at 30 GHz: deviation within ±0.35 dB Parallel to the field propagation ($\psi = 0^{\circ} - 90^{\circ}$) at 60 GHz: deviation within ±0.39 dB

Certificate No: EUmm-9641_Oct24

Page 6 of 18



October 10, 2024

EUmmWV4 - SN:9641

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
0		CW	CW	0.00	±4.7
10010	CAB	SAR Validation (Square, 100 ms, 10 ms)	Test	10.00	+9.6
10011	CAC	UMTS-FDD (WCDMA)	WCDMA	2.91	+9.6
10012	CAB	IEEE 802.11b WIFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	+9.6
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	±9.6
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	+9.6
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	±9.6
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	±9.6
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	±9.6
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	±9,6
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4,80	±9.6
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	±9.6
10029	DAC	EDGE-FDD (TDMA, BPSK, TN 0-1-2)	GSM	7,78	±9.6
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	±9.6
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1,87	±9,6
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1,16	±9,6
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	±9,6
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4,53	±9.6
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	±9,6
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	±9.6
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	±9,6
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4,10	±9,6
10039	CAB	CDMA200D (1xRTT, RC1)	CDMA2000	4.57	±9,6
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	±9,6
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0,00	±9.6
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	±9.6
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	±9.6
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	±9.6
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	±9.6
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2,12	±9.6
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2,83	±9.6
10061	CAB	IEEE 802.11b WIFI 2.4 GHz (DSSS, 11 Mbps)	WLAN	3,60	±9.6
10062	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	±9.6
10063	CAE	IEEE 802.11a/h WIFi 5 GHz (OFDM, 9 Mbps)	WLAN	8,63	±9.6
10064	CAE	IEEE 802,11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	±9.6
10065	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9,00	±9.6
10066	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	±9.6
10067	CAE	IEEE 802,11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	±9.6
10068	CAE	IEEE 802.11a/h WiFI 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	±9.6
10069	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10,56	±9.6
100/1	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9,83	±9.6
100/2	CAB	IEEE 802.11g WIFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9,62	±9.6
100/3	CAB	IEEE 802.11g WIFI 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9,94	±9.5
100/4	UAH CAR	IEEE 602,11g WIFI 2,4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10,30	±9.6
100/5	CAB	IEEE 002.11g WIFI 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10,77	±9.6
100/6	CAB	IEEE 002.11g WIFI 2.4 GHZ (USSS/OFDM, 48 Mbps)	WLAN	10,94	±9.6
10077	CAB	CDMAROOD (1+OTT BOO)	WLAN	11.00	±9.6
10081	CAB	IS 54 / IS 125 EDD (TDMA/EDM BI/4 DODCH Stream	CDMA2000	3,97	±9.6
10082	DAG	CPPS FOD (TDMA/FUM, FI/4-DQPSK, Fullrate)	AMPS	4.77	±9.6
10090	CAC	UNITE EDD (JODA)	GŞM	6.56	±9.6
10097	CAC	UNITO FOD (HOUTA)	WCDMA	3,98	±9,6
10030	DAC	EDGE EDD (TDMA SPEK THA A)	WCDMA	3.98	±9.6
10100	CAE	LITE EDD (SC.EDMA 100% PD 20MUs 0000	GSM	9,55	±9.6
10100	CAF	TE-EDD (SC EDMA 100% PB 20MHz 10 CAM	LIE-FDD	5.67	±9.6
10102	CAF	TE EDD (SC EDMA 100% PD 201447 84 0444	LTE-FDD	6.42	±9.6
10102	CAH	ITE-TDD (SC-FDMA, 100% BB, 20 MHz, 04-QAM)	LTE-FDD	6.60	±9.6
10104	CAH	TE-TOD (SC-FDMA, 100% RB, 20 MHz, 15 OAM)	LIE-IDD	9,29	±9.6
10105	CAH	ITE-TOD (SC-EDMA 100% BB 20 MHz & CAM)	LIE-TOD	9,97	±9.6
10108	CAH	LTE-EDD (SC-EDMA 100% BS 10 MHz OPSK)		10,01	±9,6
10109	CAH	LTE-FOD (SC-FDMA 100% BB 10MHz 16-0AM)		5,80	±9,6
10110	CAH	LTE-FDD (SC-FDMA 100% BB 5MHz OPSK)		6.43	±9.6
10111	CAH	LTE-FDD (SC-FDMA 100% RB 5MHz 16.0AM)	LIE-PUU	5./5	±9.6
		1	LIE-FUU	0.44	#9 ,6

Certificate No: EUmm-9641_Oct24

Page 7 of 18



October 10, 2024

100	Davis	Communication Contant New		mara (1791	U. Fr. o
010	Rev	Communication System Name	Group	PAH (0B)	Unc- K = 2
10112	GAH	LIE-FUD (SG-FUMA, 100% HB, 10 MHZ, 54-QAM)		6.59	±9.6
10113	CAH	LIE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10114	CAE	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	±9.6
10115	CAE	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	±9.6
10116	CAE	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	±9.6
10117	CAE	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	±9.6
10118	CAE	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	±9.6
10119	CAE	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	±9.6
10140	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FOD	6.49	±9.6
10141	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	±9.6
10142	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10143	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	±9.6
10144	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	±9.6
10145	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	±9.6
10146	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	±9.6
10147	CAG	LTE-FDD (SC-FDMA, 100% BB, 1.4 MHz, 64-OAM)	LTE-FDD	6.72	+9.6
10149	CAF	LTE-EDD (SC-EDMA, 50% BB, 20 MHz, 16-OAM)	LTE-EDD	6.42	+9.6
10150	CAE	TTE-EDD (SC-EDMA 50% BB 20 MHz 64 OAM)	LTE-EDD	6.60	10.0
10151	CAH	TE-TOD (SC-EDMA 50% BB 20 MHz OPSK)	ITE.TDD	0.00	106
10152	CAH	LTE-TOD (SC-EDMA, 50% PB, 20 MHz, GC-SK)	LTE-TOD	9.20	10.0
10152	CAH	TE-TOD (SC-EDMA, 50% DB, 20 MHz, 10-CAM)		9.92	±9.6
10150	CALL	LTE EDD (SC FDMA, 50% ND, 20 MIN2, 64 QAM)	LIE-IDU	10.05	±9.0
10134	CALL	LTE-FDD (SC-FDMA, 50% RB, 10 MHZ, QPSK)	LIE-FUU	5.75	±9.6
10155	CAH	LTE-FDD (SC-FDMA, 50% HB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10156	CAH	LIE-FUD (SC-FUMA, 50% RB, 5 MHZ, QPSK)	LTE-FDD	5.79	±9.6
10157	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10158	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10159	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6.56	±9.6
10160	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, QPSK)	LTE-FDD	5.82	±9.6
10161	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10162	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, 64-QAM)	LTE-FDD	6.58	±9.6
10166	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	±9.6
10167	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.21	±9.6
10168	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.79	±9.6
10169	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	±9.6
10170	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	+9.6
10171	AAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	+9.6
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, OPSK)		9.21	+9.6
10173	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	ITE-TDD	9.48	+9.6
10174	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-OAM)		10.25	19.0
10175	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, OPSK)	ITE-FOD	5.72	10.0
10176	CAH	LTE-EDD (SC-EDMA, 1 BB, 10 MHz, 16-OAM)	175,555	5.72	±3.0
10177	CAI	LTE-EDD (SC-EDMA 1 BB 5MHz OPSK)	LIE-FOD	6.32	19.0
10178	CAH	ITE-EDD (SC-EDMA 1 BB SMH2 16-OAM)	LIE-FUD	5.73	±9.0
10179	CAH	ITE-FDD (SC-FDMA, 1 PB, 10MHz, 54-CAM)		6.52	±9.6
10180	CALL	TE EDD (SC EDMA 1 DB CAME & CAME		6.50	±9.6
10100	CAE	LTE FOD (SC FDMA, 1 RB, 15 Mile, OPDI/)	LIE-FDD	6.50	±9.5
10102	CAE	TE-SOD (SC-EDMA, 1 PE 15 MHz, 45 OAAN	LIE-FUU	5.72	±9.5
10102	AAE	TE EDD (SO EDMA 1 DD 15MHz 04 CAN)		6.52	±9.6
10103	CAE	LTE COD (SC EDMA, I RE, ISMRZ, 64-UAM)	LTE-FDD	6.50	±9.6
10104	CAF	LICTUD (SUTUMA, 1 HB, 3MHZ, UPSK)	LIE-FDD	5.73	±9.6
10185	LAP	LIE-FOD (SC-FDMA, 1 HB, 3MHZ, 16-QAM)	LTE-FDD	6.51	±9.6
10186	AAF	LIE-FUD (SG-FUMA, 1 HB, 3MHZ, 64-QAM)	LTE-FDD	6.50	±9.6
10187	CAG	LIE-FDU (SG-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-FDD	5.73	±9.6
10188	CAG	LIE-FUD (SG-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10189	AAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10193	CAE	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	±9.6
10194	CAE	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	±9.6
10195	CAE	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	8.21	±9.6
10196	CAE	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	WLAN	8.10	±9.6
10197	CAE	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.13	±9.6
10198	CAE	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	±9.6
10219	CAE	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	WLAN	8.03	±9.6
10220	CAE	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.13	±9.6
10221	CAE	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.27	±9.6
10222	CAE	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	WLAN	8.06	±9.6
10223	CAE	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8.48	+9.6
10224	CAE	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	+9.6

Certificate No: EUmm-9641_Oct24

Page 8 of 18



October 10, 2024

105	Deu	Communication System Name	Group	PAR (dB)	
10225	CAC	UMTS-EDD (HSPAL)	WCDMA	5.97	+9.6
10225	CAC	LTE.TOD (SC.EDMA 1 BB 1 4MHz 16-QAM)	LTE-TDD	9.49	±9.6
10220	CAC	ITE-TOD (SC-FDMA 1 BB 14/MHz 64-QAM)	LTE-TPD	10.26	±9.6
10227	CAC	LTE-TOD (SC-FDMA 1 BB 14 MHz OPSK)	LTE-TDD	9.22	±9.6
10220	CAF	LTE-TDD (SC-FDMA, 1 RB, 3MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10225	CAE	LTE-TOD (SC-FDMA, 1 RB, 3MHz, (C-CAM)	LTE-TDD	10.25	+9.6
10230	CAE	LTE-TOD (SC-EDMA 1 RB 3MHz OPSK)	LTE-TDD	9.19	+9.6
10237	CAH	LTE-TOD (SC-EDMA, 1 BB SMHz, Grony	LTE-TOD	9.48	+9.6
10232	CAH	LTE-TOD (SC-EDMA 1 RB 5MHz 64-OAM)	LTE-TDD	10.25	+96
10200	CAN	TTE TOD (SC EDMA, 1 PB & MHz, OPCK)	LTE-TDD	9.21	+9.6
10234	CAH	TE-TOD (SC-EDMA, 1 PB, 10MH- 16,0AM)	ITE-TDD	948	+9.6
10233	CAH	LTE TOD (SC-EDMA 1 BB 10MHz 64-0AM)	LTE-TOD	10.25	+9.6
10230	CAH		ITE TOD	0.21	10.0
1023/	CAG	ITE TOD (SC-FDMA, I RB, ISMU, IS-OAM)		948	+9.6
10230	CAG	LTE TOD (SC EDMA, 1 PB, ISMITZ, IOCAM)		10.25	10.0
10239	CAG	LTE TOD (SC FDMA, 1 PD, ISMITZ, OF-CAM)	ITE TOD	0.21	19.6
10240	CAG	LTE-TOD (SC-FDMA, THD, ISMITZ, GFSK)	LTE-TOD	0.82	19.6
10241	CAC	LTE-TOD (SC-FDMA, 50% RD, 1.4 MHz, 10-CAM)		9.02	10.6
10242	CAC	LTE TOD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)		9.00	19.0
10243	CAC	LIE-TOD (SC-FDMA, 50% RD, 1.4 MRZ, QFSK)		3,40	10.C
10244	CAE	LIE-IDD (SC-FDMA, SV% RB, 3 MRZ, 10-QAM)		10.00	T2'0
10245	CAE	LIC-100 (00-FDMA, 00% RD, 3 MRZ, 04-QAM)		0.00	19.0
10246	OAL	LICHUD (SCHDMA, 50% RB, SMRZ, GESK)	LIC-IDD	3.30	19.0
10247	CAH	LIE-TOD (SC-FDMA, 50% HB, 5 MHZ, 16-QAM)		9.91	±9.6
10248	GAH	LIE-TOD (SC-FUMA, 50% HB, 5 MHZ, 64-QAM)	LIE-IDD	10.09	±9.0
10249	GAH	LIE-TUD (SC-FUMA, 50% HB, 5 MHZ, QPSK)	LIE-IDD	9.29	#9.0
10250	GAH	LIE-TDD (SC-FDMA, 50% HB, 10 MHz, 16-QAM)		9.81	±9.6
10251	CAH	LIE-TDU (SC-FDMA, 50% H5, 10 MHZ, 64-QAM)	LIE-IDD	10.17	±9,6
10252	CAH	LIE-IDD (SC-FDMA, 50% HB, 10 MHZ, QPSK)		9.24	±9.6
10253	GAG	LIE-TDD (SC-FDMA, 50% HB, 15 MHZ, 16-UAM)	LIE-IDD	9.90	±9,6
10254	CAG	LIE-TUD (SC-FDMA, 50% HB, 15 MHZ, 64-QAM)	LIE-IDD	10.14	±9.6
10255	CAG	LIE-TDD (SC-FDMA, 50% HB, 15 MHZ, QPSK)	LIE-IDD	9.20	±9.6
10256	CAG	LIE-TDD (SC-FDMA, 100% HB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	±9,6
10257	CAG	LIE-TDD (SC-FDMA, 100% HB, 1.4 MHz, 54-QAM)	LTE-TDD	10.08	±9,6
10258	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	±9,6
10259	CAE	LIE-TOD (SC-FDMA, 100% HB, 3 MHz, 16-QAM)	LTE-TOD	9.98	±9,6
10260	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	±9,6
10261	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	±9.6
10262	CAH	LIE-1DD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TOD	9.83	±9,6
10263	CAH	LIE-TOD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-TOD	10.16	±9.6
10264	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	±9.6
10265	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10266	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	±9.6
10267	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TOD	9.30	±9.6
10268	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10269	CAG	LIE-TDD (SC-FDMA, 100% RB, 15MHz, 64-QAM)	LTE-TDD	10.13	±9.6
10270	CAG	LIE-TUD (SC-PDMA, 100% RB, 15MHz, QPSK)	LTE-TDO	9.58	±9.6
10274	CAC	UM1S-FDU (HSUPA, Subtest 5, 3GPP Rel8.10)	WCDMA	4.87	±9.6
10275	GAC	UMTS-PDU (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	±9.6
10277	CAA	PHS (QPSK)	PHS	11.81	±9.6
10278	CAA	PHS (UPSK, BW 884 MHz, Rolloff 0.5)	PHS	11.81	±9.6
10279	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.38)	PHS	12.18	±9.6
10290	AAB	CDMA2000, RC1, SO55, Full Rate	CDMA2000	3.91	±9.6
10291	AAB	CDMA2000, RC3, SO55, Full Rate	CDMA2000	3.46	±9.6
10292	AAB	CDMA2000, RC3, SO32, Full Rate	CDMA2000	3.39	±9.6
10293	AAB	CDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	±9.6
10295	AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 Ir.	CDMA2000	12.49	±9.6
10297	AAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	±9.6
10298	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	±9.6
10299	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	±9.6
10300	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10301	AAA	IEEE 802.16e WIMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC)	WiMAX	12.03	±9.6
10302	AAA	IEEE 802.16e WIMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	±9.6
10303	AAA	IEEE 802.16e WIMAX (31:15, 5ms, 10 MHz, 64QAM, PUSC)	WIMAX	12.52	±9.6
10304	AAA	IEEE 802.16e WIMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)	WIMAX	11.86	±9.6
10305	AAA	IEEE 802.16e WIMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)	WIMAX	15.24	±9.6
10306	AAA	IEEE 802.16e WIMAX (29:18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)	WIMAX	14.67	±9.6

Certificate No: EUmm-9641_Oct24

Page 9 of 18



October 10, 2024

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10307	AAA	IEEE 802.16e WIMAX (29:18, 10 ms, 10 MHz, QPSK, PUSC, 18 symbols)	WIMAX	14.49	±9.6
10308	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, PUSC)	WIMAX	14.46	±9.6
10309	AAA	IEEE 802.16e WIMAX (29:18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 18 symbols)	WIMAX	14.58	±9.6
10310	AAA	IEEE 802.16e WIMAX (29:18, 10 ms, 10 MHz, QPSK, AMC 2x3, 18 symbols)	WIMAX	14.57	±9.6
10311	AAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	±9.6
10313	AAA	IDEN 1:3	IDEN	10.51	±9.6
10314	AAA	IDEN 1:6	IDEN	13.48	±9.6
10315	AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	±9.6
10316	AAB	IEEE 802.11g WIFI 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10317	AAE	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	±9.6
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	±9.6
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3,98	±9.6
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	±9.6
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	±9.6
10387	AAA	QPSK Waveform, 1 MHz	Generic	5,10	±9.6
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	±9.6
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	±9.6
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6,27	±9.6
10400	AAF	IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.37	±9.6
10401	AAF	IEEE 802.11ac WIFI (40 MHz, 54-QAM, 99pc duty cycle)	WLAN	8.60	±9.6
10402	AAF	IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.53	±9.6
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	±9.6
10404	AAB	CDMA2000 (1xEV-DO, Rev. A)	CDMA2000	3.77	±9.6
10406	AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	CDMA2000	5 22	+9.6
10410	AAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2.3,4,7,8,9, Subframe Conf=4)	LTE-TDD	7.82	+9.6
10414	AAA	WLAN CCDF. 64-OAM. 40MHz	Generic	8.54	+9.6
10415	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	WLAN	1.54	+9.6
10416	AAA	IEEE 802.11o WiFi 2.4 GHz (ERP-OFDM, 6 Mbos, 99pc duty cycle)	WLAN	8.23	+9.6
10417	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8 23	+9.6
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preambule)	WLAN	8 14	+9.6
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preambule)	WLAN	8.19	+9.6
10422	AAD	IEEE 802.11n (HT Greenfield, 7.2 Mpps, BPSK)	WLAN	8.32	+9.6
10423	AAD	IEEE 802.11n (HT Greenlield, 43.3 Mbos, 16-QAM)	WLAN	8.47	+9.6
10424	GAA	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	+9.6
10425	AAD	IEEE 802.11n (HT Greenlield, 15 Mbos, BPSK)	WLAN	8.41	+9.6
10426	AAD	IEEE 802.11n (HT Greenfield, 90 Mbos, 16-QAM)	WLAN	8.45	+9.6
10427	AAD	IEEE 802.11n (HT Greenfield, 150 Mbrs, 64-QAM)	WLAN	B 41	+9.6
10430	AAE	LTE-EDD (OEDMA, 5MHz, E-TM 3.1)	ITE-EDD	8.28	+9.6
10431	AAE	LTE-FDD (OFDMA, 10MHz, E-TM 3.1)	LTE-FDD	8.38	+9.6
10432	AAD	LTE-FDD (OFDMA, 15MHz, E-TM 3.1)	ITE-EDD	8.34	+96
10433	AAD	LTE-EDD (OEDMA, 20MHz, E-TM 3.1)	ITE-FDD	8.94	+9.6
10434	AAB	W-CDMA (BS Test Model 1, 64 DECH)	WCDMA	8.60	10.0
10435	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, OPSK, UI, Subframe=2.3.4.7.8.9)	LTE-TDD	7.89	+0.6
10447	AAE	LTE-FDD (OFDMA, 5MHz, E-TM 3.1, Clipping 44%)	ITE-EDD	7.52	10.6
10448	AAF	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clinnin 44%)	LTE-EOD	7.59	19.0
10449	AAD	LTE-FDD (OFDMA, 15MHz, E-TM 3.1, Cliping 44%)	ITE-EDD	7.51	10.0
10450	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	ITE-EDD	7.48	10.0
10451	AAB	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.50	+0.6
10453	AAE	Validation (Souare, 10 ms, 1 ms)	Test	10.00	19.0
10456	AAD	IEEE 802.11ac WIFI (160 MHz, 64-QAM, 99pc duty cycle)	WLAN	- ca.e	40.6
10457	AAB	UMTS-FDD (DC-HSDPA)	WCDMA	6.63	79.0
10458	AAA	CDMA2000 (1xEV-DO, Rev. B. 2 carriers)	CDMA2000	20.0	70.0
10459	AAA	CDMA2000 (1xEV-DO, Rev. B. 3 carriers)	CDMA2000	0.00	705
10460	AAR	UMTS-FDD (WCDMA_AMB)	WCDMA	2.20	706
10461	AAC	LTE-TDD (SC-FDMA, 1 BB, 14 MHz, OPSK, UI, Subframe-2 3.4.7.9.9)	ITE.TDD	2.00 7 00	13.0
10462	AAC	LTE-TDD (SC-FDMA 1 RB. 14 MHz 16-DAM III Subframa=234799)	ITE TOO	1.02	100
10463	AAC	LTE-TDD (SC-FDMA 1 BR 14MHz 64-DAM III Subframe=234790)	ITE-TOD	0,30	±9.0
10464	AAD	LTE-TDD (SC-FDMA 1 BB 3MHz OPSK 11 Subframe_034780)	LIE-TOD	0.00	19.0
10465	AAD	LTE-TDD (SC-FDMA, 1 RB, 3MHz, 16-OAM, UL Subframe=2.3.4.7.8.0)	LITE-TOD	7.02	19.D
10466	AAD	LTE-TDD (SC-FDMA 1 BB 3 MHz 64-DAM 11 Subframe=2.3.4.7.8.0)	LITE-TOD	0.32	70.0 Za'D
10467	AAG	TE-TDD (SC-EDMA 1 BR 5 MHz OPSK 11 Subframe-2.3.4.7.8.0)	LTE-TOD	8.5/	±9,6
10469	AAC.	TE-TOD (SC-FOMA, 1 RB 6 MHz 16 OAM 11 Publisher 2.2.4.7.8.0)	LTE-TOD	7,82	±9,6
10460	AAG	TE-TOD (CC-FOMM, THO, SMITZ, TO CAM, UL SUBTRITE-2,3,4,7,8,9)	LIE-IDD	8.32	±9,6
10439	1 440	ITE TDD (SC.50MA 1 BB 10MHz OPSK 11 Subleme 0.94780)	LIE-TOD	8,56	±9,6
10470	DAA D	TE-TDD (SC-EDWA, FRB, TUMPZ, QPSN, UL SUDITATRE=2,3,4,7,8,9)	LIE-IDU	/.82	±9.6
19471	ANAG	LICTIDD (SCEDWA, LING, LUMIZ, 16-QAM, UL SUbframe=2,3,4,7,8,9)	LIE-IDD	8.32	±9.6

Certificate No: EUmm-9641_Oct24

Page 10 of 18



October 10, 2024

מוע	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10472	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subirame=2,3,4,7,8,9)	LTE-TOD	8.57	±9.6
10473	AAF	LTE-TDD (SC-FDMA, 1 RB, 15MHz, QPSK, UL Subframe=2.3,4,7,8,9)	LTE-TDD	7.82	±9.6
10474	AAF	LTE-TDD (SC-FDMA, 1 RB, 15MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10475	AAF	LTE-TDD (SC-FDMA, 1 RB, 15MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10477	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10478	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10479	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10480	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.18	±9.6
10481	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10482	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subirame=2,3,4,7,8,9)	LTE-TDD	7.71	±9.6
10483	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.39	±9.6
10484	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	±9.6
10485	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subirame=2,3,4,7,8,9)	LTE-TDD	7.59	±9.6
10486	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8,38	±9.6
10487	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8,60	±9.6
10488	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, OPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.70	±9.6
10489	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-OAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10490	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10491	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7,74	±9.6
10492	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TOD	8.41	±9.6
10493	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subirame=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10494	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9,6
10495	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.37	±9.6
10496	AAG	LTE-TDD (SC-FDMA, 50% RB, 20MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TOD	8.54	±9,6
10497	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9,6
10498	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8,40	±9,6
10499	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8,68	±9.6
10500	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7,67	±9.6
10501	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.44	±9.6
10502	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.52	±9,6
10503	AAG	LTE-TDD (SC-FDMA, 100% RB, 5MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7,72	±9,6
10504	AAG	LTE-TDD (SC-FDMA, 100% RB, 5MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9,6
10505	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8,54	±9,6
10506	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9,6
10507	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.36	±9,6
10508	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subirame=2,3,4,7,8,9)	LTE-TDD	8,55	±9.6
10509	AAF	LIE-TUD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7,99	±9.6
10510	AAF	LTE-TDD (SC-FDMA, 100% HB, 15MH2, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TOD	8.49	±9.6
10510	AAF	LIE-TDD (SC-FDMA, 100% HB, 15 MHZ, 64-QAM, UL Subframe=2,3,4,7,8,9)	LIE-TDD	8.51	±9.6
10512	AAG	LIE-TOD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL SUDITATINE=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10513	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subtrame=2,3,4,7,8,9)	LTE-TDD	8,42	±9.6
10514	AAG	LEEF 100 (SC-FUMA, 100% KB, 20 MHZ, 64-QAM, UL SUDITAME=2,3,4,7,8,9)	LTE-TDD	8,45	±9.6
10510	AAA	IEEE 002.110 WIFI 2.4 GHz (DOGG, 2 MOPS, SYPC OUTY CYCIE)	WCAN	1.58	±9.6
10510	AAA	IEEE 802.110 WIFI 2.4 GHz (DOGG, D.3 MUDS, 990C 0000 CVCIB)	WELAUN	1,57	±9.6
10519	AAD	IEEE 802.11a/b WiEi 5 GHz (DEDM_RMbps_00ps duty avala)		1,58	±9.6
10510	AAD	IEEE 802.11a/h WiEi 5 GHz (OEDM. 12 Minors, 00ns duity cycle)	MILPIN MILAN	0.23	19.0
10520	AAD	IEEE 802.11a/b WiFi 5 GHz (OFDM, 18 Mbrs: 90no duty ovela)		0,39	19.0
10521	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbos 99nc duby cycle)	WIAN	7.07	10 5
10522	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbns, 99nc duty cycle)	WIAN	1,31	10.0
10523	AAD	IEEE 802.11a/h WiFI 5 GHz (OFDM, 48 Mbns, 99nc duty cycle)	WIAN	8 08	±3.0
10524	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbos, 99nc duty cycle)	WLAN	8.00	40.6
10525	AAD	IEEE 802.11ac WiFi (20 MHz, MCS0, 99oc duty cycle)	WLAN	8.36	49.6
10526	AAD	IEEE 802.11ac WiFi (20 MHz, MCS1, 99oc duty cycle)	WLAN	8.42	+9.6
10527	AAD	IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.21	+9.6
10528	AAD	IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.36	+9.6
10529	AAD	IEEE 802.11ac WiFI (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.36	+9.6
10531	AAD	IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.43	+9.6
10532	AAD	IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	+9.6
10533	AAD	IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.38	+9.6
10534	AAD	IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.45	±9.6
10535	AAD	IEEE 602.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)	WLAN	8,45	±9.6
10536	AAD	IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)	WLAN	8,32	±9.6
10537	AAD	IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)	WLAN	8,44	±9.6
10538	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.54	±9.6
10540	AAD	IEEE 802.11ac WiFI (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.39	±9.6

Certificate No: EUmm-9641_Oct24

Page 11 of 18







October 10, 2024

			1 -	1	
UID	Rev	Communication System Name	Group	PAR (dB)	$Unc^{E} k = 2$
10541	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.46	±9.6
10542	AAD	IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.65	±9.6
10543	AAD	IEEE 802.11ac WiFi (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.65	±9.6
10544	AAD	IEEE 802.11ac WiFi (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.47	±9.6
10545	AAD	IEEE 802.11ac WiFi (80 MHz, MC\$1, 99pc duty cycle)	WLAN	8.55	±9.6
10546	AAD	IEEE 802.11ac WiFi (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.35	±9.6
10547	AAD	IEEE 802.11ac WiFi (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.49	±9.6
10548	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.37	±9.6
10550	AAD	IEEE 802.11ac WiFi (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.38	±9.6
10551	AAD	IEEE 802.11ac WiFi (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.50	±9.6
10552	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.42	±9.6
10553	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.45	±9.6
10554	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.48	±9.6
10555	AAE	IEEE 802.11ac WiFi (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
10556	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.50	±9.6
10557	AAE	IEEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.52	±9.6
10558	AAE	IEEE 802.11ac WiFi (150 MHz, MCS4, 99pc duty cycle)	WLAN	8.61	±9.6
10560	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.73	±9.6
10561	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.56	±9.6
10562	AAE	IEEE 802.11ac WiFi (160 MHz, MCSB, 99pc duty cycle)	WLAN	8.69	±9.6
10563	AAE	IEEE 802.11ac WiFI (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.77	±9.6
10564	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	+9.6
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbos. 99pc duty cycle)	WLAN	8.45	+9.6
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	+9.6
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	+9.6
10568	AAA	IEEE 802.11g WIFI 2.4 GHz (DSSS-OEDM, 36 Mbps, 99pc duty cycle)	WIAN	8.37	19.6
10569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99nc duty cycle)	WLAN	8.10	19.0
10570	AAA	JEEE 802.11g WiFi 2.4 GHz (DSSS-OEDM 54 Mbrs 99pc duty cycle)	WIAN	8.30	10.0
10571	AAA	IEEE 802.11b WiEl 2.4 GHz (DSSS 1 Mbps 90cc duby cycle)	WIAN	1.00	10.0
10572	AAA	IEEE 802.115 WiFI 2.4 GHz (DSSS, 2 Mbps, 90cc duty cycla)	WIAN	1.00	10.0
10573	AAA	IEEE 802.11b WiEi 2.4 GHz (DSSS 5.5 Mbrs 90 oc duty cycle)	WIAN	1.00	10.0
10574	AAA	IEEE 802.11h WiEi 2.4 GHz (DSSS 11 Mbps 90 to duty cycla)	WI AN	1.00	19.0
10575	AAA	IEEE 802.110 WIEI 2.4 GHz (DSSS-OEDM 6 Mbps, 90pc duby cycle)	WLAN	9.50	±9.0
10576	AAA	IEEE 802.11g WIFI 2.4 GHz (DSSS-OEDM, 9 Mbps, 90pc duty cycle)	WLAN	9.55	19.0
10577	AAA	IEEE 802.11g WiEi 2.4 GHz (DSSS-OEDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	10.6
10578	AAA	IEEE 802 11g WIEI 2 4 GHz (DSSS.OEDM 18 Mbps, 90pc duty cycle)	MIAN	0.70	19.0
10579	AAA	IEEE 802.11g WIFI 2.4 GHz (DSSS-OEDM, 18 Mbps, sope duty cycle)	WLAN	0,49	19.0
10580	AAA	IEEE 802.11g WIEI 2.4 GHz (DSSS_OEDM_36 Mbps, 90ps duty cycle)	WLAN	0.30	10.C
10581	AAA	IEEE 802.11g WIEi 2.4 GHz (DSSS-OEDM 48 Mbps, 90pc duty cycle)	WIAN	0.70	10.6
10582	AAA	IFEE 802.11a WIEI 2.4 GHz (DSSS-OEDM, 64 Mbps, 90ps duby cycle)		0.00	±9.0
10583	AAD	IFEE 802.11a/h WiFi 5 GHz (DEDM & Mhos. 90os duty cycle)	MU AN	0.07	19.0
10584	AAD	IEEE 802.11a/h WiEi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.39	±9.0
10585	AAD	IEEE 802.11a/h WiEi 5 GHz (OEDM, 12 Mbps, 90ps duty cycle)	WILZIN	0.00	±9.6
10586	AAD	IEEE 802 11a/h WiEi 5 GHz (OEDM, 18 Mbps, 90pc duty cycle)	WL/UN	0.70	±9.0
10587	AAD	IEEE 802 11a/h WiEi 5 GHz (OEDM, 16 Mbps, 90pc duty cycle)		0.49	#a.e
10588	AAD	IEEE 802.11a/b WiFi 5 GHz (OEDM 36 Mbre 90as duty ovela)	WLAN	0.30	±9.0
10589	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mhps, 90ns duty cycle)	MIAN	0.70	19.0
10590	AAD	IFEE 802.11a/h WIELS GHz (OFDM 54 Mbox 90na duty cycle)		0.35	±9.6
10591	AAD	IEEE 802.11n (HT Mixed 20 MHz MCS0 90nn dubt musto)		8.67	±9.6
10592	AAD	IEEE 802.11n (HT Mixed 20 MHz MCS1 90no duty cycle)		6.63	±9.6
10593	AAD	IFFE 802.11n (HT Mixed, 20 MHz, MCS1, Sope duty cycle)	JA/LAN	8.79	±9.6
10594	AAD	IFFE 802 11n (HT Mixed 20 MHz MCS2 00 as this such)	WLAN	8.64	±9.6
10595	AAD	IFEE 802 11n (HT Mixed, 20 MHz, MCGA, 90ns that such	WLAN	8.74	±9.6
10505	AAD	IEEE 802.115 (IT Mixed, 20 MHz, MOS4, SUBC OULY CYCIB)	WLAN	8.74	±9,6
10590	AAD	IEEE 802 110 (IT Mixed, 20 MHz, MOSS, SUPC OUTY CYCle)	WLAN	8.71	±9.6
10500	AAD	IEEE 002.111 (IT Mixed, 20 MITZ, MUOD, SUDC OULY CYCle)	WLAN	8.72	±9.6
10500	AAD	IEEE 002.11n (HT Mixed, 20 MHZ, MUS7, SUDC OUTY CYCIB)	WLAN	8.50	±9,6
10000	AAD	IFEE 802.110 (HT Mixed, 40 MHz, MUSU, SUPC BULY CYCIB)	WLAN	8.79	±9,6
10601	AAD	IEEE 802.110 (HT Mixed, 40 MHz, MCC0, 00-5 duty cycle)	WLAN	8.88	±9,6
10602	AAD	IEEE 802.110 (HT Mixed, 40 MHz, MCS2, SUPC OUTY CYCIB)	WLAN	8.82	±9_6
10602	AAD	IFEE 802.110 (HT Mixed, 40 MHz, MCC4, 900 duty cycle)	WLAN	8.94	±9,6
10603	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCOS, 900-5 data such)	WLAN	9.03	±9.6
10605	AAD	IEEE 802.110 (IT Mixed, 40 MIRZ, MCS0, 900C duty cycle)	WLAN	8.76	±9,6
10606	AAD	IEEE 002.110 (IT Mixed, 40 MHz, MCS0, 90pc duty cycle)	WLAN	8.97	±9.6
10607	AAD	IEEE 002.111 (ITT WIXEU, 40 MITZ, MUSZ, SUPC OUTY CYCIB)	WLAN	8.82	±9.6
10602	AAD	IEEE 002.11ac WIEI (20 MHz, MCOU, SUPE OUTY CYCIB)	WLAN	8.64	±9,6
10000	1000	inche som i las en i (comme, modi), dope duty cycle)	1 WLAN	8.77	+96

Certificate No: EUmm-9641_Oct24

Page 12 of 18