



FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : VIVE Headset
MODEL NAME : 2Q27200
FCC ID : NM82Q27200
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Feb. 12, 2018 and testing was completed on Mar. 31, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID: NM82Q27200

Page Number : 1 of 48

Report Issued Date : Apr. 13, 2018

Report Version : Rev. 02

Report Template No.: BU5-FR15CBT4.0 Version 2.0



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	20
3.3 Power Spectral Density Measurement	21
3.4 Conducted Band Edges and Spurious Emission Measurement	30
3.5 Radiated Band Edges and Spurious Emission Measurement	39
3.6 AC Conducted Emission Measurement.....	43
3.7 Antenna Requirements.....	45
4 LIST OF MEASURING EQUIPMENT.....	46
5 UNCERTAINTY OF EVALUATION.....	48
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR821216B	Rev. 01	Initial issue of report	Apr. 12, 2018
FR821216B	Rev. 02	Revising applicant address and manufacturer address	Apr. 13, 2018



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.36 dB at 2492.520 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.83 dB at 1.523 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

HTC Corporation

NO. 88, Section 3, Zhongxing Rd., Xindian Dist, New Taipei City, Taiwan 231

1.2 Manufacturer

HTC Corporation

NO. 88, Section 3, Zhongxing Rd., Xindian Dist, New Taipei City, Taiwan 231

1.3 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, and Wi-Fi 5GHz 802.11a/n/ac

Product Specification subjective to this standard	
Antenna Type	WLAN: Dipole Antenna Bluetooth: Dipole Antenna

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Kwei-Shan District, Taoyuan City, Taiwan, R.O.C. TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH16-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: Bluetooth Link + WLAN (2.4GHz) Link + USB Cable 1 (Charging from Adapter 1)

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	iPod Earphone	Aibo	IP-E1	N/A	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
3.	Notebook	Dell	Latitude E6320	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
4.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, utility “QRCT” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<1 Mbps>

6 dB Bandwidth Plot on Channel 00




Date: 14.MAR.2018 01:23:13

6 dB Bandwidth Plot on Channel 19



Date: 14.MAR.2018 01:26:57


6 dB Bandwidth Plot on Channel 39



Date: 14.MAR.2018 01:30:16

<2 Mbps>


6 dB Bandwidth Plot on Channel 00



Date: 14.MAR.2018 01:34:45




6 dB Bandwidth Plot on Channel 19



Date: 14.MAR.2018 01:38:12

6 dB Bandwidth Plot on Channel 39



Date: 14.MAR.2018 01:41:55




3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1 Mbps>


99% Bandwidth Plot on Channel 00



Date: 14.MAR.2018 01:25:45




99% Occupied Bandwidth Plot on Channel 19



Date: 14.MAR.2018 01:28:40

99% Occupied Bandwidth Plot on Channel 39




Date: 14.MAR.2018 01:32:13



<2 Mbps>


99% Bandwidth Plot on Channel 00



Date: 14.MAR.2018 01:36:40




99% Occupied Bandwidth Plot on Channel 19



Date: 14.MAR.2018 01:40:23

99% Occupied Bandwidth Plot on Channel 39



Date: 14.MAR.2018 01:43:52

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.3 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.



3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<1 Mbps>

PSD 100kHz Plot on Channel 00



Date: 14.MAR.2018 01:23:40


PSD 100kHz Plot on Channel 19



Date: 14.MAR.2018 01:27:27



PSD 100kHz Plot on Channel 39




Date: 14.MAR.2018 01:30:51



<2 Mbps>


PSD 100kHz Plot on Channel 00



Date: 14.MAR.2018 01:35:23




PSD 100kHz Plot on Channel 19



Date: 14.MAR.2018 01:39:02

PSD 100kHz Plot on Channel 39




Date: 14.MAR.2018 01:42:35



3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<1 Mbps>

PSD 3kHz Plot on Channel 00



Date: 14.MAR.2018 01:23:27


PSD 3kHz Plot on Channel 19



Date: 14.MAR.2018 01:27:11



PSD 3kHz Plot on Channel 39




Date: 14.MAR.2018 01:30:33



<2 Mbps>


PSD 3kHz Plot on Channel 00



Date: 14.MAR.2018 01:35:05




PSD 3kHz Plot on Channel 19



Date: 14.MAR.2018 01:38:36

PSD 3kHz Plot on Channel 39



Date: 14.MAR.2018 01:42:18

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots


<1 Mbps>

Low Band Edge Plot on Channel 00



Date: 14.MAR.2018 01:23:58

High Band Edge Plot on Channel 39




Date: 14.MAR.2018 01:31:11




<2 Mbps>

Low Band Edge Plot on Channel 00



Date: 14.MAR.2018 01:35:38

High Band Edge Plot on Channel 39



Date: 14.MAR.2018 01:42:50




3.4.6 Test Result of Conducted Spurious Emission Plots

<1 Mbps>

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 14.MAR.2018 01:25:11

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00




Date: 14.MAR.2018 01:25:29



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 19



Date: 14.MAR.2018 01:27:58

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19




Date: 14.MAR.2018 01:28:23



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 39



Date: 14.MAR.2018 01:31:34

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39




Date: 14.MAR.2018 01:31:57



<2 Mbps>

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00




Date: 14.MAR.2018 01:36:00

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00




Date: 14.MAR.2018 01:36:19

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 14.MAR.2018 01:39:26

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19


Date: 14.MAR.2018 01:39:48

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39


Date: 14.MAR.2018 01:43:12

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39


Date: 14.MAR.2018 01:43:38

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.




3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB412923 44	N/A	Dec. 20, 2017	Feb. 27. 2018~ Mar. 14. 2018	Dec. 19, 2018	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US404415 48	50MHz~18GHz	Dec. 20, 2017	Feb. 27. 2018~ Mar. 14. 2018	Dec. 19, 2018	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101067	9kHz ~ 30GHz	Nov. 13, 2017	Feb. 27. 2018~ Mar. 14. 2018	Nov. 12, 2018	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~4A	Oct. 06, 2017	Feb. 27. 2018~ Mar. 14. 2018	Oct. 05, 2018	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Feb. 23, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Feb. 23, 2018	Dec. 07, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Feb. 23, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V8.4	N/A	N/A	N/A	Feb. 23, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Feb. 23, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Feb. 23, 2018	Jan. 02, 2019	Conduction (CO05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL6111D&00802N1D01N-06	47020&06	30MHz to 1GHz	Nov. 20, 2017	Mar. 08, 2018~ Mar. 31, 2018	Nov. 19, 2018	Radiation (03CH16-HY)
Horn Antenna	ESCO	3117	00211469	1GHz~18GHz	Jul. 31, 2017	Mar. 08, 2018~ Mar. 31, 2018	Jul. 30, 2018	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 27, 2017	Mar. 08, 2018~ Mar. 31, 2018	Apr. 26, 2018	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1000MHz	Sep. 27, 2017	Mar. 08, 2018~ Mar. 31, 2018	Sep. 26, 2018	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz ~ 26.5GHz	Dec. 05, 2017	Mar. 08, 2018~ Mar. 31, 2018	Dec. 04, 2018	Radiation (03CH16-HY)
Preamplifier	Jet-Power	JPA0118-55-303	1710001800054001	1GHz~18GHz	Dec. 07, 2017	Mar. 08, 2018~ Mar. 31, 2018	Dec. 06, 2018	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 05, 2017	Mar. 08, 2018~ Mar. 31, 2018	Dec. 04, 2018	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY57290111	3Hz~26.5GHz	Nov. 02, 2017	Mar. 08, 2018~ Mar. 31, 2018	Nov. 01, 2018	Radiation (03CH16-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN12	1GHz Low Pass Filter	Sep. 18, 2017	Mar. 08, 2018~ Mar. 31, 2018	Sep. 17, 2018	Radiation (03CH16-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN3	3 GHz Highpass	Jul. 06, 2017	Mar. 08, 2018~ Mar. 31, 2018	Jul. 05, 2018	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	MY1082/26EA	30M~18GHz	Oct. 17, 2017	Mar. 08, 2018~ Mar. 31, 2018	Oct. 16, 2018	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Oct. 17, 2017	Mar. 08, 2018~ Mar. 31, 2018	Oct. 16, 2018	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40GHz	Oct. 17, 2017	Mar. 08, 2018~ Mar. 31, 2018	Oct. 16, 2018	Radiation (03CH16-HY)
Software	AUDIX	E3 6.2009-8-24	RK001136	N/A	N/A	Mar. 08, 2018~ Mar. 31, 2018	N/A	Radiation (03CH16-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.80
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.90
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Kai Liao	Temperature:	21~25	°C
Test Date:	2018/02/27 ~ 2018/03/14	Relative Humidity:	51~54	%

<1Mbps>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.030	0.656	0.50	Pass
BLE	1Mbps	1	19	2440	1.028	0.656	0.50	Pass
BLE	1Mbps	1	39	2480	1.030	0.660	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	5.93	30.00	-5.00	0.93	36.00	Pass
BLE	1Mbps	1	19	2440	6.24	30.00	-5.00	1.24	36.00	Pass
BLE	1Mbps	1	39	2480	6.32	30.00	-5.00	1.32	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.06	5.43
BLE	1Mbps	1	19	2440	2.06	5.84
BLE	1Mbps	1	39	2480	2.06	5.83

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.17	-8.73	-5.00	8.00	Pass
BLE	1Mbps	1	19	2440	6.52	-8.36	-5.00	8.00	Pass
BLE	1Mbps	1	39	2480	6.47	-8.46	-5.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

<2Mbps>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	2.040	1.128	0.50	Pass
BLE5.0	2Mbps	1	19	2440	2.040	1.128	0.50	Pass
BLE5.0	2Mbps	1	39	2480	2.040	1.136	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	0	2402	6.03	30.00	0.00	6.03	36.00	Pass
BLE5.0	2Mbps	1	19	2440	6.48	30.00	0.00	6.48	36.00	Pass
BLE5.0	2Mbps	1	39	2480	6.41	30.00	0.00	6.41	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE5.0	2Mbps	1	0	2402	4.88	5.38
BLE5.0	2Mbps	1	19	2440	4.88	5.80
BLE5.0	2Mbps	1	39	2480	4.88	5.81

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE5.0	2Mbps	1	0	2402	6.15	-12.22	0.00	8.00	Pass
BLE5.0	2Mbps	1	19	2440	6.53	-11.86	0.00	8.00	Pass
BLE5.0	2Mbps	1	39	2480	6.45	-11.89	0.00	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Blue Lan	Temperature :	24~25℃
		Relative Humidity :	51~53%

EUT Information

Report NO : 821216
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	29.43	55.75	26.32	L1	OFF	19.5
0.154500	45.87	---	65.75	19.88	L1	OFF	19.5
0.307500	---	33.99	50.04	16.05	L1	OFF	19.5
0.307500	40.00	---	60.04	20.04	L1	OFF	19.5
0.924000	---	32.63	46.00	13.37	L1	OFF	19.5
0.924000	38.07	---	56.00	17.93	L1	OFF	19.5
1.536000	---	33.17	46.00	12.83	L1	OFF	19.6
1.536000	36.70	---	56.00	19.30	L1	OFF	19.6
4.017750	---	31.14	46.00	14.86	L1	OFF	19.6
4.017750	35.28	---	56.00	20.72	L1	OFF	19.6
4.607250	---	30.70	46.00	15.30	L1	OFF	19.6
4.607250	35.17	---	56.00	20.83	L1	OFF	19.6
15.972000	---	31.86	50.00	18.14	L1	OFF	19.8
15.972000	36.38	---	60.00	23.62	L1	OFF	19.8

EUT Information

Report NO : 821216
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	31.01	55.88	24.87	N	OFF	19.5
0.152250	51.36	---	65.88	14.52	N	OFF	19.5
0.307500	---	31.73	50.04	18.31	N	OFF	19.5
0.307500	36.77	---	60.04	23.27	N	OFF	19.5
0.503250	---	25.28	46.00	20.72	N	OFF	19.5
0.503250	28.37	---	56.00	27.63	N	OFF	19.5
0.926250	---	30.48	46.00	15.52	N	OFF	19.5
0.926250	34.71	---	56.00	21.29	N	OFF	19.5
3.995250	---	28.59	46.00	17.41	N	OFF	19.6
3.995250	32.05	---	56.00	23.95	N	OFF	19.6
5.237250	---	25.40	50.00	24.60	N	OFF	19.6
5.237250	28.70	---	60.00	31.30	N	OFF	19.6
16.590750	---	28.94	50.00	21.06	N	OFF	19.8
16.590750	33.77	---	60.00	26.23	N	OFF	19.8



Appendix C. Radiated Spurious Emission

Test Engineer :	Peter Liao and Andy Yang	Temperature :	23~25°C
		Relative Humidity :	57~62%



<1Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2368.065	59.59	-14.41	74	40.91	32.13	16.54	29.99	203	357	P	H
		2372.58	49.31	-4.69	54	30.59	32.16	16.55	29.99	203	357	A	H
	*	2402	103.28	-	-	84.5	32.18	16.59	29.99	203	357	P	H
	*	2402	102.76	-	-	83.98	32.18	16.59	29.99	203	357	A	H
													H
													H
		2386.44	59.88	-14.12	74	41.12	32.18	16.57	29.99	383	62	P	V
		2363.445	49.12	-4.88	54	30.45	32.13	16.54	30	383	62	A	V
	*	2402	99.8	-	-	81.02	32.18	16.59	29.99	383	62	P	V
	*	2402	99.22	-	-	80.44	32.18	16.59	29.99	383	62	A	V
													V
													V
BLE CH 19 2440MHz		2343.6	58.85	-15.15	74	40.23	32.11	16.51	30	217	358	P	H
		2366.56	49.37	-4.63	54	30.69	32.13	16.54	29.99	217	358	A	H
	*	2440	103.18	-	-	84.27	32.24	16.65	29.98	217	358	P	H
	*	2440	102.61	-	-	83.7	32.24	16.65	29.98	217	358	A	H
		2497.69	59.43	-14.57	74	40.36	32.3	16.73	29.96	217	358	P	H
		2496.92	49.45	-4.55	54	30.38	32.3	16.73	29.96	217	358	A	H
		2355.92	58.99	-15.01	74	40.34	32.13	16.52	30	122	322	P	V
		2358.3	48.86	-5.14	54	30.2	32.13	16.53	30	122	322	A	V
	*	2440	97.04	-	-	78.13	32.24	16.65	29.98	122	322	P	V
	*	2440	96.56	-	-	77.65	32.24	16.65	29.98	122	322	A	V
		2496.01	59.09	-14.91	74	40.02	32.3	16.73	29.96	122	322	P	V
		2488.03	49.28	-4.72	54	30.23	32.3	16.72	29.97	122	322	A	V



BLE CH 39 2480MHz	*	2480	101.65	-	-	82.63	32.28	16.71	29.97	204	358	P	H
	*	2480	101.05	-	-	82.03	32.28	16.71	29.97	204	358	A	H
		2483.68	59.34	-14.66	74	40.32	32.28	16.71	29.97	204	358	P	H
		2492.52	49.64	-4.36	54	30.58	32.3	16.72	29.96	204	358	A	H
													H
													H
	*	2480	97.39	-	-	78.37	32.28	16.71	29.97	392	67	P	V
	*	2480	96.79	-	-	77.77	32.28	16.71	29.97	392	67	A	V
		2486.76	59.92	-14.08	74	40.89	32.28	16.72	29.97	392	67	P	V
		2492.12	49.39	-4.61	54	30.33	32.3	16.72	29.96	392	67	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	43.8	-30.2	74	57.62	34	10.72	58.54	100	0	P	H
													H
													H
													H
		4804	40.87	-33.13	74	54.69	34	10.72	58.54	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	48.42	-25.58	74	62.13	34	10.81	58.52	100	0	P	H
		7320	41.97	-32.03	74	52.02	35.77	13.14	58.96	100	0	P	H
													H
													H
		4880	43.06	-30.94	74	56.77	34	10.81	58.52	100	0	P	V
		7320	41.85	-32.15	74	51.9	35.77	13.14	58.96	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	51.42	-22.58	74	65.03	34	10.9	58.51	247	336	P	H
		4960	48.09	-5.91	54	61.7	34	10.9	58.51	247	336	A	H
		7440	41.69	-32.31	74	51.57	35.79	13.18	58.85	100	0	P	H
													H
		4960	44.7	-29.3	74	58.31	34	10.9	58.51	100	0	P	V
		7440	41.26	-32.74	74	51.14	35.79	13.18	58.85	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		32.16	24.47	-15.53	40	31.09	25.04	0.79	32.45	-	-	P	H
		215.49	33.16	-10.34	43.5	47.21	16.3	2.07	32.42	-	-	P	H
		266.52	41.52	-4.48	46	52.13	19.52	2.31	32.44	100	317	QP	H
	!	266.52	47.7	1.7	46	58.31	19.52	2.31	32.44	100	317	P	H
		315.4	40.07	-5.93	46	49.88	20.16	2.5	32.47	-	-	P	H
		781.6	31.99	-14.01	46	32.55	27.95	3.95	32.46	-	-	P	H
		995.8	32.7	-21.3	54	29.29	29.92	4.48	30.99	-	-	P	H
													H
													H
													H
													H
													H
		34.05	33.7	-6.3	40	41.47	23.88	0.8	32.45	100	0	P	V
		207.66	26.77	-16.73	43.5	40.9	16.25	2.03	32.41	-	-	P	V
		266.79	35.17	-10.83	46	45.78	19.52	2.31	32.44	-	-	P	V
		314.7	32.93	-13.07	46	42.74	20.16	2.5	32.47	-	-	P	V
		703.2	31.16	-14.84	46	33.43	26.66	3.73	32.66	-	-	P	V
		889.4	34.88	-11.12	46	33.65	28.94	4.22	31.93	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2383.815	49.56	-24.44	74	40.74	32.16	6.65	29.99	346	359	P	H
		2338.245	41.31	-12.69	54	32.63	32.11	6.58	30.01	346	359	A	H
	*	2402	101.97	-	-	93.11	32.18	6.67	29.99	346	359	P	H
	*	2402	100.76	-	-	91.9	32.18	6.67	29.99	346	359	A	H
													H
													H
		2317.245	49.36	-24.64	74	40.75	32.07	6.55	30.01	175	318	P	V
		2315.355	40.92	-13.08	54	32.32	32.07	6.54	30.01	175	318	A	V
	*	2402	96.04	-	-	87.18	32.18	6.67	29.99	175	318	P	V
	*	2402	94.76	-	-	85.9	32.18	6.67	29.99	175	318	A	V
													V
													V
BLE CH 19 2440MHz		2354.94	49.56	-24.44	74	40.83	32.13	6.6	30	298	359	P	H
		2362.92	41.13	-12.87	54	32.39	32.13	6.61	30	298	359	A	H
	*	2440	101.46	-	-	92.47	32.24	6.73	29.98	298	359	P	H
	*	2440	100.13	-	-	91.14	32.24	6.73	29.98	298	359	A	H
		2485.93	49.23	-24.77	74	40.13	32.28	6.79	29.97	298	359	P	H
		2499.3	41.16	-12.84	54	32.01	32.3	6.81	29.96	298	359	A	H
		2376.92	49.37	-24.63	74	40.56	32.16	6.64	29.99	119	309	P	V
		2323.44	40.69	-13.31	54	32.05	32.09	6.56	30.01	119	309	A	V
	*	2440	96.31	-	-	87.32	32.24	6.73	29.98	119	309	P	V
	*	2440	95.09	-	-	86.1	32.24	6.73	29.98	119	309	A	V
		2496.36	50.23	-23.77	74	41.08	32.3	6.81	29.96	119	309	P	V
		2493.28	41.48	-12.52	54	32.33	32.3	6.81	29.96	119	309	A	V



BLE CH 39 2480MHz	*	2480	101.21	-	-	92.11	32.28	6.79	29.97	206	353	P	H
	*	2480	99.23	-	-	90.13	32.28	6.79	29.97	206	353	A	H
		2483.56	53.1	-20.9	74	44	32.28	6.79	29.97	206	353	P	H
		2483.52	41.87	-12.13	54	32.77	32.28	6.79	29.97	206	353	A	H
													H
													H
	*	2480	94.95	-	-	85.85	32.28	6.79	29.97	147	323	P	V
	*	2480	93.61	-	-	84.51	32.28	6.79	29.97	147	323	A	V
		2493.88	49.94	-24.06	74	40.79	32.3	6.81	29.96	147	323	P	V
		2497.04	41.26	-12.74	54	32.11	32.3	6.81	29.96	147	323	A	V
													V
													V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	43.82	-30.18	74	57.64	34	10.72	58.54	100	0	P	H
													H
													H
													H
		4804	40.45	-33.55	74	54.27	34	10.72	58.54	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	47.68	-26.32	74	61.39	34	10.81	58.52	100	0	P	H
		7320	43.45	-30.55	74	53.5	35.77	13.14	58.96	100	0	P	H
													H
													H
		4880	44.02	-29.98	74	57.73	34	10.81	58.52	100	0	P	V
		7320	42.5	-31.5	74	52.55	35.77	13.14	58.96	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	51.11	-22.89	74	64.72	34	10.9	58.51	246	335	P	H
		4960	47.02	-6.98	54	60.63	34	10.9	58.51	246	335	A	H
		7440	42.45	-31.55	74	52.33	35.79	13.18	58.85	100	0	P	H
													H
		4960	44.81	-29.19	74	58.42	34	10.9	58.51	100	0	P	V
		7440	41.93	-32.07	74	51.81	35.79	13.18	58.85	100	0	P	V
													V
													V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)

2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Peter Liao and Andy Yang	Temperature :	23~25°C
		Relative Humidity :	57~62%

Note symbol





-L	Low channel location
-R	High channel location







<1Mbps>





2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 4	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 4
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 4	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 4







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 4	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 4
Avg	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 4	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 4

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HV Condition : PEAK_BE_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 5	 Site : 03CH16-HV Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 5
Avg.	 Site : 03CH16-HV Condition : AVG_BE_54 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 5	 Site : 03CH16-HV Condition : AVG_54 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 5









BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_0021469 HORIZONTAL Detector : Peak Project : 821216 Mode : 5	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_0021469 HORIZONTAL Detector : Peak Project : 821216 Mode : 5	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 5	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 5
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 5	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 5





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 5	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 5	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 6	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 6
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 6	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 6

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : R21216 Mode : 6	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : R21216 Mode : 6
	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : R21216 Mode : 6	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : R21216 Mode : 6



2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-1FY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 4	 Site : 03CH16-1FY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 4

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : B21216 Mode : S	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : B21216 Mode : S







BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 6	Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 6

Emission below 1GHz
2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH16-HY Condition : QP 3m BTL06_47020406 HORIZONTAL Detector : Peak Project : 821216 Mode : 29	 Site : 03CH16-HY Condition : QP 3m BTL06_47020406 VERTICAL Detector : Peak Project : 821216 Mode : 29





<2Mbps>
2.4GHz 2400~2483.5MHz
BLE (Band Edge @ 3m)



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 7	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 7
	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 7	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 821216 Mode : 7







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 7	Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 7
Avg	Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 7	Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 7









BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HV Condition : PEAK_BE_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 8	 Site : 03CH16-HV Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 8
Avg.	 Site : 03CH16-HV Condition : AVG_BE_54 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 8	 Site : 03CH16-HV Condition : AVG_54 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 8

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 8	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 8	Left blank





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 8	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 8
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 8	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 8





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 8	Left blank
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 8	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9
	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 HORIZONTAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH16-HY Condition : PEAK_BE_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9
Avg.	 Site : 03CH16-HY Condition : AVG_BE_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9	 Site : 03CH16-HY Condition : AVG_54 3m HORN_3117_00211469 VERTICAL RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 821216 Mode : 9

2.4GHz 2400~2483.5MHz
BLE (Harmonic @ 3m)


BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-1FY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 7	 Site : 03CH16-1FY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 7

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 8	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 8


BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 HORIZONTAL Detector : Peak Project : 821216 Mode : 9	 Site : 03CH16-HY Condition : PEAK_74 3m HORN_3117_00211469 VERTICAL Detector : Peak Project : 821216 Mode : 9

Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
Bluetooth LE for 1 Mbps	62.18	388	2.58	3kHz	2.06
Bluetooth LE for 2 Mbps	32.48	204	4.90	10kHz	4.88

Bluetooth - LE
<1 Mbps>


Date: 27.FEB.2018 19:12:47

<2 Mbps>


Date: 27.FEB.2018 19:15:30