

ALS BETRIEBSGEHEIMNIS ANVERTRAUT. ALLE RECHTE VORBEHALTEN. PROPRIETARY DATA, COMPANY CONFIDENTIAL. ALL RIGHTS RESERVED.

White label with black lettering

1) 2) 3) 4) 5) 6) 7) 8) 9) 10)

SIEMENS SL65 Made xx xxxxxxxx

S30880-SXXXX-XXXX YY

CE 0168 FCC ID: PWX-SL65
IC: 267E-SL65

XXXXXXXX SSSSSS C

10) XXXXXXXX Typ-Approval Code TAC
10) SSSSSS Current serial number (6 digits), Assigned by PICS
10) C CHECK DIGIT 15. digit
space between TAC, serial no. and 15.digit

Ink ribbon: TTR-Band Ricoh 110-C

Font: Title blocks concentric

1) Corporate logo: 1.5 SN 66324
2) Product name: Internal font B, size 3
3) Made xx xxxxxxx: Internal font A, size 4 / Depending on production location
4) Code of date: Internal font D, size 4
e.g. F3 — March
1995
5) Code number: Internal font D, size 4
6) CE - identification: Height: 5mm
7) Barcode IMEI-no.: Code: 128 Size 2 Ratio: 3.0 Height: 3mm
Typ 128, table C and B
Characteristic: IMEI-No. has 15 digits
Digit 1-14 is generated as Barcode with table C.
Digit 15 is printed with table B.
8) IMEI-no. (plain writing): Internal font D, size 4, space between TAC,serial no. and 15.digit
9) Canada IC and US FCC: Internal font B, size 3
10) Document for IMEI-no. allocation: DIS - 74300-* BOM 000 xx
Valid is the highest level in the system

				Date	14.05.2004	MOBILE PHONE IMEI-LABEL/SL65/STD	BNR
				Name	Endres		
					PD HW4 MCH2		
1		14.05.04	End			LETTERING PLAN	
Version	Memorandum	Date	Token	SIEMENS AG		DIS 75364	BLATT 1 VON 1

A24850-V1-A4-2

VORSTD.DOC

