



FCC SAR TEST REPORT

The following samples were submitted and identified on behalf of the client as:

EUT Description GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac, GPS and NFC
Company Name Sony Corporation
Company Address 1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
Standards IEEE/ANSI C95.1-1992, IEEE 1528-2013, KDB 248227D01v02r02,
KDB 865664 D01v01r04, KDB 865664 D02v01r02, KDB 941225 D01v03r01,
KDB 941225 D06v02r01, KDB 447498 D01v06, KDB 941225 D05v02r05,
KDB 648474 D04 v01r03
FCC ID PY7-63649Q
Date of Receipt: 2020-12-23
Date of Test: 2021-03-17 to 2021-03-22
Date of Issue: 2021-03-31
Test Result: **PASS ***

In the configuration tested, the EUT complied with the standards specified above.

Remarks:

This report details the results of the testing carried out on one sample, the results contained in this test do not relate to other samples of the same product. The manufacturer should ensure that all production series production are in conformity with the product sample detailed in this report.

Signed on behalf of SGS

Sr. Engineer

Jackson Li

Date: Mar. 31, 2021

Supervisor

Simon Ling

Date: Mar. 31, 2021

Authorized Signature:

Derek Yang

Derek Yang

Wireless Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

REVISION HISTORY

Report Number	Revision	Description	Issue Date
ZR/2020/C004701	01	Original	2021-03-31





CONTENTS

1	General Information	4
1.1	Testing Laboratory	4
1.2	Details of Applicant	4
1.3	Test Facility	5
1.4	Description of EUT	6
1.5	Test Environment.....	29
1.6	Operation Description	29
1.7	Positioning Procedure.....	42
1.8	Evaluation Procedures	44
1.9	Probe Calibration Procedures.....	45
1.9.1	Transfer Calibration with Temperature Probes.....	45
1.9.2	Calibration with Analytical Fields.....	46
1.10	The SAR Measurement System	47
1.11	System Component	48
1.12	SAR System Check.....	52
1.13	Tissue Simulant Fluid for the Frequency Band	54
1.14	Test Standards and Limits	56
2	Summary of Results	58
3	Simultaneous Transmission Analysis.....	68
3.1	Simultaneous Transmission Scenarios:	68
3.2	Simultaneous Transmission Combination Scenario	69
4	Instruments List	70
5	Measurements	72
6	SAR System Performance Check	72
7	Photographs	72
8	DAE & Probe Calibration Certificate.....	72
9	SAR measurement variability and uncertainty	73





1 General Information

1.1 Testing Laboratory

Company:	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address:	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code:	518057
Telephone:	+86 (0) 755 2601 2053
Fax:	+86 (0) 755 2671 0594

1.2 Details of Applicant

Applicant:	Sony Corporation
Address:	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
Manufacturer:	Sony Corporation
Address:	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan



1.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

• **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Industry Canada (IC)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006

IC#: 4620C.



1.4 Description of EUT

EUT Description	GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac, GPS and NFC			
FCC ID	PY7-63649Q			
SN:	005129ADNVM2			
Mode of Operation	<input checked="" type="checkbox"/> GSM <input checked="" type="checkbox"/> GPRS <input checked="" type="checkbox"/> EGPRS <input checked="" type="checkbox"/> WCDMA <input checked="" type="checkbox"/> HSDPA <input checked="" type="checkbox"/> DC-HSDPA <input checked="" type="checkbox"/> HSUPA <input checked="" type="checkbox"/> HSPA+ <input checked="" type="checkbox"/> LTE FDD <input checked="" type="checkbox"/> LTE TDD <input checked="" type="checkbox"/> WIFI 2.4G 802.11 b/g/n(20M) <input checked="" type="checkbox"/> WIFI 5G 802.11 a(20M)/ac(20M/40M/80M)/n(20M/40M) <input checked="" type="checkbox"/> Bluetooth			
Duty Cycle	GSM	1/8.3		
	GPRS (support multi class 33 max)	1/2.075 (1Dn4UP) 1/2.77 (1Dn3UP) 1/4.15 (1Dn2UP) 1/8.3 (1Dn1UP)		
	LTE FDD	1:1		
	LTE TDD	1:1.58		
	WCDMA	1:1		
	WLAN802.11 b	99%		
	WLAN802.11 ac 80M	94%		
	Bluetooth	77%		
TX Frequency Range (MHz)	GSM850	824	—	849
	GSM1900	1850	—	1910
	WCDMA Band IV	1710	—	1755
	LTE FDD Band 4	1710	—	1755
	LTE FDD Band 12	698	—	716
	LTE TDD Band 41	2496	—	2690
	WiFi 2.4GHz	2412	—	2462
	WiFi 5GHz	5150	—	5250
		5250	—	5350
		5470	—	5725
		5725	—	5850
	Bluetooth	2402	—	2480

Note: This project WLAN 5GHz (5250-5350 & 5470-5725) does not support Hotspot.



TEST SUMMARY

Frequency Band	Maximum Reported SAR(W/kg)			
	Head	Body-worn	Hotspot	Product specific 10g SAR
GSM850	0.41	0.36	0.54	/
GSM1900	0.16	0.13	0.29	/
WCDMA Band IV	0.12	0.16	0.34	/
LTE Band 4	0.09	0.10	0.23	/
LTE Band 12	0.21	0.36	0.41	/
LTE Band 41	0.13	0.52	0.96	/
WI-FI (2.4GHz)	0.56	0.08	0.17	/
WI-FI (5GHz)	0.56	0.23	0.29	1.15
BT	0.21	0.03	0.07	/
SAR Limited(W/kg)	1.6			
Maximum Simultaneous Transmission SAR (W/kg)				
Scenario	Head	Body-worn	Hotspot	Product specific 10g SAR
Sum SAR	1.03	0.78	1.32	1.15
SPLSR	N/A	N/A	N/A	NA
SPLSR Limited	0.04			

DUT Antenna Locations:

Please see the Appendix D for antenna locations.

The test device is a mobile phone. The overall diagonal dimension of this device is 163.0 mm. Per KDB 648474 D04, because the diagonal distance of this device is $\geq 160\text{mm}$, so it is a phablet.

According to the distance between LTE/WCDMA/GSM&WIFI&BT antennas and the sides of the EUT we can draw the conclusion that:

EUT Sides for SAR Testing						
Mode	Front	Back	Left	Right	Top	Bottom
Main Ant (Ant0 & Ant1)	Yes	Yes	Yes	Yes	No	Yes
WIFI&BT Ant (Ant6 & Ant7)	Yes	Yes	Yes	Yes	Yes	No

Table 1 : EUT Sides for SAR Testing

Note:

- 1) When the antenna-to-edge distance is greater than 2.5cm, such position does not need to be tested.



Power reduction by country code detection mechanism:

This device uses the mobile country code (MCC) to indicate whether the users in CE countries or FCC countries. The selection between CE countries and FCC countries power levels is based on the country code detection mechanism. It can determine the countries where users are and set the relevant power level for 2/3/4G/WiFi 2.4G antenna accordingly.

Antenna Power Level (dBm)	
Band	MCC OF FCC COUNTRY (FCC standard)
GSM1900	28.0
WCDMA Band IV	23.0
LTE Band 4	21.5
LTE Band 41	22.8
WiFi 2.4G 802.11b	19.0
WiFi 2.4G 802.11g	18.0
WiFi 2.4G 802.11n 20M	18.0

For FCC SAR test:

For FCC SAR test, SAR test should be evaluated at the power level of FCC mobile country code for each exposure conditions.



GSM – conducted power table:

GSM 850										
Burst Output Power(dBm)					Tune up	Division Factors	Frame-Average Output Power(dBm)			Tune up
Channel		128	190	251			128	190	251	
GSM(GMSK)	GSM	32.74	32.69	32.61	33.50	-9.19	23.55	23.50	23.42	24.31
GPRS/EGPRS (GMSK)	1 TX Slot	32.70	32.72	32.67	33.50	-9.19	23.51	23.53	23.48	24.31
	2 TX Slots	29.97	30.00	29.95	31.50	-6.18	23.79	23.82	23.77	25.32
	3 TX Slots	29.16	29.10	29.10	30.00	-4.42	24.74	24.68	24.68	25.58
	4 TX Slots	27.67	27.70	27.64	29.00	-3.17	24.50	24.53	24.47	25.83
EGPRS(8PSK)	1 TX Slot	26.26	26.34	26.42	27.00	-9.19	17.07	17.15	17.23	17.81
	2 TX Slots	25.04	24.97	24.97	25.50	-6.18	18.86	18.79	18.79	19.32
	3 TX Slots	24.34	24.28	24.27	24.50	-4.42	19.92	19.86	19.85	20.08
	4 TX Slots	23.13	23.13	23.07	23.50	-3.17	19.96	19.96	19.90	20.33
GSM 1900										
Burst Output Power(dBm)					Tune up	Division Factors	Frame-Average Output Power(dBm)			Tune up
Channel		512	661	810			512	661	810	
GSM(GMSK)	GSM	27.27	26.95	27.15	28.00	-9.19	18.08	17.76	17.96	18.81
GPRS/EGPRS (GMSK)	1 TX Slot	27.05	26.97	26.92	28.00	-9.19	17.86	17.78	17.73	18.81
	2 TX Slots	25.83	25.90	25.88	27.00	-6.18	19.65	19.72	19.70	20.82
	3 TX Slots	24.61	24.54	24.63	25.00	-4.42	20.19	20.12	20.21	20.58
	4 TX Slots	22.19	22.19	22.18	24.00	-3.17	19.02	19.02	19.01	20.83
EGPRS(8PSK)	1 TX Slot	23.87	23.87	23.80	24.50	-9.19	14.68	14.68	14.61	15.31
	2 TX Slots	21.58	21.64	21.61	23.50	-6.18	15.40	15.46	15.43	17.32
	3 TX Slots	19.58	19.54	19.60	21.50	-4.42	15.16	15.12	15.18	17.08
	4 TX Slots	18.50	18.56	18.59	20.50	-3.17	15.33	15.39	15.42	17.33

Note:

- 1) . CMW500 measures GSM peak and average output power for active timeslots. For SAR the time based average power is relevant. The difference in between depends on the duty cycle of the TDMA signal:

No. of timeslots	1	2	3	4
Duty Cycle	1:8.3	1:4.15	1:2.77	1:2.075
Time based avg. power compared to slotted avg. power	-9.19	-6.18	-4.42	-3.17

- 2) . The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

$$\text{Frame-averaged power} = 10 \times \log (\text{Burst-averaged power mW} \times \text{Slot used} / 8)$$

- 3) . When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel must be used



WCDMA - conducted power table:

WCDMA Band IV					
Average Conducted Power(dBm)					
Channel		1312	1412	1513	Tune up
WCDMA	12.2kbps RMC	21.95	21.82	22.21	23.00
	12.2kbps AMR	21.93	21.80	22.19	23.00
HSDPA	Subtest 1	20.64	20.54	20.52	21.50
	Subtest 2	21.00	20.84	20.85	21.50
	Subtest 3	20.29	20.20	20.27	21.00
	Subtest 4	20.33	20.14	20.32	21.00
HSUPA	Subtest 1	20.76	20.73	20.80	21.50
	Subtest 2	18.93	18.50	18.63	19.50
	Subtest 3	19.94	19.64	19.55	20.50
	Subtest 4	18.85	18.60	18.75	19.50
	Subtest 5	20.69	20.66	20.88	21.50
DC-HSDPA	Subtest 1	20.71	20.58	20.71	21.50
	Subtest 2	20.98	20.65	20.97	21.50
	Subtest 3	20.42	20.43	20.48	21.00
	Subtest 4	20.21	20.00	20.15	21.00
HSPA+	16QAM	19.97	19.90	19.89	20.50





LTE - conducted power table:

LTE Band 4				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19957	20175	20393	
1.4MHz	QPSK	1	0	19.85	19.94	20.26	21.50
		1	2	19.98	20.09	20.32	21.50
		1	5	19.95	20.06	20.31	21.50
		3	0	19.91	20.02	20.30	21.50
		3	2	20.07	20.10	20.36	21.50
		3	3	19.88	19.98	20.22	21.50
		6	0	18.98	19.03	19.34	20.50
	16QAM	1	0	19.57	19.27	19.48	20.50
		1	2	19.71	19.47	19.89	20.50
		1	5	19.12	19.24	19.32	20.50
		3	0	18.98	19.17	19.41	20.50
		3	2	19.02	19.13	19.48	20.50
		3	3	19.09	19.11	19.47	20.50
		6	0	18.10	18.06	18.27	19.50
	64QAM	1	0	18.59	18.98	18.73	19.50
		1	2	18.56	18.64	18.59	19.50
		1	5	18.50	18.78	18.49	19.50
		3	0	18.57	18.35	18.53	19.50
		3	2	18.55	18.70	18.67	19.50
		3	3	18.35	18.62	18.53	19.50
		6	0	17.54	17.64	17.60	18.50
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19965	20175	20385	
3MHz	QPSK	1	0	20.03	20.05	20.30	21.50
		1	7	19.98	20.04	20.40	21.50
		1	14	20.12	20.14	20.26	21.50
		8	0	19.13	19.11	19.41	20.50
		8	4	19.07	19.14	19.40	20.50
		8	7	19.04	19.17	19.35	20.50
		15	0	19.12	19.22	19.39	20.50
	16QAM	1	0	19.71	19.62	19.44	20.50
		1	7	19.42	19.07	19.97	20.50
		1	14	19.61	19.44	20.04	20.50
		8	0	18.21	18.29	18.33	19.50
		8	4	18.19	18.34	18.42	19.50
		8	7	18.09	18.20	18.44	19.50



		15	0	18.10	18.13	18.42	19.50
	64QAM	1	0	18.92	18.54	18.58	19.50
		1	7	18.68	19.05	18.83	19.50
		1	14	18.62	18.56	18.40	19.50
		8	0	17.52	17.53	17.47	18.50
		8	4	17.50	17.75	17.57	18.50
		8	7	17.42	17.56	17.62	18.50
		15	0	17.43	17.67	17.58	18.50
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				19975	20175	20375	
5MHz	QPSK	1	0	19.99	20.15	20.28	21.50
		1	13	20.02	20.11	20.45	21.50
		1	24	20.09	20.06	20.37	21.50
		12	0	19.03	19.13	19.48	20.50
		12	6	19.13	19.13	19.45	20.50
		12	13	19.11	19.13	19.43	20.50
		25	0	19.14	19.13	19.51	20.50
	16QAM	1	0	19.22	19.62	19.92	20.50
		1	13	19.08	19.23	19.63	20.50
		1	24	19.36	19.17	20.05	20.50
		12	0	18.19	18.21	18.48	19.50
		12	6	18.22	18.16	18.46	19.50
		12	13	18.15	18.15	18.56	19.50
		25	0	18.11	18.14	18.56	19.50
	64QAM	1	0	18.91	18.53	18.57	19.50
		1	13	18.64	19.01	18.79	19.50
		1	24	18.61	18.55	18.39	19.50
		12	0	17.56	17.57	17.51	18.50
		12	6	17.48	17.73	17.55	18.50
		12	13	17.39	17.53	17.59	18.50
		25	0	17.46	17.70	17.61	18.50
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20000	20175	20350	
10MHz	QPSK	1	0	19.94	20.04	20.14	21.50
		1	25	19.84	20.09	20.35	21.50
		1	49	19.99	19.98	20.11	21.50
		25	0	19.11	19.16	19.37	20.50
		25	13	19.14	19.19	19.38	20.50
		25	25	19.00	19.24	19.38	20.50
		50	0	19.08	19.13	19.35	20.50
	16QAM	1	0	19.14	19.64	19.31	20.50
		1	25	19.15	19.64	19.19	20.50



		1	49	19.60	19.49	19.91	20.50
		25	0	18.12	18.25	18.44	19.50
		25	13	18.13	18.30	18.47	19.50
		25	25	17.96	18.14	18.38	19.50
		50	0	18.12	18.18	18.30	19.50
	64QAM	1	0	18.93	18.55	18.59	19.50
		1	25	18.68	19.05	18.83	19.50
		1	49	18.64	18.58	18.42	19.50
		25	0	17.53	17.54	17.48	18.50
		25	13	17.51	17.76	17.58	18.50
		25	25	17.40	17.54	17.60	18.50
		50	0	17.43	17.67	17.58	18.50
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20025	20175	20325	
15MHz	QPSK	1	0	19.92	19.88	20.06	21.50
		1	38	19.78	19.84	20.12	21.50
		1	74	19.77	19.84	20.12	21.50
		36	0	18.94	19.03	19.11	20.50
		36	18	18.94	19.06	19.29	20.50
		36	39	18.85	19.01	19.21	20.50
		75	0	18.86	19.00	19.18	20.50
	16QAM	1	0	18.87	19.23	19.18	20.50
		1	38	19.40	19.09	19.29	20.50
		1	74	19.32	18.97	19.37	20.50
		36	0	17.93	18.04	18.16	19.50
		36	18	17.85	17.98	18.30	19.50
		36	39	17.85	18.08	18.21	19.50
		75	0	17.80	18.01	18.15	19.50
	64QAM	1	0	18.89	18.51	18.55	19.50
		1	38	18.68	19.05	18.83	19.50
		1	74	18.62	18.56	18.40	19.50
		36	0	17.54	17.55	17.49	18.50
		36	18	17.44	17.69	17.51	18.50
		36	39	17.37	17.51	17.57	18.50
		75	0	17.35	17.59	17.50	18.50
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				20050	20175	20300	
20MHz	QPSK	1	0	19.86	19.84	20.01	21.50
		1	50	19.68	20.15	20.11	21.50
		1	99	19.79	19.80	20.07	21.50
		50	0	18.90	19.27	19.00	20.50
		50	25	18.88	18.95	19.16	20.50



	16QAM	50	50	18.80	18.93	19.19	20.50
		100	0	18.88	18.97	18.95	20.50
		1	0	18.75	19.10	19.22	20.50
		1	50	19.27	19.20	19.00	20.50
		1	99	19.33	19.10	19.35	20.50
		50	0	17.92	17.87	18.03	19.50
		50	25	17.86	18.00	18.09	19.50
		50	50	17.75	17.91	18.14	19.50
		100	0	17.89	17.98	18.15	19.50
	64QAM	1	0	18.89	18.51	18.55	19.50
		1	50	18.54	18.91	18.69	19.50
		1	99	18.65	18.59	18.43	19.50
		50	0	17.44	17.45	17.39	18.50
		50	25	17.39	17.64	17.46	18.50
		50	50	17.37	17.51	17.57	18.50
		100	0	17.39	17.63	17.54	18.50

LTE Band 12				Conducted Power(dBm)			
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23017	23095	23173	
1.4MHz	QPSK	1	0	23.24	23.17	23.30	24.50
		1	2	23.08	23.28	23.18	24.50
		1	5	22.91	23.14	23.17	24.50
		3	0	23.38	23.29	23.27	24.50
		3	2	23.25	23.13	23.22	24.50
		3	3	23.25	23.18	23.16	24.50
		6	0	22.34	22.35	22.44	23.50
	16QAM	1	0	22.73	22.91	22.86	23.50
		1	2	22.28	22.47	22.59	23.50
		1	5	22.19	22.06	22.58	23.50
		3	0	22.43	22.34	22.36	23.50
		3	2	22.10	22.27	22.28	23.50
		3	3	22.42	22.41	22.44	23.50
		6	0	21.58	21.48	21.51	22.50
	64QAM	1	0	21.52	21.98	22.04	22.50
		1	2	21.41	21.54	21.41	22.50
		1	5	21.13	21.25	21.63	22.50
		3	0	21.47	21.23	21.14	22.50
		3	2	21.26	21.51	21.41	22.50
		3	3	21.11	21.14	21.24	22.50
		6	0	20.47	20.67	20.72	21.50



Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23025	23095	23165	
3MHz	QPSK	1	0	23.28	23.52	23.25	24.50
		1	7	23.16	23.14	23.18	24.50
		1	14	23.27	23.33	23.25	24.50
		8	0	22.39	22.38	22.42	23.50
		8	4	22.49	22.49	22.51	23.50
		8	7	22.26	22.36	22.30	23.50
		15	0	22.41	22.21	22.29	23.50
	16QAM	1	0	22.74	23.07	22.92	23.50
		1	7	22.57	22.79	23.02	23.50
		1	14	22.36	22.50	22.65	23.50
		8	0	21.42	21.37	21.34	22.50
		8	4	21.58	21.62	21.66	22.50
		8	7	21.54	21.61	21.58	22.50
		15	0	21.37	21.34	21.37	22.50
	64QAM	1	0	21.60	21.78	21.64	22.50
		1	7	21.41	21.99	22.20	22.50
		1	14	21.32	21.61	21.42	22.50
		8	0	20.56	20.55	20.39	21.50
		8	4	20.42	20.35	20.72	21.50
		8	7	20.39	20.33	20.41	21.50
		15	0	20.27	20.37	20.24	21.50
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23035	23095	23155	
5MHz	QPSK	1	0	23.26	23.33	23.47	24.50
		1	13	23.34	23.49	23.31	24.50
		1	24	23.45	23.60	23.45	24.50
		12	0	22.51	22.37	22.59	23.50
		12	6	22.46	22.44	22.61	23.50
		12	13	22.52	22.46	22.37	23.50
		25	0	22.43	22.39	22.25	23.50
	16QAM	1	0	22.43	22.17	22.73	23.50
		1	13	22.57	22.86	22.40	23.50
		1	24	22.31	22.69	22.42	23.50
		12	0	21.45	21.68	21.44	22.50
		12	6	21.54	21.51	21.58	22.50
		12	13	21.57	21.65	21.57	22.50
		25	0	21.47	21.29	21.41	22.50
	64QAM	1	0	21.53	21.81	21.89	22.50
		1	13	21.53	21.64	21.87	22.50
		1	24	21.50	21.49	21.78	22.50





		12	0	20.17	20.07	20.37	21.50
		12	6	20.63	20.38	20.72	21.50
		12	13	20.51	20.24	20.28	21.50
		25	0	20.33	20.42	20.33	21.50
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Tune up
				23060	23095	23130	
10MHz	QPSK	1	0	23.72	23.49	23.47	24.50
		1	25	23.71	23.53	23.72	24.50
		1	49	23.53	23.75	23.72	24.50
		25	0	22.62	22.54	22.73	23.50
		25	13	22.66	22.49	22.61	23.50
		25	25	22.54	22.74	22.55	23.50
		50	0	22.97	22.75	22.48	23.50
	16QAM	1	0	23.01	22.85	23.16	23.50
		1	25	22.49	22.90	23.04	23.50
		1	49	22.91	22.57	23.13	23.50
		25	0	21.66	21.67	21.75	22.50
		25	13	21.49	21.56	21.72	22.50
		25	25	21.50	21.80	21.60	22.50
		50	0	21.73	21.77	21.37	22.50
	64QAM	1	0	21.54	21.77	21.72	22.50
		1	25	21.58	21.80	21.78	22.50
		1	49	21.54	21.67	21.55	22.50
		25	0	20.63	20.22	20.34	21.50
		25	13	20.43	20.47	20.53	21.50
		25	25	20.48	20.60	20.59	21.50
		50	0	20.63	20.53	20.51	21.50

LTE Band 41				Conducted Power(dBm)					
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Channel	Channel	Tune up
				39675	40148	40620	41093	41565	
5MHz	QPSK	1	0	21.34	21.65	21.78	21.68	21.46	22.80
		1	13	21.69	21.87	21.96	21.91	21.61	22.80
		1	24	21.55	21.78	21.88	21.82	21.54	22.80
		12	0	20.56	20.84	20.86	20.85	20.65	21.80
		12	6	20.62	20.91	20.91	20.90	20.75	21.80
		12	13	20.55	20.71	20.81	20.71	20.55	21.80
		25	0	20.54	20.83	20.94	20.81	20.69	21.80
	16QAM	1	0	20.54	20.89	20.81	20.76	20.51	21.80
		1	13	20.58	20.93	21.02	21.00	20.58	21.80



		1	24	20.52	20.90	20.84	20.81	20.68	21.80
		12	0	19.40	19.74	19.77	19.73	19.48	20.80
		12	6	19.67	19.89	19.90	19.89	19.56	20.80
		12	13	19.70	19.88	19.82	19.83	19.56	20.80
		25	0	19.65	19.89	19.90	19.88	19.63	20.80
	64QAM	1	0	19.71	19.91	19.75	19.62	19.76	20.80
		1	13	19.48	19.86	19.98	20.14	19.65	20.80
		1	24	19.60	19.85	19.78	20.02	19.71	20.80
		12	0	18.42	18.64	18.51	18.87	18.22	19.80
		12	6	18.45	18.83	19.02	18.94	18.43	19.80
		12	13	18.55	18.89	18.88	18.95	18.52	19.80
		25	0	18.65	18.96	18.71	18.62	18.63	19.80
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Channel	Channel	Tune up
				39700	40160	40620	41080	41540	
10MHz	QPSK	1	0	21.52	21.74	21.79	21.65	21.35	22.80
		1	25	21.38	21.62	21.73	21.64	21.30	22.80
		1	49	21.37	21.72	21.56	21.65	21.44	22.80
		25	0	20.43	20.70	20.75	20.72	20.54	21.80
		25	13	20.48	20.69	20.94	20.82	20.67	21.80
		25	25	20.56	20.74	20.90	20.69	20.67	21.80
		50	0	20.69	20.85	21.01	20.86	20.77	21.80
	16QAM	1	0	20.58	20.64	20.91	20.93	20.42	21.80
		1	25	20.71	20.79	20.72	20.77	20.61	21.80
		1	49	20.60	20.80	20.76	20.80	20.54	21.80
		25	0	19.76	19.90	19.98	20.00	19.63	20.80
		25	13	19.76	19.79	19.97	19.81	19.77	20.80
		25	25	19.69	19.91	19.99	19.87	19.72	20.80
		50	0	19.44	19.65	19.84	19.69	19.55	20.80
	64QAM	1	0	19.66	19.93	19.73	19.86	19.61	20.80
		1	25	19.63	19.68	20.16	20.00	19.64	20.80
		1	49	19.56	19.91	19.86	19.87	19.70	20.80
		25	0	18.61	18.76	19.00	18.74	18.58	19.80
		25	13	18.60	18.74	18.93	18.92	18.50	19.80
		25	25	18.34	18.73	18.50	18.68	18.50	19.80
		50	0	18.68	18.74	18.91	18.96	18.72	19.80
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Channel	Channel	Tune up
				39725	40173	40620	41068	41515	
15MHz	QPSK	1	0	21.11	21.44	21.66	21.60	21.44	22.80
		1	38	21.44	21.53	21.58	21.65	21.29	22.80
		1	74	21.48	21.72	21.65	21.70	21.29	22.80





		36	0	20.52	20.79	20.85	20.79	20.59	21.80
		36	18	20.49	20.65	20.80	20.66	20.49	21.80
		36	39	20.47	20.65	20.81	20.65	20.37	21.80
		75	0	20.54	20.74	20.79	20.67	20.48	21.80
	16QAM	1	0	20.44	20.80	20.80	20.75	20.52	21.80
		1	38	20.61	20.72	20.89	20.77	20.49	21.80
		1	74	20.44	20.87	20.71	20.67	20.42	21.80
		36	0	19.44	19.60	19.68	19.64	19.38	20.80
		36	18	19.39	19.55	19.74	19.62	19.38	20.80
		36	39	19.39	19.68	19.65	19.73	19.36	20.80
		75	0	19.50	19.83	19.90	19.82	19.63	20.80
	64QAM	1	0	19.44	20.13	19.78	19.98	19.47	20.80
		1	38	19.43	19.76	19.96	19.94	19.71	20.80
		1	74	19.85	19.95	20.12	19.81	19.81	20.80
		36	0	18.42	18.90	18.67	18.68	18.47	19.80
		36	18	18.66	19.14	18.78	18.75	18.43	19.80
		36	39	18.45	18.89	18.59	18.66	18.27	19.80
		75	0	18.45	18.88	18.79	18.84	18.58	19.80
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel	Channel	Channel	Tune up
				39750	40185	40620	41055	41490	
20MHz	QPSK	1	0	21.16	21.41	21.56	21.56	21.43	22.80
		1	50	21.38	21.58	21.60	21.48	21.27	22.80
		1	99	21.47	21.58	21.81	21.51	21.41	22.80
		50	0	20.62	20.75	20.76	20.72	21.38	21.80
		50	25	20.47	20.64	20.66	20.55	20.59	21.80
		50	50	20.38	20.58	20.64	20.62	20.61	21.80
		100	0	20.49	20.67	20.77	20.71	20.50	21.80
		100	50	20.49	20.67	20.77	20.71	20.50	21.80
	16QAM	1	0	20.51	20.71	20.94	20.87	20.72	21.80
		1	50	20.26	20.62	20.54	20.56	20.48	21.80
		1	99	20.58	20.81	20.85	20.74	20.56	21.80
		50	0	19.68	19.84	19.89	19.85	20.76	20.80
		50	25	19.44	19.67	19.82	19.69	19.51	20.80
		50	50	19.59	19.64	19.71	19.69	19.58	20.80
		100	0	19.50	19.67	19.78	19.68	19.39	20.80
		100	50	19.50	19.67	19.78	19.68	19.39	20.80
	64QAM	1	0	19.55	20.06	19.72	19.99	19.67	20.80
		1	50	19.80	20.02	20.30	20.31	19.88	20.80
		1	99	19.55	20.04	20.08	19.81	19.66	20.80
		50	0	18.37	18.73	18.99	18.80	18.45	19.80
		50	25	18.68	18.64	18.65	18.78	18.38	19.80
		50	50	18.79	18.66	18.89	18.98	18.73	19.80
		50	0	18.37	18.73	18.99	18.80	18.45	19.80
		50	25	18.68	18.64	18.65	18.78	18.38	19.80



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

		100	0	18.88	18.93	19.05	19.03	18.64	19.80
--	--	-----	---	-------	-------	-------	-------	-------	-------

DL LTE CA Class	PCC							SCC1				Power(dBm)		
	LTE Band	BW (MHz)	Modulation	UL Freq. (MHz)	UL Channel	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	DL LTE CA Tx.Power	LTE Rel 8 Tx.Power	Tune-up
CA_41C	Band 41	20M	QPSK	2506	39750	1	99	Band 41	20M	2525.8	39948	21.40	21.47	22.80



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



WiFi 2.4G - conducted power table:

ANT6

Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11b	1	2412	1	14.48	16.00	Yes
	6	2437		14.83	16.00	Yes
	11	2462		15.17	16.00	Yes
802.11g	1	2412	6	14.51	15.00	No
	6	2437		14.53	15.00	No
	11	2462		13.77	15.00	No
802.11n HT20	1	2412	6.5	14.13	15.00	No
	6	2437		14.31	15.00	No
	11	2462		13.84	15.00	No

ANT7

Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11b	1	2412	1	15.01	16.00	Yes
	6	2437		14.94	16.00	Yes
	11	2462		14.95	16.00	Yes
802.11g	1	2412	6	13.60	15.00	No
	6	2437		13.91	15.00	No
	11	2462		13.25	15.00	No
802.11n HT20	1	2412	6.5	14.45	15.00	No
	6	2437		14.09	15.00	No
	11	2462		14.13	15.00	No

MIMO

Mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11b	1	2412	1	17.76	19.00	Yes
	6	2437		17.90	19.00	Yes
	11	2462		18.07	19.00	Yes
802.11g	1	2412	6	17.09	18.00	No
	6	2437		17.24	18.00	No
	11	2462		16.53	18.00	No
802.11n HT20	1	2412	6.5	17.30	18.00	No
	6	2437		17.21	18.00	No
	11	2462		17.00	18.00	No





WiFi 5G - conducted power table:

ANT6

5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11a	U-NII-1	36	5180	6	14.00	15.00	No
		40	5200		13.92	15.00	No
		44	5220		14.12	15.00	No
		48	5240		14.48	15.00	No
	U-NII-2A	52	5260		14.23	15.00	No
		56	5280		13.46	15.00	No
		60	5300		14.34	15.00	No
		64	5320		13.99	15.00	No
	U-NII-2C	100	5500		12.28	13.00	No
		104	5520		13.63	15.00	No
		108	5540		14.33	15.00	No
		112	5560		14.00	15.00	No
		116	5580		9.38	10.50	No
		120	5600		14.02	15.00	No
		124	5620		14.35	15.00	No
		128	5640		13.74	15.00	No
		132	5660		14.02	15.00	No
		136	5680		13.97	15.00	No
		140	5700		12.93	14.00	No
		144	5720		14.30	15.00	No
	U-NII-3	149	5745		13.39	14.50	No
		153	5765		14.29	15.00	No
		157	5785		14.30	15.00	No
		161	5805		14.36	15.00	No
		165	5825		13.80	15.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11n-HT20	U-NII-1	36	5180	MCS0	14.05	15.00	No
		40	5200		14.35	15.00	No
		44	5220		13.93	15.00	No
		48	5240		13.94	15.00	No
	U-NII-2A	52	5260		14.01	15.00	No
		56	5280		13.99	15.00	No
		60	5300		13.87	15.00	No
		64	5320		13.46	15.00	No
	U-NII-2C	100	5500		12.38	13.00	No
		104	5520		13.91	15.00	No
		108	5540		14.42	15.00	No
		112	5560		14.32	15.00	No
		116	5580		10.56	11.50	No
		120	5600		14.09	15.00	No
		124	5620		13.84	15.00	No
		128	5640		13.65	15.00	No
		132	5660		13.97	15.00	No
		136	5680		14.21	15.00	No
		140	5700		13.23	14.00	No
		144	5720		14.08	15.00	No
	U-NII-3	149	5745		13.53	14.50	No



		153	5765		14.26	15.00	No
		157	5785		14.09	15.00	No
		161	5805		13.89	15.00	No
		165	5825		13.92	15.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11n-HT40	U-NII-1	38	5190	MCS0	14.08	15.00	No
		46	5230		13.67	15.00	No
	U-NII-2A	54	5270		13.81	15.00	No
		62	5310		13.93	15.00	No
	U-NII-2C	102	5510		13.37	14.00	No
		110	5550		10.86	12.00	No
		118	5590		13.68	15.00	No
		126	5630		13.91	15.00	No
		134	5670		12.68	14.00	No
		142	5710		13.03	15.00	No
		151	5755		13.52	14.50	No
		159	5795		13.60	15.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac-20	U-NII-1	36	5180	MCS0	14.44	15.00	No
		40	5200		14.39	15.00	No
		44	5220		14.00	15.00	No
		48	5240		13.82	15.00	No
	U-NII-2A	52	5260		13.85	15.00	No
		56	5280		14.03	15.00	No
		60	5300		14.14	15.00	No
		64	5320		14.35	15.00	No
	U-NII-2C	100	5500		11.95	13.50	No
		104	5520		14.22	15.00	No
		108	5540		13.84	15.00	No
		112	5560		14.46	15.00	No
		116	5580		10.31	11.00	No
		120	5600		13.89	15.00	No
		124	5620		14.30	15.00	No
		128	5640		13.92	15.00	No
		132	5660		13.42	15.00	No
		136	5680		14.24	15.00	No
		140	5700		13.17	14.00	No
		144	5720		13.90	15.00	No
	U-NII-3	149	5745		12.83	14.50	No
		153	5765		13.95	15.00	No
		157	5785		13.74	15.00	No
		161	5805		14.10	15.00	No
		165	5825		13.67	15.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac-40	U-NII-1	38	5190	MCS0	14.52	15.00	No
		46	5230		14.13	15.00	No
	U-NII-2A	54	5270		13.66	15.00	No
		62	5310		14.06	15.00	No
	U-NII-2C	102	5510		12.76	13.50	No
		110	5550		10.91	12.00	No





	U-NII-3	118	5590		13.82	15.00	No
		126	5630		13.68	15.00	No
		134	5670		13.37	14.00	No
		142	5710		14.11	15.00	No
		151	5755		13.62	15.00	No
		159	5795		13.79	15.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac 80M	U-NII-1	42	5210	MCS0	14.05	15.00	Yes
	U-NII-2A	58	5290		14.18	15.00	Yes
	U-NII-2C	106	5530		14.20	14.00	No
		122	5610		12.18	13.00	No
		138	5690		13.87	15.00	Yes
	U-NII-3						
		155	5775		13.59	15.00	Yes

ANT7

5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11a	U-NII-1	36	5180	6	13.59	14.00	No
		40	5200		13.32	14.00	No
		44	5220		13.07	14.00	No
		48	5240		12.79	14.00	No
	U-NII-2A	52	5260		12.64	14.00	No
		56	5280		13.24	14.00	No
		60	5300		12.53	14.00	No
		64	5320		12.78	14.00	No
	U-NII-2C	100	5500		10.74	12.00	No
		104	5520		13.10	14.00	No
		108	5540		12.84	14.00	No
		112	5560		13.22	14.00	No
		116	5580		8.61	9.50	No
		120	5600		12.76	14.00	No
		124	5620		12.85	14.00	No
		128	5640		12.81	14.00	No
		132	5660		13.20	14.00	No
		136	5680		14.06	14.00	No
		140	5700		11.74	13.00	No
		144	5720		12.80	14.00	No
	U-NII-3	149	5745		12.56	13.50	No
		153	5765		12.89	14.00	No
		157	5785		12.74	14.00	No
		161	5805		12.74	14.00	No
		165	5825		12.69	14.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11n- HT20	U-NII-1	36	5180	MCS0	13.62	14.00	No
		40	5200		12.92	14.00	No
		44	5220		12.82	14.00	No
		48	5240		12.98	14.00	No
	U-NII-2A	52	5260		12.74	14.00	No
		56	5280		12.79	14.00	No
		60	5300		12.86	14.00	No





	U-NII-2C	64	5320		13.49	14.00	No
		100	5500		11.53	12.00	No
		104	5520		13.08	14.00	No
		108	5540		13.07	14.00	No
		112	5560		13.25	14.00	No
		116	5580		9.79	10.50	No
		120	5600		12.99	14.00	No
		124	5620		12.52	14.00	No
		128	5640		13.15	14.00	No
		132	5660		13.40	14.00	No
		136	5680		13.45	14.00	No
		140	5700		12.15	13.00	No
		144	5720		12.12	14.00	No
	U-NII-3	149	5745		12.12	13.50	No
		153	5765		12.90	14.00	No
		157	5785		13.38	14.00	No
		161	5805		13.24	14.00	No
		165	5825		13.27	14.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11n-HT40	U-NII-1	38	5190	MCS0	13.12	14.00	No
		46	5230		12.80	14.00	No
	U-NII-2A	54	5270		12.98	14.00	No
		62	5310		13.13	14.00	No
	U-NII-2C	102	5510		11.92	13.00	No
		110	5550		9.75	11.00	No
		118	5590		12.83	14.00	No
		126	5630		12.95	14.00	No
		134	5670		12.63	13.00	No
		142	5710		13.23	14.00	No
	U-NII-3	151	5755		12.31	13.50	No
		159	5795		12.75	14.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac-20	U-NII-1	36	5180	MCS0	12.95	14.00	No
		40	5200		13.09	14.00	No
		44	5220		12.88	14.00	No
		48	5240		13.41	14.00	No
	U-NII-2A	52	5260		12.53	14.00	No
		56	5280		13.13	14.00	No
		60	5300		13.20	14.00	No
		64	5320		12.98	14.00	No
	U-NII-2C	100	5500		11.48	12.50	No
		104	5520		13.18	14.00	No
		108	5540		13.13	14.00	No
		112	5560		13.41	14.00	No
		116	5580		9.08	10.00	No
		120	5600		12.80	14.00	No
		124	5620		13.07	14.00	No
		128	5640		13.15	14.00	No
		132	5660		12.93	14.00	No
		136	5680		12.80	14.00	No
		140	5700		11.95	13.00	No



		144	5720		13.06	14.00	No
		149	5745		12.78	13.50	No
		153	5765		12.95	14.00	No
		157	5785		13.00	14.00	No
		161	5805		13.29	14.00	No
		165	5825		13.30	14.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac-40	U-NII-1	38	5190	MCS0	12.67	14.00	No
		46	5230		13.01	14.00	No
	U-NII-2A	54	5270		12.81	14.00	No
		62	5310		13.11	14.00	No
	U-NII-2C	102	5510		11.90	12.50	No
		110	5550		9.99	11.00	No
		118	5590		13.35	14.00	No
		126	5630		12.97	14.00	No
		134	5670		12.28	13.00	No
		142	5710		12.92	14.00	No
		151	5755		13.28	14.00	No
		159	5795		12.80	14.00	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac 80M	U-NII-1	42	5210	MCS0	13.35	14.00	Yes
	U-NII-2A	58	5290		13.48	14.00	Yes
	U-NII-2C	106	5530		11.95	13.00	No
		122	5610		10.86	12.00	No
		138	5690		12.53	14.00	Yes
	U-NII-3	155	5775		13.43	14.00	Yes

MIMO

5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11a	U-NII-1	36	5180	6	16.81	17.54	No
		40	5200		16.64	17.54	No
		44	5220		16.64	17.54	No
		48	5240		16.73	17.54	No
	U-NII-2A	52	5260		16.52	17.54	No
		56	5280		16.36	17.54	No
		60	5300		16.54	17.54	No
		64	5320		16.44	17.54	No
	U-NII-2C	100	5500		14.59	15.54	No
		104	5520		16.38	17.54	No
		108	5540		16.66	17.54	No
		112	5560		16.64	17.54	No
		116	5580		12.02	13.04	No
		120	5600		16.45	17.54	No
		124	5620		16.67	17.54	No
		128	5640		16.31	17.54	No
		132	5660		16.64	17.54	No
		136	5680		17.03	17.54	No
		140	5700		15.39	16.54	No
		144	5720		16.62	17.54	No



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
Shenzhen Branch / 深圳分公司 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

		149	5745		16.01	17.04	No
		153	5765		16.66	17.54	No
		157	5785		16.60	17.54	No
		161	5805		16.64	17.54	No
		165	5825		16.29	17.54	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11n-HT20	U-NII-1	36	5180	MCS0	16.85	17.54	No
		40	5200		16.70	17.54	No
		44	5220		16.42	17.54	No
		48	5240		16.50	17.54	No
	U-NII-2A	52	5260		16.43	17.54	No
		56	5280		16.44	17.54	No
		60	5300		16.40	17.54	No
		64	5320		16.49	17.54	No
	U-NII-2C	100	5500		14.99	15.54	No
		104	5520		16.53	17.54	No
		108	5540		16.81	17.54	No
		112	5560		16.83	17.54	No
		116	5580		13.20	14.04	No
		120	5600		16.59	17.54	No
		124	5620		16.24	17.54	No
		128	5640		16.42	17.54	No
		132	5660		16.70	17.54	No
		136	5680		16.86	17.54	No
		140	5700		15.73	16.54	No
		144	5720		16.22	17.54	No
	U-NII-3	149	5745		15.89	17.04	No
		153	5765		16.64	17.54	No
		157	5785		16.76	17.54	No
		161	5805		16.59	17.54	No
		165	5825		16.62	17.54	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11n-HT40	U-NII-1	38	5190	MCS0	16.64	17.54	No
		46	5230		16.27	17.54	No
	U-NII-2A	54	5270		16.43	17.54	No
		62	5310		16.56	17.54	No
	U-NII-2C	102	5510		15.72	16.54	No
		110	5550		13.35	14.54	No
		118	5590		16.29	17.54	No
		126	5630		16.47	17.54	No
		134	5670		15.67	16.54	No
		142	5710		16.14	17.54	No
	U-NII-3	151	5755		15.97	17.04	No
		159	5795		16.21	17.54	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac-20	U-NII-1	36	5180	MCS0	16.77	17.54	No
		40	5200		16.80	17.54	No
		44	5220		16.49	17.54	No
		48	5240		16.63	17.54	No
	U-NII-2A	52	5260		16.25	17.54	No



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

		56	5280		16.61	17.54	No
		60	5300		16.71	17.54	No
		64	5320		16.73	17.54	No
	U-NII-2C	100	5500		14.73	16.04	No
		104	5520		16.74	17.54	No
		108	5540		16.51	17.54	No
		112	5560		16.98	17.54	No
		116	5580		12.75	13.54	No
		120	5600		16.39	17.54	No
		124	5620		16.74	17.54	No
		128	5640		16.56	17.54	No
		132	5660		16.19	17.54	No
		136	5680		16.59	17.54	No
		140	5700		15.61	16.54	No
		144	5720		16.51	17.54	No
	U-NII-3	149	5745		15.82	17.04	No
		153	5765		16.49	17.54	No
		157	5785		16.40	17.54	No
		161	5805		16.72	17.54	No
		165	5825		16.50	17.54	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac-40	U-NII-1	38	5190	MCS0	16.70	17.54	No
		46	5230		16.62	17.54	No
	U-NII-2A	54	5270		16.27	17.54	No
		62	5310		16.62	17.54	No
	U-NII-2C	102	5510		15.36	16.04	No
		110	5550		13.48	14.54	No
		118	5590		16.60	17.54	No
		126	5630		16.35	17.54	No
		134	5670		15.87	16.54	No
		142	5710		16.57	17.54	No
	U-NII-3	151	5755		16.46	17.54	No
		159	5795		16.33	17.54	No
5GHz	mode	Channel	Frequency(MHz)	Data Rate(Mbps)	Average Power (dBm)	Tune up	SAR Test
802.11ac 80M	U-NII-1	42	5210	MCS0	16.72	17.54	Yes
	U-NII-2A	58	5290		16.85	17.54	Yes
	U-NII-2C	106	5530		16.23	16.54	No
		122	5610		14.58	15.54	No
		138	5690		16.26	17.54	Yes
	U-NII-3	155	5775		16.52	17.54	Yes



BT - conducted power table:

ANT6

BT		Average Conducted Power(dBm)			
Band	Channel	0	39	78	Tune up
BT	GFSK	10.56	11.55	12.03	12.50
	$\pi/4$ DQPSK	8.26	9.15	10.33	12.50
	8DPSK	8.13	8.88	10.21	12.50
Band	Channel	0	19	39	Tune up
BLE	1M	4.61	4.68	5.46	7.50
BLE	2M	4.39	4.53	4.71	7.50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1.5 Test Environment

Ambient Temperature: 22±2° C
Tissue Simulating Liquid: 22±2° C

1.6 Operation Description

1. The EUT is controlled by using a Radio Communication Tester (MT8821C & CMU200), and the communication between the EUT and the tester is established by air link.
2. Measurements are performed respectively on the lowest, middle and highest channels of the operating band(s). The EUT is set to maximum power level during all tests, and at the beginning of each test the battery is fully charged.
3. During the SAR testing, the DASY 5 system checks power drift by comparing the e-field strength of one specific location measured at the beginning with that measured at the end of the SAR testing.
4. SAR test reduction for GPRS mode is determined by the source-based time-averaged output power. The data mode with highest specified time-averaged output power should be tested for SAR compliance.
5. The 3G SAR test reduction procedure is applied to HSDPA with 12.2 kbps RMC as the primary mode. Since the maximum output power in a secondary mode (HSDPA) is $\leq \frac{1}{4}$ dB higher than the primary mode (WCDMA), SAR measurement is not required for the secondary mode (HSDPA).
6. The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) with 12.2 kbps RMC as the primary mode. Since the maximum output power in a secondary mode (HSPA) is $\leq \frac{1}{4}$ dB higher than the primary mode (WCDMA), SAR measurement is not required for the secondary mode (HSPA).



7. LTE modes test according to KDB 941225D05v02r05.

- a. Per Section 5.2.1, the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation.
 - Using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
 - When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel.
 - When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.
- b. Per Section 5.2.2, the largest channel bandwidth and measure SAR for QPSK with 50% RB allocation
 - The procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.
- c. Per Section 5.2.3, the largest channel bandwidth and measure SAR for QPSK with 100% RB allocation
 - For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are ≤ 0.8 W/kg.
 - Otherwise, SAR is measured for the highest output power channel and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
- d. Per Section 5.2.4, Higher order modulations
 - For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in sections 5.2.1, 5.2.2 and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.
- e. Per Section 5.3, other channel bandwidth standalone SAR test requirements
 - For the other channel bandwidths used by the device in a frequency band, apply all the procedures required for the largest channel bandwidth in section 5.2 to determine the channels and RB configurations that need SAR testing and only measure SAR when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is $> \frac{1}{2}$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg. The equivalent channel configuration for the RB allocation, RB offset and modulation etc. is determined for the smaller channel bandwidth according to the same number of RB allocated in the largest channel bandwidth.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

The EUT LTE test information:

Test Modulation	QPSK/16QAM/64QAM			
TX Frequency Range (MHz)	LTE FDD Band 4		1710	— 1755
	LTE TDD Band 12		699	— 716
	LTE TDD Band 41		2496	— 2690
Bands	Test Frequency ID	Bandwidths	Channels	Frequencies
LTE B4	Low Range	1.4	19957	1710.7
		3	19965	1711.5
		5	19975	1712.5
		10	20000	1715
		15	20025	1717.5
		20	20050	1720
	Mid-Range	1.4/3/5/10/15/20	20175	1732.5
	High Range	1.4	20393	1754.3
		3	20385	1753.5
		5	20375	1752.5
		10	20350	1750
		15	20325	1747.5
		20	20300	1745
LTE B12	Low Range	1.4	23017	699.7
		3	23025	700.5
		5	23035	701.5
		10	23060	704
	Mid-Range	1.4/3/5/10	23095	707.5
	High Range	1.4	23173	715.3
		3	23165	714.5
		5	23155	713.5
		10	23130	711
	LTE B41	Low Range	5	39675
10			39700	2501
15			39725	2503.5
20			39750	2506
Mid-Range		5/10/15/20	40620	2593
High Range		5	41565	2687.5
		10	41540	2685
		15	41515	2682.5
		20	41490	2680



LTE transmitter and antenna implementation	For each LTE Band the device has one integral antenna used for transmitting.																																																														
Maximum power reduction (MPR)	<table><tr><th rowspan="2">Modulation</th><th colspan="6">Channel bandwidth / Transmission bandwidth configuration [RB]</th><th rowspan="2">MPR (dB)</th></tr><tr><th>1.4 MHz</th><th>3.0 MHz</th><th>5 MHz</th><th>10 MHz</th><th>15 MHz</th><th>20 MHz</th></tr><tr><td>QPSK</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 1</td></tr><tr><td>16 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 2</td></tr><tr><td>64 QAM</td><td>≤ 5</td><td>≤ 4</td><td>≤ 8</td><td>≤ 12</td><td>≤ 16</td><td>≤ 18</td><td>≤ 2</td></tr><tr><td>64 QAM</td><td>> 5</td><td>> 4</td><td>> 8</td><td>> 12</td><td>> 16</td><td>> 18</td><td>≤ 3</td></tr><tr><td>256 QAM</td><td colspan="6">≥ 1</td><td>≤ 5</td></tr></table>	Modulation	Channel bandwidth / Transmission bandwidth configuration [RB]						MPR (dB)	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	256 QAM	≥ 1						≤ 5
Modulation	Channel bandwidth / Transmission bandwidth configuration [RB]						MPR (dB)																																																								
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz																																																									
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1																																																								
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1																																																								
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2																																																								
64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2																																																								
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3																																																								
256 QAM	≥ 1						≤ 5																																																								
Spectrum plots for RB configurations	A properly configured base station simulator was used for the SAR and power measurements, therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.																																																														



8. WLAN

Initial Test Position SAR Test Reduction Procedure

DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. The initial test position procedure is described in the following:

- 1) . When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other (remaining) test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band. SAR is also not required for that exposure configuration in the subsequent test configuration(s).
- 2) . When the reported SAR of the initial test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position using subsequent highest extrapolated or estimated 1-g SAR conditions determined by area scans or next closest/smallest test separation distance and maximum RF coupling test positions based on manufacturer justification, on the highest maximum output power channel, until the reported SAR is ≤ 0.8 W/kg or all required test positions (left, right, touch, tilt or subsequent surfaces and edges) are tested.
- 3) . For all positions/configurations tested using the initial test position and subsequent test positions, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested. a) Additional power measurements may be required for this step, which should be limited to those necessary for identifying the subsequent highest output power channels.

Initial Test Configuration Procedures

An initial test configuration is determined for OFDM transmission modes according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. SAR is measured using the highest measured maximum output power channel. For configurations with the same specified or measured maximum output power, additional transmission mode and test channel selection procedures are required. SAR test reduction for subsequent highest output test channels is determined according to reported SAR of the initial test configuration.

For next to the ear, hotspot mode and UMC mini-tablet exposure configurations where multiple test positions are required, the initial test position procedure is applied to minimize the number of test positions required for SAR measurement using the initial test configuration transmission mode. For fixed exposure conditions that do not have multiple SAR test positions, SAR is measured in the transmission mode determined by the initial test configuration.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

When the reported SAR of the initial test configuration is > 0.8 W/kg, SAR measurement is required for subsequent next highest measured output power channel(s) in the initial test configuration until reported SAR is ≤ 1.2 W/kg or all required channels are tested.

Subsequent Test Configuration Procedure

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. The initial test position procedure is applied to next to the ear, UMPC mini-tablet and hotspot mode configurations. When the same maximum output power is specified for multiple transmission modes, additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. The subsequent test configuration and SAR measurement procedures are described in the following.

- 1) . When SAR test exclusion provisions of KDB Publication 447498 are applicable and SAR measurement is not required for the initial test configuration, SAR is also not required for the next highest maximum output power transmission mode subsequent test configuration(s) in that frequency band or aggregated band and exposure configuration.
- 2) . When the highest reported SAR for the initial test configuration (when applicable, include subsequent highest output channels), according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.
- 3) . The number of channels in the initial test configuration and subsequent test configuration can be different due to differences in channel bandwidth. When SAR measurement is required for a subsequent test configuration and the channel bandwidth is smaller than that in the initial test configuration, all channels in the subsequent test configuration that overlap with the larger bandwidth channel tested in the initial test configuration should be used to determine the highest maximum output power channel. This step requires additional power measurement to identify the highest maximum output power channel in the subsequent test configuration to determine SAR test reduction.
 - a) SAR should first be measured for the channel with highest measured output power in the subsequent test configuration.
 - b) SAR for subsequent highest measured maximum output power channels in the subsequent test configuration is required only when the reported SAR of the preceding higher maximum output power channel(s) in the subsequent test configuration is > 1.2 W/kg or until all required channels are tested. i) For channels with the same measured maximum output power, SAR should be measured using the channel closest to the center frequency of the larger channel bandwidth channel in the initial test configuration.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4) . SAR measurements for the remaining highest specified maximum output power OFDM transmission mode configurations that have not been tested in the initial test configuration (highest maximum output) or subsequent test configuration(s) (subsequent next highest maximum output power) is determined by recursively applying the subsequent test configuration procedures in this section to the remaining configurations according to the following:

- a) replace “subsequent test configuration” with “next subsequent test configuration” (i.e., subsequent next highest specified maximum output power configuration)
- b) replace “initial test configuration” with “all tested higher output power configurations”

2.4 GHz WiFi SAR Procedures:

Separate SAR procedures are applied to DSSS and OFDM configurations in the 2.4 GHz band to simplify DSSS test requirements. For 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions. When SAR measurement is required for an OFDM configuration, the initial test configuration, subsequent test configuration and initial test position procedures are applied. The SAR test exclusion requirements for 802.11g/n OFDM configurations are described in following.

802.11b DSSS SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) . When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) . When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (section 5.3, including sub-sections). SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) . When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) . When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

SAR Test Requirements for OFDM configurations



When SAR measurement is required for 802.11 g/n OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

5 GHz WiFi SAR Procedures:

U-NII-1 and U-NII-2A Bands

For devices that operate in only one of the U-NII-1 and U-NII-2A bands, the normally required SAR procedures for OFDM configurations are applied. For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following :

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, both bands are tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, both bands are tested independently for SAR.
- 3) The two U-NII bands may be aggregated to support a 160 MHz channel on channel number 50. Without additional testing, the maximum output power for this is limited to the lower of the maximum output power certified for the two bands. When SAR measurement is required for at least one of the bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is > 1.2 W/kg, SAR is required for the 160 MHz channel. This procedure does not apply to an aggregated band with maximum output higher than the standalone band(s); the aggregated band must be tested independently for SAR. SAR is not required when the 160 MHz channel is operating at a reduced maximum power and also qualifies for SAR test exclusion.

U-NII-2C and U-NII-3 Bands

The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. when Terminal Doppler Weather Radar (TDWR) restriction applies, all channels that operate at 5.60 – 5.65 GHz must be included to apply the SAR test reduction and measurement procedures.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

When the same transmitter and antenna(s) are used for U-NII-2C band and U-NII-3 band or 5.8 GHz band of §15.247, the bands may be aggregated to enable additional channels with 20, 40 or 80 MHz bandwidth to span across the band gap, as illustrated in Appendix B. The maximum output power for the additional band gap channels is limited to the lower of those certified for the bands. Unless band gap channels are permanently disabled, they must be considered for SAR testing. The frequency range covered by these bands is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. To maintain SAR measurement accuracy and to facilitate test reduction, the channels in U-NII-2C band above 5.65 GHz may be grouped with the 5.8 GHz channels in U-NII-3 or §15.247 band to enable two SAR probe calibration frequency points to cover the bands, including the band gap channels. When band gap channels are supported and the bands are not aggregated for SAR testing, band gap channels must be considered independently in each band according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

OFDM Transmission Mode SAR Test Configuration and Channel Selection Requirements

The initial test configuration for 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band. SAR for the initial test configuration is measured using the highest maximum output power channel determined by the default power measurement procedures. When multiple configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined according to the following steps applied sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n. After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following. These channel selection procedures apply to both the initial test configuration and subsequent test configuration(s), with respect to the default power measurement procedures or additional power measurements required for further SAR test reduction. The same procedures also apply to subsequent highest output power channel(s) selection.

- a) The channel closest to mid-band frequency is selected for SAR measurement.
- b) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

SAR Test Requirements for OFDM configurations:

When SAR measurement is required for 802.11 a/n/ac OFDM configurations, each standalone and frequency aggregated band is considered separately for SAR test reduction. When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies. When band gap channels between U-NII-2C band and 5.8 GHz U-NII-3 or §15.247 band are supported, the highest maximum output power transmission mode configuration and maximum output power channel across the bands must be used to determine SAR test reduction, according to the initial test configuration and subsequent test configuration requirements. In applying the initial test configuration and subsequent test configuration procedures, the 802.11 transmission configuration with the highest specified maximum output power and the channel within a test configuration with the highest measured maximum output power should be clearly distinguished to apply the procedures.

WiFi CDD/MIMO SAR Considerations

Per KDB 248227D01v02r02, simultaneous transmission provisions in KDB Publication 447498 should be used to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1-g SAR single transmission SAR measurement is $< 1.6 \text{ W/kg}$, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

9. According to KDB447498D01v06, testing of other required channels is not required when the reported 1-g SAR for the highest output channel is $\leq 0.8 \text{ W/kg}$, when the transmission band is $\leq 100 \text{ MHz}$.


10. According to KDB865664D01v01r04, SAR measurement variability must be assessed for each frequency band. When the original highest measured SAR is $\geq 0.8 \text{ W/kg}$, repeated that measurement once. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45 \text{ W/kg}$ ($\sim 10\%$ from the 1-g SAR limit)

11. According to KDB447498D01v06 – The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances $\leq 50 \text{ mm}$ are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for product specific 10-g SAR.

Duty cycle:


2.4GHz Wi-Fi 802.11b:

duty cycle=99%




5GHz Wi-Fi 802.11ac 80M:

duty cycle=94.0%




BT:

duty cycle=77.0%




1.7 Positioning Procedure

Head SAR measurement statement



Phone position 1, “cheek” or “touch” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.



Phone position 2, “tilted position.” The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning.

Cheek/Touch Position:

The handset was brought toward the mouth of the head phantom by pivoting against the ear reference point until any point of the mouthpiece or keypad touched the phantom.

Ear/Tilt Position:

With the phone aligned in the Cheek/Touch position, the handset was tilted away from the mouth with respect to the test device reference point by 15 degrees.

Body SAR measurement statement

1. Body-worn exposure: 15mm

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative test separation distance configuration may be used to support both SAR conditions. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.

2. Hotspot exposure: 10mm

A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge when the form factor of a handset is larger than $9 \text{ cm} \times 5 \text{ cm}$,

Test configurations of WWAN:

- (1) Front side
- (2) Back side
- (3) Bottom side
- (4) Right side
- (5) Left side

Test configurations of WLAN:

- (1) Front side
- (2) Back side
- (3) Top side
- (4) Right side
- (5) Left side

3. Extremity exposure conditions

Per FCC KDB 648474D04, for smart phones with a display diagonal dimension $> 15.0 \text{ cm}$ or an overall diagonal dimension $> 16.0 \text{ cm}$ that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the device is marketed as "Phablet".

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at $\leq 25 \text{ mm}$ from that surface or edge, in direct contact with a flat phantom, for Product Specific 10-g SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, Product Specific 10-g SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR $> 1.2 \text{ W/kg}$; however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.

Due to the SAR result, WWAN bands do not need to be test with 0mm for the Product Specific 10-g SAR.



1.8 Evaluation Procedures

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan.
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters).
3. The generation of a high-resolution mesh within the measured volume.
4. The interpolation of all measured values from the measurement grid to the high-resolution grid.
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface.
6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within -2 dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7x7x7 scans.

The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30x30x30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. Boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume. In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is the moved around until the highest averaged SAR is found.

If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.



1.9 Probe Calibration Procedures

For the calibration of E-field probes in lossy liquids, an electric field with an accurately known field strength must be produced within the measured liquid. For standardization purposes it would be desirable if all measurements which are necessary to assess the correct field strength would be traceable to standardized measurement procedures. In the following two different calibration techniques are summarized:

1.9.1 Transfer Calibration with Temperature Probes

In lossy liquids the specific absorption rate (SAR) is related both to the electric field (E) and the temperature gradient ($\delta T / \delta t$) in the liquid.

$$SAR = C \frac{\delta T}{\delta t},$$

Whereby σ is the conductivity, ρ the density and c the heat capacity of the liquid.

1. Hence, the electric field in lossy liquid can be measured indirectly by measuring the temperature gradient in the liquid. Non-disturbing temperature probes (optical probes or thermistor probes with resistive lines) with high spatial resolution (<1-2 mm) and fast reaction time (<1 s) are available and can be easily calibrated with high precision [1]. The setup and the exciting source have no influence on the calibration; only the relative positioning uncertainties of the standard temperature probe and the E-field probe to be calibrated must be considered. However, several problems limit the available accuracy of probe calibrations with temperature probes:

2. The temperature gradient is not directly measurable but must be evaluated from temperature measurements at different time steps. Special precaution is necessary to avoid measurement errors caused by temperature gradients due to energy equalizing effects or convection currents in the liquid. Such effects cannot be completely avoided, as the measured field itself destroys the thermal equilibrium in the liquid. With a careful setup these errors can be kept small.

3. The measured volume around the temperature probe is not well defined. It is difficult to calculate the energy transfer from a surrounding gradient temperature field into the probe. These effects must be considered, since temperature probes are calibrated in liquid with homogeneous temperatures. There is no traceable standard for temperature rise measurements.

The calibration depends on the assessment of the specific density, the heat capacity and the conductivity of the medium. While the specific density and heat capacity can be measured accurately with standardized procedures (~ 2% for c ; much better for ρ), there is no standard for the measurement of the conductivity. Depending on the method and liquid, the error can well exceed $\pm 5\%$.

4. Temperature rise measurements are not very sensitive and therefore are often performed at a higher power level than the E-field measurements. The nonlinearities in the system (e.g., power measurements, different components, etc.) must be considered.

Considering these problems, the possible accuracy of the calibration of E-field probes with temperature gradient measurements in a carefully designed setup is about $\pm 10\%$ (RSS) [2]. Recently, a setup which is a combination of the waveguide techniques and the thermal measurements was presented in [3]. The estimated uncertainty of the setup is $\pm 5\%$ (RSS) when the same liquid is used for the calibration and for actual measurements and $\pm 7-9\%$ (RSS) when not, which is in good agreement with the estimates given in [2].



1.9.2 Calibration with Analytical Fields

In this method a technical setup is used in which the field can be calculated analytically from measurements of other physical magnitudes (e.g., input power). This corresponds to the standard field method for probe calibration in air; however, there is no standard defined for fields in lossy liquids.

When using calculated fields in lossy liquids for probe calibration, several points must be considered in the assessment of the uncertainty:

1. The setup must enable accurate determination of the incident power.
2. The accuracy of the calculated field strength will depend on the assessment of the dielectric parameters of the liquid.
3. Due to the small wavelength in liquids with high permittivity, even small setups might be above the resonant cutoff frequencies. The field distribution in the setup must be carefully checked for conformity with the theoretical field distribution.

References

- 1) N. Kuster, Q. Balzano, and J.C. Lin, Eds., Mobile Communications Safety, Chapman & Hall, London, 1997.
- 2) K. Meier, M. Burkhardt, T. Schmid, and N. Kuster, "Broadband calibration of E-field probes in lossy media", IEEE Transactions on Microwave Theory and Techniques, vol. 44, no. 10, pp. 1954-1962, Oct. 1996.
- 3) K. Jokela, P. Hyysalo, and L. Puranen, "Calibration of specific absorption rate (SAR) probes in waveguide at 900 MHz", IEEE Transactions on Instrumentation and Measurements, vol. 47, no. 2, pp. 432-438, Apr. 1998.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

1.10 The SAR Measurement System

This SAR Measurement System uses a Computer-controlled 3-D stepper motor system (SPEAG DASY5 professional system). A E-field probe is used to determine the internal electric fields. The SAR can be obtained from the equation $SAR = \sigma (|E|)^2 / \rho$ where σ and ρ are the conductivity and mass density of the tissue-Simulate.


The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stabile RX family) with controller, teach pendant and software .An arm extension for accommodation the data acquisition electronics (DAE).

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.




F-1. SAR Measurement System Configuration


- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 7.
- DASY5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand, right-hand and Body Worn usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing to validating the proper functioning of the system.

1.11 System Component


EX3DV4 E-Field Probe

	<p>Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)</p>
Calibration	<p>ISO/IEC 17025 calibration service available.</p>
Frequency	<p>10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)</p>
Directivity	<p>± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)</p>
Dynamic Range	<p>10 μW/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)</p>
Dimensions	<p>Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm</p>
Application	<p>High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%.</p>
Compatibility	<p>DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI</p>

Data Acquisition Electronics (DAE)

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY4/5 embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV,400mV)	
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 f A	
Dimensions	60 x 60 x 68 mm	


SAM Twin Phantom

Material	Vynlester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions (incl. Wooden Support)	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	
Wooden Support	SPEAG standard phantom table	

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.

Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.

ELI Phantom

Material	Vinylester, glass fiber reinforced (VE-GF)	
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	
Wooden Support	SPEAG standard phantom table	

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.

ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.

Device Holder for Transmitters




F-2. Device Holder for Transmitters

- The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centres for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.
- The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon=3$ and loss tangent $\delta=0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

1.12 SAR System Check

The microwave circuit arrangement for system Check is sketched in F-12. The daily system accuracy verification occurs within the flat section of the SAM phantom. A SAR measurement was performed to see if the measured SAR was within $\pm 10\%$ from the target SAR values. The tests were conducted on the same days as the measurement of the EUT. The obtained results from the system accuracy verification are displayed in the following table (A power level of 250mW (below 3GHz) or 100mW (3-6GHz) was input to the dipole antenna). During the tests, the ambient temperature of the laboratory was in the range $22\pm 2^{\circ}\text{C}$, the relative humidity was in the range 60% and the liquid depth above the ear reference points was above 15 ± 0.5 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values.



F-12. The block diagram of system check



Validation Kit		Measured SAR 250mW	Measured SAR 250mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W) (±10%)	Target SAR (normalized to 1W) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)		
D750V3	Head	2.11	1.38	8.44	5.52	8.39 (7.55~9.23)	5.63 (5.07~6.19)	22.1	2021/3/18
D835V2	Head	2.37	1.54	9.48	6.16	9.64 (8.68~10.60)	6.29 (5.66~6.92)	22.1	2021/3/18
D1750V2	Head	9.28	4.94	37.12	19.76	36.3 (32.67~39.93)	19.2 (17.28~21.12)	22.2	2021/3/22
D1900V2	Head	8.90	4.62	35.60	18.48	39.3 (35.37~43.23)	20.2 (18.18~22.22)	22.3	2021/3/19
D2450V2	Head	12.90	5.91	51.60	23.64	51.9 (46.71~57.09)	23.8 (21.42~26.18)	22.0	2021/3/21
D2600V2	Head	13.60	6.10	54.40	24.40	56.8 (51.12~62.48)	24.9 (22.41~27.39)	22.1	2021/3/17
Validation Kit		Measured SAR 100mW	Measured SAR 100mW	Measured SAR (normalized to 1W)	Measured SAR (normalized to 1W)	Target SAR (normalized to 1W) (±10%)	Target SAR (normalized to 1W) (±10%)	Liquid Temp. (°C)	Measured Date
		1g (W/kg)	10g (W/kg)	1g (W/kg)	10g (W/kg)	1-g(W/kg)	10-g(W/kg)		
D5GHzV2	Head(5.25GHz)	7.67	2.20	76.70	22.00	75.2 (67.68~82.72)	21.5 (19.35~23.65)	22.2	2021/3/21
	Head(5.6GHz)	8.41	2.39	84.10	23.90	80 (72~88)	22.7 (20.43~24.97)	22.2	2021/3/21
	Head(5.75GHz)	8.32	2.37	83.20	23.70	78.7 (70.83~86.57)	22.3 (20.07~24.53)	22.2	2021/3/21

Table 1. Results of system check



1.13 Tissue Simulant Fluid for the Frequency Band

The dielectric properties for this Tissue Simulate Liquids were measured by using the Agilent Model 85070E Dielectric Probe in conjunction with Agilent E5071C Network Analyzer (300 KHz-8500 MHz). The Conductivity (σ) and Permittivity (ρ) are listed in bellow table. For the SAR measurement given in this report. The temperature variation of the Tissue Simulate Liquids was $22 \pm 2^\circ\text{C}$.

Tissue Type	Measured Frequency (MHz)	Target Tissue ($\pm 5\%$)		Measured Tissue		Liquid Temp. ($^\circ\text{C}$)	Measured Date
		ϵ_r	$\sigma(\text{S/m})$	ϵ_r	$\sigma(\text{S/m})$		
750 Head	750	41.9 (39.81~44)	0.89 (0.85~0.94)	43.670	0.862	22.1	2021/3/18
835 Head	835	41.5 (39.43~43.58)	0.90 (0.86~0.95)	43.077	0.887	22.1	2021/3/18
1750 Head	1750	40.1 (38.10~42.11)	1.37 (1.30~1.44)	40.679	1.336	22.2	2021/3/22
1900 Head	1900	40.0 (38.00~42.00)	1.40 (1.33~1.47)	38.457	1.449	22.3	2021/3/19
2450 Head	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	39.326	1.765	22.0	2021/3/21
2600 Head	2600	39.0 (37.05~40.95)	1.96 (1.86~2.06)	38.835	1.934	22.1	2021/3/17
5250Head	5250	35.9 (34.11~37.70)	4.71 (4.47~4.95)	36.011	4.721	22.2	2021/3/21
5600 Head	5600	35.5 (33.73~37.28)	5.07 (4.82~5.32)	35.059	5.107	22.2	2021/3/21
5750 Head	5750	35.4 (33.63~37.17)	5.22 (4.96~5.48)	34.695	5.279	22.2	2021/3/21

Table 2. Dielectric Parameters of Tissue Simulant Fluid



The composition of the tissue simulating liquid:

Ingredients (% by weight)	Frequency (MHz)				
	450	900	1800-2000	2300-2500	2500-2700
Water	38.56	40.30	55.24	55.00	54.92
Salt (NaCl)	3.95	1.38	0.31	0.2	0.23
Sucrose	56.32	57.90	0	0	0
HEC	0.98	0.24	0	0	0
Bactericide	0.19	0.18	0	0	0
Tween	0	0	44.45	44.80	44.85
Salt: 99+% Pure Sodium Chloride Sucrose: 98+% Pure Sucrose Water: De-ionized, 16 MΩ ⁺ resistivity HEC: Hydroxyethyl Cellulose Tween: Polyoxyethylene (20) sorbitan monolaurate					
HSL5GHz is composed of the following ingredients : Water : 50-65% Mineral oil : 10-30% Emulsifiers : 8-25% Sodium salt : 0-1.5%					

Table 3. Recipes for tissue simulating liquid



1.14 Test Standards and Limits

According to FCC 47CFR §2.1093(d) The limits to be used for evaluation are based generally on criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate ("SAR") in Section 4.2 of "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.1, By the Institute of Electrical and Electronics Engineers, Inc., New York, New York 10017.

These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields," NCRP Report No. 86, Section 17.4.5. Copyright NCRP, 1986, Bethesda, Maryland 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards. The criteria to be used are specified in paragraphs (d)(1) and (d)(2) of this section and shall apply for portable devices transmitting in the frequency range from 100 kHz to 6 GHz. Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified in § 1.1310 of this chapter.

Measurements and calculations to demonstrate compliance with MPE field strength or power density limits for devices operating above 6 GHz should be made at a minimum distance of 5 cm from the radiating source.

1. Limits for Occupational/Controlled exposure: 0.4 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 8 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 20 W/kg, as averaged over a 10 grams of tissue (defined as a tissue volume in the shape of a cube).

Occupational/Controlled limits apply when persons are exposed as a consequence of their employment provided these persons are fully aware of and exercise control over their exposure. Awareness of exposure can be accomplished by use of warning labels or by specific training or education through appropriate means, such as an RF safety program in a work environment.

2. Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube).



Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube).

General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure.

Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section (Table .4)

Human Exposure	Uncontrolled Environment General Population	Controlled Environment Occupational
Spatial Peak SAR (Brain)	1.60 W/kg	8.00 W/kg
Spatial Average SAR (Whole Body)	0.08 W/kg	0.40 W/kg
Spatial Peak SAR (Hands/Feet/Ankle/Wrist)	4.00 W/kg	20.00 W/kg

Table 4. RF exposure limits

Notes:

1. Uncontrolled environments are defined as locations where there is potential exposure of individuals who have no knowledge or control of their potential exposure.
2. Controlled environments are defined as locations where there is potential exposure of individuals who have knowledge of their potential exposure and can exercise control over their exposure.



2 Summary of Results

<GSM 850>

Ant0 Test Record										
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp
Head Test data										
Left cheek	GPRS 4TS	190/836.6	1:2.075	0.195	0.01	27.70	29.00	1.349	0.263	22.1
Left tilted	GPRS 4TS	190/836.6	1:2.075	0.127	0.06	27.70	29.00	1.349	0.171	22.1
Right cheek	GPRS 4TS	190/836.6	1:2.075	0.304	0.14	27.70	29.00	1.349	0.410	22.1
Right tilted	GPRS 4TS	190/836.6	1:2.075	0.155	0.11	27.70	29.00	1.349	0.209	22.1
Body worn Test data(Separate 15mm)										
Front side	GPRS 4TS	190/836.6	1:2.075	0.213	0.01	27.70	29.00	1.349	0.287	22.1
Back side	GPRS 4TS	190/836.6	1:2.075	0.263	-0.15	27.70	29.00	1.349	0.355	22.1
Hotspot Test data(Separate 10mm)										
Front side	GPRS 4TS	190/836.6	1:2.075	0.205	0.07	27.70	29.00	1.349	0.277	22.1
Back side	GPRS 4TS	190/836.6	1:2.075	0.397	-0.14	27.70	29.00	1.349	0.536	22.1
Left side	GPRS 4TS	190/836.6	1:2.075	0.138	0.06	27.70	29.00	1.349	0.186	22.1
Right side	GPRS 4TS	190/836.6	1:2.075	0.181	0.05	27.70	29.00	1.349	0.244	22.1
Bottom side	GPRS 4TS	190/836.6	1:2.075	0.159	0.11	27.70	29.00	1.349	0.214	22.1

<GSM 1900>

Ant1 Test Record										
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp
Head Test data										
Left cheek	GPRS 4TS	661/1880	1:2.075	0.104	0.01	22.19	24.00	1.517	0.158	22.3
Left tilted	GPRS 4TS	661/1880	1:2.075	0.003	0.05	22.19	24.00	1.517	0.005	22.3
Right cheek	GPRS 4TS	661/1880	1:2.075	0.071	0.19	22.19	24.00	1.517	0.108	22.3
Right tilted	GPRS 4TS	661/1880	1:2.075	0.002	0.05	22.19	24.00	1.517	0.003	22.3
Body worn Test data(Separate 15mm)										
Front side	GPRS 4TS	661/1880	1:2.075	0.062	0.05	22.19	24.00	1.517	0.094	22.3
Back side	GPRS 4TS	661/1880	1:2.075	0.086	-0.15	22.19	24.00	1.517	0.131	22.3
Hotspot Test data(Separate 10mm)										
Front side	GPRS 4TS	661/1880	1:2.075	0.158	0.11	22.19	24.00	1.517	0.240	22.3
Back side	GPRS 4TS	661/1880	1:2.075	0.193	0.15	22.19	24.00	1.517	0.293	22.3
Left side	GPRS 4TS	661/1880	1:2.075	0.105	0.06	22.19	24.00	1.517	0.159	22.3
Right side	GPRS 4TS	661/1880	1:2.075	0.001	0.01	22.19	24.00	1.517	0.002	22.3
Bottom side	GPRS 4TS	661/1880	1:2.075	0.157	0.03	22.19	24.00	1.517	0.238	22.3



<WCDMA Band IV>

Ant1 Test Record										
Test position	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted Power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp
Head Test data										
Left cheek	RMC	1412/1732.4	1:1	0.088	0.01	21.82	23.00	1.312	0.115	22.1
Left tilted	RMC	1412/1732.4	1:1	0.084	0.08	21.82	23.00	1.312	0.110	22.1
Right cheek	RMC	1412/1732.4	1:1	0.092	0.16	21.82	23.00	1.312	0.120	22.1
Right tilted	RMC	1412/1732.4	1:1	0.069	0.01	21.82	23.00	1.312	0.091	22.1
Body worn Test data(Separate 15mm)										
Front side	RMC	1412/1732.4	1:1	0.108	0.06	21.82	23.00	1.312	0.142	22.1
Back side	RMC	1412/1732.4	1:1	0.122	0.08	21.82	23.00	1.312	0.160	22.1
Hotspot Test data(Separate 10mm)										
Front side	RMC	1412/1732.4	1:1	0.242	-0.07	21.82	23.00	1.312	0.318	22.1
Back side	RMC	1412/1732.4	1:1	0.260	-0.16	21.82	23.00	1.312	0.341	22.1
Left side	RMC	1412/1732.4	1:1	0.131	0.06	21.82	23.00	1.312	0.172	22.1
Right side	RMC	1412/1732.4	1:1	0.048	0.09	21.82	23.00	1.312	0.063	22.1
Bottom side	RMC	1412/1732.4	1:1	0.234	-0.05	21.82	23.00	1.312	0.307	22.1



<LTE Band 4>

Ant1 Test Record											
Test position	BW.	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data(1RB)											
Left cheek	20	QPSK 1RB_50	20175/1732.5	1:1	0.067	0.06	20.15	21.50	1.365	0.091	22.2
Left tilted	20	QPSK 1RB_50	20175/1732.5	1:1	0.051	0.15	20.15	21.50	1.365	0.070	22.2
Right cheek	20	QPSK 1RB_50	20175/1732.5	1:1	0.061	0.18	20.15	21.50	1.365	0.083	22.2
Right tilted	20	QPSK 1RB_50	20175/1732.5	1:1	0.051	-0.01	20.15	21.50	1.365	0.070	22.2
Head Test data(50%RB)											
Left cheek	20	QPSK 50RB_0	20175/1732.5	1:1	0.058	0.02	19.27	20.50	1.327	0.077	22.2
Left tilted	20	QPSK 50RB_0	20175/1732.5	1:1	0.043	0.08	19.27	20.50	1.327	0.057	22.2
Right cheek	20	QPSK 50RB_0	20175/1732.5	1:1	0.053	-0.03	19.27	20.50	1.327	0.070	22.2
Right tilted	20	QPSK 50RB_0	20175/1732.5	1:1	0.042	0.06	19.27	20.50	1.327	0.056	22.2
Body worn Test data(Separate 15mm 1RB)											
Front side	20	QPSK 1RB_50	20175/1732.5	1:1	0.063	-0.09	20.15	21.50	1.365	0.086	22.2
Back side	20	QPSK 1RB_50	20175/1732.5	1:1	0.072	-0.01	20.15	21.50	1.365	0.098	22.2
Body worn Test data (Separate 15mm 50%RB)											
Front side	20	QPSK 50RB_0	20175/1732.5	1:1	0.061	0.02	19.27	20.50	1.327	0.081	22.2
Back side	20	QPSK 50RB_0	20175/1732.5	1:1	0.065	-0.05	19.27	20.50	1.327	0.086	22.2
Hotspot Test data(Separate 10mm 1RB)											
Front side	20	QPSK 1RB_50	20175/1732.5	1:1	0.145	0.00	20.15	21.50	1.365	0.198	22.2
Back side	20	QPSK 1RB_50	20175/1732.5	1:1	0.167	-0.07	20.15	21.50	1.365	0.228	22.2
Left side	20	QPSK 1RB_50	20175/1732.5	1:1	0.108	0.01	20.15	21.50	1.365	0.147	22.2
Right side	20	QPSK 1RB_50	20175/1732.5	1:1	0.041	0.06	20.15	21.50	1.365	0.056	22.2
Bottom side	20	QPSK 1RB_50	20175/1732.5	1:1	0.152	-0.11	20.15	21.50	1.365	0.207	22.2
Hotspot Test data (Separate 10mm 50%RB)											
Front side	20	QPSK 50RB_0	20175/1732.5	1:1	0.142	-0.13	19.27	20.50	1.327	0.188	22.2
Back side	20	QPSK 50RB_0	20175/1732.5	1:1	0.154	0.03	19.27	20.50	1.327	0.204	22.2
Left side	20	QPSK 50RB_0	20175/1732.5	1:1	0.059	0.03	19.27	20.50	1.327	0.078	22.2
Right side	20	QPSK 50RB_0	20175/1732.5	1:1	0.033	0.06	19.27	20.50	1.327	0.044	22.2
Bottom side	20	QPSK 50RB_0	20175/1732.5	1:1	0.150	-0.19	19.27	20.50	1.327	0.199	22.2



<LTE Band 12>

Ant0 Test Record											
Test position	BW.	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data(1RB)											
Left cheek	10	QPSK 1RB 49	23095/707.5	1:1	0.133	0.05	23.75	24.50	1.189	0.158	22.1
Left tilted	10	QPSK 1RB 49	23095/707.5	1:1	0.081	-0.02	23.75	24.50	1.189	0.096	22.1
Right cheek	10	QPSK 1RB 49	23095/707.5	1:1	0.179	-0.03	23.75	24.50	1.189	0.213	22.1
Right tilted	10	QPSK 1RB 49	23095/707.5	1:1	0.094	0.19	23.75	24.50	1.189	0.112	22.1
Head Test data(50%RB)											
Left cheek	10	QPSK 25RB 25	23095/707.5	1:1	0.111	0.13	22.74	23.50	1.191	0.132	22.1
Left tilted	10	QPSK 25RB 25	23095/707.5	1:1	0.071	0.05	22.74	23.50	1.191	0.085	22.1
Right cheek	10	QPSK 25RB 25	23095/707.5	1:1	0.131	-0.01	22.74	23.50	1.191	0.156	22.1
Right tilted	10	QPSK 25RB 25	23095/707.5	1:1	0.059	0.15	22.74	23.50	1.191	0.070	22.1
Body worn Test data(Separate 15mm 1RB)											
Front side	10	QPSK 1RB 49	23095/707.5	1:1	0.215	0.02	23.75	24.50	1.189	0.256	22.1
Back side	10	QPSK 1RB 49	23095/707.5	1:1	0.306	-0.04	23.75	24.50	1.189	0.364	22.1
Body worn Test data (Separate 15mm 50%RB)											
Front side	10	QPSK 25RB 25	23095/707.5	1:1	0.181	0.02	22.74	23.50	1.191	0.216	22.1
Back side	10	QPSK 25RB 25	23095/707.5	1:1	0.251	-0.03	22.74	23.50	1.191	0.299	22.1
Hotspot Test data(Separate 10mm 1RB)											
Front side	10	QPSK 1RB 49	23095/707.5	1:1	0.181	-0.01	23.75	24.50	1.189	0.215	22.1
Back side	10	QPSK 1RB 49	23095/707.5	1:1	0.348	0.04	23.75	24.50	1.189	0.414	22.1
Left side	10	QPSK 1RB 49	23095/707.5	1:1	0.208	-0.09	23.75	24.50	1.189	0.247	22.1
Right side	10	QPSK 1RB 49	23095/707.5	1:1	0.301	-0.05	23.75	24.50	1.189	0.358	22.1
Bottom side	10	QPSK 1RB 49	23095/707.5	1:1	0.081	0.05	23.75	24.50	1.189	0.096	22.1
Hotspot Test data (Separate 10mm 50%RB)											
Front side	10	QPSK 25RB 25	23095/707.5	1:1	0.175	0.06	22.74	23.50	1.191	0.208	22.1
Back side	10	QPSK 25RB 25	23095/707.5	1:1	0.281	-0.02	22.74	23.50	1.191	0.335	22.1
Left side	10	QPSK 25RB 25	23095/707.5	1:1	0.171	0.06	22.74	23.50	1.191	0.204	22.1
Right side	10	QPSK 25RB 25	23095/707.5	1:1	0.251	0.03	22.74	23.50	1.191	0.299	22.1
Bottom side	10	QPSK 25RB 25	23095/707.5	1:1	0.062	0.11	22.74	23.50	1.191	0.074	22.1



<LTE Band 41>

Ant0 Test Record											
Test position	BW.	Test mode	Test Ch./Freq.	Duty Cycle	SAR (W/kg)1-g	Power Drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data(1RB)											
Left cheek	20	QPSK 1RB_99	40620/2593	1:1.58	0.106	0.04	21.81	22.80	1.256	0.133	22.1
Left tilted	20	QPSK 1RB_99	40620/2593	1:1.58	0.033	0.16	21.81	22.80	1.256	0.041	22.1
Right cheek	20	QPSK 1RB_99	40620/2593	1:1.58	0.032	0.03	21.81	22.80	1.256	0.040	22.1
Right tilted	20	QPSK 1RB_99	40620/2593	1:1.58	0.013	0.13	21.81	22.80	1.256	0.016	22.1
Head Test data(50%RB)											
Left cheek	20	QPSK 50RB_0	41490/2680	1:1.58	0.051	0.19	21.38	21.80	1.102	0.056	22.1
Left tilted	20	QPSK 50RB_0	41490/2680	1:1.58	0.022	0.01	21.38	21.80	1.102	0.024	22.1
Right cheek	20	QPSK 50RB_0	41490/2680	1:1.58	0.020	0.06	21.38	21.80	1.102	0.022	22.1
Right tilted	20	QPSK 50RB_0	41490/2680	1:1.58	0.008	-0.10	21.38	21.80	1.102	0.009	22.1
Body worn Test data(Separate 15mm 1RB)											
Front side	20	QPSK 1RB_99	40620/2593	1:1.58	0.088	-0.09	21.81	22.80	1.256	0.111	22.1
Back side	20	QPSK 1RB_99	40620/2593	1:1.58	0.413	-0.01	21.81	22.80	1.256	0.519	22.1
Body worn Test data (Separate 15mm 50%RB)											
Front side	20	QPSK 50RB_0	41490/2680	1:1.58	0.077	-0.09	21.38	21.80	1.102	0.085	22.1
Back side	20	QPSK 50RB_0	41490/2680	1:1.58	0.220	-0.01	21.38	21.80	1.102	0.242	22.1
Hotspot Test data(Separate 10mm 1RB)											
Front side	20	QPSK 1RB_99	40620/2593	1:1.58	0.165	0.18	21.81	22.80	1.256	0.207	22.1
Back side	20	QPSK 1RB_99	40620/2593	1:1.58	0.767	0.15	21.81	22.80	1.256	0.963	22.1
Left side	20	QPSK 1RB_99	40620/2593	1:1.58	0.055	0.02	21.81	22.80	1.256	0.069	22.1
Right side	20	QPSK 1RB_99	40620/2593	1:1.58	0.065	0.16	21.81	22.80	1.256	0.082	22.1
Bottom side	20	QPSK 1RB_99	40620/2593	1:1.58	0.471	0.11	21.81	22.80	1.256	0.592	22.1
Back side	20	QPSK 1RB_99	39750/2506	1:1.58	0.599	0.03	21.47	22.80	1.358	0.814	22.1
Back side	20	QPSK 1RB_99	40185/2549.5	1:1.58	0.621	0.13	21.58	22.80	1.324	0.822	22.1
Back side	20	QPSK 1RB_0	41055/2636.5	1:1.58	0.551	0.06	21.56	22.80	1.330	0.733	22.1
Back side	20	QPSK 1RB_0	41490/2680	1:1.58	0.457	0.05	21.43	22.80	1.371	0.626	22.1
Hotspot Test data (Separate 10mm 50%RB)											
Front side	20	QPSK 50RB_0	41490/2680	1:1.58	0.190	0.01	21.38	21.80	1.102	0.209	22.1
Back side	20	QPSK 50RB_0	41490/2680	1:1.58	0.563	0.11	21.38	21.80	1.102	0.620	22.1
Left side	20	QPSK 50RB_0	41490/2680	1:1.58	0.049	0.16	21.38	21.80	1.102	0.054	22.1
Right side	20	QPSK 50RB_0	41490/2680	1:1.58	0.058	0.02	21.38	21.80	1.102	0.064	22.1
Bottom side	20	QPSK 50RB_0	41490/2680	1:1.58	0.441	0.13	21.38	21.80	1.102	0.486	22.1
Hotspot Test data (Separate 10mm 100%RB)											
Back side	20	QPSK 100RB_0	40620/2593	1:1.58	0.561	0.13	20.82	21.80	1.253	0.703	22.1



<WiFi 2.4G>

Wi-Fi 2.4G SAR Test Record ANT6											
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data											
Left cheek	802.11b	11/2462	99.00%	1.01	0.201	0.06	15.17	16.00	1.211	0.246	22.0
Left tilted	802.11b	11/2462	99.00%	1.01	0.115	-0.06	15.17	16.00	1.211	0.141	22.0
Right cheek	802.11b	11/2462	99.00%	1.01	0.458	0.04	15.17	16.00	1.211	0.560	22.0
Right tilted	802.11b	11/2462	99.00%	1.01	0.238	0.02	15.17	16.00	1.211	0.291	22.0
Body worn Test data(Separate 15mm)											
Front side	802.11b	11/2462	99.00%	1.01	0.001	0.01	15.17	16.00	1.211	0.001	22.0
Back side	802.11b	11/2462	99.00%	1.01	0.064	-0.08	15.17	16.00	1.211	0.078	22.0
Hotspot Test data (Separate 10mm)											
Front side	802.11b	11/2462	99.00%	1.01	0.056	0.11	15.17	16.00	1.211	0.068	22.0
Back side	802.11b	11/2462	99.00%	1.01	0.141	-0.02	15.17	16.00	1.211	0.172	22.0
Left side	802.11b	11/2462	99.00%	1.01	0.042	0.03	15.17	16.00	1.211	0.051	22.0
Right side	802.11b	11/2462	99.00%	1.01	0.002	0.02	15.17	16.00	1.211	0.002	22.0
Top side	802.11b	11/2462	99.00%	1.01	0.075	0.15	15.17	16.00	1.211	0.092	22.0
Wi-Fi 2.4G SAR Test Record ANT7											
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data											
Left cheek	802.11b	1/2412	99.00%	1.01	0.093	0.09	15.01	16.00	1.256	0.118	22.0
Left tilted	802.11b	1/2412	99.00%	1.01	0.002	0.01	15.01	16.00	1.256	0.003	22.0
Right cheek	802.11b	1/2412	99.00%	1.01	0.002	0.06	15.01	16.00	1.256	0.003	22.0
Right tilted	802.11b	1/2412	99.00%	1.01	0.001	0.01	15.01	16.00	1.256	0.001	22.0
Body worn Test data(Separate 15mm)											
Front side	802.11b	1/2412	99.00%	1.01	0.012	-0.03	15.01	16.00	1.256	0.015	22.0
Back side	802.11b	1/2412	99.00%	1.01	0.014	0.06	15.01	16.00	1.256	0.018	22.0
Hotspot Test data (Separate 10mm)											
Front side	802.11b	1/2412	99.00%	1.01	0.001	0.03	15.01	16.00	1.256	0.001	22.0
Back side	802.11b	1/2412	99.00%	1.01	0.044	-0.02	15.01	16.00	1.256	0.056	22.0
Left side	802.11b	1/2412	99.00%	1.01	0.002	0.16	15.01	16.00	1.256	0.003	22.0
Right side	802.11b	1/2412	99.00%	1.01	0.001	0.17	15.01	16.00	1.256	0.001	22.0
Top side	802.11b	1/2412	99.00%	1.01	0.002	0.03	15.01	16.00	1.256	0.003	22.0
Wi-Fi 2.4G SAR Test Record (MIMO)											
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data											
Left cheek	802.11b	6/2437	99.00%	1.01	0.179	0.06	18.07	19.00	1.238	0.224	22.0
Left tilted	802.11b	6/2437	99.00%	1.01	0.136	0.02	18.07	19.00	1.238	0.170	22.0
Right cheek	802.11b	6/2437	99.00%	1.01	0.378	0.04	18.07	19.00	1.238	0.473	22.0
Right tilted	802.11b	6/2437	99.00%	1.01	0.223	0.09	18.07	19.00	1.238	0.279	22.0
Body worn Test data(Separate 15mm)											
Front side	802.11b	6/2437	99.00%	1.01	0.045	-0.02	18.07	19.00	1.238	0.056	22.0
Back side	802.11b	6/2437	99.00%	1.01	0.052	0.03	18.07	19.00	1.238	0.066	22.0
Hotspot Test data (Separate 10mm)											
Front side	802.11b	6/2437	99.00%	1.01	0.081	0.03	18.07	19.00	1.238	0.101	22.0
Back side	802.11b	6/2437	99.00%	1.01	0.108	-0.04	18.07	19.00	1.238	0.135	22.0
Left side	802.11b	6/2437	99.00%	1.01	0.051	-0.11	18.07	19.00	1.238	0.064	22.0
Right side	802.11b	6/2437	99.00%	1.01	0.003	0.06	18.07	19.00	1.238	0.004	22.0
Top side	802.11b	6/2437	99.00%	1.01	0.071	0.11	18.07	19.00	1.238	0.089	22.0



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



<WiFi 5G>

Wi-Fi 5G SAR Test Record ANT6											
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data of U-NII-2A											
Left cheek	802.11ac80	58/5290	94.00%	1.064	0.225	0.03	14.18	15.00	1.208	0.289	22.2
Left tilted	802.11ac80	58/5290	94.00%	1.064	0.278	0.12	14.18	15.00	1.208	0.357	22.2
Right cheek	802.11ac80	58/5290	94.00%	1.064	0.316	0.03	14.18	15.00	1.208	0.406	22.2
Right tilted	802.11ac80	58/5290	94.00%	1.064	0.439	-0.04	14.18	15.00	1.208	0.564	22.2
Head Test data of U-NII-2C											
Left cheek	802.11ac80	138/5690	94.00%	1.064	0.111	0.03	13.87	15.00	1.297	0.153	22.2
Left tilted	802.11ac80	138/5690	94.00%	1.064	0.139	-0.12	13.87	15.00	1.297	0.192	22.2
Right cheek	802.11ac80	138/5690	94.00%	1.064	0.158	-0.01	13.87	15.00	1.297	0.218	22.2
Right tilted	802.11ac80	138/5690	94.00%	1.064	0.175	0.09	13.87	15.00	1.297	0.242	22.2
Head Test data of U-NII-3											
Left cheek	802.11ac80	155/5775	94.00%	1.064	0.118	0.02	13.59	15.00	1.384	0.174	22.2
Left tilted	802.11ac80	155/5775	94.00%	1.064	0.152	0.03	13.59	15.00	1.384	0.224	22.2
Right cheek	802.11ac80	155/5775	94.00%	1.064	0.159	0.02	13.59	15.00	1.384	0.234	22.2
Right tilted	802.11ac80	155/5775	94.00%	1.064	0.106	-0.18	13.59	15.00	1.384	0.156	22.2
Body worn Test data of U-NII-2A (Separate 15mm)											
Front side	802.11ac80	58/5290	94.00%	1.064	0.059	0.11	14.18	15.00	1.208	0.076	22.2
Back side	802.11ac80	58/5290	94.00%	1.064	0.101	-0.09	14.18	15.00	1.208	0.130	22.2
Body worn Test data of U-NII-2C (Separate 15mm)											
Front side	802.11ac80	138/5690	94.00%	1.064	0.088	0.08	13.87	15.00	1.297	0.121	22.2
Back side	802.11ac80	138/5690	94.00%	1.064	0.093	-0.14	13.87	15.00	1.297	0.128	22.2
Body worn Test data of U-NII-3 (Separate 15mm)											
Front side	802.11ac80	155/5775	94.00%	1.064	0.075	-0.18	13.59	15.00	1.384	0.110	22.2
Back side	802.11ac80	155/5775	94.00%	1.064	0.119	0.09	13.59	15.00	1.384	0.175	22.2
Hotspot Test data of U-NII-1 (Separate 10mm)											
Front side	802.11ac80	42/5210	94.00%	1.064	0.010	0.18	14.05	15.00	1.245	0.013	22.2
Back side	802.11ac80	42/5210	94.00%	1.064	0.171	0.05	14.05	15.00	1.245	0.226	22.2
Left side	802.11ac80	42/5210	94.00%	1.064	0.138	-0.07	14.05	15.00	1.245	0.183	22.2
Right side	802.11ac80	42/5210	94.00%	1.064	0.051	-0.06	14.05	15.00	1.245	0.068	22.2
Top side	802.11ac80	42/5210	94.00%	1.064	0.110	0.11	14.05	15.00	1.245	0.146	22.2
Hotspot Test data of U-NII-3 (Separate 10mm)											
Front side	802.11ac80	155/5775	94.00%	1.064	0.089	0.08	13.59	15.00	1.384	0.131	22.2
Back side	802.11ac80	155/5775	94.00%	1.064	0.105	0.13	13.59	15.00	1.384	0.155	22.2
Left side	802.11ac80	155/5775	94.00%	1.064	0.074	-0.08	13.59	15.00	1.384	0.109	22.2
Right side	802.11ac80	155/5775	94.00%	1.064	0.071	0.07	13.59	15.00	1.384	0.105	22.2
Top side	802.11ac80	155/5775	94.00%	1.064	0.083	0.14	13.59	15.00	1.384	0.122	22.2
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)10-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Product specific 10gSAR Test data of U-NII-2A (Separate 0mm)											
Front side	802.11ac80	58/5290	94.00%	1.064	0.161	-0.13	14.18	15.00	1.208	0.207	22.2
Back side	802.11ac80	58/5290	94.00%	1.064	0.381	0.06	14.18	15.00	1.208	0.490	22.2
Left side	802.11ac80	58/5290	94.00%	1.064	0.191	0.17	14.18	15.00	1.208	0.245	22.2
Right side	802.11ac80	58/5290	94.00%	1.064	0.015	0.18	14.18	15.00	1.208	0.019	22.2
Top side	802.11ac80	58/5290	94.00%	1.064	0.359	0.19	14.18	15.00	1.208	0.461	22.2
Product specific 10gSAR Test data of U-NII-2C (Separate 0mm)											
Front side	802.11ac80	138/5690	94.00%	1.064	0.094	-0.13	13.87	15.00	1.297	0.130	22.2
Back side	802.11ac80	138/5690	94.00%	1.064	0.792	0.00	13.87	15.00	1.297	1.093	22.2
Left side	802.11ac80	138/5690	94.00%	1.064	0.159	0.18	13.87	15.00	1.297	0.219	22.2
Right side	802.11ac80	138/5690	94.00%	1.064	0.026	0.01	13.87	15.00	1.297	0.036	22.2
Top side	802.11ac80	138/5690	94.00%	1.064	0.189	-0.05	13.87	15.00	1.297	0.261	22.2
Wi-Fi 5G SAR Test Record ANT7											
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.





Head Test data of U-NII-2A											
Left cheek	802.11ac80	58/5290	94.00%	1.064	0.030	0.04	13.48	14.00	1.127	0.036	22.2
Left tilted	802.11ac80	58/5290	94.00%	1.064	0.021	0.17	13.48	14.00	1.127	0.025	22.2
Right cheek	802.11ac80	58/5290	94.00%	1.064	0.029	0.03	13.48	14.00	1.127	0.035	22.2
Right tilted	802.11ac80	58/5290	94.00%	1.064	0.024	-0.11	13.48	14.00	1.127	0.029	22.2
Head Test data of U-NII-2C											
Left cheek	802.11ac80	138/5690	94.00%	1.064	0.029	-0.07	12.53	14.00	1.403	0.043	22.2
Left tilted	802.11ac80	138/5690	94.00%	1.064	0.030	-0.03	12.53	14.00	1.403	0.045	22.2
Right cheek	802.11ac80	138/5690	94.00%	1.064	0.027	-0.03	12.53	14.00	1.403	0.040	22.2
Right tilted	802.11ac80	138/5690	94.00%	1.064	0.026	-0.13	12.53	14.00	1.403	0.039	22.2
Head Test data of U-NII-3											
Left cheek	802.11ac80	155/5775	94.00%	1.064	0.039	0.02	13.43	14.00	1.140	0.047	22.2
Left tilted	802.11ac80	155/5775	94.00%	1.064	0.013	0.01	13.43	14.00	1.140	0.016	22.2
Right cheek	802.11ac80	155/5775	94.00%	1.064	0.027	-0.08	13.43	14.00	1.140	0.033	22.2
Right tilted	802.11ac80	155/5775	94.00%	1.064	0.010	-0.01	13.43	14.00	1.140	0.012	22.2
Body worn Test data of U-NII-2A (Separate 15mm)											
Front side	802.11ac80	58/5290	94.00%	1.064	0.051	0.16	13.48	14.00	1.127	0.061	22.2
Back side	802.11ac80	58/5290	94.00%	1.064	0.123	-0.02	13.48	14.00	1.127	0.148	22.2
Body worn Test data of U-NII-2C (Separate 15mm)											
Front side	802.11ac80	138/5690	94.00%	1.064	0.051	-0.04	12.53	14.00	1.403	0.076	22.2
Back side	802.11ac80	138/5690	94.00%	1.064	0.078	-0.17	12.53	14.00	1.403	0.116	22.2
Body worn Test data of U-NII-3 (Separate 15mm)											
Front side	802.11ac80	155/5775	94.00%	1.064	0.036	0.16	13.43	14.00	1.140	0.044	22.2
Back side	802.11ac80	155/5775	94.00%	1.064	0.051	-0.06	13.43	14.00	1.140	0.062	22.2
Hotspot Test data of U-NII-1 (Separate 10mm)											
Front side	802.11ac80	42/5210	94.00%	1.064	0.065	0.09	13.35	14.00	1.161	0.080	22.2
Back side	802.11ac80	42/5210	94.00%	1.064	0.232	0.09	13.35	14.00	1.161	0.287	22.2
Left side	802.11ac80	42/5210	94.00%	1.064	0.076	0.11	13.35	14.00	1.161	0.094	22.2
Right side	802.11ac80	42/5210	94.00%	1.064	0.089	0.13	13.35	14.00	1.161	0.110	22.2
Top side	802.11ac80	42/5210	94.00%	1.064	0.061	-0.08	13.35	14.00	1.161	0.075	22.2
Hotspot Test data of U-NII-3 (Separate 10mm)											
Front side	802.11ac80	155/5775	94.00%	1.064	0.071	-0.06	13.43	14.00	1.140	0.086	22.2
Back side	802.11ac80	155/5775	94.00%	1.064	0.168	0.02	13.43	14.00	1.140	0.204	22.2
Left side	802.11ac80	155/5775	94.00%	1.064	0.088	-0.13	13.43	14.00	1.140	0.107	22.2
Right side	802.11ac80	155/5775	94.00%	1.064	0.102	-0.12	13.43	14.00	1.140	0.124	22.2
Top side	802.11ac80	155/5775	94.00%	1.064	0.063	-0.13	13.43	14.00	1.140	0.076	22.2
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)10-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Product specific 10gSAR Test data of U-NII-2A (Separate 0mm)											
Front side	802.11ac80	58/5290	94.00%	1.064	0.025	-0.19	13.48	14.00	1.127	0.030	22.2
Back side	802.11ac80	58/5290	94.00%	1.064	0.051	-0.01	13.48	14.00	1.127	0.061	22.2
Left side	802.11ac80	58/5290	94.00%	1.064	0.019	-0.17	13.48	14.00	1.127	0.023	22.2
Right side	802.11ac80	58/5290	94.00%	1.064	0.152	0.03	13.48	14.00	1.127	0.182	22.2
Top side	802.11ac80	58/5290	94.00%	1.064	0.026	0.19	13.48	14.00	1.127	0.031	22.2
Product specific 10gSAR Test data of U-NII-2C (Separate 0mm)											
Front side	802.11ac80	138/5690	94.00%	1.064	0.031	0.03	12.53	14.00	1.403	0.046	22.2
Back side	802.11ac80	138/5690	94.00%	1.064	0.773	0.10	12.53	14.00	1.403	1.154	22.2
Left side	802.11ac80	138/5690	94.00%	1.064	0.016	-0.16	12.53	14.00	1.403	0.024	22.2
Right side	802.11ac80	138/5690	94.00%	1.064	0.229	0.01	12.53	14.00	1.403	0.342	22.2
Top side	802.11ac80	138/5690	94.00%	1.064	0.027	-0.18	12.53	14.00	1.403	0.040	22.2
Wi-Fi 5G SAR Test Record (MIMO)											
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data of U-NII-2A											
Left cheek	802.11ac80	58/5290	94.00%	1.064	0.201	0.00	16.85	17.54	1.171	0.250	22.2
Left tilted	802.11ac80	58/5290	94.00%	1.064	0.261	0.12	16.85	17.54	1.171	0.325	22.2
Right cheek	802.11ac80	58/5290	94.00%	1.064	0.255	-0.11	16.85	17.54	1.171	0.318	22.2
Right tilted	802.11ac80	58/5290	94.00%	1.064	0.391	0.04	16.85	17.54	1.171	0.487	22.2





Head Test data of U-NII-2C											
Left cheek	802.11ac80	138/5690	94.00%	1.064	0.081	0.03	16.26	17.54	1.342	0.116	22.2
Left tilted	802.11ac80	138/5690	94.00%	1.064	0.111	0.16	16.26	17.54	1.342	0.159	22.2
Right cheek	802.11ac80	138/5690	94.00%	1.064	0.139	-0.01	16.26	17.54	1.342	0.199	22.2
Right tilted	802.11ac80	138/5690	94.00%	1.064	0.129	0.13	16.26	17.54	1.342	0.184	22.2
Head Test data of U-NII-3											
Left cheek	802.11ac80	155/5775	94.00%	1.064	0.116	-0.17	16.52	17.54	1.264	0.156	22.2
Left tilted	802.11ac80	155/5775	94.00%	1.064	0.112	0.04	16.52	17.54	1.264	0.151	22.2
Right cheek	802.11ac80	155/5775	94.00%	1.064	0.109	-0.14	16.52	17.54	1.264	0.147	22.2
Right tilted	802.11ac80	155/5775	94.00%	1.064	0.083	-0.02	16.52	17.54	1.264	0.112	22.2
Body worn Test data of U-NII-2A (Separate 15mm)											
Front side	802.11ac80	58/5290	94.00%	1.064	0.071	-0.19	16.85	17.54	1.171	0.088	22.2
Back side	802.11ac80	58/5290	94.00%	1.064	0.111	0.07	16.85	17.54	1.171	0.138	22.2
Body worn Test data of U-NII-2C (Separate 15mm)											
Front side	802.11ac80	138/5690	94.00%	1.064	0.106	0.06	16.26	17.54	1.342	0.151	22.2
Back side	802.11ac80	138/5690	94.00%	1.064	0.159	-0.03	16.26	17.54	1.342	0.227	22.2
Body worn Test data of U-NII-3 (Separate 15mm)											
Front side	802.11ac80	155/5775	94.00%	1.064	0.061	-0.16	16.52	17.54	1.264	0.082	22.2
Back side	802.11ac80	155/5775	94.00%	1.064	0.106	-0.17	16.52	17.54	1.264	0.143	22.2
Hotspot Test data of U-NII-1 (Separate 10mm)											
Front side	802.11ac80	42/5210	94.00%	1.064	0.101	-0.02	16.72	17.54	1.207	0.130	22.2
Back side	802.11ac80	42/5210	94.00%	1.064	0.200	0.07	16.72	17.54	1.207	0.257	22.2
Left side	802.11ac80	42/5210	94.00%	1.064	0.133	-0.13	16.72	17.54	1.207	0.171	22.2
Right side	802.11ac80	42/5210	94.00%	1.064	0.091	0.06	16.72	17.54	1.207	0.117	22.2
Top side	802.11ac80	42/5210	94.00%	1.064	0.198	0.16	16.72	17.54	1.207	0.254	22.2
Hotspot Test data of U-NII-3 (Separate 10mm)											
Front side	802.11ac80	155/5775	94.00%	1.064	0.102	-0.14	16.52	17.54	1.264	0.137	22.2
Back side	802.11ac80	155/5775	94.00%	1.064	0.177	0.14	16.52	17.54	1.264	0.238	22.2
Left side	802.11ac80	155/5775	94.00%	1.064	0.068	0.04	16.52	17.54	1.264	0.091	22.2
Right side	802.11ac80	155/5775	94.00%	1.064	0.094	-0.02	16.52	17.54	1.264	0.126	22.2
Top side	802.11ac80	155/5775	94.00%	1.064	0.091	0.08	16.52	17.54	1.264	0.122	22.2
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)10-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Product specific 10gSAR Test data of U-NII-2A (Separate 0mm)											
Front side	802.11ac80	58/5290	94.00%	1.064	0.165	-0.02	16.85	17.54	1.171	0.206	22.2
Back side	802.11ac80	58/5290	94.00%	1.064	0.492	0.07	16.85	17.54	1.171	0.613	22.2
Left side	802.11ac80	58/5290	94.00%	1.064	0.195	0.00	16.85	17.54	1.171	0.243	22.2
Right side	802.11ac80	58/5290	94.00%	1.064	0.166	0.17	16.85	17.54	1.171	0.207	22.2
Top side	802.11ac80	58/5290	94.00%	1.064	0.406	-0.06	16.85	17.54	1.171	0.506	22.2
Product specific 10gSAR Test data of U-NII-2C (Separate 0mm)											
Front side	802.11ac80	138/5690	94.00%	1.064	0.106	0.13	16.26	17.54	1.342	0.151	22.2
Back side	802.11ac80	138/5690	94.00%	1.064	0.421	-0.02	16.26	17.54	1.342	0.601	22.2
Left side	802.11ac80	138/5690	94.00%	1.064	0.142	0.04	16.26	17.54	1.342	0.203	22.2
Right side	802.11ac80	138/5690	94.00%	1.064	0.201	-0.10	16.26	17.54	1.342	0.287	22.2
Top side	802.11ac80	138/5690	94.00%	1.064	0.222	0.10	16.26	17.54	1.342	0.317	22.2

Note: This project WLAN 5GHz (5250-5350 & 5470-5725) does not support Hotspot.



<BT>

Bluetooth SAR Test Record ANT6											
Test position	Test mode	Test Ch./Freq.	Duty Cycle	Duty Cycle Scaled factor	SAR (W/kg)1-g	Power drift(dB)	Conducted power(dBm)	Tune up Limit(dBm)	Scaled factor	Scaled SAR(W/kg)	Liquid Temp.
Head Test data											
Left cheek	DH5	78/2480	0.77	1.30	0.069	0.16	12.03	12.50	1.114	0.100	22
Left tilted	DH5	78/2480	0.77	1.30	0.039	0.01	12.03	12.50	1.114	0.056	22
Right cheek	DH5	78/2480	0.77	1.30	0.148	-0.03	12.03	12.50	1.114	0.214	22
Right tilted	DH5	78/2480	0.77	1.30	0.076	-0.01	12.03	12.50	1.114	0.110	22
Body worn Test data(Separate 15mm)											
Front side	DH5	78/2480	0.77	1.30	0.002	0.06	12.03	12.50	1.114	0.003	22
Back side	DH5	78/2480	0.77	1.30	0.024	0.01	12.03	12.50	1.114	0.034	22
Hotspot Test data (Separate 10mm)											
Front side	DH5	78/2480	0.77	1.30	0.006	0.01	12.03	12.50	1.114	0.009	22
Back side	DH5	78/2480	0.77	1.30	0.048	-0.09	12.03	12.50	1.114	0.069	22
Left side	DH5	78/2480	0.77	1.30	0.002	0.12	12.03	12.50	1.114	0.003	22
Right side	DH5	78/2480	0.77	1.30	0.001	0.01	12.03	12.50	1.114	0.001	22
Top side	DH5	78/2480	0.77	1.30	0.003	-0.12	12.03	12.50	1.114	0.004	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

3 Simultaneous Transmission Analysis

3.1 Simultaneous Transmission Scenarios:

NO.	Simultaneous Transmission Configuration	Head	Body worn	Hotspot
1	GSM + WiFi	Yes	Yes	Yes
2	GSM + BT	Yes	Yes	Yes
3	WCDMA + WiFi	Yes	Yes	Yes
4	WCDMA + BT	Yes	Yes	Yes
5	LTE + WiFi	Yes*	Yes	Yes
6	LTE + BT	Yes	Yes	Yes
7	BT + 5G WIFI	Yes	Yes	Yes
8	BT + 2.4G WIFI(ANT6)	No	No	No
9	BT + 2.4G WIFI(ANT7)	Yes	Yes	Yes
10	GSM + BT + 5G WIFI	Yes	Yes	Yes
11	WCDMA + BT + 5G WIFI	Yes	Yes	Yes
12	LTE + BT + 5G WIFI	Yes*	Yes	Yes

Note:

- 1) Wi-Fi 2.4G(ANT6) and Bluetooth (ANT6) can't transmit simultaneously.
- 2) The device does not support DTM function.
- 3) * VoLTE or pre-installed VOIP applications are considered.
- 4) This project WLAN 5GHz (5250-5350 & 5470-5725) does not support Hotspot.



3.2 Simultaneous Transmission Combination Scenario

Test position		1						2	3	4	5	1+2	1+3	1+4	1+3+4	1+4+5
		Main Antenna SARmax (W/kg)						WiFi/BT Antenna SARmax (W/kg)			WIFI 2.4G ANT7	Summed 1g SARmax (W/kg)	Summed 1g SARmax (W/kg)	Summed 1g SARmax (W/kg)	Summed 1g SARmax (W/kg)	Summed 1g SARmax (W/kg)
		GSM850	GSM1900	WCDMA Band IV	LTE Band 4	LTE Band 12	LTE Band 41	WiFi 2.4G	WiFi 5G	BT	WiFi 2.4G					
Head	Left Touch	0.263	0.158	0.115	0.091	0.158	0.133	0.246	0.289	0.100	0.118	0.509	0.552	0.363	0.652	0.481
	Left Tilt	0.171	0.005	0.110	0.070	0.096	0.041	0.170	0.357	0.056	0.003	0.341	0.528	0.227	0.584	0.230
	Right Touch	0.410	0.108	0.120	0.083	0.213	0.040	0.560	0.406	0.214	0.003	0.970	0.816	0.624	1.030	0.627
	Right Tilt	0.209	0.003	0.091	0.070	0.112	0.016	0.291	0.564	0.110	0.001	0.500	0.773	0.319	0.883	0.320
Body 15mm	Front	0.287	0.094	0.142	0.086	0.256	0.111	0.056	0.151	0.003	0.015	0.343	0.438	0.290	0.441	0.305
	Back	0.355	0.131	0.160	0.098	0.364	0.519	0.078	0.227	0.034	0.018	0.597	0.746	0.553	0.780	0.571
Hotspot	Front	0.277	0.240	0.318	0.198	0.215	0.209	0.101	0.137	0.009	0.001	0.419	0.455	0.327	0.464	0.328
	Back	0.536	0.293	0.341	0.228	0.414	0.963	0.172	0.287	0.069	0.056	1.135	1.250	1.032	1.319	1.088
	Left	0.186	0.159	0.172	0.147	0.247	0.069	0.064	0.183	0.003	0.003	0.311	0.430	0.250	0.433	0.253
	Right	0.244	0.002	0.063	0.056	0.358	0.082	0.004	0.126	0.001	0.001	0.362	0.484	0.359	0.485	0.360
	Top	/	/	/	/	/	/	0.092	0.254	0.004	0.003	0.092	0.254	0.004	0.258	0.007
	Bottom	0.214	0.238	0.307	0.207	0.096	0.592	/	/	/	/	0.592	0.592	0.592	0.592	0.592
Product specific 10g SAR	Front	/	/	/	/	/	/	/	0.207	/	/	/	0.207	/	0.207	/
	Back	/	/	/	/	/	/	/	1.154	/	/	/	1.154	/	1.154	/
	Left	/	/	/	/	/	/	/	0.245	/	/	/	0.245	/	0.245	/
	Right	/	/	/	/	/	/	/	0.342	/	/	/	0.342	/	0.342	/
	Top	/	/	/	/	/	/	/	0.506	/	/	/	0.506	/	0.506	/
	Bottom	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com



4 Instruments List

Test Platform		SPEAG DASY5 Professional				
Location		SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch				
Description		SAR Test System (Frequency range 300MHz-6GHz)				
Software Reference		DASY52; SEMCAD				
Hardware Reference						
Equipment		Manufacturer	Model	Serial Number	Calibration Date	Due date of calibration
<input checked="" type="checkbox"/>	Twin Phantom	SPEAG	SAM 2	1913	NCR	NCR
<input checked="" type="checkbox"/>	DAE	SPEAG	DAE4	1267	2020-06-12	2021-06-11
<input checked="" type="checkbox"/>	E-Field Probe	SPEAG	EX3DV4	3748	2020-07-29	2021-07-28
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D750V3	1160	2019-05-22	2022-05-21
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D835V2	4d105	2019-12-17	2022-12-16
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D1750V2	1149	2019-05-21	2022-05-20
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D1900V2	5d028	2019-12-17	2022-12-16
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D2450V2	733	2019-12-17	2022-12-16
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D2600V2	1125	2019-05-20	2022-05-19
<input checked="" type="checkbox"/>	Validation Kits	SPEAG	D5GHzV2	1165	2019-12-20	2022-12-19
<input checked="" type="checkbox"/>	Agilent Network Analyzer	Agilent	E5071C	MY46523590	2020-04-02	2021-04-01
<input checked="" type="checkbox"/>	Dielectric Probe Kit	Agilent	85070E	US01440210	NCR	NCR
<input checked="" type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	124587	2020-04-02	2021-04-01
<input checked="" type="checkbox"/>	Radio Communication Analyzer	Anritsu Corporation	MT8821C	6201502984	2020-06-11	2021-06-10
<input checked="" type="checkbox"/>	RF Bi-Directional Coupler	Agilent	86205-60001	MY31400031	NCR	NCR
<input checked="" type="checkbox"/>	Signal Generator	Agilent	N5171B	MY53050736	2020-04-15	2021-04-14
<input checked="" type="checkbox"/>	Preamplifier	Mini-Circuits	ZHL-42W	15542	NCR	NCR
<input checked="" type="checkbox"/>	Preamplifier	Compliance Directions Systems Inc.	AMP28-3W	073501433	NCR	NCR
<input checked="" type="checkbox"/>	Power Meter	Agilent	E4416A	GB41292095	2020-04-15	2021-04-14
<input checked="" type="checkbox"/>	Power Sensor	Agilent	8481H	MY41091234	2020-04-15	2021-04-14
<input checked="" type="checkbox"/>	Power Sensor	R&S	NRP-Z92	100025	2020-04-16	2021-04-15
<input checked="" type="checkbox"/>	Attenuator	SHX	TS2-3dB	30704	NCR	NCR
<input checked="" type="checkbox"/>	Coaxial low pass filter	Mini-Circuits	VLF-2500(+)	NA	NCR	NCR
<input checked="" type="checkbox"/>	Coaxial low pass filter	Microlab Fxr	LA-F13	NA	NCR	NCR
<input checked="" type="checkbox"/>	DC POWER SUPPLY	SAKO	SK1730SL5A	NA	NCR	NCR





<input checked="" type="checkbox"/>	Speed reading thermometer	MingGao	T809	NA	2020-04-15	2021-04-14
<input checked="" type="checkbox"/>	Humidity and Temperature Indicator	KIMTOKA	KIMTOKA	NA	2020-04-21	2021-04-20

Note: All the equipments are within the valid period when the tests are performed.



5 Measurements

Please see the Appendix B

6 SAR System Performance Check

Please see the Appendix A

7 Photographs

Please see the Appendix D

8 DAE & Probe Calibration Certificate

Please see the Appendix C



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
 Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

9 SAR measurement variability and uncertainty

SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.

SAR measurement variability

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

---END---

