





9.2.4. LTE BAND 13 EMISSION MASK

LIMITS

FCC: §27.53

ſ

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) Emissions in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals. (-70 dBW/MHz = -40dBm/MHz).

Test Engineer ID:85502Test Date:2024-03-08EUT Serial Number:QV7700DSLQ
--

Note: Compliance to Part 27.53(6), was performed with a 6.8kHz RBW instead of a 6.25kHz RBW as worst-case. No corrections were applied.

Page 79 of 205

LTE BAND 13



Page 80 of 205



Page 81 of 205

9.2.5. LTE BAND 41 AND 5G NR n41 EMISSION MASK

LIMITS

FCC: §27.53

(m)(4) For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between 5 between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees.

Test Engineer ID: 85502 Test Date: 2024-03-06 EUT Serial Number: QV7700DSLQ

Page 82 of 205

LTE BAND 41



Page 83 of 205





Page 85 of 205



Page 86 of 205

<u>5G NR n41</u>



Page 87 of 205



Page 88 of 205



Page 89 of 205



Page 90 of 205



Page 91 of 205







Page 94 of 205



Page 95 of 205

9.2.6. LTE BAND 66 AND 5G NR n66 EMISSION MASK

LIMITS

FCC: §27.53(h)

l

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

Test Engineer ID:	33499/85502	Test Date:	2024-03-11 2024-03-18	EUT Serial Number:	QV77000KL2 QV7700DSLQ
-------------------	-------------	------------	--------------------------	--------------------	--------------------------